Feedback — Stacks and Queues

Help Center

You submitted this quiz on **Sun 13 Sep 2015 9:50 AM EDT**. You got a score of **2.60** out of **3.00**. You can attempt again, if you'd like.

To specify an array or sequence of values in an answer, separate the value s in

the sequence by whitespace. For example, if the question asks for the firs

ten powers of two (starting at 1), then the following answer is acceptabl e:

1 2 4 8 16 32 64 128 256 512

If you wish to discuss a particular question and answer in the forums, ple ase

post the entire question and answer, including the seed (which can be used by

the course staff to uniquely identify the question) and the explanation (w

contains the correct answer).

Question 1

(seed = 96193)

Suppose that an intermixed sequence of 10 push and 10 pop operations are performed

on a LIFO stack. The push operations add the values \emptyset through 9 to the stack, in the

order given; the intermixed pop operations delete and print out the return values

Which of the following output sequence(s) could occur? Check all that apply.

Your Answer

Score Explanation

2 1 4 3 0 6 7 9 5 8	✔ 0.20	When 9 is pushed, both 5 and 8 are still on the stack. So, 8 would be popped before 5.
2 1 0 3 4 5 6 7 8 9	✔ 0.20	0123-4-5-6-7-8-9-
0 5 9 8 7 6 4 3 2 1	✔ 0.20	0-12345-6789
0 2 1 4 5 9 8 7 6 3	✔ 0.20	0-1234-5-6789
1 3 4 6 2 7 8 5 0 9	✔ 0.20	When 6 is pushed, both 2 and 5 are still on the stack. So, 5 would be popped before 2.
Total	1.00 / 1.00	
Question Explanat	ion	

Question 2

(seed = 580692)

Suppose that an intermixed sequence of 10 enqueue and 10 dequeue operations are performed

on a FIFO queue. The enqueue operations add the values 0 through 9 to the d ata structure,

in the order given; the dequeue operations delete and print out the return values.

Which of the following output sequence(s) could occur? Check all that appl y.

Your Answer Score Explanation

```
0.20
                                   The second item enqueued is 1 but the second item
0 7 1 3 4 9 5 8
                                   dequeued is 7.
2 6
                         0.20
                                   The second item enqueued is 1 but the second item
                                   dequeued is 2.
0 2 6 8 4 3 1 9
7 5
                         0.00
                                   The eighth item enqueued is 7 but the eighth item
4
0 1 2 3 4 5 6 8
                                   dequeued is 8.
7 9
                         0.20
                                   The second item enqueued is 1 but the second item
0 2 8 1 3 5 9 6
                                   dequeued is 2.
4 7
                         0.00
                                   0-1-2-3-4-5-6-7-8-9-
0 1 2 3 4 5 6 7
Total
                         0.60/
                         1.00
Question Explanation
```

Question 3

```
(seed = 503415)
Consider an object of type MysteryBox that stores N items of type double
in an array items[] of length N.

public class MysteryBox {
    private int N;
    private double[] items;

...
}
```

Using the 64-bit memory cost model from the lecture, how many bytes does it use as a function of N?

Include all memory referenced by the object and use tilde notation to simpl ify your answer.

For example, enter \sim 4N if the number of bytes as a function of N is 4N + 3 2.

You entered:

```
~ 8N
```

Your Answer		Score	Explanation
~ 8N	~	1.00	
Total		1.00 / 1.00	

Question Explanation

```
A correct answer matches the regular expression: s^*\sim 1s^*
For example, the following is a correct answer: ~ 8N
Below is a detailed accounting:
public class MysteryBox {
                                            // 16 (object overhea
d)
                                            //
                                                     4 (int)
   private int N;
   private double[] items;
                                            //
                                                      8 (reference to ar
ray)
                                            // 8N + 24 (array of doubl
e)
                                                      4 (padding to roun
d up to a multiple of 8)
}
                                                _____
                                                8N + 56 \sim 8N
```