

# Security incident report

## Section 1: Identify the network protocol involved in the incident

TCP

## Section 2: Document the incident

The information was obtained by the Tcpdump

The source computer your.machine.52444 used port 52444 to send a DNS resolution request to dns.google.domain: The reply to the source from the DNS server to the source computer with IP address 203.0.113.22.

The next section shows a connection request Flags [S] from source your.machine.36086 using port 36086 directly to the [destinationyummyrecipesforme.com](#).http. The .http suffix is the port number; http is commonly associated with port 80.

The log entry HTTP: GET / HTTP/1.1 shows a request for data and this could be the download request for the malicious file from yummyrecipesforme.com.http

The destination acknowledged the request. The connection went for about 2 minutes, until 14:20:32.192571. At this time a DNS request from source 14:20:32.192571 IP your.machine.52444 > dns.google.domain: 21899+ A? [greatrecipesforme.com](#), from port 52444.

The DNS server has now routed the traffic to a new IP address ,192.0.2.17 and the associated URL [greatrecipesforme.com](#).http

The traffic changes from the source to the spoofed website. Outgoing your.machine.56378 > [greatrecipesforme.com](#).http: and incoming greatrecipesforme.com.http > your.machine.56378:

Notice how the port number changed to 56378 when redirected to the new site.

### **Section 3: Recommend one remediation for brute force attacks**

- Enforcing two-factor authentication (2FA)

This will create another layer of security for bad actors who recently left the company and for external bad actors.