

NANO PIGMENTED

NANOtij[®] - porous

Features:

- ✓ Highest Optical Density
- ✓ Yields upto 4 times more
- ✓ Ideal for barcodes printability
- ✓ Resistant to fading, smearing & chemicals
- ✓ Compliant with RHos, PFAS Free
- ✓ Suitable for intermittent & continuous printing
- ✓ 12 month shelf life

Compliance:



Shipping:



Cartridge weight:
Without clip = 106g
With clip = 113g
Total package = 160g

digital
ink technologies



Precision marking
for barcoding

DATA SHEET

NANOtij[®] is highly resistant to fading, smearing and chemical alterations ensuring it is ideal for barcoding on porous substrates such as kraft paper, cardboard and various coated papers.

Exceptionally high optical density with precision marking is expected; ideal for mailing, packaging applications and ticketing applications.

Specification

HP Cartridge Type	HP 45A
Ink Colour	Black
Ink Density (sg)	1.05
Firing Voltage (V)	10.2
Pulse Width (microseconds)	2.0
Firing Frequency (kHz)	10
Shelf Life (weeks)	52
Pulse Warming Temperature (C °)	20
Maximum Temperature (C °)	31
Usable Ink Volume (ml)	39
Operating Temperature	15°C - 35°C
Storage Temperature	10°C - 35°C

Remarks

Refer to SDS before use for safe handling.
Before use, wipe the printhead gently with a dry lint-free cloth.

After use, seal the printhead with the originally attached cartridge clip and store the cartridge with the position of its printhead UP until next use.

All technical information here is based on internal laboratory testing & can vary in external conditions.

Conducting print test under real user conditions is recommended.

The information provided is subject to change without notice.
Current as at 1st January 2025.

Copyright © 2025 Digital Ink Technologies Pty Ltd. All Rights Reserved

