

**"Innovation,
not imitation"**

A SERIES

ISOLATED, PROPORTIONAL DC TO HV DC CONVERTERS


100V to 6000V @ 1.0 and 1.5 Watts

**Extremely Low Profile: 0.25 inches
and volume of < 0.100 cubic inches¹⁵**



PRODUCT DESCRIPTION

The A Series is a new line of ultra-miniature, DC to HV DC converters that set an industry standard in high voltage miniaturization. This unique package occupies less than one tenth of a cubic inch of volume¹⁵, and features an extremely low profile of only 0.250 inches (6.35mm)! Controllable output voltages range from 100 volts to 6000 volts. These component-sized converters are ideal for applications requiring minimal size and weight. Please refer to our AG series data sheet for surface mount options.



APPLICATIONS

Avalanche Photodiodes
Capacitor Charging
Electrophoresis
Photomultiplier Tubes
Piezo Devices
Mass Spectrometry
Sustaining Ion Pumps

OPTIONS

1 Watt and 1.5 Watt Versions Available (A/AH)
Available in Three Standard Input Voltage Ranges: 0 to 5, 12 or 24VDC
Polarity: Choose Positive or Negative Output (P/N)
Extended Operating Temperature (A Models / 1.0W) (T Suffix)
Alternate Input / Output Voltages (Consult Factory)
See Ordering Information (Page 11)

PRODUCT SELECTION TABLE

VDC	STANDARD 1 WATT - A MODEL		1.5 WATT OPTION - AH MODEL	
	MODEL	MAXIMUM OUTPUT CURRENT*1	MODEL	MAXIMUM OUTPUT CURRENT*1
100 VDC	A01	10 mA	AH01	15 mA
200 VDC	A02	5 mA	AH02	7.5 mA
250 VDC	A025	4 mA	AH025	6 mA
300 VDC	A03	3.33 mA	AH03	5mA
400 VDC	A04	2.5 mA	AH04	3.75 mA
500 VDC	A05	2 mA	AH05	3 mA
600 VDC	A06	1.67 mA	AH06	2.5 mA
700 VDC	A07	1.43 mA	AH07	2.15 mA
800 VDC	A08	1.25 mA	AH08	1.87 mA
900 VDC	A09	1.1 mA	AH09	1.67 mA
1000 VDC	A10	1 mA	AH10	1.5 mA
1200 VDC	A12	0.83 mA	AH12	1.25 mA
1500 VDC	A15	0.66 mA	AH15	1 mA
2000 VDC	A20	0.5 mA	AH20	0.75 mA
3000 VDC	A30	0.32 mA	AH30	0.5 mA
4000 VDC	A40	0.24 mA	AH40	0.375 mA
5000 VDC	A50	0.2 mA	AH50	0.3 mA
6000 VDC	A60	0.167 mA	AH60	0.25 mA

Complete List of Models on page 2

FEATURES

- Proportional Input/Output
- Low Noise Quasi-sinewave Oscillator
- Control Pin
- Low Leakage Current
- Low Input/Output Capacitance
- Input to Output Galvanic Isolation
- Short Circuit Protection, 1 Minute Minimum
- No Minimum Load Required
- Designed to meet RoHS and REACH Directives
- MTBF > 1,862,000 hours, per Bellcore TR 332
- UL94V-0 Listed Proprietary Encapsulant
- No External Components Required

INPUT CURRENT

INPUT CURRENT													
MODEL	A MODELS - 1 WATT						MODEL	AH MODELS - 1.5 WATT					
	5 VOLT INPUT		12 VOLT INPUT		24 VOLT INPUT			5 VOLT INPUT		12 VOLT INPUT		24 VOLT INPUT	
	No-Load	Full-Load	No-Load	Full-Load	No-Load	Full-Load		No-Load	Full-Load	No-Load	Full-Load	No-Load	Full-Load
A01	<100mA	<300mA	<100mA	<185mA	<25mA	<75mA	AH01	<200mA	<550mA	<125mA	<250mA	<40mA	<120mA
A02	<200mA	<470mA	<50mA	<160mA	<25mA	<60mA	AH02	<150mA	<450mA	<75mA	<225mA	<40mA	<120mA
A025	<30mA	<375mA	<30mA	<125mA	<25mA	<60mA	AH025	<300mA	<550mA	<125mA	<250mA	<40mA	<120mA
A03	<100mA	<375mA	<100mA	<185mA	<25mA	<60mA	AH03	<150mA	<450mA	<125mA	<250mA	<40mA	<120mA
A04	<200mA	<470mA	<100mA	<185mA	<25mA	<60mA	AH04	<300mA	<550mA	<125mA	<550mA	<40mA	<120mA
A05	<200mA	<470mA	<100mA	<185mA	<25mA	<60mA	AH05	<200mA	<550mA	<75mA	<225mA	<40mA	<120mA
A06	<200mA	<470mA	<100mA	<185mA	<25mA	<60mA	AH06	<200mA	<550mA	<125mA	<250mA	<40mA	<120mA
A07	<200mA	<470mA	<100mA	<185mA	<25mA	<60mA	AH07	<200mA	<550mA	<125mA	<250mA	<40mA	<120mA
A08	<200mA	<470mA	<100mA	<185mA	<25mA	<60mA	AH08	<200mA	<550mA	<125mA	<250mA	<40mA	<120mA
A09	<200mA	<470mA	<100mA	<185mA	<25mA	<60mA	AH09	<200mA	<550mA	<125mA	<250mA	<40mA	<120mA
A10	<100mA	<375mA	<100mA	<185mA	<25mA	<75mA	AH10	<300mA	<550mA	<125mA	<250mA	<40mA	<120mA
A12	<200mA	<470mA	<50mA	<160mA	<25mA	<60mA	AH12	<200mA	<550mA	<125mA	<250mA	<40mA	<120mA
A15	<200mA	<470mA	<100mA	<300mA	<25mA	<60mA	AH15	<200mA	<550mA	<125mA	<250mA	<40mA	<120mA
A20	<100mA	<375mA	<50mA	<160mA	<25mA	<60mA	AH20	<300mA	<550mA	<125mA	<250mA	<40mA	<120mA
A30	<200mA	<470mA	<50mA	<160mA	<25mA	<60mA	AH30	<200mA	<500mA	<125mA	<250mA	<40mA	<120mA
A40	<200mA	<375mA	N/A	N/A	N/A	N/A	AH40	<200mA	<550mA	N/A	N/A	N/A	N/A
A50	<200mA	<470mA	N/A	N/A	N/A	N/A	AH50	<300mA	<600mA	N/A	N/A	N/A	N/A
A60	<200mA	<470mA	N/A	N/A	N/A	N/A	AH60	<300mA	<600mA	N/A	N/A	N/A	N/A

ELECTRICAL SPECIFICATIONS*3

OUTPUT VOLTAGE*2 (To select polarity, see pg. 10 - How to Order)	STANDARD 1 WATT - A MODEL			1.5 WATT OPTION - AH MODEL		
	MODEL	MAXIMUM OUTPUT CURRENT*1	RIPPLE P-P*4	MODEL	MAXIMUM OUTPUT CURRENT*1	RIPPLE P-P*4
0 to 100 VDC	A01	10 mA	5%	AH01	15 mA	4%
0 to 200 VDC	A02	5 mA	1%	AH02	7.5 mA	3%
0 to 250 VDC	A025	4 mA	.90%	AH025	6 mA	1.2%
0 to 300 VDC	A03	3.33 mA	.70%	AH03	5 mA	.70%
0 to 400 VDC	A04	2.5mA	.50%	AH04	3.75 mA	.75%
0 to 500 VDC	A05	2 mA	.50%	AH05	3 mA	.70%
0 to 600 VDC	A06	1.67 mA	1%	AH06	2.5 mA	2%
0 to 700 VDC	A07	1.43 mA	.50%	AH07	2.15 mA	1.2%
0 to 800 VDC	A08	1.25 mA	1%	AH08	1.87 mA	1.2%
0 to 900 VDC	A09	1.1 mA	1%	AH09	1.67 mA	1.2%
0 to 1000 VDC	A10	1 mA	.79%	AH10	1.5 mA	1%
0 to 1200 VDC	A12	0.83 mA	.50%	AH12	1.25 mA	.60%
0 to 1500 VDC	A15	0.67 mA	.40%	AH15	1 mA	.60%
0 to 2000 VDC	A20	0.5 mA	.30%	AH20	0.75 mA	.50%
0 to 3000 VDC	A30	0.33 mA	.20%	AH30	0.5 mA	.20%
0 to 4000 VDC	A40	0.25 mA	.12%	AH40	0.37 mA	.18%
0 to 5000 VDC	A50	0.2 mA	.15%	AH50	0.3mA	.16%
0 to 6000 VDC	A60	0.167 mA	.15%	AH60	0.25 mA	.25%

ELECTRICAL SPECIFICATIONS*3

PARAMETER	VALUE
INPUT VOLTAGE	0 TO 5, 12, OR 24V (FOR MODELS UP TO 3KV)
	0 TO 5V (FOR MODELS OVER 3KV)
TURN-ON VOLTAGE	<0.7 VDC
ISOLATION	< +/- 500V BIAS ON PIN 4
OUTPUT VOLTAGE TOLERANCE	+10%, -10% FULL LOAD, MAX. INPUT VOLTAGE
INPUT/OUTPUT COUPLING CAPACITANCE	<250 pf TYPICAL
INPUT/OUTPUT LEAKAGE CURRENT	<50 nA TYPICAL
CONTROL PIN	0 to MAX. INPUT VOLTAGE
INTERNAL OSCILLATOR FREQUENCY	50kHz - 350kHz
STANDARD TEMPERATURE RANGES	OPERATING: -25° TO +75°C (CASE)
	STORAGE: -55° TO +105°C
EXTENDED TEMPERATURE RANGES (-T OPTION)	OPERATING: -55 TO +85°C (CASE) [A Models / 1.0W]
	STORAGE: -55° TO +105°C

DETAILED PRODUCT DESCRIPTION

The A Series is a new line of ultra-miniature, DC to HV DC converters that set an industry standard in high voltage miniaturization. This unique package occupies less than one tenth of a cubic inch of volume^{*5}, and features an extremely low profile of only 0.250 inches (6.35mm)! Controllable output voltages range from 100 volts to 6000 volts. These component-sized converters are ideal for applications requiring minimal size and weight.

Turn-on voltage is very low at less than 0.7 volts, allowing for wide output voltage operating range. Use of a resonant, quasi-sinewave oscillator and fully shielded transformer result in clean, reliable high voltage conversion with inherently low ripple, EMI/RFI and input ripple current, making this product ideal for integration into noise sensitive equipment.

A separate high impedance control pin is standard and is designed for external error amplifier and/or DAC control in closed or open loop systems. Or simply connect the control pin to the + input for proportional input to output operation (see schematic and performance charts below).


Output power is 1 watt standard, with 1.5 watts available as an option. No minimum load is required. A proprietary encapsulation process and custom 94V-0 listed, high performance formula are used to achieve excellent high voltage and thermal properties. Isolation is +/- 500V bias on the output return. Input to output leakage current is very low at less than 100 nA and coupling capacitance is also low at <250 pF.

The new A Series leverages EMCO's Best-in-Class long term reliability, utilizing proven DC to high voltage DC conversion technology, perfected by over four decades of high voltage design experience in the most demanding applications. All EMCO products are designed by our team of specialized engineers and scientists. Our extensive in-house capabilities enable us to meet specific customer requirements with standard, modified and custom solutions quickly, easily, and economically. Technical assistance is readily available.

This series is designed and manufactured to provide consistent, built-in, long-term reliability for which EMCO products are known. The A Series is manufactured in EMCO's "Flex-Chain" lean, demand-flow process that provides maximum quality, short leadtimes, and assures our customers the lowest total cost of ownership.

Small quantities available from stock from our factory or our stocking distributor in Switzerland, Condatas AG. For large quantity requests please consult our factory or our stocking distributor in Switzerland, Condatas AG.

MECHANICAL SPECIFICATIONS (100V - 2,000V)




Dimensions are in inches (Metric Equivalents Parenthesis)
 Dimensional Tolerances: .xx +/- 0.02 (0.51mm)
 .xxx +/- 0.005 (0.127mm)

PARAMETER	VALUE
WEIGHT	< 0.20 OZ. (5.66 GRAMS)
VOLUME	< 0.10 CUBIC INCHES (1.696 CUBIC CENTIMETERS)
DIMENSIONS	0.92L (23.37L) x 0.45W (11.43W) x 0.25H (6.35H)

PIN #	FUNCTION
1	(-) INPUT
2	(+) INPUT
3	HV OUT
4	HV RTN
5	CONTROL

MECHANICAL SPECIFICATIONS (3,000V - 5,000V)




Dimensions are in inches (Metric Equivalents Parenthesis)
 Dimensional Tolerances: .xx +/- 0.02 (0.51mm)
 .xxx +/- 0.005 (0.127mm)

PARAMETER	VALUE
WEIGHT	< 0.25 OZ. (5.66 GRAMS)
VOLUME	< 0.12 CUBIC INCHES (2.082 CUBIC CENTIMETERS)
DIMENSIONS	1.129L (28.69L) x 0.45W (11.43W) x 0.25H (6.35H)

PIN #	FUNCTION
1	(-) INPUT
2	(+) INPUT
3	HV OUT
4	HV RTN
5	CONTROL

MECHANICAL SPECIFICATIONS (6,000V)




Dimensions are in inches (Metric Equivalents Parenthesis)
 Dimensional Tolerances: .xx +/- 0.02 (0.51mm)
 .xxx +/- 0.005 (0.127mm)

PARAMETER	VALUE
WEIGHT	< 0.30 OZ. (8.49 GRAMS)
VOLUME	< 0.15 CUBIC INCHES (2.45 CUBIC CENTIMETERS)
DIMENSIONS	1.33L (33.78L) x 0.45W (11.43W) x 0.25H (6.35H)

PIN #	FUNCTION
1	(-) INPUT
2	(+) INPUT
3	HV OUT
4	HV RTN
5	CONTROL

MECHANICAL SPECIFICATIONS


100V - 2,000V



RECOMMENDED LAYOUT

Dimensions are in inches (Metric Equivalents Parenthesis)
 Dimensional Tolerances: .xx +/- 0.02 (0.51mm)
 .xxx +/- 0.005 (0.127mm)


3,000 - 5,000V



RECOMMENDED LAYOUT


Dimensions are in inches (Metric Equivalents Parenthesis)
 Dimensional Tolerances: .xx +/- 0.02 (0.51mm)
 .xxx +/- 0.005 (0.127mm)

MECHANICAL SPECIFICATIONS




APPLICATION NOTES

Typical HV Output vs. Control Voltage



TYPICAL INPUT vs. OUTPUT VOLTAGE




OPTION CODES

ORDERING INFORMATION		ORDER CODE
OUTPUT VOLTAGE	1 WATT	A
	1.5 WATT	AH
POLARITY DESIGNATOR	POSITIVE OUTPUT	P
	NEGATIVE OUTPUT	N
INPUT VOLTAGE	5 VDC	5
	12 VDC	12
	24 VDC	24
STANDARD TEMPERATURE RANGES	OPERATING: -25 TO +75°C (CASE)	BLANK
	STORAGE: -55 TO +105°C	BLANK
EXTENDED TEMPERATURE RANGES	OPERATING: -55 TO +85°C (CASE) [A Models / 1.0W]	T
	STORAGE: -55 TO +105°C	T

HOW TO ORDER

PART NUMBER SELECTOR:



EXAMPLE: **A20N-12T** (**A** - Model, **20** - Output Voltage, **N** - Negative, **12** - Input Voltage, **T** - Extended Operating Temperature)

*Note:

1. At maximum rated output voltage
2. Output Voltage is load dependent. Under light or no-load conditions, reduce the Input Voltage so maximum rated Output Voltage is not exceeded.
3. Specifications after 30 minute warm-up, full-load, at 25°C, unless otherwise noted.
4. Ripple may be reduced substantially by the addition of an external RC filter.
5. Volume will vary depending on package size.

We Reserve the Right To Make Changes without Notification.