

Nouns Conc-Abs: Reaction Time Graphs

morgan moyer

2025-03-25

Looking at overall Log ReactionTime for the data


Before removing outliers

Summary Stats

```
agr <- d %>%  
  group_by(Task) %>%  
  summarize(MeanRT = mean(ReactionTime),  
            SD = sd(ReactionTime),  
            MeanLogRT = mean(LogReactionTime))  
print(agr)
```


```
## # A tibble: 2 x 4  
##   Task      MeanRT    SD MeanLogRT  
##   <chr>    <dbl> <dbl>    <dbl>  
## 1 Concrete 1011. 1473.    6.74  
## 2 Valence  832. 1324.    6.57
```

```
ggplot(d, aes(ReactionTime, fill=Task)) +  
  geom_density(alpha = .5)
```



Long tail justifies outlier removal?

```
ggplot(d, aes(LogReactionTime, fill=Task)) +  
  geom_density(alpha = .5)
```



```
summary(d$LogReactionTime)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      1.099   6.410   6.582   6.654   6.852   11.233
```

First Remove participants who aren't super , aggregating over Task

```
length(unique(d$ID.true))
```

```
## [1] 40
```

```
inacc.parts <- d %>%
  group_by(ID.true, Task) %>%
  summarise(MeanAccuracy = mean(Accuracy)) %>%
  filter(MeanAccuracy < .75)
```

```
## `summarise()` has grouped output by 'ID.true'. You can override using the
## `.groups` argument.
```

```
# How many participants have Accuracy < .75?
length(unique(inacc.parts$ID.true))
```

```
## [1] 2
```

```
d.inaccurate.removed <- d %>%
  anti_join(inacc.parts, by = "ID.true")
```

```
# Sanity check
```

```
length(unique(d.inaccurate.removed$ID.true))
```

```
## [1] 38
```

remove all inaccurate trials

```
orig <- nrow(d.inaccurate.removed)
d.inaccurate.removed <- d.inaccurate.removed %>%
  filter(Accuracy == 1)
nrow(d.inaccurate.removed)/orig*100
```

```
## [1] 92.87393
```

```
# Remove subjects with ReactionTime higher than 3x IQR
summary(d.inaccurate.removed$LogReactionTime)
```


```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
##      2.303   6.417   6.583   6.685   6.844   10.528
```

```
# Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
# 6.924   7.328   7.436   7.479   7.579   10.008
range(d.inaccurate.removed$LogReactionTime)
```

```
## [1] 2.302585 10.527553
```

```
hist(d.inaccurate.removed$LogReactionTime, breaks=100, col="lightblue", xlab="LogReactionTime (ms)",
     main="Histogram with Normal Curve")
```

Histogram with Normal Curve



```
quantile(d.inaccurate.removed$LogReactionTime, na.rm = TRUE)
```

```
##      0%      25%      50%      75%     100%
```


```
## 2.302585 6.416732 6.583409 6.843750 10.527553
IQR(d.inaccurate.removed$LogReactionTime, na.rm = TRUE)*3 # 0.7526289

## [1] 1.281053
cutoff.high <- quantile(d.inaccurate.removed$LogReactionTime, na.rm = TRUE)[4] + IQR(d.inaccurate.removed$LogReactionTime, na.rm = TRUE)
cutoff.low <- quantile(d.inaccurate.removed$LogReactionTime, na.rm = TRUE)[2] - IQR(d.inaccurate.removed$LogReactionTime, na.rm = TRUE)

# remove subjects with ReactionTime higher than 3 x IQR
df.outliers.removed <- subset(d.inaccurate.removed, (d.inaccurate.removed$LogReactionTime > cutoff.low) && (d.inaccurate.removed$LogReactionTime < cutoff.high))

hist(df.outliers.removed$LogReactionTime, col="lightblue", xlab="LogReactionTime (ms)",
      main="Histogram with Normal Curve")
```

Histogram with Normal Curve



Summary Stats

```
agr <- d.inaccurate.removed %>%
  group_by(Task) %>%
  summarize(MeanRT = mean(ReactionTime),
            SD = sd(ReactionTime),
            MeanLogRT = mean(LogReactionTime))
print(agr)
```


```
## # A tibble: 2 x 4
##   Task      MeanRT      SD MeanLogRT
##   <chr>    <dbl> <dbl>    <dbl>
## 1 Concrete  998. 1035.    6.77
## 2 Valence  822.  736.    6.61
```

LogReactionTime by Task

```
agr <- df.outliers.removed %>%
  group_by(Task, Word) %>%
  summarize(MeanLogReactionTime = mean(LogReactionTime),
            CILow = ci.low(LogReactionTime),
            CIHigh = ci.high(LogReactionTime)) %>%
  mutate(YMin = MeanLogReactionTime - CILow,
         YMax = MeanLogReactionTime + CIHigh)

## `summarise()` has grouped output by 'Task'. You can override using the
## `.groups` argument.

ggplot(agr, aes(x=Task, y=MeanLogReactionTime, fill=Task)) +
  geom_violin(trim=FALSE, alpha=.4) +
  geom_jitter(shape=16, position=position_jitter(0.2)) +
  guides(fill = "none")
```




ReactionTime by Task

```
agr <- df.outliers.removed %>%
  group_by(Task, Word) %>%
  summarize(MeanReactionTime = mean(ReactionTime),
            CILow = ci.low(ReactionTime),
            CIHigh = ci.high(ReactionTime)) %>%
  mutate(YMin = MeanReactionTime - CILow,
```

```
YMax = MeanReactionTime + CIHigh)
```

```
## `summarise()` has grouped output by 'Task'. You can override using the
## `.groups` argument.
```

```
ggplot(agr, aes(x=Task, y=MeanReactionTime, fill=Task)) +
  geom_violin(trim=FALSE, alpha=.4) +
  geom_jitter(shape=16, position=position_jitter(0.2)) +
  guides(fill = "none")
```




ReactionTime by BlockOrder and Task

```
agr <- df.outliers.removed %>%
  group_by(BlockOrder, Task, Word) %>%
  summarize(MeanReactionTime = mean(ReactionTime),
            CILow = ci.low(ReactionTime),
            CIHigh = ci.high(ReactionTime)) %>%
  mutate(YMin = MeanReactionTime - CILow,
         YMax = MeanReactionTime + CIHigh)
```

```
## `summarise()` has grouped output by 'BlockOrder', 'Task'. You can override
## using the `.groups` argument.
```

```
ggplot(agr, aes(x=Task, y=MeanReactionTime, fill=BlockOrder)) +
  geom_violin(trim=FALSE, alpha=.4) +
  geom_jitter(shape=16, position=position_jitter(0.2))
```



By Item

```
agr <- df.outliers.removed %>%
  group_by(Task, Word) %>%
  summarize(MeanReactionTime = mean(ReactionTime), CILow = ci.low(ReactionTime), CIHigh = ci.high(ReactionTime),
    mutate(YMin = MeanReactionTime - CILow, YMax = MeanReactionTime + CIHigh))

## `summarise()` has grouped output by 'Task'. You can override using the
## `.groups` argument.

dodge = position_dodge(.9)
ggplot(data=agr, aes(x=Task, y=MeanReactionTime, fill=Task)) +
  geom_bar(position=dodge, stat="identity") +
  facet_wrap(~Word) +
  geom_errorbar(aes(ymin=YMin, ymax=YMax), width=.25, position=position_dodge(0.9)) +
  theme(axis.text.x = element_text(angle = 45, hjust = 1))
```





```
# guides(fill = "none")
```

By ConcValCombo category and Task

Mean Raw ReactionTime and Effects of Word Valence/Concreteness

```
agr <- df.outliers.removed %>%
  group_by(Task, ConcValCombo) %>%
  reframe(MeanReactionTime = mean(ReactionTime), CILow = ci.low(ReactionTime), CIHigh = ci.high(ReactionTime),
  mutate(YMin = MeanReactionTime - CILow, YMax = MeanReactionTime + CIHigh))

dodge = position_dodge(.9)
ggplot(data=agr, aes(x=Task, y=MeanReactionTime, fill=ConcValCombo)) +
  geom_bar(position=dodge, stat="identity") +
  # facet_wrap(~Task) +
  geom_errorbar(aes(ymin=YMin, ymax=YMax), width=.25, position=position_dodge(0.9))
```




```
# theme(axis.text.x = element_text(angle = 45, hjust = 1))
# guides(fill = "none")
```

Variance


```
agr <- df.outliers.removed %>%
  group_by(Task, Word) %>%
  mutate(VarianceLogRT = var(LogReactionTime))

ggplot(agr, aes(VarianceLogRT, fill=Task)) +
  geom_density(alpha = .5)
```



```
agr <- df.outliers.removed %>%
  group_by(Task, Word) %>%
  mutate(VarianceRT = var(ReactionTime))

ggplot(agr, aes(VarianceRT, fill=Task)) +
  geom_density(alpha = .5)
```




ReactionTime by Task

```
agr <- df.outliers.removed %>%
  group_by(Task, Word) %>%
  mutate(VarianceLogRT = var(LogReactionTime)) %>%
  summarize(MeanVarianceLogRT = mean(VarianceLogRT),
            CILow = ci.low(VarianceLogRT),
            CIHigh = ci.high(VarianceLogRT)) %>%
  mutate(YMin = MeanVarianceLogRT - CILow,
         YMax = MeanVarianceLogRT + CIHigh)

## `summarise()` has grouped output by 'Task'. You can override using the
## `.groups` argument.

ggplot(agr, aes(x=Task, y=MeanVarianceLogRT, fill=Task)) +
  geom_violin(trim=FALSE, alpha=.4) +
  geom_jitter(shape=16, position=position_jitter(0.2)) +
  guides(fill = "none")
```




LogReactionTime by BlockOrder and Task

```
agr <- df.outliers.removed %>%
  group_by(BlockOrder, Task, Word) %>%
  mutate(VarianceLogRT = var(LogReactionTime)) %>%
  summarize(MeanVarianceLogRT = mean(VarianceLogRT),
            CILow = ci.low(VarianceLogRT),
            CIHigh = ci.high(VarianceLogRT)) %>%
  mutate(YMin = MeanVarianceLogRT - CILow,
         YMax = MeanVarianceLogRT + CIHigh)
```

`summarise()` has grouped output by 'BlockOrder', 'Task'. You can override
using the `.groups` argument.

```
ggplot(agr, aes(x=Task, y=MeanVarianceLogRT, fill=BlockOrder)) +
  geom_violin(trim=FALSE, alpha=.4) +
  geom_jitter(shape=16, position=position_jitter(0.2))
```



By Item

```
agr <- df.outliers.removed %>%
  group_by(Task, Word) %>%
  mutate(VarianceLogRT = var(LogReactionTime)) %>%
  summarize(MeanVarianceLogRT = mean(VarianceLogRT),
            CILow = ci.low(VarianceLogRT),
            CIHigh = ci.high(VarianceLogRT)) %>%
  mutate(YMin = MeanVarianceLogRT - CILow,
         YMax = MeanVarianceLogRT + CIHigh)

## `summarise()` has grouped output by 'Task'. You can override using the
## `.groups` argument.

dodge = position_dodge(.9)
ggplot(data=agr, aes(x=Task, y=MeanVarianceLogRT, fill=Task)) +
  geom_bar(position=dodge, stat="identity") +
  facet_wrap(~Word) +
  geom_errorbar(aes(ymin=YMin, ymax=YMax), width=.25, position=position_dodge(0.9))
```



```
# theme(axis.text.x = element_text(angle = 45, hjust = 1))
# guides(fill = "none")
```