

TI PROGRAMMABLE 57 REFERENCE GUIDE



Always refer to *Making Tracks into Programming* for complete details of calculator operation.

AOS™ ENTRY METHOD

Lets you enter problems directly as they're usually written, left to right. Calculator will execute operations in the following order: 1) single variable functions 2) powers/roots 3) multiplication/division 4) add/subtract. [=] (Equals Key) completes all pending operations. This order of operations is also followed inside parentheses.

CLEARING:

Turning your calculator OFF and ON clears it completely.

[CE] — clears last number entered (if not followed by an operation).

[2nd] [C] — clears the "t" register (memory 7) only.

[CLR] — clears machine, except for memories and program steps.

[INV] [2nd] [C] — clears the display, and all memories, but not program steps.

POWERS AND ROOTS:

To raise a number (y) to any power (x)

- Enter the number (y).
- Press [y^x].
- Enter the power (x).
- Press [=] (or other function key).

To take the x^{th} root of a number (y). ($\sqrt[x]{y}$)

- Enter the number (y).
- Press [INV] [y^x].
- Enter the root (x).
- Press [=] (or other function key).

MEMORIES:

8 memories (numbered **0** through **7**) are available for your use:

STO **n** (**n** from **0** to **7**) stores the number in the display in the memory you select (**0** to **7**).

RCL **n** recalls the number from memory **n** into the display.

2nd **↔** **n** — swaps the display value with what's in memory **n**.

SUM **n** — sums the number in the display into memory **n** (the result stays in the memory).

INV **SUM** **n** — subtracts the number in the display from what's in memory **n** (the result stays in memory).

2nd **Prd** **n** — multiplies what's in memory **n** by the number in the display (result stays in memory).

INV **2nd** **Prd** **n** — divides what's in memory **n** by the number in the display (result stays in memory).

FIX DECIMAL:

To Set the Number of Decimal Places in the Display, press **2nd** **FIX** **n**, where **n** is the desired number of digits to the right of the decimal point (**0** to **8**).

Pressing **INV** **2nd** **FIX** or **2nd** **FIX** **9** removes the fix on the decimal point.

ANGLE MODE:

Your calculator is equipped to accept angle inputs, and to return angle calculation results, in 3 systems of units: Degrees, Radians, and Grads. When first turned on, the calculator is always in Degree mode.

- Press **2nd** **Rad** to change to Radian mode.
- Press **2nd** **Grad** to change to Grad mode.
- Press **2nd** **Deg** to change to Degree mode.

Be certain that your calculator is in the correct mode for the angular units you desire when performing any calculations involving angles, including:

- Trigonometric functions: **2nd** **sin**, **2nd** **cos**, **2nd** **tan**, and their inverses.
- Polar to Rectangular Conversion: **2nd** **P→R**, and its inverse.

CONVERSIONS:

Polar to Rectangular

- Enter R, Press: $\boxed{x \rightarrow t}$
- Enter θ
- Press $\boxed{2nd} \boxed{P \rightarrow R}$ — y is displayed.
- Press $\boxed{x \rightarrow t}$ to read x .

Rectangular to Polar

- Enter x • Press $\boxed{x \rightarrow t}$
- Enter y
- Press $\boxed{INV} \boxed{2nd} \boxed{P \rightarrow R}$ —
- θ is displayed.
- Press $\boxed{x \rightarrow t}$ to read R.

Degrees, Min, sec to Decimal Degrees

- Enter degrees, Press $\boxed{\circ}$
- Enter minutes (2 digits) and seconds (2 digits).
- Press $\boxed{2nd} \boxed{D.MS}$ for decimal value.

Decimal Degrees to Degrees, Min, Sec

- Enter decimal degrees.
- Press $\boxed{INV} \boxed{2nd} \boxed{D.MS}$
- (Degrees, minutes, seconds) now displayed.

STATISTICAL KEYS AND FUNCTIONS:

Begin statistical calculations by turning calculator OFF and ON; or by pressing $\boxed{INV} \boxed{2nd} \boxed{C.I}$.

If you have only one set of data to analyze:

- Enter each data point.
- Press $\boxed{2nd} \boxed{\Sigma+}$.
- Repeat for all points.
- Press $\boxed{2nd} \boxed{\bar{x}}$ to calculate the mean.
- Press $\boxed{2nd} \boxed{\sigma^2}$ to calculate the variance (with N weighting).
- Press $\boxed{2nd} \boxed{\sigma^2} \boxed{\sqrt{x}}$ to calculate the standard deviation of the data (with N weighting). ("N weighting" means that the total number of data points is used in the calculation of the variance — this type of variance is called a population variance.)

If you have two sets of data to analyze simultaneously:

Call the two sets of data "x" and "y" arrays.

- Enter an "x" data point.
- Press $\boxed{x \rightarrow t}$.
- Enter a "y" data point.
- Press $\boxed{2nd} \boxed{\Sigma+}$.
- Repeat for all points.
- Press $\boxed{INV} \boxed{2nd} \boxed{\bar{x}}$ to calculate the mean of the "x" data points.
- Press $\boxed{2nd} \boxed{\bar{x}}$ to calculate the mean of the "y" data points.
- Press $\boxed{INV} \boxed{2nd} \boxed{\sigma^2}$ to calculate the variance of the "x" data points.
- Press $\boxed{2nd} \boxed{\sigma^2}$ to calculate the variance of the "y" data points. (use $\boxed{\sqrt{x}}$ key to calculate standard deviation).

CALCULATOR KEY CODES IN NUMERICAL ORD

00	0					42	EE		
01	1					-42	INV	EE	
09	9					43	(
13	Inx					44)		
-13	INV	Inx				45	÷		
14	CE					46	2nd	Nop	
15	CLR					48	2nd	FIX	
18	2nd	log				-48	INV	2nd	FIX
-18	INV	2nd	log			49	2nd	Int	
19	2nd	C.t				-49	INV	2nd	Int
-19	INV	2nd	C.t			50	2nd	Deg	
20	2nd	tan				51	GTO		
-20	INV	2nd	tan			55	X		
22	x ² t					56	2nd	Os2	
23	x ²					-56	INV	2nd	Os2
24	√x					60	2nd	Rad	
25	1/x					61	SBR		
26	2nd	D.MS				-61	INV	SBR	
-26	INV	2nd	D.MS			65	-		
27	2nd	P→R				66	2nd	x=l	
-27	INV	2nd	P→R			-66	INV	2nd	x=l
28	2nd	sin				70	2nd	Grad	
-28	INV	2nd	sin			71	RST		
29	2nd	cos				75	+		
-29	INV	2nd	cos			76	2nd	x≠l	
30	2nd	π				-76	INV	2nd	x≠l
32	STO					80	2nd	σ ²	
33	RCL					-80	INV	2nd	σ ²
34	SUM					81	R/S		
-34	INV	SUM				83	.		
35	y ^x					84	+/-		
-35	INV	y ^x				85	=		
36	2nd	Pause				86	2nd	Lbl	
38	2nd	Exc				88	2nd	Σ+	
39	2nd	Prd				-88	INV	2nd	Σ+
-39	INV	2nd	Prd			89	2nd	x̄	
40	2nd	x				-89	INV	2nd	x̄

BASIC PROGRAMMING KEYS

LRN – “Learn” Key

- Pressing this key once, puts calculator in “learn” mode – ready to remember up to 50 program steps (numbered 00 to 49). Display switches to special format: **00 00**.
- Pressing this key once again takes calculator out of learn mode, calculator retains program steps. (Display reverts to the standard format).

RST – Reset Key

Resets program pointer to first step (step 00), whether entered from the keyboard or encountered as part of a program. (Also, clears Subroutine Return register.)

R/S – Run/Stop Key

When out of learn mode, this is the start/stop key for your program. If the program is stopped, pressing **R/S** starts it; if it's running, pressing **R/S** stops it. When **R/S** is inserted as part of a program (in learn mode) it will stop the program at that point.

2nd **Pause**

While a program is running, encountering a **2nd** **Pause** instruction causes the program to halt and display contents of the display register for about $\frac{3}{4}$ of a second.

2nd **Lbl** **n** – Label Key Sequence

Allows you to label up to 10 points in a program – **n** is from **0** to **9**. (Labels cannot be used more than once within the same program.)

GTO **n** – Go to Label **n** Key Sequence

Causes program pointer to immediately go to label **n** (**n** from **0** to **9**), whether encountered as part of a program, or used from the keyboard.

GTO **2nd** **nn** – Go to Step Number **nn** Key Sequence (**nn** from **00** to **49**) – May be used when out of learn mode only. Positions program pointer at step number **nn**.

PROGRAM DECISION-MAKING

2nd **DSZ** — Decrement and Skip on Zero Key Sequence

Works together with memory zero. When **2nd** **DSZ** is encountered in a program:

- First, the contents of memory zero are decreased by one (Increased by one if the contents are negative),
- If the result is *NOT ZERO*, the calculator proceeds to the step following **2nd** **DSZ**.
- If the result *IS ZERO*, the calculator *SKIPS* the step following **2nd** **DSZ**, and continues.

INV **2nd** **DSZ** — Decrement and Skip if not Zero Key Sequence

When encountered in a program:

- First, the contents of memory zero are decreased by one (increased if the contents are negative).
- If the result is *NOT ZERO*, the calculator *SKIPS* the step following **INV** **2nd** **DSZ** and continues.
- If the result *IS ZERO*, the calculator proceeds to the step following **2nd** **DSZ**.

x↔t — x exchange with t Key

Swaps what's in the display register with what's in the "t" or "test" register. (The t register is memory 7.)

The Conditional Transfer Test Key Sequences — cause the calculator to compare the contents of display (or "x") register with what's in the test (or "t") register, and ask one of the 4 questions below:

2nd **x=|** —

Is x equal to t?

INV **2nd** **x=|** Is x not equal to t? ($x \neq t$)

2nd **x>|** Is x greater than or equal to t?

INV **2nd** **x>|** Is x less than t? ($x < t$)

If the answer is *YES*, program goes directly to step that follows key sequence.

If the answer is *NO*, program *SKIPS* step that follows key sequence, and continues.

SUBROUTINES:

SBR n and **INV SBR** Key Sequences

To Create a Subroutine — just begin any series of program steps you need to use repetitively with a label. End the series of steps with an **INV SBR** key sequence.

To Use a Subroutine — Insert an **SBR** n Key sequence in your program where n is the label number of the subroutine.

EDITING KEYS:

SST — Single Step Key

Steps through program steps one at a time. When used in "learn" mode, displays program key codes sequentially. When used out of "learn" mode, executes program one step at a time.

BSI — Back Step Key

When used in "learn" mode, steps backwards through a program one step at a time.

To Write Over a Program Step:

Just get to the exact step number of a step you need to change, and (while in "learn" mode) key in the new instruction. It will replace the old one.

2nd Nop — No Operation Key

Can be used while in learn mode to blank out any program step with a null step.

2nd Ins — Insert Key Sequence

To insert program steps, just get to the location at which you'd like to add steps and press **2nd Ins** (while in "learn" mode). That instruction, and all that follow it, will be moved down one step.

2nd Del — Delete Key Sequence

To delete program steps, just get to the location of any step you'd like to delete, and (while in "learn" mode) press **2nd Del**. The instruction at that location will be deleted, and all those after it will be "brought up" one location to fill the gap it leaves.

CALCULATOR KEY PROGRAM CODES

Rows	No	Minus	log	18	C.t	19				
1	2nd	Code	INV	Sign	lnx	13	CE	14	CLR	15
2	D.MS	26	P→R	27	sin	28	cos	29	tan	20
	LRN	(No Code)	x↔t	22	x²	23	√x	24	1/x	25
		(No Code)								
3	Pause	36	Ins	Code)	Exc	38	Prd	39	π	30
	SST	(No Code)	STO	32	RCL	33	SUM	34	y^x	35
		(No Code)								
4	Nop	46	Del	Code)	FIX	48	Int	49	 x 	40
	BST	(No Code)	EE	42	(43)	44	÷	45
	Dsz	56							Deg	50
5	GTO	51	7	07	8	08	9	09	X	55
	x=t	66							Rad	60
6	SBR	61	4	04	5	05	6	06	-	65
	x=l	76							Grad	70
7	RST	71	1	01	2	02	3	03	X	75
	Lbl	86			Σ+	88	x̄	89	σ²	80
8	R/S	81	0	00	•	83	+/-	84	=	85

Columns

1	2	3	4	5
(for second functions)				
6	7	8	9	0

Display in "Learn" Mode

