CP-X201 series

CC Closed Captioning

Key Features

- 2,200 ANSI Lumens
- Native XGA Resolution
- 7.7 lbs.
- 2 RGB Inputs / 1 RGB Output
- 7 Watt Audio Output
- 29 dB (Whisper Mode)
- Component / Composite / S-Video Inputs

- Approx. 4,000 Hours (Whisper Mode)*
- Security Bar & Transition Detector
- Side-Mounted Hybrid Filter (2,000 Hours between maintenance)
- Instant On/Off
- Audio Pass Through
- Template Function
- Power Saving Mode

Specifications

|		
Model Name		CP-X201 Series
Liquid Crystal Panel Structure		0.63" Polysilicon Active-matrix TFT x 3
Number of Pixels		786,432 Pixels
Resolution	Video	540 TV lines
	RGB	1024 dots x 768 lines
Colors		16.7 million colors
Aspect Ratio		Native 4:3 / 16:9 compatible
Lens		F2.3 - 2.5, manual zoom x 1.2
Throw Ratio (distance : width)		1.5 - 1.7 : 1
Lamp		220W UHB
Brightness		2,200 ANSI lumens
Expected lamp Life		Approximately 3,000 hours (normal) 4,000 hours (whisper)*
Contrast Ratio		500 : 1
Speaker Output		7W (1 speaker)
Power Supply		AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption		320W
Operating Temperature		5℃ - 35℃ (41℉ - 95℉)
Input Signals	RGB	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, MAC13", MAC16"
	Composite Video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N
	Component Video	480i, 576i, 480p, 720p, 1080i
Acoustic Noise Level		35 dB (29 dB in whisper mode)
H-Sync		15 kHz - 106 kHz
V-Sync		50 kHz - 120 kHz
Vertical Keystone		+ / - 30°
Approvals		UL60950 / C-UL, FCC Part15, Class B, EN60950
RGB Input	Analog RGB	15-pin D-sub connector x 2
RGB Output	RGB	15-pin D-sub connector x 1
Video Input	S-Video	Mini DIN 4-pin connector x 1
	Composite Video	RCA jack x 1
	Component Video	RCA jack x 3
Audio	Input	Stereo mini jack x 2, RCA (L/R) x 1 pair
	Output	Stereo mini jack x 1
Control Terminals		9-pin D-sub connector x 1 (RS-232 control)
Other		USB connector (USB mouse) x 1
Dimensions (W x D x H)		13.4" x 10.6" x 3.9"
Weight		7.7 lbs.
Closed Caption		CC1, CC2, CC3, CC4, T1, T2, T3, T4
Additional Features		Kensington Slot, Digital Gamma Correction, Whiteboard / Blackboard Mode, Input Source Naming, MyMemory / MyScreen / MyButtons / MyText, Auto V Keystone, Serial Number on Side
Supplied Accessories		Remote Control, Batteries (AA), RGB cable, RCA Video Cable, US Power Cord, Multiple language operator / Safety Manual, Soft Case
Lamp		CPX201/301/401LAMP (DT00911)
Remote Control		HL02483
Filter		MU05611

Screen Size 4:3 — Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	34	41
60	48	70	84
80	64	93	112
100	80	117	140
120	96	140	169
150	120	176	211
200	160	234	282
300	240	352	423

Throw Ratio: 1.5 - 1.7:1 (distance : width)
*Measured in inches

* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage.
  Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.