


計算機程式設計

Computer Programming


Arrays

Instructor: 林英嘉

2024/10/14



[W6 Slido: #1281345](#)



[GitHub repo](#)

Before the course ...

- The scoring about this course:
 - Quiz 3% * 15 times (free for three times) = 45%
 - Assignments 5% * 5 times = 25%
 - Midterm exam 10% * 2 times = 20%
 - Final exam 10%

Before the course ...

- The scoring about this course:

- Quiz 3% * 15 times (free for three times) = 45%

- Assignments 5% * 5 times = 25%

- Midterm exam 10% * 2 times = 20%

- Final exam 10%

You will at least get 70% if you take all the quizzes and finish the assignments.



Before the course ...


- You can download the Midterm exam questions and answers via
 - <https://github.com/mcps5601/C-course-materials>

Outline

- Int Arrays
 - Uni-dimensional arrays
 - Multi-dimensional arrays
- Memory Address of Arrays
 - The concept of memory address

What are Arrays?

- Arrays: 陣列
- An array is a **data structure** containing a number of data values, all of which **have the same type**.




Arrays in different dimensions

One-dimensional Array



Two-dimensional Array



Arrays in different dimensions

One-dimensional Array

Index



0



1



2



3

Two-dimensional Array

0



1



Index

0

1

2

3

Declaration of Arrays

```
data_type array_name[num_elements];
```

the number of elements in the array



Declaration of Arrays

```
data_type array_name[num_elements];
```

the number of elements in the array

```
int score[4]; // 4 int elements in the array `score`  
float temp[7]; // 7 float elements in the array `temp`
```

Array Subscripting

To access a value in an array, we can perform **array subscripting** (or called **array indexing**).

使用索引取得陣列中的元素



	score[0]	score[1]	score[2]	score[3]
Index	1	2	3	4

Array Subscripting

To access a value in an array, we can perform **array subscripting** (or called **array indexing**).

使用索引取得陣列中的元素



```
int score[4];
```

	score[0]	score[1]	score[2]	score[3]
Index	1	2	3	4

Assigning values to an array (Example 1)

C-course-materials/04-Arrays/assigning_val_ex1.c

```
#include <stdio.h>
int main(){
    int score[4]; // 4 integer elements in the array `score`
    score[0] = 80;
    score[1] = 85;
    score[2] = 90;
    score[3] = 100;

    for (int i = 0; i < 4; i++){
        printf("Value: %d (index: %d)\n", score[i], i);
    }
}
```

Assigning values to an array (Example 2)

C-course-materials/04-Arrays/assigning_val_ex2.c

Input

80 85 90 100

```
#include <stdio.h>
int main(){
    int score[4];
    int i = 0; // i: index

    while (i < 4) {
        scanf("%d", &score[i]);
        i++;
    }
    for (int i = 0; i < 4; i++){
        printf("Value: %d (index: %d)\n", score[i], i);
    }
}
```

Array Initialization

- We can use **braces** to initialize the values for an array.

```
int score[4] = {80, 85, 90, 100};
```

Array Initialization

- We can use **braces** to initialize the values for an array.

```
int score[4] = {80, 85, 90, 100};
```

Initializer

Key Points When Initializing arrays (1)

- When an initializer is present, the **length** of the array **can be omitted**.

```
int score[] = {80, 85, 90, 100};
```

Key Points When Initializing arrays (2)

C-course-materials/04-Arrays/shorter_initializer.c

- When the initializer is shorter than the array, **zero values** will be appended.

```
#include <stdio.h>
int main(){
    int score[4] = {80, 85, 90};
    for (int i = 0; i < 4; i++){
        printf("Value: %d (index: %d)\n", score[i], i);
    }
}
```


Output

```
Value: 80 (index: 0)
Value: 85 (index: 1)
Value: 90 (index: 2)
Value: 0 (index: 3)
```

Key Points When Initializing arrays (2)

- When the initializer is shorter than the array, **zero values** will be appended.
 - This process is also called zero-initialization.
- Advantage: We can easily initialize a big array with all zeros.

```
int score[10000] = {};  
int score[10000] = {0};
```



At least one value should be placed in an initializer for earlier C standards like C90 or C99
(Default C11 in gcc 8.3)

Key Points When Initializing arrays (3)

C-course-materials/04-Arrays/longer_initializer.c

- An initializer **should not be longer** than its array.

```
#include <stdio.h>
int main(){
    int score[3] = {80, 85, 90, 100};
    for (int i = 0; i < 4; i++){
        printf("Value: %d (index: %d)\n", score[i], i);
    }
}
```

- C does not check the boundary of an array, so this code **will not cause a compilation error**.
- In this case, the last one is the **garbage value** left in the memory.



How to get the array length?

- We use `sizeof` to get the size of **an element in an array**.

```
sizeof(array)/sizeof(array[0]);
```

Get the size of the entire array

Get the size of an
element in the array



Array



An element



How to get the array length?

- We use `sizeof(array)` to get the size of **an element in an array**.

```
sizeof(array) / sizeof(array[0]);
```

Get the size of the entire array

Get the size of an
element in the array



Array



An element


How to get the array length?

- We use `sizeof` to get the size of **an element in an array**.


```
sizeof(array) / sizeof(array[0]);
```

Get the size of the entire array

Get the size of an
element in the array



- Array length = Number of elements



Array



An element

Using sizeof for arrays

C-course-materials/04-Arrays/sizeof_array.c

- We use **score[0]** to get the size of **an element in an array**.

```
#include <stdio.h>
int main(){
    int score[4] = {80, 85, 90, 100};
    printf("Size of the int array: %d bytes\n", sizeof(score));
    printf("Array length: %d\n", sizeof(score)/sizeof(score[0]));

    float f_score[4];
    printf("Size of the float array: %d bytes\n", sizeof(f_score));
    printf("Array length: %d\n", sizeof(f_score)/sizeof(f_score[0]));

    double d_score[4];
    printf("Size of the double array: %d bytes\n", sizeof(d_score));
    printf("Array length: %d\n", sizeof(d_score)/sizeof(d_score[0]));
}
```


資料類型比較

	大小 (Byte)*	Specifier	數值範圍
int	4	%d	-2,147,483,648 到 2,147,483,647 (範圍2的32次方)
char	1	%c	-128 到 127 或 0 到 255 (取決於是否有符號)
float	4	%f	約 1.2E-38 到 3.4E+38，精度約 6 位十進制之小數
double	8	%lf	約 2.2E-308 到 1.7E+308，精度約 15-16 位十進制之小數

*以64-bit系統為例

Example Problem: Fibonacci Numbers

Write a program that accepts an input N and prints the N-th Fibonacci number

$$fib(i) = \begin{cases} 0, & i = 0 \\ 1, & i = 1 \\ fib(i - 1) + fib(i - 2), & i > 1 \end{cases}$$

<i>fib(i)</i>	0	1	1	2	3	5	8	...
Index	0	1	2	3	4	5	6	

Problem: Fibonacci Numbers

C-course-materials/04-Arrays/fibonacci.c

- Print the N-th Fibonacci Number

```
#include <stdio.h>
int main(){
    int fib[100];
    int n;
    scanf("%d", &n);
    fib[0] = 0;
    fib[1] = 1;
    for (int i = 2; i < n; i++){
        fib[i] = fib[i-1] + fib[i-2];
        printf("%d\n", fib[i]);
    }
    printf("The n-th number is: %d\n", fib[n-1]);
}
```

Problem: Checking a Number for Repeated Digits

Write a program that accepts an input **positive integer** and checks if there is a repeated digit inside it.

Input

28212

Output

Repeated digit found!!

Input

12345

Output

No repeated digit!!

Problem: Checking a Number for Repeated Digits

C-course-materials/04-Arrays/repeated_digits.c

```
#include <stdio.h>
int main() {
    int digit_seen[10] = {0};
    int input_number, digit;
    scanf("%d", &input_number);

    while (input_number > 0) {
        digit = input_number % 10; // Extract the last digit
        if (digit_seen[digit] == 1) {
            printf("Repeated digit\n");
            break;
        }
        else
            digit_seen[digit] = 1; // Mark the digit as seen
        input_number /= 10; // Remove the last digit from the input number
    }
    if (input_number == 0)
        printf("No repeated digit\n");
}
```

Problem: Bubble Sort

Write a program that can print **a sequence in an increasingly sorted manner**.

```
int unsorted[5] = {26, 5, 81, 7, 63};
```

Output

```
5 7 26 63 81
```


```
int unsorted[5] = {5, 4, 3, 2, 1};
```

Output

```
1 2 3 4 5
```


Problem: Bubble Sort (illustration)

- We need to sort the sequence for an increasing order. (small to big)




Problem: Bubble Sort (illustration)

- We need to sort the sequence for an increasing order. (small to big)




Problem: Bubble Sort (illustration)

- We need to sort the sequence for an increasing order. (small to big)




Problem: Bubble Sort (illustration)

- We need to sort the sequence for an increasing order. (small to big)




Problem: Bubble Sort (illustration)

- We need to sort the sequence for an increasing order. (small to big)




Problem: Bubble Sort (illustration)

- We need to sort the sequence for an increasing order. (small to big)



Next: Only compare the items except **the most right one**


Problem: Bubble Sort (code)



C-course-materials/04-Arrays/bubble_sort.c

```
#include <stdio.h>
int main(){
    int unsorted[5] = {26, 5, 81, 7, 63};
    int temp = 0;
    // start bubble sort
    for (int i = 1; i < 5; i++){
        for (int j = 0; j < 5 - i; j++){
            if (unsorted[j] > unsorted[j+1]){
                // swap
                temp = unsorted[j];
                unsorted[j] = unsorted[j+1];
                unsorted[j+1] = temp;
            }
        }
    }
    for (int i = 0; i < 5; i++){
        printf("%d\n", unsorted[i]);
    }
}
```


Problem: Bubble Sort (code)



C-course-materials/04-Arrays/bubble_sort.c

```
#include <stdio.h>
int main(){
    int unsorted[5] = {26, 5, 81, 7, 63};
    int temp = 0;
    // start bubble sort
    for (int i = 1; i < 5; i++){
        for (int j = 0; j < 5 - i; j++){
            if (unsorted[j] > unsorted[j+1]){
                // swap
                temp = unsorted[j];
                unsorted[j] = unsorted[j+1];
                unsorted[j+1] = temp;
            }
        }
    }
    for (int i = 0; i < 5; i++){
        printf("%d\n", unsorted[i]);
    }
}
```


Problem: Bubble Sort (code)



C-course-materials/04-Arrays/bubble_sort.c

```
#include <stdio.h>
int main(){
    int unsorted[5] = {26, 5, 81, 7, 63};
    int temp = 0;
    // start bubble sort
    for (int i = 1; i < 5; i++){
        for (int j = 0; j < 5 - i; j++){
            if (unsorted[j] > unsorted[j+1]){
                // swap
                temp = unsorted[j];
                unsorted[j] = unsorted[j+1];
                unsorted[j+1] = temp;
            }
        }
    }
    for (int i = 0; i < 5; i++){
        printf("%d\n", unsorted[i]);
    }
}
```

Problem: Bubble Sort (code)



C-course-materials/04-Arrays/bubble_sort.c


```
#include <stdio.h>
int main(){
    int unsorted[5] = {26, 5, 81, 7, 63};
    int temp = 0;
    // start bubble sort
    for (int i = 1; i < 5; i++){
        for (int j = 0; j < 5 - i; j++){
            if (unsorted[j] > unsorted[j+1]){
                // swap
                temp = unsorted[j];
                unsorted[j] = unsorted[j+1];
                unsorted[j+1] = temp;
            }
        }
    }
    for (int i = 0; i < 5; i++){
        printf("%d\n", unsorted[i]);
    }
}
```


Multi-dimensional arrays

Multidimensional Arrays

- Take a two-dimensional array as an example:

```
int score[2][4];
```



```
data_type array_name[num_rows][num_columns];
```

dimensions

Array Subscripting (Two-dimensional)

Rows ↓

0	score[0][0]	score[0][1]	score[0][2]	score[0][3]
1	score[1][0]	score[1][1]	score[1][2]	score[1][3]

Index 0 1 2 3

→ **Columns**

Array Subscripting (Two-dimensional)

```
int score[2][4];
```

Rows



0	score[0][0]	score[0][1]	score[0][2]	score[0][3]
1	score[1][0]	score[1][1]	score[1][2]	score[1][3]

Index

0

1

2

3

Columns

Array Initialization (Two-dimensional)

- We can use **nested braces** to initialize the values for a 2-D array.

```
int score[2][4] = {  
    {80, 85, 90, 100},  
    {60, 65, 70, 100}  
};
```

Array Initialization (Two-dimensional)

- We can use **nested braces** to initialize the values for a 2-D array.


```
int score[2][4] = {  
    {80, 85, 90, 100},  
    {60, 65, 70, 100}  
};
```

 Corresponding to rows (2)

Array Initialization (Two-dimensional)

- We can use **nested braces** to initialize the values for a 2-D array.

```
int score[2][4] = {  
    {80, 85, 90, 100},  
    {60, 65, 70, 100}  
};
```



Corresponding to rows (2)



Corresponding to columns (4)

You can omit one of the dimensions

- Same results can be obtained from the following code.

```
int score[][4] = {  
    {80, 85, 90, 100},  
    {60, 65, 70, 100}  
};
```

```
int score[2][] = {  
    {80, 85, 90, 100},  
    {60, 65, 70, 100}  
};
```

- Omit both dimensions will raise a compilation error.

Assigning values to an array (**while**, scanf)

Input

80 85 90 100 60 65 70 100

(Page: 1/2)

```
#include <stdio.h>
int main(){
    int score[2][4];
    int i = 0, row = 0, col = 0;

    while (i < 8) {
        scanf("%d", &score[row][col]);
        i++; // index increment
        col++;
        if (i % 4 == 0){
            row++;
            col = 0;
        }
    }
}
```

Assigning values to an array (**while**, **scanf**)

(Page: 2/2)

```
for (row = 0; row < 2; row++){  
    for (col = 0; col < 4; col++){  
        printf("%d at (%d, %d)\n", score[row][col], row, col);  
    }  
}
```


Assigning values to an array (**for**, **scanf**)

Input 80 85 90 100 60 65 70 100

```
#include <stdio.h>
int main(){
    int score[2][4];
    int i = 0, row = 0, col = 0;

    for (row = 0; row < 2; row++){
        for (col = 0; col < 4; col++){
            scanf("%d", &score[row][col]);
        }
    }
    for (row = 0; row < 2; row++){
        for (col = 0; col < 4; col++){
            printf("%d at (%d, %d)\n", score[row][col], row, col);
        }
    }
}
```

Three-dimensional Arrays



Three-dimensional Arrays

Width



```
int score[3][2][4];
```

score[2][0][0]	score[2][0][1]	score[2][0][2]	score[2][0][3]
score[1][0][0]	score[1][0][1]	score[1][0][2]	score[1][0][3]
score[0][0][0]	score[0][0][1]	score[0][0][2]	score[0][0][3]
score[0][1][0]	score[0][1][1]	score[0][1][2]	score[0][1][3]

Width

Array Initialization (Three-dimensional)

- We can also use **nested braces** to initialize the values for a 3-D array.
- This is a **2-D** array initialization:

```
int score[2][4] = {  
    {80, 85, 90, 100},  
    {60, 65, 70, 100}  
};
```

Array Initialization (Three-dimensional)

- We can also use nested braces to initialize the values for a 3-D array.
- This is a **3-D** array initialization (in this case, **three times of the 2-D array**):

```
int score[3][2][4] = {{  
    {80, 85, 90, 100},  
    {60, 65, 70, 100}  
},  
{  
    {80, 85, 90, 100},  
    {60, 65, 70, 100}  
},  
{  
    {80, 85, 90, 100},  
    {60, 65, 70, 100}  
}};
```

Observation for the shape of a 3-D array

C-course-materials/04-Arrays/observe_shape_3D.c

- Get the number of all elements of the array

```
int total_elements = sizeof(score) / sizeof(score[0][0][0]);
```

- Get the size of the first dimension

```
int dim1 = sizeof(score) / sizeof(score[0]);
```

- Get the size of the second dimension

```
int dim2 = sizeof(score[0]) / sizeof(score[0][0]);
```

- Get the size of the third dimension

```
int dim3 = sizeof(score[0][0]) / sizeof(score[0][0][0]);
```


Observation for the shape of a 3-D array

- Get the number of all elements of the array

```
int total_elements = sizeof(score) / sizeof(score[0][0][0]);
```

score[2][0][0]	score[2][0][1]	score[2][0][2]	score[2][0][3]
score[1][0][0]	score[1][0][1]	score[1][0][2]	score[1][0][3]
score[0][0][0]	score[0][0][1]	score[0][0][2]	score[0][0][3]
score[0][1][0]	score[0][1][1]	score[0][1][2]	score[0][1][3]

Observation for the shape of a 3-D array

- Get the size of the first dimension [3]

```
int dim1 = sizeof(score) / sizeof(score[0]);
```

score[2][0][0]	score[2][0][1]	score[2][0][2]	score[2][0][3]
score[1][0][0]	score[1][0][1]	score[1][0][2]	score[1][0][3]
score[0][0][0]	score[0][0][1]	score[0][0][2]	score[0][0][3]
score[0][1][0]	score[0][1][1]	score[0][1][2]	score[0][1][3]

Observation for the shape of a 3-D array

- Get the size of the second dimension [2]

```
int dim2 = sizeof(score[0]) / sizeof(score[0][0]);
```

score[0][0][0]	score[0][0][1]	score[0][0][2]	score[0][0][3]
score[0][1][0]	score[0][1][1]	score[0][1][2]	score[0][1][3]


Observation for the shape of a 3-D array

- Get the size of the third dimension [4]


```
int dim3 = sizeof(score[0][0]) / sizeof(score[0][0][0]);
```

score[0][0][0]	score[0][0][1]	score[0][0][2]	score[0][0][3]
----------------	----------------	----------------	----------------

10/22 Recap for Arrays



[W7 Slido: #3533560](#)



[GitHub repo](#)


What a 2-D Array is (in index)

```
int score[2][4];
```

Rows	0	score[0][0]	score[0][1]	score[0][2]	score[0][3]
	1	score[1][0]	score[1][1]	score[1][2]	score[1][3]
Index	0	1	2	3	

Columns

(Cartesian Coordinate System)




What a 2-D Array is (in coordinate)

```
int score[2][4];
```

Rows ↓	0	(0,0)	(0,1)	(0,2)	(0,3)
	1	(1,0)	(1,1)	(1,2)	(1,3)
Index		0	1	2	3

Columns →

(Cartesian Coordinate System)



W6 Quiz: The 4x4 spiral matrix

https://github.com/mcps5601/C-course-materials/blob/main/quizzes/w6_ans.c

```
int N = 4;
int num = 1;
int arr[4][4] = {0};
int movements[4][2] = {{0, 1}, {1, 0}, {0, -1}, {-1, 0}};
int row = 0, col = 0;
int direction = 0;
```

(0,0)	(0,1)	(0,2)	(0,3)

(0,0)	(0,1)	(0,2)	(0,3)
			(1,3)
			(2,3)
			(3,3)

(0,0)	(0,1)	(0,2)	(0,3)
			(1,3)
			(2,3)
(3,0)	(3,1)	(3,2)	(3,3)

(0,0)	(0,1)	(0,2)	(0,3)
(1,0)			(1,3)
(2,0)			(2,3)
(3,0)	(3,1)	(3,2)	(3,3)

W6 Quiz: The 4x4 spiral matrix

https://github.com/mcps5601/C-course-materials/blob/main/quizzes/w6_ans.c

```
while (num <= N * N){
    arr[row][col] = num++;

    int next_row = row + movements[direction][0];
    int next_col = col + movements[direction][1];

    // over the boundary or the next cell has been filled
    if (next_row < 0 || next_col < 0 || next_row >= N || next_col >= N ||
arr[next_row][next_col] != 0){
        direction = (direction + 1) % 4;
        next_row = row + movements[direction][0];
        next_col = col + movements[direction][1];
    }
    row = next_row;
    col = next_col;
}
```


Observation for the shape of a 3-D array

- Get the number of all elements of the array

```
int total_elements = sizeof(score) / sizeof(score[0][0][0]);
```

score[2][0][0]	score[2][0][1]	score[2][0][2]	score[2][0][3]
score[1][0][0]	score[1][0][1]	score[1][0][2]	score[1][0][3]
score[0][0][0]	score[0][0][1]	score[0][0][2]	score[0][0][3]
score[0][1][0]	score[0][1][1]	score[0][1][2]	score[0][1][3]

Visualization of a 3-D Array



Observation for a 3-D array

C-course-materials/04-Arrays/observe_3D.c

```
int score[3][2][4] = {{
    {80, 85, 90, 100},
    {60, 65, 70, 100}
},
{
    {80, 85, 90, 100},
    {60, 65, 70, 100}
},
{
    {80, 85, 90, 100},
    {60, 65, 70, 100}
}};
for (int i = 0; i < 2; i++) {
    for (int j = 0; j < 4; j++) {
        printf("%2d ", score[2][i][j]);
    }
    printf("\n");
}
for (int i = 0; i < 4; i++) {
    printf("%2d ", score[0][1][i]);
}
```

Important Notes for Arrays

- In C, arrays are not treated as single objects that can be printed or returned at one time.
- Instead, we can get the elements according to **index**.

Memory Address of Arrays

scanf: 用來進行輸入的函數

c_basics p.30

```
scanf(format, &變數1, &變數2, ...);
```

- `scanf`: Read formatted data and store them according to the locations.
 - 可取得自鍵盤輸入的值
- `format`: 一段可包含 **format specifiers** 的字串 (string)
- **&代表位置運算子**，可以將數值存到變數的記憶體位置
- 同`printf`，第二個參數以後的數量與跟 **format specifiers** 一致

&: the Address Operator

- The address operator (&) returns the address of a variable (取址運算子).
- We can use the format specifier **%p** for printing an address.

```
#include <stdio.h>
int main(){
    int score = 100;
    printf("The address of score: %p\n", &score);
}
```


Print the memory address of an array

C-course-materials/04-Arrays/print_array_addr.c

```
#include <stdio.h>
int main(){
    int score[4] = {80, 85, 90, 100};
    printf("The address of this array: %p\n", &score);
    for (int i = 0; i < 4; i++){
        printf("The address of score[%d]: %p\n", i, &score[i]);
    }
}
```

Output

```
The address of this array: 0x7fffffffdd80
The address of score[0]: 0x7fffffffdd80
The address of score[1]: 0x7fffffffdd84
The address of score[2]: 0x7fffffffdd88
The address of score[3]: 0x7fffffffdd8c
```

The memory addresses are represented in base 16

二進制	十進制	十六進制
0000 0000	0	00
0000 0001	1	01
0000 0010	2	02
0000 0011	3	03
0000 0100	4	04
0000 0101	5	05
0000 0110	6	06
0000 0111	7	07
0000 1000	8	08
0000 1001	9	09
0000 1010	10	0A
0000 1011	11	0B
0000 1100	12	0C

```
#include <stdio.h>
int main(){
    int num = 12;
    printf("%x", num);
}
```

- Use %x to print base 16 integers

Properties of Array Address

- The first element of an array shares the address of the array.
- The memory addresses of an array in C are contiguous. For an int array:
 - `arr[0]` is at address A
 - `arr[1]` is at address $A + 4$
 - `arr[2]` is at address $A + 8$
 - `arr[3]` is at address $A + 12$

Memory Address for a Multi-dimensional Array

C-course-materials/04-Arrays/print_3Darray_addr.c

```
#include <stdio.h>
int main(){
    int score[2][3][4] = {
        {
            {80, 85, 90, 100},
            {75, 80, 85, 90},
            {60, 65, 70, 75}
        },
        {
            {55, 60, 65, 70},
            {50, 55, 60, 65},
            {45, 50, 55, 60}
        }
    };
    printf("The address of score: %p\n", &score);
    printf("The address of score[0]: %p\n", &score[0]);
    printf("The address of score[0][0]: %p\n", &score[0][0]);
    printf("The address of score[0][0][0]: %p\n", &score[0][0][0]);
    printf("The address of score[1]: %p\n", &score[1]);
    printf("The address of score[1][0]: %p\n", &score[1][0]);
    printf("The address of score[1][0][0]: %p\n", &score[1][0][0]);
}
```

Memory Address for a Multi-dimensional Array

C-course-materials/04-Arrays/print_3Darray_addr.c

```
#include <stdio.h>
int main(){
    int score[2][3][4] = {
        {
            {80, 85, 90, 100},
            {75, 80, 85, 90},
            {60, 65, 70, 75}
        },
        {
            {55, 60, 65, 70},
            {50, 55, 60, 65},
            {45, 50, 55, 60}
        }
    };
    printf("The address of this array: %p\n", &score);
    for (int i = 0; i < 2; i++){
        for (int j = 0; j < 3; j++){
            for (int k = 0; k < 4; k++){
                printf("The address of score[%d][%d][%d]: %p\n", i, j, k, &score[i][j][k]);
            }
        }
    }
}
```

```
The address of this array: 0x7fffffffdd20
The address of score[0][0][0]: 0x7fffffffdd20
The address of score[0][0][1]: 0x7fffffffdd24
The address of score[0][0][2]: 0x7fffffffdd28
The address of score[0][0][3]: 0x7fffffffdd2c
The address of score[0][1][0]: 0x7fffffffdd30
The address of score[0][1][1]: 0x7fffffffdd34
The address of score[0][1][2]: 0x7fffffffdd38
The address of score[0][1][3]: 0x7fffffffdd3c
The address of score[0][2][0]: 0x7fffffffdd40
The address of score[0][2][1]: 0x7fffffffdd44
The address of score[0][2][2]: 0x7fffffffdd48
The address of score[0][2][3]: 0x7fffffffdd4c
The address of score[1][0][0]: 0x7fffffffdd50
The address of score[1][0][1]: 0x7fffffffdd54
The address of score[1][0][2]: 0x7fffffffdd58
The address of score[1][0][3]: 0x7fffffffdd5c
The address of score[1][1][0]: 0x7fffffffdd60
The address of score[1][1][1]: 0x7fffffffdd64
The address of score[1][1][2]: 0x7fffffffdd68
The address of score[1][1][3]: 0x7fffffffdd6c
The address of score[1][2][0]: 0x7fffffffdd70
The address of score[1][2][1]: 0x7fffffffdd74
The address of score[1][2][2]: 0x7fffffffdd78
The address of score[1][2][3]: 0x7fffffffdd7c
```

Properties of Multi-dimensional Array Address

- **Contiguous Memory:**
 - The memory addresses of an array in C are contiguous.
 - Row major ordering
- **Same Address for Initial Elements:**
 - The address of `score`, `score[0]`, `score[0][0]`, and `score[0][0][0]` are the same, as they all point to the first element of the array.
 - The address of `score[1]`, `score[1][0]`, and `score[1][0][0]` are the same.