IntentProbe: Many Task-Specific Probes from a Single Frozen Small-Model Forward Pass

Status: public research manuscript v0.1.3; not peer reviewed
Author: Wan Sheng Leung
Publisher: MCPware, a product and research brand of GEASS LABS INC.
Updated: 19 October 2026
DOI: 10.5281/zenodo.23471117

This manuscript is the empirical systems evaluation of the public IntentProbe: One Local Model Pass, Many Task-Specific Probes architecture note. The note explains the design; this paper reports the readout search, task comparisons and shared-runtime measurements.

Abstract

Agent workflows need many guardrail and classification checks on the same input. We present IntentProbe, a CPU sidecar architecture that runs a small frozen local language model in a single forward pass, then applies independently trained activation probes to selected hidden states. It supplies task scores without generating a separate LLM-as-a-judge answer for every check. A hosted agent's hidden states are not required: the sidecar reads its own local sensor model. Prompt injection, authorization, toxicity, and memory write motivate the broader project; the shared 16-head timing suite below covers the specific tasks listed in its manifest. Our empirical programme has three parts. First, a 24-cell screen crosses six 230M--1B backbones with sentiment, spam, toxicity, and jailbreak detection. Selected pooling and depth vary by model and task; even toxicity and jailbreak labels on identical ToxicChat prompts select different readouts. Second, a six-cell sentinel compares activation heads, matched TF-IDF, and direct output judgments from two local backbones on authorization-to-execute, toxicity, and sentiment. It finds substantial task-by-model interaction rather than a universal ordering of methods. This motivates an architecture in which heads, labelled datasets, readout recipes, and even the backbone remain replaceable components instead of being treated as one fixed detector.

Third, we freeze 16 binary heads on one exact Qwen2.5-0.5B revision across five real-text sources: toxicity, jailbreak, spam, sentiment, five emotion labels, and seven conversational-pragmatics labels. Native heldout AUPRC ranges from 0.0836 to 0.9804 because the tasks and prevalences differ. On one six-core CPU, mean latency rises from 68.63 ms for one forward plus one head to 73.34 ms for the same forward plus 16 heads, a ratio of 1.069 (paired-bootstrap 95% CI 1.056--1.078). In the separate matched ten-prompt comparator, one forward plus 16 heads averages 62.70 ms and 16 repeated base-model forwards average 956.71 ms, a repeated/shared ratio of 15.26 (95% CI 15.04--15.49). Peak process memory changes by +0.73 MiB; the 16 saved probe artifacts occupy 386,121 bytes. The repeated-forward arm omits prompting, LM-head scoring, and generation, so it is a lower bound rather than a complete judge implementation. These results support a modular one-forward/many-readout runtime. The shared runtime is the stable system layer; head quality, calibration, data, and domain specificity can improve independently.

1. Introduction

A workflow may need to answer several questions about one user turn. Is it toxic? Is it a jailbreak? Does it authorize an external action? Is the conversation becoming hostile? Which route should handle it? A straightforward agentic implementation asks a language model each question separately or loads one classifier per question. Both approaches repeat substantial computation.

Frozen-model probing offers another interface. A local decoder already computes one hidden vector per token and layer. A small classifier can read those activations without generating an answer. Multiple classifiers can also share the same forward pass. The systems promise is simple: the backbone is the expensive sensor, while each task head is a small, replaceable readout.

That promise has two conditions. First, the hidden-state head must be useful enough for its own task. Second, serving many heads must actually be cheaper than rerunning the backbone or maintaining a fleet of models. Prior work establishes that hidden-state probes can outperform prompted answers in some settings and that selected tokens and layers matter. It does not make every task, backbone, or readout interchangeable.

We therefore separate four questions:

1. How much does the selected readout vary across models and tasks?
2. How does a trained hidden-state head compare with directly asking the same local model, and how should that evidence govern whether the head is installed?
3. How does CPU latency and memory scale when one forward serves 1, 2, 4, 8, or 16 independent heads?
4. Do the same heads remain numerically stable and well behaved when texts come from other domains?

Our contributions are:

- a 24-cell, six-backbone readout screen over four real-labelled binary tasks;
- a six-cell same-backbone probe-versus-judge sentinel with paired uncertainty and a 12-test AUPRC false-discovery family;
- a 16-head Qwen2.5-0.5B suite whose heads use different pooling methods and hidden-state windows;
- a paired CPU scaling experiment at K=`1,2,4,8,16`, including peak process memory, saved-artifact size, and a deliberately favourable repeated-forward lower bound;
- native heldout discrimination and calibration for every served head, plus an explicitly unlabelled five-source score-shift diagnostic; and
- complete manifests, hashes, row-level timing artifacts without source text, and tests that enforce row alignment and interpretation boundaries.

We do not claim to invent activation probing, layer search, or multi-head inference. The contribution is the measured combination: independently selected readout manifests for heterogeneous operational tasks, served from one sub-1B local backbone pass.

2. Related work

2.1 Hidden representations versus generated judgments

Tillman and Mossing compare prompted outputs with raw, prompted, and sparse-autoencoder activation probes. Their results show that generated labels are a serious baseline but do not exhaust information linearly available inside the same model. Representation-as-a-Judge reports a similar extraction gap for reasoning-quality evaluation with frozen small models. Trick or Neat finds direct prompting fragile for several ambiguity classes while layer-wise probes can be strong. Prompting Underestimates LLM Capability for Time Series Classification reports the same broad pattern in a different modality.

These papers support the premise that a model can encode a distinction without reliably verbalizing it. They do not support a universal claim that probes beat prompting. Task, prompt, training volume, backbone, readout, and distribution shift remain material.

2.2 Single-pass classification and routing

Goodfire and Rakuten deploy probes on a separate sidecar for PII detection and discuss adding further probes at low marginal inference cost. SingProbe supplies an open intrinsic guardrail framework that reuses a serving model's hidden states for intent, safety, and hallucination monitoring. Lion Warden jointly trains a compact encoder and seven security heads and provides CPU inference.

A BERTology View of LLM Orchestrations searches token- and layer-selective probes on a frozen serving model. It compares against prompted and standalone classifiers and measures the latency and memory saved by reusing a serving pass. LatentGate uses a frozen small model, mean pooling, PCA whitening, and a linear probe for semantic routing. You Only Judge Once uses a discriminative multimodal reward model to score multiple responses in one pass and reports up to N-fold wall-clock speedup and FLOP reduction. Those systems establish the value of shared computation. Our experiment narrows the question to a 0.5B CPU sidecar whose heads are independently trained, independently attachable, and allowed to read different layer windows and pooling rules.

2.3 Authorization and narrow signal contracts

Rammouz and colleagues' forthcoming access-control paper addresses permissions in large language models. Its organizational access-control setting is adjacent to our question of whether a user's language authorizes executing a specific action. Calibration, Not Answer Selection supplies an important boundary: a latent signal can be useful for one declared target while failing on a nearby decision. We apply that boundary throughout. Decodability is not causal understanding, and a probabilistic authorization score is not an execution permission.

2.4 Readout selection and operational checks

Nordby, Pais and Parrack report that useful probing layers vary across deception tasks and model architectures, and study learned multi-layer ensembles. That motivates testing the readout recipe rather than treating the final layer as a default guarantee. Our screen uses simpler adjacent windows and holds the backbone fixed during head training.

Gao separates predictive probe scores from calibrated alarm policies. Blandfort and Graham find concrete false-positive and false-negative patterns by red-teaming probes with prompted models. These studies motivate the separate calibration, shift and head-admission checks in our architecture; the timing experiment measures the cost of serving heads that have already been trained.

3. Data and tasks

3.1 Cross-backbone matrix

The six-backbone matrix uses LFM2.5-230M, Granite 4.0 350M, Qwen2.5-0.5B, Qwen3-0.6B, Qwen3.5-0.8B, and MiniCPM5-1B. It contains four binary tasks:

- binary sentiment from the official Stanford Sentiment Treebank root sentences;
- spam from the UCI SMS Spam Collection;
- toxicity from the human-authored portion of ToxicChat 0124; and
- jailbreak intent from the same ToxicChat prompts.

The cleaned SST-2 experiment retains 9,602 rows and an untouched 1,821-row official test. SMS Spam is reduced from 5,574 messages to 5,159 exact-unique messages, with 774 held out. The leakage-repaired human ToxicChat slice contains 5,441 prompts, with 2,790 official-test rows. Exact duplicates, cross-split overlaps, and label-conflict groups are handled before activation extraction according to each source manifest.

3.2 Shared 16-head suite

The shared Qwen2.5-0.5B suite adds five GoEmotions labels and seven Conversation AI Unhealthy Comments attributes to sentiment, spam, toxicity, and jailbreak detection:

Source	Served heads	Native heldout rows
ToxicChat 0124	toxicity; jailbreaking	2,790 each
UCI SMS Spam	spam	774
SST-2	positive sentiment	1,821
GoEmotions	neutral; anger; sadness; admiration; curiosity	5,409 each
Unhealthy Comments	condescending; dismissive; unfair generalisation; sarcastic; antagonize; generalisation; hostile	4,424 each

GoEmotions is pinned to the official filtered files and cleaned to 53,905 comments after removing exact-text conflict and cross-split overlap groups. Unhealthy Comments is pinned to repository revision `55934d0079073095af8b69807d235e40c8aceff4` and cleaned from 44,355 to 44,323 rows. Its labels come from human judgments, but the released files omit author and article identifiers. UCC uncertainty is therefore row-level and cannot establish unseen-author or unseen-thread performance.

3.3 Sentinel panels

The direct-judge sentinel fixes two backbones: LFM2.5-230M as the cost anchor and Qwen3.5-0.8B as the quality anchor. It evaluates 512 heldout toxicity rows, 512 heldout sentiment rows, and all 156 human-labelled DelegationCheck authorization rows in 26 construction families. The authorization activation heads are trained on the earlier silver authorization corpus and transferred without using human labels for fitting.

4. Methods




Figure 1. The activation backplane: one model pass that every probe plugs into. At runtime, independent task readouts share the frozen model's hidden states. Offline, labelled data selects each readout and fits its head. Shared inference and head application are measured here; general compatible-head loading and host policy are specified integration points.

4.1 Activation readout search

Backbone weights remain frozen. For Qwen2.5-0.5B, each input produces 25 hidden-state outputs of width 896. The simple candidate family combines:

- masked mean, last non-padding token, or featurewise masked maximum over input tokens;
- every individual hidden output and every adjacent width-two or width-three window; and
- training-split featurewise standardization followed by a class-weighted logistic head.

This gives 216 candidates per binary Qwen task. Window representations average the standardized layer features. Selection uses the task's frozen validation metric: AUROC for SST-2 and AUPRC for the imbalanced binary tasks. The winner is refit on train plus validation once,

then scored on the untouched test. The matched surface baseline is class-weighted word-and-character TF-IDF logistic regression on the same fit rows. Other backbones use the same conceptual family with candidate count adjusted for depth.

4.2 Direct same-backbone judges

For each sentinel cell, we compare the selected activation head and TF-IDF with four direct-judge arms: zero-shot and rubric prompts, each read either by normalized YES/NO next-token likelihood or strict deterministic generation. Choice likelihood supplies a continuous score without depending on the model emitting a parseable word. Generated outputs use strict parsing, and invalid outputs are retained and counted.

The primary probe-versus-judge family contains 12 paired AUPRC comparisons: two backbones, three tasks, and two choice-likelihood prompts. Each cell uses 2,000 paired bootstraps. Authorization resamples whole construction families; toxicity and sentiment resample rows. Benjamini--Hochberg controls false discovery at 0.05 across the 12 AUPRC tests.

4.3 One-forward scaling protocol

The systems experiment freezes the exact Qwen2.5-0.5B revision `060db6499f32faf8b98477b0a26969ef7d8b9987` and 16 unique probe hashes. K is cumulative and fixed at `1,2,4,8,16`. Each K cell runs in a separate process. The latency panel contains the same 80 real heldout texts at every K: 16 from each of the five sources. Batch size is one, two warm-up inference calls precede timing and are not recorded, tokenization is included, and row identity and token count must match exactly across K.

The shared path tokenizes once, calls `AutoModel` once with all hidden states, applies only the first K frozen normalization/readout recipes, and records tokenization, forward, head, and total time. Peak RSS is process `ru_maxrss`. Paired ratios use 2,000 row-bootstrap resamples.

The comparator tokenizes once and repeats the base `AutoModel` forward K times on ten fixed prompts. It omits a task prompt, language-model head, choice-likelihood calculation, parser, and generation. It therefore understates the cost of K separate LLM judges and is labelled a repeated-forward lower bound throughout.

4.4 Quality, calibration, and score shift

Every head keeps its native heldout AUPRC, AUROC, accuracy, balanced accuracy, F1, Brier score, and 10-bin expected calibration error. We do not average incompatible labels into a single product score. A separate 320-row panel applies all 16 heads to 64 texts from each source. Outside a head's native label contract, these scores have no error label. We report means, upper tails, threshold rates, and Kolmogorov--Smirnov distance from the full native score distribution as descriptive shift diagnostics only.

5. Results

5.1 Readout choice varies across model and task

The four-task, six-backbone matrix contains 24 completed binary cells.

Task	Selected pooling across six backbones	Normalized-depth range	Activation vs TF-IDF, both planned metrics
Sentiment	masked mean 5; last non-padding 1	0.500--0.607	activation advantage in 6/6 cells
SMS spam	masked mean 3; masked max 3	0.438--0.750	activation advantage in 2/6; unresolved in 4/6
Toxicity	masked mean 6	within combined ToxicChat range 0.250--0.833	activation advantage in 2/6
Jailbreak	masked mean 3; masked max 3	within combined ToxicChat range 0.250--0.833	activation advantage in 0/6

The strongest within-input evidence comes from ToxicChat: toxicity and jailbreak use identical text rows but select different depth and pooling patterns. Across its 12 cells, the median absolute within-model task difference in normalized depth is 0.1875. A descriptive variance decomposition of selected depth attributes 54.8% to model-by-task interaction, 43.5% to model, and 1.7% to task. With only two tasks, these shares have no replicated interaction error term and are not population estimates.

A universal ToxicChat readout—masked mean, width two, normalized depth 0.5—has mean validation AUPRC 0.7872. Cell-specific selection reaches 0.8220, a mean regret of 0.0348 for the universal rule on the same validation cells. A model-specific rule reduces mean regret to 0.0142. These are descriptive selection-set comparisons, but they show why a shared runtime still needs task-specific manifests.

5.2 Six-cell direct-judge sentinel

Backbone	Task	Activation AUPRC	TF-IDF AUPRC	Zero-shot choice AUPRC	Rubric choice AUPRC
LFM2.5-230M	Authorization	0.5529	0.4533	0.4423	0.5336
LFM2.5-230M	Toxicity	0.7571	0.7544	0.1300	0.1875
LFM2.5-230M	Sentiment	0.9149	0.9068	0.8896	0.6932
Qwen3.5-0.8B	Authorization	0.3567	0.4533	0.5704	0.4920
Qwen3.5-0.8B	Toxicity	0.8332	0.7544	0.1572	0.1013
Qwen3.5-0.8B	Sentiment	0.9424	0.9068	0.9369	0.9487

Six of the 12 activation-versus-choice-likelihood AUPRC comparisons reject after correction. Both backbones' toxicity activation heads beat both prompts, with corrected q=0.0024 in all four cells. For Qwen3.5 sentiment, activation differs by +0.0055 AUPRC from zero-shot choice likelihood and -0.0063 from rubric choice likelihood; both intervals include zero and both corrected q-values are 0.7971. The strongest adverse cell is Qwen3.5 authorization: activation minus zero-shot choice likelihood is -0.2137 AUPRC, with 95% group-bootstrap CI [-0.3973, -0.0335] and q=0.0480.

Generated labels are also operationally brittle for the smaller cost anchor on toxicity: 91 of 512 zero-shot generations and 163 of 512 rubric generations fail strict YES/NO parsing. Choice likelihood avoids invalid strings but does not remove the task interaction. Toxicity strongly favours the trained hidden-state readout, sentiment is competitive either way on Qwen3.5, and authorization exposes the cost of silver-to-human transfer mismatch.

5.3 Sixteen native heldout heads

The shared Qwen suite contains 11 masked-mean and five masked-max winners. Selected normalized depth spans 0.125--0.792. Native AUPRC spans 0.0836--0.9804 and AUROC 0.7330--0.9959; positive prevalence spans 0.0206--0.4992.

Head	Pooling / outputs	Prevalence	AUPRC	AUROC	Balanced accuracy	Brier	ECE
Toxicity	mean 18--20	0.127	0.709	0.909	0.828	0.091	0.087
Jailbreaking	max 5--7	0.032	0.665	0.950	0.811	0.029	0.030
Spam	max 15--17	0.124	0.980	0.996	0.964	0.012	0.012
Positive sentiment	mean 12	0.499	0.960	0.959	0.892	0.083	0.052
Emotion: neutral	mean 15--16	0.329	0.668	0.817	0.738	0.177	0.117
Emotion: anger	mean 5	0.037	0.323	0.879	0.782	0.102	0.160
Emotion: sadness	mean 16	0.029	0.337	0.911	0.830	0.089	0.136
Emotion: admiration	mean 2--4	0.093	0.601	0.917	0.851	0.105	0.158
Emotion: curiosity	mean 3	0.052	0.414	0.928	0.857	0.081	0.121
Condescending	mean 11--13	0.061	0.190	0.765	0.696	0.175	0.269
Dismissive	max 13	0.034	0.084	0.745	0.677	0.169	0.268
Unfair generalisation	max 15--17	0.021	0.100	0.830	0.717	0.126	0.185
Sarcastic	mean 4--6	0.045	0.112	0.733	0.664	0.187	0.299
Antagonize	mean 15	0.046	0.172	0.787	0.727	0.159	0.251
Generalisation	max 17	0.022	0.101	0.812	0.720	0.130	0.196
Hostile	mean 16--17	0.024	0.094	0.783	0.688	0.134	0.199

The rare UCC labels show why AUROC alone is not sufficient. Several heads rank positives above negatives reasonably well while retaining low AUPRC and poor 0.5-scale calibration. Serving a head cheaply does not make its threshold production-ready.

5.4 One forward plus K heads stays nearly flat

The first panel measures shared-path scaling on all 80 held-out inputs.

K	Shared mean total ms (n=80)	Mean head ms (n=80)	Ratio to K=1	Peak RSS MiB
1	68.63	0.38	1.000	3616.7
2	69.86	0.61	1.018	3615.5
4	70.73	0.73	1.031	3616.1
8	71.78	1.08	1.046	3614.0
16	73.34	1.85	1.069	3617.4

The second panel compares both paths on the same ten prompts.

K	One forward + K heads, mean ms (n=10)	K repeated forwards, mean ms (n=10)	Repeated/shared ratio
1	61.83	57.88	0.94
2	60.30	120.15	1.99
4	60.49	238.73	3.95
8	61.71	475.64	7.71
16	62.70	956.71	15.26

At K=16, the paired mean-latency ratio to K=1 on the 80-row shared-path panel is 1.069, 95% CI [1.056, 1.078]. The repeated-forward ratio to its own K=1 baseline is 16.53, 95% CI [16.39, 16.69]. On the matched ten prompts, the shared-path mean is 62.70 ms and the repeated-forward mean is 956.71 ms. The repeated/shared ratio is therefore 15.26, 95% CI [15.04, 15.49]. The 73.34 ms value in the first panel is the mean over all 80 shared-path rows and is not the denominator of that matched ratio.

Head application itself takes 1.85 ms on average at K=16. The recorded K=16 peak RSS is 3617.4 MiB, only 0.73 MiB above K=1. Saved probe files total 386,121 bytes. Since the shared path requests all hidden outputs even at K=1, these measurements describe the intended attachable-head backplane rather than an optimized single-head special case.

5.5 Cross-domain scores move enough to require monitoring

The 320-row diagnostic records source-dependent score movement. The largest absolute mean shift is +0.301 for the curiosity head on ToxicChat relative to its full native GoEmotions score distribution; the KS distance is 0.406. This is not an error estimate because ToxicChat has no curiosity label. It does show that a fixed threshold can fire at a very different rate when the source changes.

Live runtime scoring reproduces the archived float16-cache behavior closely on each head's 64 native rows: the worst mean absolute score difference is 0.00645 and the minimum Pearson correlation is 0.97986. The worst single-row absolute difference is larger, 0.33849, on jailbreak detection. Live deployment should therefore validate numerical precision and batch behavior instead of assuming bit identity with an offline cache.

6. Discussion

6.1 The useful unit is a readout manifest, not a universal layer

The results reject two easy defaults. The final hidden output is not consistently best, and one pooling/depth recipe does not serve every label. Even when inputs and backbone are identical, toxicity and jailbreak can select different locations. A shared runtime should therefore expose a stable activation backplane -- one model pass that every probe plugs into -- while allowing each head to declare its own renderer, token pooling, layer window, normalization, classifier, calibration, and threshold.

6.2 One pass changes the economics of workflow classification

The backbone dominates cost. Total mean latency was 6.9% higher at K=16 than at K=1. Recorded head application rose from 0.38 ms to 1.85 ms, accounting for 1.47 ms of the 4.70 ms total increase; the remaining 3.23 ms is unattributed. Repeating only the base forward 16 times increased latency approximately sixteenfold on the separate matched panel. This supports the IntentProbe shared-pass, many-probe architecture: one small local sidecar can inspect an input once and fan the same activations into many narrow functions.

This does not require access to Claude, Codex, or another hosted model's hidden states. In that deployment, IntentProbe is a local sidecar. If the primary model is itself local and exposes hidden states, the same readout design can attach to that host and avoid the extra sidecar forward.

6.3 Head quality can improve without changing the architecture

The architecture and the current head artifacts are different objects. A task head reflects one dataset, backbone, readout search, classifier, and calibration procedure at one point in time. Better labels, a stronger backbone, a wider readout search, or another bounded classifier can improve that task while leaving the backplane and every unrelated head unchanged. The sentinel in Section 5.2 is therefore a component-admission test, not a verdict on the architecture.

This separation matters operationally. The shared runtime provides the expensive model pass, versioned hidden-state access, timing, and receipts. Each detector team can improve its own task boundary and publish a new compatible manifest without retraining the backbone or unrelated heads. The general registry and hot-loading path that would promote, roll back, or disable heads at runtime remain specified rather than shipped in the current PyPI package.

Authorization especially needs a separate deterministic boundary. A probe may estimate whether the context looks like authority to act. Exact payload review, recipient binding, scope, expiry, and the right to execute remain explicit state and policy facts outside the classifier.

6.4 What remains for a full systems frontier

This experiment completes the shared-path curve and a conservative repeated-forward lower bound. Three comparison arms remain: one prompted multi-label judge call, separate judge calls with a shared cacheable prefix, and a measured fleet of compact task-specific classifiers on the same hardware. Their actual prompting and cache configurations need to be measured

before claiming the complete quality--latency--RAM frontier. The current result is narrower and still useful: given 16 existing heads, their marginal serving cost is small relative to one 0.5B forward.

7. Limitations

1. The 16-head systems result uses one Qwen2.5-0.5B revision and one CPU machine.
2. K uses one fixed cumulative head order. Random head combinations are not evaluated.
3. K cells run in ascending order without randomized interleaving or CPU-frequency pinning. Paired intervals capture prompt variation, not run-order uncertainty.
4. Peak RSS is one process observation per K and includes the Python, PyTorch, Transformers, model, and inference stack.
5. The repeated-forward arm is intentionally incomplete and cannot be reported as a full prompted LLM-judge benchmark.
6. The direct-judge sentinel uses LFM2.5 and Qwen3.5, while the systems suite uses Qwen2.5. The two experiments answer complementary rather than perfectly matched questions.
7. The one-call multi-label judge, prefix-cached separate judges and measured compact-classifier fleet remain incomplete.
8. Native heldout tasks differ in prevalence, size, source, and label definition. Their metrics must not be averaged into a universal quality number.
9. UCC lacks author and article grouping. Several other datasets also lack the independent unit required for unseen-user or unseen-conversation claims.
10. Cross-domain scoring is unlabelled outside each native task and cannot measure OOD accuracy.
11. The simple screen covers mean, max, and last-token pooling with adjacent windows and logistic heads. Learned token attention, nonlinear heads, layer mixtures, and causal interventions remain outside the confirmatory family.
12. Strong probe performance establishes predictive decodability under the sampled distribution, not a causal mechanism or human-like understanding.
13. Some source licences permit research but constrain redistribution. Public weight/data release is a separate licence decision from reporting aggregate internal research results.
14. Cold start, throughput under concurrency, energy, repeated-run variance, hot-loading semantics, and GPU performance remain unmeasured.

8. Conclusion

A frozen 0.5B local language model can serve 16 independently trained activation heads from one forward pass with modest marginal CPU latency and almost no measured process-memory growth. The architectural result is a reusable semantic sensor whose task-specific readouts can evolve independently. The 24-cell matrix shows why that modularity is necessary: model, task, depth, pooling, and readout interact rather than collapsing into one universal recipe.

The architecture is therefore modular. Run the backbone once; expose a versioned activation backplane; give each task a tested readout manifest; and keep calibration, policy, and irreversible action outside the sensor. In the measured CPU setting, this turns 16 repeated

model forwards into one forward plus 1.85 ms of head work. Later datasets, models, pooling methods, and head families can move the quality frontier while preserving the shared interface. General hot-loading remains an implementation step rather than a measured product feature.

Reproducibility and evidence map

- Paper-derived ledger: `DERIVED_RESULTS.json`
- Cross-backbone sentiment matrix: `../experiments/SENTIMENT-SST2-MODEL-MATRIX.json`
- Cross-backbone spam matrix: `../experiments/SPAM-SMS-UCI-MODEL-MATRIX.json`
- Crossed ToxicChat matrix: `../experiments/TOXICCHAT0124-MODEL-TASK-MATRIX.json`
- Six-cell sentinel: `../experiments/SENTINEL-JUDGE-VS-PROBE-EXP001/result.json`
- Sentinel human-readable summary: `../experiments/SENTINEL-JUDGE-VS-PROBE-EXP001/RESULT_SUMMARY.md`
- One-forward K-scaling result: `../experiments/ONE-FORWARD-MULTIHEAD-EXP001/result.json`
- Systems summary and interpretation boundaries: `../experiments/ONE-FORWARD-MULTIHEAD-EXP001/RESULT_SUMMARY.md`
- UCC primary result: `../experiments/PRAGMATICS-UCC-QWEN-EXP001/result.json`
- UCC expansion result: `../experiments/PRAGMATICS-UCC-EXPANSION-QWEN-EXP002/result.json`
- Dataset/task source ledger: `../SOURCE_LEDGER_2026-10-17.md`
- Literature inheritance map: `../LITERATURE_INHERITANCE_MAP_2026-10-18.md`
- Paper assumptions and remaining gates: `ANALYSIS_PLAN.md`
- Tests: `../../../tests/test_one_forward_multihead.py` and `../../../tests/test_sentinel_alignment.py`

Appendix A. Environment

The systems run records Linux 6.8, Python 3.10.12, PyTorch 2.11.0, Transformers 5.8.0, six Torch threads, and no NVIDIA GPU. Each metadata file preserves the exact model revision, timestamps, package versions, input-manifest hashes, output hashes, elapsed time, and peak RSS.

Appendix B. Evidence not combined into headline claims

The broader repository also contains an authorization-specific six-backbone pilot, memory-write experiments, and a 77-way BANKING77 negative result. BANKING77 selects masked-mean output 1 on Qwen2.5-0.5B but reaches 0.6967 accuracy and 0.7815 macro-F1, versus 0.9022 and 0.9022 for TF-IDF. That result is useful evidence against universal probe superiority but is excluded from the 16-head binary runtime because one multiclass softmax artifact is not equivalent to 77 independently trained binary heads.

Author and assistance disclosure

Wan Sheng Leung defined the research question, architecture, experiment priorities, interpretation, and release boundary. Coding assistants were used to implement and check experiments, generate figures, and edit the manuscript. Quantitative claims are regenerated from the versioned artifacts linked above and are covered by repository tests.

References

1. Tillman, H., and Mossing, D. 2025. Investigating task-specific prompts and sparse autoencoders for activation monitoring. arXiv:2504.20271.
2. Li, Z., et al. 2026. Rethinking LLM-as-a-Judge: Representation-as-a-Judge with Small Language Models via Semantic Capacity Asymmetry. ICLR 2026. arXiv:2601.22588.
3. Karamolegkou, A., Eberle, O., Rust, P., Kauf, C., and Søgaard, A. 2025. Trick or Neat: Adversarial Ambiguity and Language Model Evaluation. Findings of ACL. 10.18653/v1/2025.findings-acl.954.
4. Schumacher, D., Nourbakhsh, E., Slavin, R., and Rios, A. 2026. Prompting Underestimates LLM Capability for Time Series Classification. arXiv:2601.03464.
5. Goodfire. 2025. Deploying Interpretability to Production with Rakuten: SAE Probes for PII Detection. Official research article.
6. Sing Team. 2026. SingProbe Technical Report. arXiv:2608.30703.
7. Patronus Studio. 2026. Lion Warden AI Security Classifier. Model card.
8. Meyoyan, G. A., and Del Corro, L. 2026. A BERTology View of LLM Orchestrations: Token- and Layer-Selective Probes for Efficient Single-Pass Classification. ACL. 10.18653/v1/2026.acl-long.1955.
9. Ratnakar, S., Talasila, A., and Doifode, V. K. 2026. LatentGate: Low-Latency Semantic Routing via Frozen-Backbone Probing of Small Language Models. ACL Industry Track. 10.18653/v1/2026.acl-industry.153.
10. Yang, Y., Ma, Z., Ganti, M., Zhang, J., and Krishna, R. 2026. You Only Judge Once: Multi-response Reward Modeling in a Single Forward Pass. arXiv:2604.10966.
11. Rammouz, V., Klisura, Đ., Krishnan, R., and Rios, A. 2026. Embarrassingly Simple Access Control for Large Language Models. AACL-IJCNLP, to appear. Author publication record.
12. Xi, Y., Zhang, R., Lv, T., Luo, Z., and Zhao, R. 2026. Calibration, Not Answer Selection: Distilling Internal Confidence in Reasoning Models. arXiv:2609.33290.
13. Nordby, E., Pais, T., and Parrack, A. 2026. Linear Probe Accuracy Scales with Model Size and Benefits from Multi-Layer Ensembling. arXiv:2604.13386.
14. Gao, X. 2026. From Probe Scores to Alarm Policies: Operational Validity of Activation Monitors for Language-Model Agents. arXiv:2610.04575.
15. Blandfort, P., and Graham, R. 2025. Red-teaming Activation Probes using Prompted LLMs. arXiv:2511.00554.
16. Leung, W. S. 2026. IntentProbe: One Local Model Pass, Many Task-Specific Probes. Architecture preprint v0.1.3. 10.5281/zenodo.23467859.

Dataset release links and exact local provenance are listed in the task source ledger and the paper source ledger.