

How to change SSH port on Linux

22 September 2020 by Korbin Brown

The default port for [SSH](#) on [Linux systems](#) is 22. There are a few reasons why you may want to change this to some other number. If multiple servers share the same IP address (behind a NAT configuration, for example) you usually can't have them running SSH on the same port and expect to access them from outside the network.

The other big reason is security. [Changing the SSH port](#) would fall under “security through obscurity” which means that the security isn't technically enhanced, but the SSH port has been obscured and isn't as easy for attackers to access. In practice, this means that the thousands of bots scanning the internet for open SSH servers are a lot less likely to find yours.

In this article, we'll take you through the step by step instructions of changing the default SSH port on [Ubuntu Linux](#) and [CentOS Linux](#). Since Ubuntu is based on [Debian](#), you can also apply the same instructions to other Debian based systems, like [Linux Mint](#). CentOS is based on [Red Hat](#), so its instructions can also be extended to [Fedora](#) and other similar [Linux distributions](#).

In this tutorial you will learn:

- How to change SSH port on Ubuntu and CentOS Linux

A screenshot of a Linux desktop environment. In the center, a terminal window titled 'Terminal' is open, displaying the contents of the `/etc/ssh/sshd_config` file using the GNU nano 4.8 editor. The file's title bar shows 'Modified'. The configuration file content includes comments about the OpenSSH server, the PATH, and the strategy for options. A red rectangular box highlights the line `Port 22`. Below the configuration file, a status bar shows various keyboard shortcuts like '^G Get Help', '^X Exit', '^O Write Out', '^R Read File', '^W Where Is', '^M Replace', '^K Cut Text', '^P Paste Text', '^J Justify', '^T To Spell', '^C Cur Pos', '^G Go To Line', '^M-U Undo', and '^M-E Redo'. The desktop background is dark, and the left sidebar shows icons for Activities, Home, linuxconfig, Trash, and a question mark. The top status bar shows 'Activities', 'Terminal', and the time '14:26'. A 'LINUXCONFIG' logo is visible in the bottom right corner of the terminal window.

Changing SSH port on Linux

Software Requirements and Linux Command Line Conventions

Category	Requirements, Conventions or Software Version Used
System	Ubuntu Linux and CentOS Linux
Software	OpenSSH
Other	Privileged access to your Linux system as root or via the sudo command.
Conventions	<code>#</code> – requires given linux commands to be executed with root privileges either directly as a root user or by use of sudo command <code>\$</code> – requires given linux commands to be executed as a regular non-privileged user

Change SSH port on Ubuntu or CentOS

Open a [command line](#) terminal and follow along with the steps below to configure the SSH port on Ubuntu and other Debian based systems, as well as CentOS and other Red Hat based systems.

Step 1 Start by opening the `/etc/ssh/sshd_config` configuration file with nano or your preferred text editor.

```
$ sudo nano /etc/ssh/sshd_config
```

Step 2 Look for the `#Port 22` line. We'll need to uncomment this line and change the number to our desired port number. For this example, we'll switch the port number to `2222`.

```
From:  
#Port 22  
  
To:  
Port 2222
```

Step 3 Save the changes you've made to this file and exit. Finish up by reloading the sshd service.

```
$ sudo systemctl reload sshd
```

Step 4 To make sure everything is working, you can try to SSH on the new port. You'll need to use the `-p` option to instruct the client to use some other port than the default 22.

```
$ ssh -p 2222 user@localhost
```

Additional configuration for Ubuntu

Ubuntu has UFW firewall installed by default. If you're running UFW firewall and need to allow traffic to the new port, use the command below. Alternatively, check out our full [guide on using UFW firewall](#).

```
$ sudo ufw allow 2222/tcp
```

Additional configuration for CentOS

CentOS doesn't use UFW by default, but if you happen to have it installed, make sure you also use the UFW command above.

CentOS uses SELinux (Security Enhanced Linux module) and firewalld by default. We'll need to add an exception in order to allow SSH access on the newly configured port.

Step 1 First, make sure SELinux is actually enabled. If it's not, you can skip this entirely.

```
# sestatus  
SELinux status: enabled
```

Step 2 Use the semanage utility to add a new port number for SSH.

```
# semanage port -a -t ssh_port_t -p tcp 2222
```

Step 3 Add the new port to firewalld's configured zone ("public" by default).

```
# firewall-cmd --zone=public --add-port=2222/tcp --permanent
```

Step 4 Reload firewalld to finalize the changes.

```
# firewall-cmd --reload
```

Closing Thoughts

In this guide, we saw how to change the default SSH port on Ubuntu and CentOS, as well as similar distributions. Following these steps will offer some security through obscurity and, if nothing else, cut down on the intrusion attempts constantly launched by bots around the world.

Related Linux Tutorials:

- [How to automate interactive cli commands with expect](#)
- [Best Linux Distro: How to Choose Guide for Every User](#)
- [Ultimate Web Server Benchmark: Apache, NGINX,...](#)
- [An Introduction to Linux Automation, Tools and Techniques](#)
- [How to install Arch Linux alongside Ubuntu \(Dual Boot\)](#)
- [Things to do after installing Ubuntu 22.04 Jammy...](#)
- [How often do you have to reboot your Linux server?](#)
- [How to install Arch Linux alongside Windows 11 \(Dual Boot\)](#)
- [Setting the Hostname on Ubuntu 24.04](#)
- [Setting a Static IP Address in Ubuntu 24.04 via the...](#)

- » administration, networking
- < Rsync: exclude directory
- > Advanced Linux Subshells With Examples

Comments and Discussions

[Start Discussion](#)

0 replies

NEWSLETTER

Subscribe to Linux Career Newsletter to receive latest news, jobs, career advice and featured configuration tutorials.

SUBSCRIBE

WRITE FOR US

LinuxConfig is looking for a technical writer(s) geared towards GNU/Linux and FLOSS technologies. Your articles will feature various GNU/Linux configuration tutorials and FLOSS technologies used in combination with GNU/Linux operating system.

When writing your articles you will be expected to be able to keep up with a technological advancement regarding the above mentioned technical area of expertise. You will work independently and be able to produce at minimum 2 technical articles a month.

APPLY NOW

TAGS

18.04 **administration** [apache](#) [applications](#) [backup](#) **bash** **beginner** [browser](#) [centos](#) [centos8](#)
commands [database](#) [debian](#) **desktop** **development** [docker](#) [error](#) [fedora](#) **filesystem** [firewall](#)
[gaming](#) [gnome](#) [Hardware](#) **installation** [kali](#) [multimedia](#) **networking** [nvidia](#) **programming** [python](#)
[raspberrypi](#) [redhat](#) [rhel8](#) **scripting** **security** **server** [ssh](#) [storage](#) **terminal** **ubuntu** **ubuntu**
20.04 [video](#) [virtualization](#) [webapp](#) **webserver**

ABOUT US

FEATURED TUTORIALS

How to install the NVIDIA drivers on Ubuntu 22.04

How to mount USB drive in Linux

How to install tar.gz file on Linux

How to enable/disable wayland on Ubuntu Desktop

Linux IP forwarding

Netplan static IP on Ubuntu configuration

Google Chrome for Linux: Download and Installation

Ubuntu Network Configuration Guide

[How to Check NVIDIA Driver Version on Linux](#)

[How to find my IP address on Ubuntu Linux](#)

[Change IP address on Ubuntu Server](#)

[How to use curl to get public IP address](#)

[How to install the NVIDIA drivers on Ubuntu 20.04 Focal Fossa Linux](#)

[How to make a bootable USB from an ISO in Linux](#)

[How to install missing ifconfig command on Linux](#)

[How to install Yum on Linux](#)

[Ubuntu 24.04 LTS vs 22.04 LTS: A Comparison Guide and What's New](#)

[Ubuntu Remote Desktop Access from Windows 10/11](#)

[How to Install Adobe Acrobat Reader on Ubuntu and Debian Linux](#)

[Resolving the 'No Space Left on Device' Error on Linux](#)

[Ubuntu Static IP configuration](#)

[Bash Scripting Tutorial](#)

LATEST TUTORIALS

[Unlock Powerful System Monitoring: Your Guide to Prometheus and Grafana](#)

[Dockerfile Build – Best Practices & Errors](#)

[Shell Upgrade: Supercharge Your Terminal with Zsh & Oh My Zsh](#)

[Enhancing Privacy on Linux: Mounting Logs and Temporary Directories in RAM](#)

[Start Docker Daemon on Linux](#)

[Docker Run With Logs – Capturing and Debugging Output](#)

[Check If Docker Is Running – Linux Commands](#)

[Bash Function to Sort Docker Ps Output](#)

[Docker Basic Commands on Linux](#)

[How to Network Connect Two Containers With Docker-compose](#)

[How to Convert Markdown to Pdf on Linux](#)

[How to Add a Sql User in a Docker Container](#)

[Docker Container Vulnerability Scanning Tools](#)

[How to Show Hidden Files on Linux](#)

[How to Hash a File on Linux](#)

[How to Increase Swap Space on Linux](#)

[How to Enable X11 Forwarding on Linux](#)

[How to Update Docker on Debian/Ubuntu Linux](#)

[Syncing Files with Docker-Compose Watch](#)

[How to Install ZFS on Debian/Ubuntu](#)