

LDA: Banknotes

Gustavo Cepparo and Milica Cudina

We reconsider the **banknote** data set. It exists in the **MixGHD** library.

```
#install.packages("MixGHD")  
library(MixGHD)
```

```
## Loading required package: MASS
```

The data set **banknote** is used to predict the **Status** of Swiss Franc bills based on measurements of the bills.


```
data(banknote)  
names(banknote)
```

```
## [1] "Status" "Length" "Left" "Right" "Bottom" "Top" "Diagonal"
```

```
attach(banknote)  
data<-banknote
```

We can start with visualization (as usual).

```
pairs(data,  
       col="lightblue", pch=19)
```



Our aim is to perform the linear discriminant analysis here. First, we will partition our data into training and testing.

```
set.seed(1)
ind.train <- sample(nrow(data), floor(nrow(data)*0.6))
training<-data[ind.train,]
testing<-data[-ind.train,]
```

My goal with this example is to ultimately demonstrate how to plot a partition in the plane. So, I will arbitrarily choose two explanatory variables: Top and Diagonal.

```
library(MASS)
linear <- lda(Status~Top+Diagonal, data=training)
summary(linear)
```

```
##          Length Class  Mode
## prior      2      -none- numeric
## counts     2      -none- numeric
## means      4      -none- numeric
## scaling    2      -none- numeric
## lev        2      -none- character
## svd         1      -none- numeric
## N           1      -none- numeric
## call        3      -none- call
## terms       3      terms  call
## xlevels     0      -none- list
```

Histogram

```
p <- predict(linear, training)
ldahist(data = p$x[,1], g = training$Status)
```

