

# LDA: Banknotes

Gustavo Cepparo and Milica Cudina

We consider another **banknote** data set. It exists in the **MixGHD** library.

```
#install.packages("MixGHD")  
library(MixGHD)
```

```
## Loading required package: MASS
```

The data set **banknote** is used to predict the **Status** of Swiss Franc bills based on measurements of the bills.


```
data(banknote)  
names(banknote)
```

```
## [1] "Status" "Length" "Left" "Right" "Bottom" "Top" "Diagonal"
```

```
attach(banknote)  
data<-banknote
```

We can start with visualization (as usual).

```
pairs(data,  
       col="lightblue", pch=19)
```



Our aim is to perform the linear discriminant analysis here. First, we will partition our data into training and testing.

```
set.seed(1)
ind.train <- sample(nrow(data), floor(nrow(data)*0.6))
training<-data[ind.train,]
testing<-data[-ind.train,]
```

My goal with this example is to ultimately demonstrate how to plot a partition in the plane. So, I will “arbitrarily” choose two explanatory variables: Top and Diagonal.

```
library(MASS)
linear <- lda(Status~Top+Diagonal, data=training)
summary(linear)
```

```
##          Length Class  Mode
## prior      2      -none- numeric
## counts     2      -none- numeric
## means      4      -none- numeric
## scaling    2      -none- numeric
## lev        2      -none- character
## svd         1      -none- numeric
## N           1      -none- numeric
## call        3      -none- call
## terms       3      terms  call
## xlevels     0      -none- list
```


```
linear
```

```
## Call:
## lda(Status ~ Top + Diagonal, data = training)
##
## Prior probabilities of groups:
## counterfeit    genuine
##   0.5583333    0.4416667
##
## Group means:
##              Top Diagonal
## counterfeit 11.11791 139.4463
## genuine     10.28679 141.4132
##
## Coefficients of linear discriminants:
##              LD1
## Top          -0.3911736
## Diagonal     1.9162568
```

Now, we try to create a partition plot.


```
#install.packages("klaR")
library(klaR)
partimat(Status~Top+Diagonal, data = training, method = "lda")
```

## Partition Plot



```
partimat(Status~Top+Diagonal, data = training, method = "qda")
```

## Partition Plot



Finally, let's consider the confusion matrix and accuracy, both on the training set and the testing set.

*#the training set*

```
p.tr <- predict(linear, training)$class
tab.tr <- table(Predicted = p.tr, Actual = training$Status)
tab.tr
```

```
##           Actual
## Predicted   counterfeit genuine
## counterfeit      67         1
## genuine         0         52
```

```
sum(diag(tab.tr))/sum(tab.tr)
```

```
## [1] 0.9916667
```

*#this is the error rate indicated in the label on the plot above*

```
1-sum(diag(tab.tr))/sum(tab.tr)
```

```
## [1] 0.008333333
```

*#the testing set*

```
p.te <- predict(linear, testing)$class
tab.te <- table(Predicted = p.te, Actual = testing$Status)
tab.te
```

```
##           Actual
## Predicted   counterfeit genuine
## counterfeit      33         0
## genuine         0         47
```

```
sum(diag(tab.te))/sum(tab.te)
```

```
## [1] 1
```