

---

```
curl -X PUT http://127.0.0.1:8000/event/edit/1 -H "accept: application/json" -H
"Content-Type: application/json" -d '{"title":"Packts FastAPI book launch
II\'}'
```

---

정상적으로 요청이 처리되면 다음과 같은 결과가 표시된다.

---

```
[
  {
    "id": 1,
    "title": "Packts FastAPI book launch II",
    "image": "fastapi-book.jpeg",
    "description": "We will be discussing the contents of the FastAPI book in this
event.Ensure to come with your own copy to win gifts!",
    "tags": ["python","fastapi", "book", "launch"],
    "location": "Google Meet"
  }
]
```

---

## 이벤트 삭제

events.py 파일에서 기존 DELETE 라우트를 다음과 같이 변경한다.

---

```
@event_router.delete("/delete/{id}")
async def delete_event(id: int, session=Depends(get_session)) -> dict:
    event = session.get(Event, id)
    if event:
        session.delete(event)
        session.commit()
        return {
            "message": "Event deleted successfully."
        }

    raise HTTPException(
        status_code=status.HTTP_404_NOT_FOUND,
        detail="Event with supplied ID does not exist"
    )
```

---

이 코드는 해당 ID의 이벤트가 존재하는지 확인한 후 존재하면 데이터베이스에서 삭제한다.