

```

test_payload = {
    "title": "Updated FastAPI event"
}

headers = {
    "Content-Type": "application/json",
    "Authorization": f"Bearer {access_token}"
}

url = f"/event/{str(mock_event.id)}"

response = await default_client.put(url, json=test_payload, headers=headers)

assert response.status_code == 200
> assert response.json()["title"] == "This test should fail"
E   AssertionError: assert 'Updated FastAPI event' == 'This test should fail'
E       - This test should fail
E       + Updated FastAPI event

tests/test_routes.py:103: AssertionError
===== short test summary info =====
FAILED tests/test_routes.py::test_update_event - AssertionError: assert 'Updated FastAPI event' == 'This test should fail'
===== 1 failed, 4 passed in 0.09s =====
(venv) + planner git:(main) x

```

그림 8-11 응답이 달라 실패한 테스트

## 삭제 라우트 테스트

마지막으로 삭제 라우트 테스트 함수를 작성해보자.

---

```

@pytest.mark.asyncio
async def test_delete_event(default_client: httpx.AsyncClient, mock_event: Event,
access_token: str) -> None:
    test_response = {
        "message": "Event deleted successfully."
    }

    headers = {
        "Content-Type": "application/json",
        "Authorization": f"Bearer {access_token}"
    }

    url = f"/event/{mock_event.id}"

    response = await default_client.delete(url, headers=headers)

    assert response.status_code == 200
    assert response.json() == test_response

```

---