

Train End Clean - External

Review date: 20/09/13

Document no.	Work description		
SMS-06-SW-0493	Cleaning external ends		
Scope	Exterior surfaces of carriages		
Review date	Reference		
20/09/13	<ul style="list-style-type: none"> • OHS Act 2000 section 8 (1.2) 20 (1.2) 21 • SMS-06-GD-0001 Guide to Manual Handling • SMS-12-01-0886 Red Flagging Trains in Stabling Yards, Depots or Maintenance Centres • Relevant up-to-date MSDS 		
Responsible supervisor <i>Insert name in BLOCK letters</i>	PPE and precautions	Competencies or qualifications	Licences or permits required
Supervisor/Team Leader	<ul style="list-style-type: none"> • Red flag • Personal Identity Card (PID) • High visibility vest • Safety Footwear • Rubber gauntlet gloves • Face Shield • Disposable Overalls 	Induction On-the-Job Training Track & Electrical Safety Awareness RISI	N/A
Tools and equipment required			
High-pressure spray attachment, broom, maxi-bucket, chemicals, extension pole broom, hose & fittings			
IF CONTROL MEASURES ARE NOT SUITABLE AND MAJOR CHANGES ARE NEEDED, CONDUCT A RISK ASSESSMENT AND DEVELOP NEW CONTROLS ACCORDING TO SMS-06-PR-0104 WORKPLACE RISK MANAGEMENT.			

	Warning Before starting work on the train Employees must clip their discipline's RED flag to the blind in the Driver's window at the leading end with the clips provided. Employees intending to work on a rail vehicle consist must attach their identification (PID card) to their discipline's RED flag displayed in the Driver's window at the leading end. Look out for trains moving into and around the work area.
---	---

Preparation	<ul style="list-style-type: none"> • Collect cleaning equipment from store. • Proceed to train. • Place your red flag in the driver's compartment.
--------------------	---

	Warning Take care not to spray water onto overhead electrical wiring. Take care that equipment does not touch the overhead electrical wiring. Use appropriate PPE to ensure that the caustic cleaning chemical cannot come into contact with skin and eyes. The high pressure hose connection can be very hot because of the use of hot water. High pressure hoses are never to be pointed at people.
---	---

End cleaning	<ul style="list-style-type: none"> • Clean the drainage gutter with a scratcher or with high-pressure water. • Make sure the outlet is free of rubbish. • Fill maxi-bucket with chemical. • Use a broom/extension pole to apply chemical to window and metal surface. • Agitate chemical with broom. • Use high pressure hose to wash down all surfaces, including passenger bridge. • Continue process until all ends have been cleaned.
---------------------	--

Clean up	<ul style="list-style-type: none"> • Remove your red flag from the driver's compartment. • Thoroughly clean equipment. • Return equipment to store.
-----------------	--

Additional controls