

CSCI235 Database Systems

Transaction Processing in Oracle DBMS

Dr Janusz R. Getta

School of Computing and Information Technology -
University of Wollongong

Transaction Processing in Oracle DBMS

Outline

Transaction scope

Isolation levels and read consistency levels

Rollback/Undo segments

READ COMMITTED versus SERIALIZABLE levels

Locking

READ COMMITTED isolation level

SERIALIZABLE isolation level

Transaction scope

Transaction starts from the first executable SQL statement after connection, **COMMIT**, or **ROLLBACK** statement

Transaction ends with either **COMMIT**, **ROLLBACK**, or DDL statement **CREATE**, **DROP**, **ALTER**

Transaction also ends with disconnection (**auto-commit** or **auto-rollback** depending on default or set up parameters) or process failure followed by automatic **ROLLBACK** statement

Transaction Processing in Oracle DBMS

Outline

[Transaction scope](#)

[Isolation levels and read consistency levels](#)

[Rollback/Undo segments](#)

[READ COMMITTED versus SERIALIZABLE levels](#)

[Locking](#)

[READ COMMITTED isolation level](#)

[SERIALIZABLE isolation level](#)

Isolation levels and read consistency levels

Oracle DBMS implements three **isolation levels**

READ COMMITTED - a transaction may exhibit:

- non-repeatable read phenomenon,
- phantom phenomenon

SERIALIZABLE - a transaction may exhibit:

- none of the phenomena

READ ONLY - a transaction consists only of **read** operations

At **READ COMMITTED** isolation level all data read by a query (**SELECT** statement) come from a single point in time (**statement-level read consistency**)

At **SERIALIZABLE** isolation level all queries (**SELECT** statements) in a transaction read data that come from a single point in time (**transaction-level read consistency**)

Transaction Processing in Oracle DBMS

Outline

[Transaction scope](#)

[Isolation levels and read consistency levels](#)

[Rollback/Undo segments](#)

[READ COMMITTED versus SERIALIZABLE levels](#)

[Locking](#)

[READ COMMITTED isolation level](#)

[SERIALIZABLE isolation level](#)

Rollback/undo segments


Rollback/undo segments consist of data blocks that contain the old values of data that have been changed by the uncommitted or recently committed transactions

Each time a row in a data a block is changed a new version of the block together with a **timestamp** is added to **rollback/undo segment**

A new version of a data block obtains a **timestamp** higher than the previous version

A data block may have many versions updated in the different moments in time

See below the data blocks read by a transaction **T** with a timestamp t_i such that $t_2, t_3 > t_i > t_0, t_1$



Transaction Processing in Oracle DBMS

Outline

[Transaction scope](#)

[Isolation levels and read consistency levels](#)

[Rollback/Undo segments](#)

[READ COMMITTED versus SERIALIZABLE levels](#)

[Locking](#)

[READ COMMITTED isolation level](#)

[SERIALIZABLE isolation level](#)

READ COMMITTED versus SERIALIZABLE levels

At **READ COMMITTED** isolation level each query executes with respect to its own materialized view time, thereby permitting nonrepeatable reads and phantoms for multiple executions of a query

READ COMMITTED isolation level is recommended when few transactions are likely to conflict

If a transaction **T** running at **SERIALIZABLE** isolation level tries to update or delete data modified by a transaction that commits after the serializable transaction **T** began then the system aborts transaction **T**

If a serializable transaction fails then it is possible to:

- commit the work executed to that point,
- execute additional (but different) statements,
- rollback the entire transaction

Transaction Processing in Oracle DBMS

Outline

Transaction scope

Isolation levels and read consistency levels

Rollback/Undo segments

READ COMMITTED versus SERIALIZABLE levels

Locking

READ COMMITTED isolation level

SERIALIZABLE isolation level

Locking

Locking is performed automatically by the system

It is also possible to lock data items manually

There are two types of locks:

- **shared** (read locks),
- **exclusive** (write locks)

A transaction holds **exclusive row locks** for all rows **inserted**, **updated**, or **deleted** within the transaction

The system releases all locks acquired by a transaction when the transaction either **commits** or **rollbacks**

The system automatically converts a lock of **lower restrictiveness** to one of **higher restrictiveness** when it is appropriate

For example, **SELECT** statement with **FOR UPDATE** clause initially locks the rows in **shared mode**, then when **UPDATE** is performed the locks are upgraded to **exclusive locks**

Locking

Both **READ COMMITTED** and **SERIALIZABLE** transactions use row-level locking to ensure database consistency

A transaction must wait if it tries to change a row updated by an uncommitted transaction

If a transaction rolls back then the waiting transactions regardless of its isolation mode can proceed to change the previously locked row

If a transaction commits than any other transaction at **READ COMMITTED** level waiting for a locked row can proceed to change the previously locked row

If a transaction commits than any other transaction at **SERIALIZABLE** level waiting for a locked row fails with the error "Cannot serialize access", because the other transaction has committed a change that was made since the serializable transaction began

Locking

A **deadlock** occurs when two or more users are waiting for data locked by each other

The system automatically detects a **deadlock** and rolls back one of the statements involved in the deadlock

It is possible to perform **manual locking** of entire relational table with **LOCK TABLE** statement

Transaction Processing in Oracle DBMS

Outline

[Transaction scope](#)

[Isolation levels and read consistency levels](#)

[Rollback/Undo segments](#)

[READ COMMITTED versus SERIALIZABLE levels](#)

[Locking](#)

[READ COMMITTED isolation level](#)

[SERIALIZABLE isolation level](#)

READ COMMITTED isolation level

Setting **READ COMMITTED isolation level** is performed at the beginning of transaction with the following statement

```
SET TRANSACTION ISOLATION LEVEL READ COMMITTED;
```

At **READ COMMITTED** isolation level each query executes with the respect to its own materialized view time, thereby permitting **nonrepeatable reads** and **phantoms** for multiple processing of the same query

READ COMMITTED isolation level is recommended when few transactions are likely to conflict

READ COMMITTED is a default isolation level

READ COMMITTED isolation level

Sample concurrent processing of database transactions at **READ COMMITTED** isolation level that **does not corrupt** a database

Concurrent processing of database transactions at READ COMMITTED isolation level	
Transaction 1	Transaction 2
	<code>SELECT budget FROM DEPARTMENT WHERE name = 'Sales';</code>
	2000
<code>UPDATE DEPARTMENT SET budget = budget + 1000 WHERE NAME = 'Sales';</code>	
	<code>SELECT budget FROM DEPARTMENT WHERE name = 'Sales';</code>
	2000

Transaction 2 cannot read uncommitted modifications

READ COMMITTED isolation level

Sample concurrent processing of database transactions at **READ COMMITTED** isolation level that **does not corrupt** a database

Concurrent processing of database transactions at READ COMMITTED isolation level	
Transaction 1	Transaction 2
	<pre>SELECT budget FROM Department WHERE name = 'Sales';</pre>
	2000
<pre>UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'Sales';</pre>	
COMMIT;	
	<pre>SELECT budget FROM Department WHERE name = 'Sales';</pre>
	3000

Transaction 2 can only read committed modifications

READ COMMITTED isolation level

Sample concurrent processing of database transactions at **READ COMMITTED** isolation level that **does not corrupt** a database

Concurrent processing of database transactions at READ COMMITTED isolation level	
Transaction 1	Transaction 2
SELECT budget FROM DEPARTMENT WHERE name = 'Sales';	
3000	
	UPDATE DEPARTMENT SET budget = budget + 10 WHERE name = 'Sales';
UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'Sales';	
Wait	
	COMMIT;
SELECT budget FROM DEPARTMENT WHERE name = 'Sales'	
4010	

TOP

READ COMMITTED isolation level

Transaction 1	Transaction 2	Processing at READ COMMITTED isolation level
SELECT budget FROM DEPARTMENT WHERE name = 'Sales';		
3000		
	UPDATE DEPARTMENT SET budget = budget + 10 WHERE name = 'Sales';	
UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'Sales';		
Wait		
	COMMIT;	
SELECT budget FROM DEPARTMENT WHERE name = 'Sales'		
4010		

Transaction 1 must wait until Transaction 2 either commits or rolls back its update

READ COMMITTED isolation level

Sample concurrent processing of database transactions at **READ COMMITTED** isolation level that **does not corrupt** a database

Transaction 1	Transaction 2	Processing at READ COMMITTED isolation level
SSELECT budget FROM DEPARTMENT WHERE name = 'Sales'		
3000		
	UPDATE DEPARTMENT SET budget = budget + 10 WHERE name = 'Sales'	
UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'Sales';		
Wait		
	ROLLBACK;	
SELECT budget FROM DEPARTMENT WHERE name = 'Sales'		
4000		

READ COMMITTED isolation level

Transaction 1	Transaction 2	Processing at READ COMMITTED isolation level
SSELECT budget FROM DEPARTMENT WHERE name = 'Sales'		
3000		
	UPDATE DEPARTMENT SET budget = budget + 10 WHERE name = 'Sales'	
UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'Sales';		
Wait		
	ROLLBACK;	
SELECT budget FROM DEPARTMENT WHERE name = 'Sales'		
4000		

Transaction 1 must wait until Transaction 2 either commits or rolls back its update

READ COMMITTED isolation level

A sample processing of database transactions at **READ COMMITTED** isolation level that **corrupts** a database

Processing at READ COMMITTED isolation level	
Transaction 1	Transaction 2
<pre>UPDATE DEPARTMENT SET budget = (SELECT budget FROM DEPARTMENT WHERE name = 'Sales') WHERE name = 'Finance';</pre>	
	<pre>UPDATE DEPARTMENT SET budget = 500 WHERE name = 'Sales'; COMMIT;</pre>
<pre>UPDATE DEPARTMENT SET budget = budget + (SELECT budget FROM DEPARTMENT WHERE name = 'Sales') WHERE name = 'Finance'; COMMIT;</pre>	

Transaction 1 corrupts a database, because a budget of department **Finance** is not equal to $2 * \text{budget of department Sales}$

[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2022

22/26

Transaction Processing in Oracle DBMS

Outline

[Transaction scope](#)

[Isolation levels and read consistency levels](#)

[Rollback/Undo segments](#)

[READ COMMITTED versus SERIALIZABLE levels](#)

[Locking](#)

[READ COMMITTED isolation level](#)

[SERIALIZABLE isolation level](#)

SERIALIZABLE isolation level

If a transaction **T** running at **SERIALIZABLE** isolation level tries to update or delete data modified by a transaction that commits after the serializable transaction **T** began then the system aborts transaction **T**

A sample processing of database transactions at **SERIALIZABLE** isolation level that **fails** one of the transactions

Processing database transactions at SERIALIZABLE isolation level	
Transaction 1	Transaction 2
	UPDATE DEPARTMENT SET budget = budget + 10 WHERE name = 'Sales'
UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'Sales';	
Wait	
	COMMIT;
ERROR at line 2: ORA-08177: can't serialize access for this transaction	

SERIALIZABLE isolation level

A sample processing of database transactions at **SERIALIZABLE** isolation level that ends **successfully** for both transactions

Processing database transactions at SERIALIZABLE isolation level	
Transaction 1	Transaction 2
	<pre>SELECT budget FROM Department WHERE name = 'Sales'</pre>
	2000
<pre>UPDATE DEPARTMENT SET budget = budget + 1000 WHERE name = 'Sales';</pre>	
COMMIT	
	<pre>SELECT budget FROM Department WHERE name = 'Sales'</pre>
	2000

Transaction 1 creates a new version of a row for **Sales** department

References

T. Connolly, C. Begg, Database Systems, A Practical Approach to Design, Implementation, and Management, Chapter 22.5 Concurrency Control and Recovery in Oracle, Pearson Education Ltd, 2015