

CSCI235 Database Systems

MongoDB Query Language

Dr Janusz R. Getta

School of Computing and Information Technology -
University of Wollongong

MongoDB Query language

Outline

[MongoDB query language](#)

[A sample database](#)

[Simple queries](#)

[Queries with Boolean operations](#)

[Queries on nested documents](#)

[Queries on arrays](#)

[Projections](#)

[Queries about **NULLs** and missing keys](#)

[Iterations over a cursor](#)

MongoDB query language

MongoDB query language is based on a concept of pattern matching

A query is expressed as a **BSON** pattern and all documents that match the pattern are included in an answer

A method `find()` can be used to match a pattern with the documents in a collection `orders`

```
db.orders.find({"_id":"ALFKI"})
```

`find()`

Matching of an empty pattern `{}` with a collection `orders` returns an entire collection

```
db.orders.find({})
```

`find()`

Finding the first 3 documents in a collection `orders`

```
db.orders.find({}).limit(3)
```

`find()`

Finding all documents in a collection `orders` and listing the results in a nice format

```
db.orders.find({}).pretty()
```

`find()`

MongoDB Query language

Outline

[MongoDB query language](#)

[A sample database](#)

[Simple queries](#)

[Queries with Boolean operations](#)

[Queries on nested documents](#)

[Queries on arrays](#)


[Projections](#)

[Queries about **NULLs** and missing keys](#)

[Iterations over a cursor](#)


A sample database

A conceptual schema of a database with information about **suppliers**, **products**, **customers**, **orders**, and **details of orders**



A sample database

A sample collection **orders**



[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2022

6/34

A sample database

A sample document, that belongs to a class **CUSTOMER**

```
{
  "_id" : "ALFKI",
  "CUSTOMER" : {
    "customer code" : "ALFKI",
    "company name" : "Alfreds Futterkiste",
    "contact name" : "Maria Anders",
    "contact title" : "Sales Representative",
    "address" : "Obere Str. 57",
    "city" : "Berlin",
    "region" : null,
    "postal code" : "12209",
    "country" : "Germany",
    "phone" : "030-0074321",
    "fax" : "030-0076545",
    "submits" : [ ]
  }
}
```

CUSTOMER

A sample database

A sample nested document, that belongs to a class **CUSTOMER**

```
{
  "_id" : "FAMIA",
  "CUSTOMER" : {
    "customer code" : "FAMIA",
    ... ..
    "submits" : [
      {
        "ORDER" : {
          "order id" : 328,
          ... ..
          "consists of" : [
            {
              "ORDER DETAIL" : {
                "product name" : "Louisiana Fiery Hot Pepper Sauce",
                ... ..
              }
            },
            {
              "ORDER DETAIL" : {
                "product name" : "Raclette Courdavault",
                ... ..
              }
            }
          ]
        }
      }
    ]
  }
}
```

CUSTOMER[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2022

8/34

A sample database

A sample nested document, that belongs to a class **SUPPLIER**

```
{
  "_id" : "Karkki Oy",
  "SUPPLIER" : {
    "company name" : "Karkki Oy",
    "contact name" : "Anne Heikkonen",
    "contact title" : "Product Manager",
    "address" : "Valtakatu 12",
    ... ..
    "supplies" : [
      {
        "PRODUCT" : {
          "product name" : "Maxilaku",
          "category name" : "Confections",
          ... ..
        }
      },
      {
        "PRODUCT" : {
          "product name" : "Valkoinen suklaa",
          "category name" : "Confections",
          ... ..
        }
      }
    ]
  }
}
```

SUPPLIER

MongoDB Query language

Outline

[MongoDB query language](#)

[A sample database](#)

[Simple queries](#)

[Queries with Boolean operations](#)

[Queries on nested documents](#)

[Queries on arrays](#)

[Projections](#)

[Queries about **NULLs** and missing keys](#)

[Iterations over a cursor](#)

Simple queries

Find total number of documents in a collection

```
db.orders.count()
```

count()

Find all information about all customers

```
db.orders.find({"CUSTOMER":{"exists:true}})
```

Find entire class

Find all information about all suppliers

```
db.orders.find({"SUPPLIER":{"exists:true}})
```

Find entire class

Find all information about the customers living in **Germany**

```
db.orders.find({"CUSTOMER.country":"Germany"})
```

Access path

Find all information about the suppliers living in a city of **Oviedo**

```
db.orders.find({"SUPPLIER.city":"Oviedo"})
```

Access path

Find all information about the suppliers who live in the **Netherlands**
and have a contact title **Accounting Manager**

```
db.orders.find({"SUPPLIER.country":"Netherlands",  
               "SUPPLIER.contact title":"Accounting Manager"})
```

And

MongoDB Query language

Outline

[MongoDB query language](#)

[A sample database](#)

[Simple queries](#)

[Queries with Boolean operations](#)

[Queries on nested documents](#)

[Queries on arrays](#)

[Projections](#)

[Queries about **NULLs** and missing keys](#)

[Iterations over a cursor](#)

Queries with Boolean operations

Comparison "key"="value"

```
{"key":"value"}
```

=

```
{"key":{"$eq":"value"}}
```

=

Comparison "key" > "value"

```
{"key":{"$gt":"value"}}
```

>

Disjunction ("key1"="value1") or ("key2"="value2")

```
{"$or":[{"key1":"value1"}, {"key2":"value2"}]}
```

\$or

Conjunction ("key1"="value1") and ("key2"="value2")

```
{"$and":[{"key1":"value1"}, {"key2":"value2"}]}
```

\$and

Boolean expression (("key1"="value1") or ("key2"="value2"))
and ("key3"="value3")

```
{"$and":[{"$or":[{"key1":"value1"}, {"key2":"value2"}]}, {"key3":"value3"}]}
```

Boolean expression

Queries with Boolean operations

Negation of a comparison `"key" not = "value"`

```
{"key":{$not:{$eq:"value"}}
```

not =

Negation of an expression `not (("key1"="value1") or ("key2"="value2"))`

```
{$nor:[{"key1":"value1"}, {"key2":"value2"}]}
```

not or

Negation `nor ("key1"="value1")`

```
{$nor:[{"key1":"value1"}]}
```

not =

Queries with Boolean operations

Find all information about the suppliers who live in the **Netherlands** **and** have a contact title **Accounting Manager**

```
db.orders.find({$and:[{"SUPPLIER.country":"Netherlands"},  
{"SUPPLIER.contact title":"Accounting Manager"}]})
```

\$and

Find all information about the suppliers who live in the **Netherlands** **or** have a contact title **Accounting Manager**

```
db.orders.find({$or:[{"SUPPLIER.country":"Netherlands"},  
{"SUPPLIER.contact title":"Accounting Manager"}]})
```

\$or

Find all information about the customers who live in **France** **or** in **Germany**

```
db.orders.find({"CUSTOMER.country":{"$in":["France","Germany"]}})
```

\$in

Queries with Boolean operations

Find all information about the customers who do not live in **Germany**

```
db.orders.find({"CUSTOMER.country":{"$not":{"$eq":"Germany"}}})
```

\$not

Find all information about the customers who do not **both** live in **Netherlands** **or** have a contact title **Accounting Manager**

Find all information about the customers who do not live in **Netherlands** **and** do not have a contact title **Accounting Manager**

```
db.orders.find({$nor:[{"SUPPLIER.country":"Netherlands"},  
{"SUPPLIER.contact title":"Accounting Manager"}]})
```

\$nor

Find all information about the customers who do not live in **Germany**

```
db.orders.find({$nor:[{"CUSTOMER.country":"Germany"}]})
```

\$nor

MongoDB Query language

Outline

[MongoDB query language](#)

[A sample database](#)

[Simple queries](#)

[Queries with Boolean operations](#)

[Queries on nested documents](#)

[Queries on arrays](#)


[Projections](#)

[Queries about **NULLs** and missing keys](#)

[Iterations over a cursor](#)

Queries on nested documents

A sample collection **orders**



[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2022

18/34

Queries on nested documents

Find all information about suppliers who supply a product named **Laughing Lumberjack Lager**

```
db.orders.find({"SUPPLIER.supplies.PRODUCT.product name":"Laughing Lumberjack Lager"})
```

path

Find all information about suppliers living in **London** who supply a product named **Chai**

```
db.orders.find({$and: [{"SUPPLIER.city":"London"},  
  {"SUPPLIER.supplies.PRODUCT.product name":"Chai"}]})
```

path and path

Find all information about suppliers living in **London** who supply a product named **Chai** or a product named **Chang**

```
db.orders.find({$and: [{"SUPPLIER.city":"London"},  
  {$or: [{"SUPPLIER.supplies.PRODUCT.product name":"Chai"},  
    {"SUPPLIER.supplies.PRODUCT.product name":"Chang"}]}}])
```

(path or path) and path

```
db.orders.find({$and: [{"SUPPLIER.city":"London"},  
  {"SUPPLIER.supplies.PRODUCT.product name":{"$in":["Chai","Chang"]}}]})
```

path and path

Queries on nested documents

Find all information about suppliers living in **London** who supply a product named **Chai** and a product named **Chang**

```
db.orders.find({$and:[{"SUPPLIER.city":"London"},  
                      {"SUPPLIER.supplies.PRODUCT.product name":"Chai"},  
                      {"SUPPLIER.supplies.PRODUCT.product name":"Chang"}]})
```

path and path and path

Find all information about suppliers who supply at least one product

```
db.orders.find({$and:[{"SUPPLIER.supplies":{"$exists:true}},  
                      {"SUPPLIER.supplies":{"$ne:[]}}]})
```

path and path

Find all information about suppliers who do not supply any products

```
db.orders.find({$and:[{"SUPPLIER.supplies":{"$exists:true}},  
                      {"SUPPLIER.supplies":{"$eq:[]}}]})
```

path and path

Find all information about customers who submitted an order for at least one product **Flotemysost**

```
db.orders.find({"CUSTOMER.submits.ORDER.consists of.ORDER DETAIL.product name":"Flotemysost"})
```

long path

MongoDB Query language

Outline

[MongoDB query language](#)

[A sample database](#)

[Simple queries](#)

[Queries with Boolean operations](#)

[Queries on nested documents](#)

[Queries on arrays](#)

[Projections](#)

[Queries about **NULLs** and missing keys](#)

[Iterations over a cursor](#)

Queries on arrays

Array equal to `[1,2,3,4,5]`

```
{"array":{$all:[1,2,3,4,5]}}
```

find()

Array includes an element that satisfies a condition

```
{"array":{$elemMatch:{$eq:2}}}
```

find()

```
{"array":{$elemMatch:{$gt:2,$lt:4}}}
```

find()

Array includes a document satisfies a condition

```
{"array":{$elemMatch:{"key":{$eq:2}}}}
```

find()

```
{"array":{$elemMatch:{"key":{$gt:2,$lt:4}}}}
```

find()

Size of an array

```
{"array":{$size:5}}
```

find()

```
{"array":{$size:0}}
```

find()

```
{"array":[]}
```

find()

Queries on arrays

Find all information about customers who submitted an order that contains only a product **Boston Crab Meat** at unit price **14.7** in quantity **20** with discount equal to **0**

```
db.orders.find({"CUSTOMER.submits.ORDER.consists of":  
               {$eq: [{"ORDER DETAIL":{"product name":"Boston Crab Meat",  
                                     "unit price":14.7,  
                                     "quantity":20,  
                                     "discount":0}}]}})
```

= array

Find all information about suppliers such that the second supplied product is named **Chang**

```
db.orders.find({"SUPPLIER.supplies.1.PRODUCT.product name":"Chang"})
```

path.n.path

Find all information about suppliers such that the first supplied product is named **Chai** and the second supplied product is named **Chang**

```
db.orders.find({$and: [{"SUPPLIER.supplies.0.PRODUCT.product name":"Chai"},  
                      {"SUPPLIER.supplies.1.PRODUCT.product name":"Chang"}]})
```

path.n.path and path.n.path

Queries on arrays

Find all information about customers who purchased at least one product with discount greater than 0.2

```
db.orders.find({"CUSTOMER.submits.ORDER.consists of.ORDER DETAIL.discount":{"$gt:0.2}})
```

path > v

```
db.orders.find({"CUSTOMER.submits.ORDER.consists of":{"$elemMatch":{"ORDER DETAIL.discount":{"$gt:0.2}}}})
```

path &elemMatch v

Find all information about customers who purchased at least one product with discount equal to 0.25 and quantity equal to 16

```
db.orders.find({"CUSTOMER.submits.ORDER.consists of":{"$elemMatch":{"ORDER DETAIL.discount":{"$eq:0.25},  
"ORDER DETAIL.quantity":{"$eq:16}}}})
```

path &elemMatch v1, ..., vn

Find all information about customers who purchased 4 products in one order

```
db.orders.find({"CUSTOMER.submits.ORDER.consists of":{"$size:4}})
```

\$size

Queries on arrays

Find all information about customers who purchased more than 4 products in one order

```
db.orders.find({"CUSTOMER.submits.ORDER.consists of.4":{"$exists:true}})
```

path.n \$exists

MongoDB Query language

Outline

[MongoDB query language](#)

[A sample database](#)

[Simple queries](#)

[Queries with Boolean operations](#)

[Queries on nested documents](#)

[Queries on arrays](#)


[Projections](#)

[Queries about **NULLs** and missing keys](#)

[Iterations over a cursor](#)

Projections

A sample collection **orders**



[TOP](#)

Created by Janusz R. Getta, CSCI235 Database Systems, Spring 2022

27/34

Projections

Find only a company name and contact name for all suppliers

```
db.orders.find({"SUPPLIER":{"exists:true"}}, {"_id":0, "SUPPLIER.company name":1, "SUPPLIER.contact name":1})
```

Projection

Find all information about suppliers except a company name, contact name and _id

```
db.orders.find({"SUPPLIER":{"exists:true"}}, {"_id":0, "SUPPLIER.company name":0, "SUPPLIER.contact name":0})
```

Projection

Find all information about suppliers except products supplied by suppliers and _id

```
db.orders.find({"SUPPLIER":{"exists:true"}}, {"_id":0, "SUPPLIER.supplies":0})
```

Projection

Find only information about products supplied by suppliers

```
db.orders.find({"SUPPLIER":{"exists:true"}}, {"_id":0, "SUPPLIER.supplies":1})
```

Projection

```
db.orders.find({"SUPPLIER":{"exists:true"}}, {"_id":0, "SUPPLIER.supplies.PRODUCT":1})
```

Projection

Projections

Find only the names of products supplied by suppliers

Projection

```
db.orders.find({"SUPPLIER":{"exists:true"}}, {"_id":0, "SUPPLIER.supplies.PRODUCT.product name":1})
```

Find only the names of products and categories of products supplied by suppliers

Projection

```
db.orders.find({"SUPPLIER":{"exists:true"}}, {"_id":0, "SUPPLIER.supplies.PRODUCT.product name":1,
"SUPPLIER.supplies.PRODUCT.category name":1})
```

Find only company names of suppliers and the names of products supplied by suppliers

Projection

```
db.orders.find({"SUPPLIER":{"exists:true"}}, {"_id":0, "SUPPLIER.company name":1,
"SUPPLIER.supplies.PRODUCT.product name":1})
```

MongoDB Query language

Outline

[MongoDB query language](#)

[A sample database](#)

[Simple queries](#)

[Queries with Boolean operations](#)

[Queries on nested documents](#)

[Queries on arrays](#)

[Projections](#)

[Queries about **NULLs** and missing keys](#)

[Iterations over a cursor](#)

Queries about nulls and missing keys

Find all information about the customers who have no **region** information

```
db.orders.find({"CUSTOMER.region":null})
```

null

Find all information about the customers who have **region** information

```
db.orders.find({"CUSTOMER.region":{"$not":{"$eq:null"}}})
```

\$not null

Find all information about the customers who have **PO Box** in their description

```
db.orders.find({"CUSTOMER.PO Box":{"$exists:true"}})
```

\$exists

Find all information about the customers who do not have **PO Box** in their description

```
db.orders.find({"CUSTOMER.PO Box":{"$exists:false"}})
```

\$exists

```
db.orders.find({"CUSTOMER.PO Box":{"$not":{"$exists:true"}}})
```

\$ not \$exists

MongoDB Query language

Outline

[MongoDB query language](#)

[A sample database](#)

[Simple queries](#)

[Queries with Boolean operations](#)

[Queries on nested documents](#)

[Queries on arrays](#)

[Projections](#)

[Queries about **NULLs** and missing keys](#)

[Iterations over a cursor](#)

Iterations over a cursor

Create a cursor and display all information about suppliers

```
var cursor = db.orders.find({"SUPPLIER":{"$exists:true"}})
while(cursor.hasNext())
{ print(tojson(cursor.next())); }
```

cursor

```
var cursor = db.orders.find({"SUPPLIER":{"$exists:true"}})
cursor.forEach(printjson)
```

cursor

References

[MongoDB Reference, Operators, Query and Projection Operators](#)

Banker K., Bakkum P., Verch S., Garret D., Hawkins T., MongoDB in Action, 2nd ed., Manning Publishers, 2016