

Security incident report

Section 1: Identify the network protocol involved in the incident

The network protocols involved were DNS, TCP, HTTP, and IP. DNS was used to resolve the domain names into IP addresses, TCP was used to establish the connection, HTTP was used to request the webpage and malicious file, and IP was used to route the traffic between the user and the websites.

Section 2: Document the incident

A cybersecurity incident occurred on **yummyrecipesforme.com** after a former employee used a **brute force attack** to gain access to the website's administrative account. The attacker guessed the default password, accessed the admin panel, and inserted malicious JavaScript into the website's source code. This code prompted visitors to download an executable file, which redirected them to **greatrecipesforme.com**, a spoofed website containing malware. The incident was discovered after multiple customers reported unexpected download prompts, browser redirection, and slower computer performance. Evidence from customer complaints, sandbox testing, tcpdump logs, and source code review confirmed the compromise.

Section 3: Recommend one remediation for brute force attacks

One recommended remediation is to enforce multi-factor authentication (MFA) for administrative accounts and limit repeated login attempts. This is effective because the attacker in this incident was able to gain access by guessing the default password through a brute force attack. With MFA, the attacker would still need a second form of verification, such as a code sent to

a phone or email, before logging in. Limiting login attempts would also help stop repeated password guessing. Together, these controls make unauthorized access much more difficult and help protect the website from similar attacks in the future.