



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or just to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to continue practicing applying the NIST CSF framework to different situations you may encounter.

Summary	The company went through a security incident whereby all the network services became unavailable. From the investigations made by the cybersecurity team, it was discovered that the attack was a DDoS (distributed denial of services) attack using a flood of ICMP packets. The team countered this problem by stopping the attacks and all the non-critical network services.
Identify	An attacker or attackers conducted an ICMP flood attack against the organization. The whole internal network was affected by this incident. All network resources had to be protected and restored to their operational state.
Protect	A new firewall rule restricting the rate of incoming ICMP packets and an IDS/IPS system which filters certain ICMP packets because of their suspicious attributes have been used by the cyber security team.
Detect	The cyber security team configured the firewall to validate the source IP address to scan for any spoofing of IP addresses of incoming ICMP packets and installed network monitoring tools to identify unusual traffic patterns.
Respond	For future security events, the cybersecurity team will isolate affected systems to prevent further disruption to the network. They will attempt to restore any critical systems and services that were disrupted by the event. Then, the team

	will analyze network logs to check for suspicious and abnormal activity. The team will also report all incidents to upper management and appropriate legal authorities, if applicable.
Recover	In order to recover from DDoS attack through ICMP flooding, access to network services has to be recovered to its usual functioning level. For future purposes, any external ICMP flood attacks could be prevented through the firewall. Following that, all non-critical network services have to be shut down to cut off internal traffic on the network. After that, critical network services have to be turned on. Lastly, when ICMP packets timeout, all non-critical network services have to be reactivated.

Reflections/Notes: