

ICPC Asia Dhaka Regional 2025

Team: BUBT_Sunday_Monday_Close

Team Members:

1. Md. Tuhin Hasnat
2. Amir Hamza Miraz
3. Rakin Absar Ratul

Generated: December 19, 2025

Contents

1	Utilities	1
1.1	Template	1
1.2	Sublime Build System	1
2	Number Theory	1
2.1	Bigmod	1
2.2	Derangement	1
2.3	Divisors Pre Clc	1
2.4	Prime Factor Sieve	1
2.5	Prime Factor Spf	2
2.6	Sieve	2
2.7	Cumulative Sum 2d	2
2.8	Divisors	2
2.9	Kadanes	2
2.10	Log B N	2
2.11	Ncr Npr Pre Calculation	2
2.12	Number Hashing Rng	3
2.13	Trailing zeroes Of Factorial Number	3
3	String Algorithm	3
3.1	Aho Corasick	3
3.2	Double Hashing	4
3.3	Kmp	4
3.4	Trie Tree	5
3.5	Hashing Longest Common Prefix	5
3.6	Hashing String Divisor	5
4	Backtracking	5
4.1	Combination	5
4.2	Nqueen	5
4.3	Permutation	6
5	Dynamic Programming	6
5.1	1 Knapsack	6
5.2	Edit Distance	6
5.3	Knight Tour	6
5.4	Lcs	7
5.5	Lcs Lexicography Minimum String	7
5.6	Lis Lower Bound	7
5.7	Lis Using Segment Tree	7
5.8	Mcm Burst Balloons	7
5.9	Coin Change Distinct Way	8
5.10	Coin Change Use One More Time Arbitrary Order	8
5.11	Longest Common Substring	8
5.12	Number Of Palindrome In Range Query	8

5.13	Two Player Optimal Moves	8
5.14	Digit DP	8
6	Geometry	9
6.1	Formulas	9
6.2	Convex Hull	9
6.3	Segment Intersect	10
6.4	Segment Intersect 3D	10
7	Tree Algos	11
7.1	Diameter Of A Tree Dfs	11
7.2	Lowest Common Ancestor Sparse Table	11
7.3	Merge Sorttree Number Of Element Greater Than K	11
7.4	Segmenttree Lazypropagation	12
7.5	Segment Tree	12
8	Graph	13
8.1	Articulation Point	13
8.2	Bellman Ford	13
8.3	Bipartite Graph Dfs	14
8.4	Bridges	14
8.5	Dfs	14
8.6	Dfs Cycle Finder	15
8.7	Dijkstra Using Pq	15
8.8	Floyd Warshall	16
8.9	Kruskal Union By Size	16
8.10	Max Flow Dinics Algorithm	17
8.11	Stronglyconnectedcomponents	17
8.12	Topologicalsort Khans	18
9	Matrix	18
9.1	Matrix Exponential	18

Utilities

Template

Code in C++:

```
-----
#include<bits/stdc++.h>
using namespace std;

//For Debugging
#define debug(a...) {cout<<__LINE__<<" #->
    < " ;dbg,a; cout<<endl;}
struct debugger
{
    template<typename T> debugger& operator , (const T v)
```

```
{
    cout<<v<<" ";
    return *this;
}
} dbg;

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
template<class T>using iset=tree<T,null_type,less<T>,//d
    < _ascending_order=greater<T>,multi_iset=less_equal<T>
rb_tree_tag,tree_order_statistics_node_update> ;//exmp=
    < iset<double>st
//who is k'th position= *(set.find_by_order(k)),index of
    < v = set.order_of_key(v);

typedef long long ll;// 1e18;
//typedef __int128_t LL;// 1e32;
#define deb(a) cout<<__LINE__<<"# "<<#a<<" ->
    < " <<a<<endl;
#define lbv(vec,x)
    < lower_bound(all(vec),x)-vec.begin()//retrun index
#define lba(ar,n,x) lower_bound(ar,ar+n,x)-&ar[0]//return
    < index

#define LCM(a,b) (a*b)/__gcd(a,b)
#define deg(n) n*180/PI // radian to degree
#define sp(n,d) fixed << setprecision(d) <<n

template <typename T>
using minHeap = priority_queue<T, vector<T>, greater<T>>;

const double PI = acos(-1);
const double EPS = 1e-7; //1*10^-7
const int oo = 1e9+10;
const ll MOD = 1e9 +7;// Prime
signed main()
{
    #ifndef ONLINE_JUDGE
    // freopen("inputf.in", "r", stdin); //To read from
    < a file.
    // freopen("outputf.in", "w", stdout); //To write a
    < file.
    #endif
    cin.tie(nullptr)->sync_with_stdio(false);
}

}
```

Sublime Build System

Code in Bash:

```
{
    "shell_cmd": "g++ -std=c++17 \"${file}\" -o
    \"${file_path}/${file_base_name}\" &&
    \"${file_path}/${file_base_name}\" <
    \"${file_path}/inputf.in\" >
    \"${file_path}/outputf.out\"",
    "working_dir": "${file_path}",
    "selector": "source.cpp"
}
```

Number Theory

Bigmod

Code in C++:

```
ll mul(ll a, ll b, ll mod) { // a * b % mod
    return __int128(a) * b % mod;
}
ll power(ll a, ll b, ll mod) { // a^b % mod
    ll ans = 1 % mod;
    while (b) {
        if (b & 1) ans = mul(ans, a, mod);
        a = mul(a, a, mod);
        b >>= 1;
    }
    return ans;
}
ll inverse(ll a, ll mod) { // (1 / a) % mod
    return power(a, mod - 2, mod);
}
```

Derangement

Code in C++:

```
ll der[MAXN];
void precalculate_derangements() {
    der[0]=1;der[1]=0;der[2]=1;
    for (int i = 3; i < MAXN; i++) {
        der[i]=(i-1)*(der[i-1]+der[i-2])%MOD;
    }
}
```

Divisors Pre Clc

Code in C++:

```
///nlog(log(n))
vector<int>divisors[1000010];
void Divisor_pre_clc(){
    for(int div=1;div<=1000000;div++){
        for(int num=div;num<=1000000;num+=div)
            divisors[num].push_back(div);
    }
}
```

Prime Factor Sieve

Code in C++:

```
-----
#define SIZE_N 10000000 // 10^7
bool isprime[SIZE_N + 4];
vector<int> prime;
void sieve() {
    for(int i=3;i<=SIZE_N;i+=2)isprime[i]=true;
    isprime[2] = true;
    prime.push_back(2);
    for (ll i = 3; i <= SIZE_N; i += 2) {
        if (isprime[i]) {
            prime.push_back((int)i);
            if ((ll)SIZE_N / i >= i) {
                for (ll j = i * i; j <= SIZE_N; j += 2 *
                    i)
                    isprime[j] = false;
            }
        }
    }
    //it handle up to 10^14 with current sieve
    void prime_factors(ll n) {
        for(int i=0;i<prime.size()&&(ll)prime[i]*prime[i]<=n;i++){
            while (n % prime[i] == 0) {
                cout << prime[i] << " ";
                n /= prime[i];
            }
        }
        if (n > 1) cout << n;
    }
    int main() {
        sieve();
        prime_factors(100000000000000LL); // 10^14
    }
}
```

Prime Factor Spf

Code in C++:

```
-----
int spf[N];///smallest prime factor
void spf_pre_clc(){///nlog(log(n))
    for(int i=2;i<=N;i++){
        spf[i]=i;
    }
    for(int div=2;div<=N;div++){
        for(int i=div;i<=N;i+=div){
            spf[i]=min(spf[i],div);
        }
    }
}
void prime_factors(int n){///log(n)
    while(n>1){
        cout<<spf[n]<<" ";
    }
}
```

```
        n/=spf[n];
    }
}
int32_t main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    spf_pre_clc();
    int n;
    cin>>n;
    prime_factors(n);
}
```

Sieve

Code in C++:

```
-----
///Nlog(N)
const int N = 1e7 + 9;
bitset<N> not_prime;
vector<int> primes;
void sieve(){
    not_prime[1] = true;
    for (int i = 2; i * i <= N; i++) {
        if (!not_prime[i]) {///prime
            for (int j = i * i; j <= N; j += i) {
                not_prime[j] = true;
            }
        }
    }
    for (int i = 2; i <= N; i++) {
        if (!not_prime[i]) { /// prime
            primes.push_back(i);
        }
    }
}
```

Cumulative Sum 2d

Code in C++:

```
-----
int r,c;
scanf("%d%d",&r,&c);
int ar[r+5][c+5],px[r+5][c+5];
for(int i=1;i<=r;i++)
    for(int j=1;j<=c;j++){
        cin>>ar[i][j];

        for(int i=0;i<=r;i++)px[i][0]=0;
        for(int j=0;j<=c;j++)px[0][j]=0;

        px[1][1]=ar[1][1];
        for(int i=2;i<=r;i++){
            px[i][1]=px[i-1][1]+ar[i][1];
        }
        for(int j=2;j<=c;j++){
```

```

    px[1][j]=px[1][j-1]+ar[1][j];
}
for(int i=2;i<=r;i++){
    for(int j=2;j<=c;j++){
        px[i][j]=px[i-1][j]+px[i][j-1]+ar[i][j]-px[i-1][j]
        - -1];
    }
    cout<<"\nprefix sum array : "<<endl;
for(int i=1;i<=r;i++){
    for(int j=1;j<=c;j++){
        cout<<px[i][j]<<" ";
    }
    cout<<"\n";
}
cout<<"Range of summation array (i1,j1)->(i2,j2)"<<endl;
int i1,i2,j1,j2,ans;
cin>>i1>>j1>>i2>>j2;
if(i1>i2)swap(i1,i2);
if(j1>j2)swap(j1,j2);

ans=px[i2][j2]-px[i2][j1-1]-px[i1-1][j2]+px[i1-1][j1-1];

cout<<"sum of range = "<<ans<<endl;

```

Divisors

Code in C++:

```

void divisors(int n){
    vector<int> divs;
    for (int i=1;i*i<=n;i++){
        if (n%i==0){
            divs.push_back(i);
            if (i!=n/i)divs.push_back(n/i);
        }
    }
    sort(divs.begin(), divs.end());
    for (auto x: divs) cout << x << ' ';
}

```

Kadanes

Code in C++:

```

cin>>n;
ll ar[n+6];
ll mx=-999999999;
ll sum=0;
for(int i=1;i<=n;i++){
    cin>>ar[i];
    sum=max(ar[i],sum+ar[i]);
    mx=max(mx,sum);
}

```

```
cout<<mx<<"\n";
```

Log B N

Code in C++:

```

int n,b;cin>>n>>b;
double ans;
ans=(log2(n)/log2(b));
cout<<ans<<"\n";

```

Ncr Npr Pre Calculation

Code in C++:

```

template <typename T>
T INV(T base,T mod=1e9+7){
    return BIGMOD(base%mod,mod-2,mod)%mod;
}

long long fact[N+10];
long long inv_fact[N+10];
void pre() {
    fact[0] = 1;
    for (long long i = 1; i <= N; i++)
        fact[i] = (fact[i - 1] * i)%MOD;

    inv_fact[N] = INV(fact[N]);
    for (long long i=N-1;i>=0;i--)
        inv_fact[i] = (inv_fact[i + 1]*(i+1))%MOD;
}

long long nCr(long long n, long long r) {
    if (r > n || r < 0) return 0;
    return fact[n] * inv_fact[r]%MOD*inv_fact[n-r]%MOD;
}

long long nPr(long long n, long long r) {
    if (r > n || r < 0) return 0;
    return fact[n] * inv_fact[n-r]%MOD;
}

signed main(){
    pre();
    int n,r;
    cin>>n>>r;
    cout<<nCr(n,r)<<" "<<nPr(n,r)<<"\n";
}

other way NCR
long long ncr(int n, int r){
    int res = 1;
    for (int i=0; i<r; i++){
        res *= (n-i);
        res /= (i+1);
    }
    return res;
}

```

Number Hashing Rng

Code in C++:

```

struct custom_hash {
    static uint32_t splitmix32(uint32_t x) {
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator()(uint32_t x) const {
        static const uint32_t FIXED_RANDOM =
            chrono::steady_clock::now().time_since_epoch().count();
        return splitmix32(x + FIXED_RANDOM);
    }
}rng;

signed main(){
    int a=rng(1);
    int b=rng(2);
    int c=rng(3);
    cout<<a<<" "<<bitset<32>(a)<<"\n";
    cout<<b<<" "<<bitset<32>(b)<<"\n";
    cout<<c<<" "<<bitset<32>(c)<<"\n";
    // if xor 1,2,3 then generally ans will be
    // zero.because (1^2=3) ^ 3 =0
    // if we this function then ans will never be zero
    // because
    // (rng(1)^rng(2) != rng(3)) ^ rng(3) = 0
    // There can be only one way ans will be zero when we
    // xor the same number with it.
    // rng(num)^rng(num) = 0 // rng(num)-rng(num)=0
}

```

Trailing zeroes Of Factorial Number

Code in C++:

```

int findTrailingZeros(int n){
    int count = 0;
    for (int i = 5; n / i >= 1; i *= 5)
        count += n / i;
    return count;
}

```

String Algorithm

Aho Corasick

Code in C++:

```

//Time Complexity: O(n + l + z), where 'n' is the length
↳ of the text, 'l'(sum of all ptrns len) is the length
↳ of keywords, and 'z' is the number of matches.
const int MX_P = 100; // maximum number of patterns
struct AhoCorasick{
    int nod_no, ptrn_no;
    const int root = 0;
    vector<vector<int>>> next;
    vector<int> link; // suffix link/failure link
    vector<bitset<MX_P>>> output; // bitset points which
↳ which patterns output indicated by this state
    bitset<MX_P> zero; // zero
    vector<int> occr;

    AhoCorasick(): nod_no(0), ptrn_no(0){node();}

    int node(){
        next.emplace_back(26, 0);
        link.emplace_back(root); // all link initialize by
↳ root;
        output.emplace_back(zero); // each node initialize
↳ by 0 set bit
        occr.emplace_back(0); // each pattern occraance
↳ initialize by zero
        return nod_no++; // increase node count
    }

    void add_pattern(const string &s){ // trie building
        int currentState = root;
        for(auto c : s){
            int ch = c - 'a';
            if(!next[currentState][ch])
                next[currentState][ch] = node(); //
↳ node() = create a new node in this state
↳ and also next[currentState][ch] set
↳ with a state number
            currentState = next[currentState][ch];
        }
        output[currentState][ptrn_no] = 1; // this states
↳ end point of prth_no th pattern
        // output[currentState].set(ptrn_no, 1);
        ptrn_no++; // increase pattern count
    }

    void build_Automaton(){
        queue<int> Q;
        for(int ch = 0; ch < 26; ch++){
            if(next[root][ch]){
                int stat_lv1 = next[root][ch]; //
↳ stat_lv1 = state which connect with
↳ root
                link[stat_lv1] = root; // make level 1
↳ states failure link with root
                Q.push(stat_lv1);
            }
        }
    }
}

```

```

while(Q.size()){
    int currentState = Q.front(); Q.pop();
    for(int ch = 0; ch < 26; ch++){
        if(next[currentState][ch]){
            int child_state = next[currentState][ch];
            ↳ ;
            int failure = link[currentState];

            while(failure != root &&
                ↳ !next[failure][ch]) // finding
                ↳ failure node
                failure = link[failure];
            failure = next[failure][ch];

            link[child_state] = failure;
            output[child_state] |= output[failure];
            ↳ // a state also indicate
            ↳ failure states all outputs
            Q.push(child_state);
        }
    }
}

int find_NextState(int currentState, int ch){
    while(currentState != root &&
        ↳ !next[currentState][ch])
        currentState = link[currentState];

    return currentState = next[currentState][ch];
}

void searchWords(string pattern[], string &text){
    int currentState = root;
    for(int i = 0; i < text.size(); i++){
        int ch = text[i] - 'a';
        currentState = find_NextState(currentState, ch);
        if(output[currentState].any()) // chacking
            ↳ this state point any output
            for(int j = 0; j < ptrn_no; j++){
                if(output[currentState][j]) // if i'th
                    ↳ bit is on
                    cout << pattern[j] << " appears from
                    ↳ "<<i-pattern[j].size()+1<<" to
                    ↳ "<<i<<"\n";
                    occr[j]++; // increse j'th
                    ↳ patterns occurence
            }
        }
    }
}

int main(){
    int n; cin >> n;
    string pattern[n+1];
    string text;
}

```

```

AhoCorasick aho;
for(int i = 0; i < n; i++){
    cin >> pattern[i];
    aho.add_pattern(pattern[i]);
}
cin >> text;
aho.build_Automaton();
aho.searchWords(pattern, text);
for(int i = 0; i < n; i++){
    cout << pattern[i] << " occurs " << aho.occrr[i] << "
    ↳ times\n";
}
}

```

Double Hashing

Code in C++:

```

const int MAX = 1e6 + 10; // string max size
const ll MOD1 = 1e9 + 7;
const ll MOD2 = 1e9 + 9;
const ll base1 = 269; // 31, // 53
const ll base2 = 277; // 31, // 53
pair<ll, ll> pw[MAX], inv_pw[MAX];
void pow_clc(){
    ll rev_base1 = BIGMOD(base1, MOD1-2, MOD1); // base1^-1
    ll rev_base2 = BIGMOD(base2, MOD2-2, MOD2); // base2^-1
    pw[0] = {1, 1};
    inv_pw[0] = {1, 1};
    for(int i = 1; i < MAX; i++){
        pw[i].F = 1LL * pw[i-1].F * base1 % MOD1;
        inv_pw[i].F = 1LL * inv_pw[i-1].F * rev_base1 %
            ↳ MOD1;

        pw[i].S = 1LL * pw[i-1].S * base2 % MOD2;
        inv_pw[i].S = 1LL * inv_pw[i-1].S * rev_base2 %
            ↳ MOD2;
    }
}

ll compute_prehash(string const &s) // 0 (string size)
pair<ll, ll> hash_value = {0, 0};
for(int i = 0; i < s.size(); i++){
    hash_value.F = (hash_value.F +
        ↳ (s[i]*pw[i].F)%MOD1)%MOD1;
    hash_value.S = (hash_value.S +
        ↳ (s[i]*pw[i].S)%MOD2)%MOD2;
}
return (hash_value.F*MOD2 + hash_value.S);
}

vector<pair<ll, ll>> prehsh, sufsh;
int len;
void hashing(string const &s) // make a hash array in
↳ O(string size)
    len = s.size();
    prehsh.resize(len+4);
    sufsh.resize(len+4);
}

```

```

for(int i=0;i<len;i++){
    prehsh[i].F= (1LL*s[i]*pw[i].F) %MOD1;
    prehsh[i].S= (1LL*s[i]*pw[i].S) %MOD2;
    if(i){
        prehsh[i].F= (prehsh[i].F + prehsh[i-1].F)
        ↪ %MOD1;
        prehsh[i].S= (prehsh[i].S + prehsh[i-1].S)
        ↪ %MOD2;
    }
    sufhsh[i].F= (1LL*s[i]*pw[len-i-1].F) %MOD1;
    sufhsh[i].S= (1LL*s[i]*pw[len-i-1].S) %MOD2;
    if(i){
        sufhsh[i].F= (sufhsh[i].F + sufhsh[i-1].F)
        ↪ %MOD1;
        sufhsh[i].S= (sufhsh[i].S + sufhsh[i-1].S)
        ↪ %MOD2;
    }
}
}
ll substring_hash(int i,int j){//O(1)
    assert(i<=j);
    pair<ll,ll>hs({0,0});
    hs.F=prehsh[j].F;
    hs.S=prehsh[j].S;
    if(i){
        hs.F=(hs.F- prehsh[i-1].F +MOD1)%MOD1;
        hs.S=(hs.S- prehsh[i-1].S +MOD2)%MOD2;
    }
    hs.F= (1LL* hs.F * inv_pw[i].F)%MOD1;
    hs.S= (1LL* hs.S * inv_pw[i].S)%MOD2;
    return (hs.F*MOD2 + hs.S);
}
ll GetPrefixHash(int i,int j){
    return substring_hash(i, j);
}
ll GetSuffixHash(int i,int j){
    assert(i<=j);
    pair<ll,ll>hs({0,0});
    hs.F=sufhsh[j].F;
    hs.S=sufhsh[j].S;
    if(i){
        hs.F=(hs.F- sufhsh[i-1].F +MOD1)%MOD1;
        hs.S=(hs.S- sufhsh[i-1].S +MOD2)%MOD2;
    }
    hs.F= (1LL* hs.F * inv_pw[len-j-1].F)%MOD1;
    hs.S= (1LL* hs.S * inv_pw[len-j-1].S)%MOD2;
    return (hs.F*MOD2 + hs.S);
}
bool IsPalindrome(int l , int r) {
    return (GetPrefixHash(l , r) == GetSuffixHash(l , r));
}
void string_matching(string const &txt,string const
    ↪ &pat){//O(N)//Rabin Karp
    hashing(txt);
    ll pat_hsh=compute_prehash(pat);

```

```

int substr_len=pat.size();
vector<int>idx;
for(int i=0;i+substr_len-1<txt.size();i++){
    ll substr_hsh=substring_hash(i,i+substr_len-1);
    if(substr_hsh==pat_hsh)idx.push_back(i+1);
}
if(idx.size()){
    cout<<"pattern found at index : ";
    for(auto it: idx)cout<<it<<" ";
    cout<<"\n";
}else{
    cout<<"pattern not found\n";
}
}
int main() {
    pow_clc();
    string txt,pat;
    while(cin>>txt>>pat){
        hashing(txt);
        string_matching(txt,pat);
    }
    return 0;
}

```

Kmp

Code in C++:

```

vector<int> failure_function(string &p){
    vector<int>failure_idx(p.size(),0);
    for(int i=1;i<p.size();i++){
        int j=failure_idx[i-1];
        while(j>0 && p[i]!=p[j]){
            j=failure_idx[j-1];
        }
        if(p[i]==p[j])failure_idx[i]=++j;
    }
    return failure_idx;
}
void KMP(string &txt,string &pat){
    vector<int>failure_idx=failure_function(pat);
    int j=0;
    for(int i=0;i<txt.size();i++){
        while(j>0 && txt[i]!=pat[j])j=failure_idx[j-1];
        if(txt[i]==pat[j]){
            j++;
            if(j==pat.size()){
                cout<<i-pat.size()+1<<" ";
                j=failure_idx[j-1];
            }
        }
    }
}

```

Trie Tree

Code in C++:

```

struct node{
    bool End;
    vector<node*>next;
    node(){
        End=false;
        next.resize(26,nullptr);
    }
};
class Trie {
public:
    node* root;
    Trie() {
        root=new node();
    }
    void insert(string &word) {
        node*cur=root;
        for(auto ch : word){
            if(!cur->next[ch-'a'])cur->next[ch-'a']=new
                ↪ node();
            cur=cur->next[ch-'a'];
        }
        cur->End=true;
    }
    bool search(string &word) {
        node*cur=root;
        for(auto ch : word){
            if(!cur->next[ch-'a'])return false;
            cur=cur->next[ch-'a'];
        }
        return cur->End;
    }
    bool startsWith(string &prefix) {
        node*cur=root;
        for(auto ch : prefix){
            if(!cur->next[ch-'a'])return false;
            cur=cur->next[ch-'a'];
        }
        return true;
    }
};

```

Hashing Longest Common Prefix

Code in C++:

```

void lcp(int i1,int j1,int i2,int j2){
    int l=1,r=min(j1-i1+1,j2-i2+1);// minimum length of
    ↪ two string
    int ans=0;
    while(l<=r){

```

```

        int mid = l+r >>1;
        if(sub_hash(i1,i1+mid-1,txthsh)==sub_hash(i2,i2+mid-1,txthsh)){
            mid=mid+1;
        }else{
            mid=mid-1;
        }
    }
    cout<<ans<<"\n";
    cout<<txt.substr(i1,ans)<<"\n";
}

```

Hashing String Divisor

Code in C++:

```

void string_divisors(string const &s){/// nlog(n)
    hashing(s);
    int n=s.size();
    for(int len=1;len<=n;len++){
        bool ok=true;
        for(int i=0;i+len-1<n;i+=len){
            ok &= sub_hash(i,i+len-1)==sub_hash(0,len-1);

            if(i+len+len-1>=n && i+len<=n-1){///partial
                ok &= sub_hash(i+len,n-1)==sub_hash(0,n-1-i-len);
            }
        }
        if(ok==true){
            cout<<s.substr(0,len)<<"\n";
        }
    }
}

```

Backtracking

Combination

Code in C++:

```

int sto[20];
int N, R;
void bt(int start, int depth){
    if(depth == R){
        for(int i=0;i<R;i++){
            cout<<sto[i]<<" ";
            cout<<endl;
            return;
        }
        for(int i = start;i<=N;i++){
            sto[depth] = i;
            bt(i+1, depth+1);
        }
    }
}

```

```

    }
}
int main(){
    while(cin>>N>>R){
        bt(1, 0);
    }
}

```

Nqueen

Code in C++:

```

int n;
vector<vector<string>>boards;
bool UnderAttack(int row,int col,vector<string>&board){
    int duprow = row;
    int dupcol = col;
    while(row>=0 && col>=0){
        if(board[row][col]=='Q'){
            return true;
        }
        --row,--col;
    }
    col = dupcol;
    row = duprow;
    while(row<n && col<=0){
        if(board[row][col]=='Q'){
            return true;
        }
        ++row,--col;
    }
    row = duprow;
    col = dupcol;
    while(col<=0){
        if(board[row][col]=='Q'){
            return true;
        }
        --col;
    }
    return false;
}
void res(int col,vector<string>&board){
    if(col==n){
        boards.push_back(board);
        return;
    }
    for(int row=0;row<n;row++){
        if(UnderAttack(row,col,board)){
            continue;
        }
        board[row][col]='Q';
        res(col+1,board);
        board[row][col]='.';
    }
}
int main(){

```

```

    cin>>n;
    vector<string>board(n,string(n,'.'));
    res(0,board);
    int w=0;
    for(auto ans : boards){
        cout<<"Possible Way : "<<w++<<el;
        for(auto r : ans){
            cout<<r<<el;
        }
        cout<<el;
    }
    board.clear(),boards.clear();
}

```

}

Permutation

Code in C++:

```

int n,r;
int color[S],sto[S];
void go(int depth){
    if(depth==r){
        for(int i=0;i<r;i++){
            printf("%d ",sto[i]);
        }
        printf("\n");
        return;
    }
    for(int i=1;i<=n;i++){
        if(color[i]==false){
            color[i]=true;
            sto[depth]=i;
            go(depth+1);
            color[i]=false;
        }
    }
}
int main(){
    while(cin>>n>>r){
        memset(color, false, sizeof color);
        go(0);
    }
}

```

Dynamic Programming

1 Knapsack

Code in C++:


```

int knapSack(int i, int sto) {
    if (sto < 0) return INT_MIN;
    if (i < 0 || sto == 0) return 0;

    if(memo[i][sto] != -1) return memo[i][sto];

    int in = val[i] + knapSack(i-1, sto-wt[i]);
    int ex = knapSack(i-1, sto);
    return memo[i][sto] = max(in, ex);
}

void path(int i, int sto) {
    if(sto < 0) return;
    if(i < 0 || sto == 0) return;
    int in = memo[i-1][sto-wt[i]] + val[i];
    int ex = memo[i-1][sto];
    if(in > ex) {
        v.push_back(val[i]);
        path(i-1, sto-wt[i]);
    }
    else {
        path(i-1, sto);
    }
}

```

Edit Distance

Code in C++:

```

int EditDistance(int i, int j) {
    if(i < 0) return j+1;
    if(j < 0) return i+1;

    if(memo[i][j] != -1) return memo[i][j];

    if(s1[i] == s2[j])
        return memo[i][j] = EditDistance(i-1, j-1);

    // any move cost 1
    int Insert = 1 + EditDistance(i, j-1);
    int Delete = 1 + EditDistance(i-1, j);
    int Remove = 1 + EditDistance(i-1, j-1);
    return memo[i][j] = min({Insert, Delete, Remove});
}

```

Knight Tour

Code in C++:

```

typedef struct {int x, y;} co;
int dis[1006][1006], n;
int dp[1<<17][17];
int N, k;

```

```

co ic[20];
void BFS() {
    queue<co> q;
    int r, c, ur, uc,
    dr[] = {2, 2, 1, 1, -1, -1, -2, -2},
    dc[] = {1, -1, 2, -2, 2, -2, 1, -1};
    memset(dis, -1, sizeof(dis));
    dis[2][2] = 0;
    q.push({2, 2});

    while(!q.empty()) {
        ur = q.front().x;
        uc = q.front().y;
        q.pop();
        for(int i=0; i<8; i++) {
            r = ur + dr[i]; c = uc + dc[i];
            if(r >= 0 && c >= 0 && r <= 1002 && c <= 1002 &&
            dis[r][c] == -1) {
                q.push({r, c});
                dis[r][c] = dis[ur][uc] + 1;
            }
        }
    }
}

int DIS(co a, co b) {
    if(
        (a.x==1 && a.y==1 && b.x==2 && b.y==2) ||
        (a.x==2 && a.y==2 && b.x==1 && b.y==1) ||
        (a.x==n-1 && a.y==n-1 && b.x==n && b.y==n) ||
        (a.x==n && a.y==n && b.x==n-1 && b.y==n-1) ||
        (a.x==1 && a.y==n && b.x==2 && b.y==n-1) ||
        (a.x==2 && a.y==n-1 && b.x==1 && b.y==n) ||
        (a.x==n && a.y==1 && b.x==n-1 && b.y==2) ||
        (a.x==n-1 && a.y==2 && b.x==n && b.y==1)
    )
        return 4;
    return dis[abs(a.x-b.x)+2][abs(a.y-b.y)+2];
}

int go(int msk, int cur) {
    if(msk == ((1<<k)-1)) return DIS(ic[cur], ic[0]);
    int &rf = dp[msk][cur];
    if(rf != -1) return rf;
    rf = 1<<30;
    for(int i=0; i<k; i++) {
        if((msk & (1<<i)) == 0) {
            rf = min(rf, go((msk | (1<<i)), i) + DIS(ic[cur], ic[i]));
        }
    }
    return rf;
}

int main() {
    co s, a, b; int t, ks=0;
    BFS(); //pre
    cin >> t;

```

```

    while(t--){
        memset(dp, -1, sizeof dp);
        cin >> n >> k;
        for(int i=0; i<k; i++){
            cin >> ic[i].x >> ic[i].y;
        }
        cout << go(0, 0) << "\n";
    }
}

```

Lcs

Code in C++:

```

int lcs(int t, int p) {
    if(t==n || p==m) return 0;
    if(memo[t][p] != -1) return memo[t][p];
    if(txt[t] == pat[p]) {
        memo[t][p] = 1 + lcs(t+1, p+1);
    }
    else {
        memo[t][p] = max(lcs(t+1, p), lcs(t, p+1));
    }
    return memo[t][p];
}

void path(int t, int p) {
    if(t==n || p==m) return;
    if(txt[t] == pat[p]) {
        ans += txt[t];
        path(t+1, p+1);
    }
    else if(memo[t+1][p] > memo[t][p+1]) {
        path(t+1, p);
    }
    else {
        path(t, p+1);
    }
}

```

Lcs Lexicography Minimum String

Code in C++:

```

string dp[105][105];
bool vis[105][105];
string lcs(int i, int j) {
    if(i==n || j==m) return "";
    if(vis[i][j]) return dp[i][j];

    vis[i][j] = true;
    string ans = "";
    if(txt[i] == pat[j]) {
        ans = txt[i] + lcs(i+1, j+1);
    }
    else {

```



```

string a=lcs(i+1,j);
string b=lcs(i,j+1);
if(a.size()>b.size()){
    ans=a;
}else if(a.size()<b.size()){
    ans=b;
}else{
    ans=min(a,b);
}
}
dp[i][j]=ans;
return dp[i][j];
}

```

Lis Lower Bound

Code in C++:

```

int LIS(vector<int>&a){
    vector<int>v;
    int ans=0;
    for(auto x : a){
        auto it =lower_bound(v.begin(),v.end(),x);
        ans=max(ans,(int)(it-v.begin()+1));
        if(it==v.end()){
            v.push_back(x);
        }else{
            *it=x;
        }
    }
    return ans;
}

```

Lis Using Segment Tree

Code in C++:

```

void solve(){
    cin>>n;
    int ar[n+2];
    for(int i=0;i<n;i++){
        cin>>ar[i];
    }

    // segmenttree not working above 1e6 // needs to
    // compress values
    // coordinate compression, now all a[i] are 1 <= a[i]
    // <= n which is cute
    /**
    set<int>s;
    for(int i=0;i<n;i++)s.insert(ar[i]);
    int id=0;
    map<int,int>mp;
    for(auto it : s)mp[it]=++id;
    for(int i=0;i<n;i++)ar[i]=mp[ar[i]];
    */

```

```

*/
int max_value=n;// after compression max value will be
    ~ n or id
// segment tree on value
// MAX Segment Tree
st.build(1,1,max_value);
vector<int>dp(n+2,1);
int mx=1;
for(int i=0;i<n;i++){
    // for(int j=0;j<i;j++){
    //     if(ar[j]<ar[i]){
    //         dp[i]=max(dp[i],1+dp[j]);
    //     }
    // }
    // mx=max(dp[i],mx);
    dp[i]=max(dp[i],st.query(1,1,max_value,1,ar[i]-1)
    ~ +1);// MAX Segment
    ~ Tree
    st.update(1,1,max_value,ar[i],dp[i]);// MAX
    ~ Segment Tree update
    mx=max(mx,dp[i]);
}
cout<<mx<<"\n";
}

```

Mcm Burst Balloons

Code in C++:

```

int go(int i,int j){
    if(i>j)return 0;
    int &rf=dp[i][j];
    if(rf!=-1)return rf;
    rf=-9999999;
    for(int idx=i;idx<=j;idx++){
        rf=max(rf,ar[i-1]*ar[idx]*ar[j+1]+go(i,idx-1)+go(
        ~ idx+1,j));
    }
    return rf;
}

```

Coin Change Distinct Way

Code in C++:

```

memset(dp,0,sizeof dp);
dp[0]=1;
for(int i=0;i<n;i++){
    for(int j=0;j<=s;j++){
        if(j-c[i]>=0){
            dp[j]=dp[j]+dp[j-c[i]]%MOD;
        }
    }
}
cout<<dp[s]%MOD<<endl;

```

Coin Change Use One More Time Arbitrary Order

Code in C++:

```

int way(int W) {
    if (W < 0) return INF;
    if (W == 0) return 0;

    int &rf=memo[W];
    if (rf != -1) {
        return rf;
    }
    rf = INF;
    for (int i = 0; i < NC; i++) {
        rf = min(rf, 1 + way(W - C[i]));
    }
    return rf;
}

```

Longest Common Substring

Code in C++:

```

int lcs(string &s1, string &s2)
{
    int l1=s1.size(),l2=s2.size();
    vector<vector<int>>dp(l1+3,vector<int>(l2+3,0));
    int ans=0;
    for(int i=l1-1;i>=0;i--){
        for(int j=l2-1;j>=0;j--){
            if(s1[i]==s2[j]){
                dp[i][j]=1+dp[i+1][j+1];
            }else{
                dp[i][j]=0;
            }
            ans=max(ans,dp[i][j]);
        }
    }
    return ans;
}

```

Number Of Palindrome In Range Query

Code in C++:

```

string s;int q;
int ispal[5010][5010];
int IsPalindrome(int l , int r) {

```

```

    if(l>r)return 1;
    if(ispal[l][r]!=-1)return ispal[l][r];
    return ispal[l][r]= s[l]==s[r] &
        ↪ IsPallindrome(l+1,r-1);
}
int dp[5010][5010];
int num_of_palin(int l,int r){
    if(l>r)return 0;
    if(dp[l][r]!=-1)return dp[l][r];
    return dp[l][r]=IsPallindrome(l,r)+
        num_of_palin(l+1,r)+num_of_palin(l,r-1)-num_of_pa
        ↪ lin(l+1,r-1);
}
}
int main() {
    cin>>s>>q;
    memset(dp,-1,sizeof dp);
    memset(ispal,-1,sizeof ispal);
    while(q--){
        int l,r;
        cin>>l>>r;
        l--,r--;
        cout<<num_of_palin(l,r)<<"\n";
    }
}

```

Two Player Optimal Moves

Code in C++:

```

ll dp1[3005][3005];
bool vis1[3005][3005];
ll dp2[3005][3005];
bool vis2[3005][3005];
ll ar[3005];
ll first_player_optimal(int i,int j);///function prototype
ll second_player_optimal(int i,int j){

    if(i>j)return 0;

    if(vis2[i][j])return dp2[i][j];
    vis2[i][j]=true;

    ll left =first_player_optimal(i+1 ,j)-ar[i];
    ll right =first_player_optimal(i ,j-1)-ar[j];
    return dp2[i][j] = min(left,right);
}

ll first_player_optimal(int i,int j){

    if(i>j)return 0;

    if(vis1[i][j])return dp1[i][j];
    vis1[i][j]=true;

    ll left =second_player_optimal(i+1,j)+ar[i];
    ll right =second_player_optimal(i,j-1)+ar[j];
}

```

```

        return dp1[i][j] = max(left,right);
    }
}

```

Digit DP

Code in C++:

```

ll dp[10][10][2][2];
ll go(ll pos,ll st,ll ever_sm,ll val,int len,string &s){
    if(pos==len)return val;
    ll &rf=dp[pos][val][ever_sm][st];
    if(rf!=-1)return rf;
    rf=0;
    if(st){
        if(ever_sm){
            for(ll i=0;i<=9;i++){
                rf+=go(pos+1,1,1,val+(i==0),len,s);
            }
        }else{
            for(ll i=0;i<=s[pos]-'0';i++){
                rf+=go(pos+1,1,ever_sm|(i<(s[pos]-'0')),v
                ↪ al+(i==0),len,s);
            }
        }
    }else{
        rf+=go(pos+1,0,1,0,len,s);
        if(pos==0){
            for(ll i=1;i<=s[0]-'0';i++){
                rf+=go(pos+1,1
                ↪ ,ever_sm|(i<(s[pos]-'0')),0,len,s);
            }
        }else{
            for(ll i=1;i<=9;i++){
                rf+=go(pos+1,1 ,1,0,len,s);
            }
        }
    }
    return rf;
}
}

```

Geometry

Formulas

Vector Algebra


Magnitude / Length: $|\vec{a}| = \sqrt{a_x^2 + a_y^2 + a_z^2}$

ভেক্টরের দৈর্ঘ্য বা মান (Magnitude) নির্ণয় করতে এটি ব্যবহৃত হয়।

Dot Product: $\vec{a} \cdot \vec{b} = a_x b_x + a_y b_y + a_z b_z = |\vec{a}| |\vec{b}| \cos \theta$

দুটি ভেক্টর লম্ব (Perpendicular) কিনা তা চেক করতে $(\vec{a} \cdot \vec{b} = 0)$ অথবা তাদের মধ্যবর্তী কোণ θ বের করতে ব্যবহৃত হয়।

Angle Between Vectors: $\cos \theta = \frac{\vec{a} \cdot \vec{b}}{|\vec{a}| |\vec{b}|}$



Projection

Projection of \vec{a} onto \vec{b} :

$$\text{proj}_{\vec{b}} \vec{a} = \frac{\vec{a} \cdot \vec{b}}{|\vec{b}|^2} \vec{b}$$

ভেক্টর \vec{a} এর ছায়া বা উপাংশ ভেক্টর \vec{b} এর ওপর কতটুকু তা বের করার জন্য।

Cross Product: $\vec{a} \times \vec{b} = \begin{vmatrix} \hat{i} & \hat{j} & \hat{k} \\ a_x & a_y & a_z \\ b_x & b_y & b_z \end{vmatrix}$

দুটি ভেক্টরের লম্ব ভেক্টর (Normal Vector) পেতে অথবা তাদের দ্বারা গঠিত সামান্তরিকের ক্ষেত্রফল (Area of Parallelogram) এবং ত্রিভুজের ক্ষেত্রফল $(0.5 \times |\vec{a} \times \vec{b}|)$ বের করতে।

Coordinate Geometry Rotation

একটি বিন্দু (x, y) কে মূলবিন্দুর (Origin) সাপেক্ষে θ কোণে ঘড়ির কাঁটার বিপরীতে (Counter-Clockwise) ঘোরাতে:

2D / Rotation around Z-axis:

$$x' = x \cos \theta - y \sin \theta, \quad y' = x \sin \theta + y \cos \theta$$

Rotation around X-axis (x remains fixed):

$$y' = y \cos \theta - z \sin \theta, \quad z' = y \sin \theta + z \cos \theta$$

Rotation around Y-axis (y remains fixed):

$$x' = x \cos \theta + z \sin \theta, \quad z' = -x \sin \theta + z \cos \theta$$

Rodrigues' Formula: (Rotation of vector \vec{v} by angle θ around axis unit vector \vec{u})

$$\vec{v}_{rot} = \vec{v} \cos \theta + (\vec{u} \times \vec{v}) \sin \theta + \vec{u}(\vec{u} \cdot \vec{v})(1 - \cos \theta)$$

যেকোনো 3D ভেক্টরকে যেকোনো অক্ষ (Axis) সাপেক্ষে ঘোরাতে এটি সবচেয়ে পাওয়ারফুল সূত্র।

Solid Geometry

Sphere (□□□□):

$$\text{Volume} = \frac{4}{3} \pi r^3$$

$$\text{Surface Area} = 4 \pi r^2$$

Cone (□□□□):

$$\text{Volume} = \frac{1}{3} \pi r^2 h$$

$$\text{Surface Area} = \pi r(r + \sqrt{h^2 + r^2})$$



Cone

Pyramid:

$$\text{Volume} = \frac{1}{3} \times \text{Base Area} \times \text{Height}$$

পিরামিডের আয়তন বের করতে ভূমির ক্ষেত্রফল জানা থাকতে হবে।

Triangle Properties


Equilateral Triangle Area: $\frac{\sqrt{3}}{4} a^2$

Inradius (r): $r = \frac{\Delta}{s}$ (Δ = ত্রিভুজের এরিয়া, s = অর্ধপরিসীমা)

Circumradius (R): $R = \frac{abc}{4\Delta}$ (a, b, c হলো তিন বাহু)

Sine Rule: $\frac{a}{\sin A} = \frac{b}{\sin B} = \frac{c}{\sin C} = 2R$
ত্রিভুজের বাহু এবং বিপরীত কোণের সম্পর্ক। পরিবৃত্তের ব্যাসার্ধ বের করতেও লাগে।

Cosine Rule: $\cos A = \frac{b^2+c^2-a^2}{2bc}$
তিনটি বাহু জানা থাকলে কোণ বের করতে, অথবা দুটি বাহু ও অন্তর্ভুক্ত কোণ জানা থাকলে তৃতীয় বাহু বের করতে।



Number Theory

Divisors of N $= p_1^{a_1} p_2^{a_2} \dots :$

Count $= (a_1 + 1)(a_2 + 1) \dots$

Sum $= \prod \frac{p_i^{a_i+1} - 1}{p_i - 1}$

Logarithm: $\log_b x = k \iff b^k = x$

Number of Digits in Base $b = \lfloor \log_b(N) \rfloor + 1$

যেকোনো সংখ্যার ডিজিট সংখ্যা বের করার শটকাট।

Linear Algebra (Cramer's Rule)

দুই চলক বিশিষ্ট সরল সমীকরণ সমাধান করতে:

System: $ax + by = e, cx + dy = f$

$D = \begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc$

$D_x = \begin{vmatrix} e & b \\ f & d \end{vmatrix} = ed - bf, \quad D_y = \begin{vmatrix} a & e \\ c & f \end{vmatrix} = af - ce$

Answer: $x = \frac{D_x}{D}, \quad y = \frac{D_y}{D}$ (Valid if $D \neq 0$)

Convex Hull

Code in C++:

```
struct P{
    double x,y;
};
P pvt;
P vec(P a,P b){return {b.x-a.x,b.y-a.y};}
double Cross(P a,P b){return a.x*b.y-a.y*b.x;}
double eDis(P a,P b){return
    sqrt(sqr(a.x-b.x)+sqr(a.y-b.y));}
```

```
bool comp(P a,P b)
{
    double c = Cross(vec(pvt,a),vec(pvt,b));

    if(c) return c>0;
    return eDis(pvt,a)<eDis(pvt,b);
}

vector<P> makeConvexHull(vector<P> p){
    int nConvex=p.size(),i,j;
    if(nConvex<2) return p;
    /** IF ALL POINTS ARE CO-LINER */
    // j=0;
    // for(i=2;i<nConvex;i++)
    //     if(Cross(vec(p[0],p[1]),vec(p[0],p[i]))==0)
    //         j++;
    // if(j+2==nConvex) return P
    pvt=p[0];
    for(int i=1;i<nConvex;i++)
        if(pvt.y>p[i].y) pvt=p[i];
        else if(pvt.y==p[i].y && pvt.x>p[i].x)
            pvt=p[i];

    sort(all(p),comp);
    j=2;
    for(int i=2;i<nConvex;i++)
    {
        //while(j>1 &&
        //    Cross(vec(p[j-2],p[j-1]),vec(p[j-2],p[i]))<=0)
        //    skip same line
        while(j>1 &&
            Cross(vec(p[j-2],p[j-1]),vec(p[j-2],p[i]))<0)
            j--;
        p[j++]=p[i];
    }
    p.resize(j);
    return p;
}

void solve(int n) {
    vector<P>v;
    for(int i=0;i<n;i++){
        double x,y;cin>>x>>y;
        v.push_back({x,y});
    }
    double Perimeter=0;
    if(n==1){
        cout<<" "<<sp(v[0].x,1)<<" "<<sp(v[0].y,1)<<"\n";
        cout<<"Perimeter length = "
            <<" "<<sp(Perimeter,2)<<"\n";
        return;
    }
    v=makeConvexHull(v);
    reverse(all(v));
    for(int i=0;i<v.size();i++){
        cout<<" "<<sp(v[i].x,1)<<" "<<sp(v[i].y,1)<<"-";
        Perimeter+=(eDis(v[i],v[(i+1)%v.size()]));
    }
```

```
}
    cout<<" "<<sp(v[0].x,1)<<" "<<sp(v[0].y,1)<<"\n";
    cout<<"Perimeter length = "
        <<" "<<sp(Perimeter,2)<<"\n";
}
```

Segment Intersect

Code in C++:

```
struct P{
    double x,y;
};
P vec2d(P &a,P &b){
    return{b.x - a.x, b.y - a.y};
}
double cross(P &a, P &b) {
    return A.x * B.y - A.y * B.x;
}
bool onSegment(P &a,P &b, P &p) {
    return min(a.x,b.x)-1e-9<=p.x<=max(a.x,b.x)+1e-9
        && min(a.y,b.y)-1e-9<=p.y<=max(a.y,b.y)+1e-9;
}
P getIntersectionPoint(P a, P b, P c, P d) {
    P AB = vec2d(a, b);
    P CD = vec2d(c, d);
    P AC = vec2d(a, c);
    double det = cross(AB, CD);
    double t = cross(AC, CD) / det;
    return {a.x + t * AB.x, a.y + t * AB.y};
}
bool segmentIntersect(P &a,P &b, P &c, P&d){
    P AB=vec2d(a,b);
    P AC=vec2d(a,c);
    P AD=vec2d(a,d);
    P CD=vec2d(c,d);
    P CB=vec2d(c,b);
    P CA=vec2d(c,a);

    if(cross(AB,AC)*cross(AB,AD)<0 &&
        cross(CD,CB)*cross(CD,CA)<0)
        return true;
    if(cross(AB,AC)==0 && onSegment(a,b,c))return true;
    if(cross(AB,AD)==0 && onSegment(a,b,d))return true;
    if(cross(CD,CB)==0 && onSegment(c,d,b))return true;
    if(cross(CD,CA)==0 && onSegment(c,d,a))return true;
    return false;
}

void solve() {
    P a,b,c,d;
    cin>>a.x>>a.y>>b.x>>b.y>>c.x>>c.y>>d.x>>d.y;

    if(segmentIntersect(a,b,c,d)){
        YES
    }
```

```
// Special case: check if lines are collinear
P AB = vec2d(a, b);
P CD = vec2d(c, d);
if(abs(cross(AB, CD))<1e-9){
    cout<<"Segments are collinear"<<endl;
} else {
    P it = getIntersectionPoint(a, b, c, d);
    cout << "Point: " << it.x << " " << it.y <<
        << endl;
}
} else {
    NO
}
}
```

}

Segment Intersect 3D

Code in C++:

```
const double EPS = 1e-9;
struct P {
    double x, y, z;
};
P vec3d(const P &a, const P &b) {
    return {b.x - a.x, b.y - a.y, b.z - a.z};
}
P cross(P A, P B) {
    return {
        A.y * B.z - A.z * B.y,
        A.z * B.x - A.x * B.z,
        A.x * B.y - A.y * B.x
    };
}
double dot(P A, P B) {
    return A.x * B.x + A.y * B.y + A.z * B.z;
}
double magSq(P A) {
    return dot(A, A);
}
bool onSegment(const P &a, const P &b, const P &p){
    return p.x>=min(a.x,b.x)-EPS&&p.x<=max(a.x,b.x)+EPS&&
        p.y>=min(a.y,b.y)-EPS&&p.y<=max(a.y,b.y)+EPS&&
        p.z>=min(a.z,b.z)-EPS&&p.z<=max(a.z,b.z)+EPS;
}
P getIntersectionPoint(P a, P b, P c, P d){
    P AB = vec3d(a, b);
    P CD = vec3d(c, d);
    P AC = vec3d(a, c);

    double t=dot(cross(AC,CD),cross(AB,CD))/dot(cross(AB,
        << CD),cross(AB,CD));
    return {a.x + t * AB.x, a.y + t * AB.y, a.z + t *
        << AB.z};
}
```

```
bool segmentIntersect(const P &a, const P &b, const P &c,
    << const P &d) {
    P AB = vec3d(a, b);
    P CD = vec3d(c, d);
    P AC = vec3d(a, c);

    P cp = cross(AB, CD);
    double cp_mag2 = magSq(cp);

    // Case 1: Parallel or Collinear Lines
    if (cp_mag2 < 1e-18) {
        // Check if they lie on the same infinite line by
        << checking if AC is parallel to AB
        if (magSq(cross(AC, AB)) > 1e-18) return false;

        // If they are on the same line, check if they
        << overlap
        return onSegment(a, b, c) || onSegment(a, b, d)
            << ||
                onSegment(c, d, a) || onSegment(c, d, b);
    }

    // Case 2: Skew Lines Check (Coplanarity)
    // In 3D, lines must be in the same plane to
    << intersect.
    // The volume of the parallelepiped formed by AC, AB,
    << and CD must be 0.
    if (abs(dot(AC, cp)) > EPS) return false;

    // Case 3: Calculate point and check if it is within
    << both segments
    P intersect = getIntersectionPoint(a, b, c, d);
    return onSegment(a, b, intersect) && onSegment(c, d,
        << intersect);
}
void solve() {
    P a, b, c, d;
    cin >> a.x >> a.y >> a.z >> b.x >> b.y >> b.z
        >> c.x >> c.y >> c.z >> d.x >> d.y >> d.z;
    if (segmentIntersect(a, b, c, d)) {
        cout << "YES" << endl;
        P AB = vec3d(a, b);
        P CD = vec3d(c, d);
        if (magSq(cross(AB, CD)) < 1e-18) {
            cout << "Segments are collinear and
                << overlapping." << endl;
        } else {
            P res = getIntersectionPoint(a, b, c, d);
            cout << fixed << setprecision(10) << "Point:
                << "
                    << res.x << " " << res.y << " " << res.z
                    << << endl;
        }
    } else {
        cout << "NO" << endl;
    }
}
```

}

Tree Algos

Diameter Of A Tree Dfs

Code in C++:

```
int depth[Size];
vector<int>graph[Size];
int max_depth;
int max_depth_node;
void init(int V){
    for(int i=0;i<V+5;i++){
        graph[i].clear();depth[i]=0;
    }
    max_depth=0;
}
int dfs(int u,int par=-1){
    if(depth[u]>max_depth){
        max_depth=depth[u];
        max_depth_node=u;
    }
    for(auto v : graph[u]){
        if(v==par)continue;
        depth[v]=depth[u]+1;
        dfs(v,u);
    }
    return max_depth_node;
}
int main(){
    int V,u,v;cin>>V;
    init(V);
    int E=V-1;
    for(int i=0;i<E;i++){
        cin>>u>>v;
        graph[u].push_back(v);
        graph[v].push_back(u);
    }
    max_depth_node=dfs(1);///one based
    memset(depth,0,sizeof depth);
    max_depth=0;
    max_depth_node=dfs(max_depth_node);
    cout<<"Diameter of this Tree =
        << " << depth[max_depth_node]<<"\n";
}
```

Lowest Common Ancestor Sparse Table

Code in C++:

```

///Complexity:  $O(N \lg N, \lg N)$ 
int E,V;
int LVL[Size];
int par[Size];
int A[Size][20];
vector<int>adj[Size];
/// finding nodes tree level and parent
void leveling_dfs(int u){
    for(auto v : adj[u]){
        if(v==par[u])continue;
        LVL[v]=LVL[u]+1;
        par[v]=u;
        leveling_dfs(v);
    }
}
void Sparse_Table(){
    for(int p=0;p<=log2(V)+1;p++){
        for(int i=1;i<=V;i++){
            if(p==0)
                A[i][p] = par[i];///2^p = 2^0 = 1'th
                ↳ parent
            else
                A[i][p] = A[A[i][p-1]][p-1];/// A[i][p] =
                ↳ i'th nodes 2^p'th parant
        }
    }
}
int LCA(int u,int v){
    if(LVL[u]>LVL[v])
        swap(u,v);
    //Bring u and v in same level
    for(int i=log2(V)+1;i>=0;i--){
        int x = A[v][i];
        if(LVL[u]==LVL[x]){
            v=x;
            break;
        }
        if(LVL[u]<LVL[x])
            v = x;
    }
    if(u==v)return u;
    for(int i=log2(V)+1;i>=0;i--){
        if(A[u][i] != -1 && A[v][i] != A[v][i]){
            u = A[u][i];
            v = A[v][i];
        }
    }
    return par[u];
}
void build_LCA(int source){
    LVL[source]=1,par[source]=source;
    leveling_dfs(source);
    Sparse_Table();
}
int main(){
    ///one based code

```

```

int i,j,u,v,q;
scanf("%d",&V);
for(i=0;i<V+2;i++){
    adj[i].clear();
    for(j=0;j<=log2(V+1);j++){
        A[i][j] = -1;
    }
}
for(i=1;i<V;i++){
    scanf("%d%d",&u,&v);
    adj[u].push_back(v);
    adj[v].push_back(u);
}
int source=1;
build_LCA(source);
scanf("%d%d",&u,&v);
printf("%d\n",LCA(u,v));
}

```

Merge Sorttree Number Of Element Greater Than K

Code in C++:

```

vector<ll>ar;
vector<vector<ll>>>tree;
vector<ll> marge(vector<ll>&a,vector<ll>&b){
    int n=a.size(),m=b.size();
    vector<ll>c;
    int i=0,j=0;
    while(i<n && j<m){
        if(a[i]<=b[j]){
            c.push_back(a[i]);
            i++;
        }else{
            c.push_back(b[j]);
            j++;
        }
    }
    while(i<n)c.push_back(a[i]),i++;
    while(j<m)c.push_back(b[j]),j++;
    return c;
}
void build(int node,int left,int right){
    if(left==right){
        tree[node].push_back(ar[left]);
        return ;
    }
    int mid=(left+right)/2;
    build(node*2,left,mid);
    build(node*2+1,mid+1,right);
    tree[node]=marge(tree[node*2],tree[node*2+1]);
}
int query(int node,int left,int right,int ql,int qr,ll
    ↳ k){///query left=ql,right=qr
    if(left>=ql && right<=qr){
        int ans= (int)tree[node].size()

```

```

        - (upper_bound(tree[node].begin(),tree[node].end(),
        ↳ ,k)-tree[node].begin());
        return ans;
    }
    int mid=(left+right)/2;
    if(qr<=mid){
        return query(2*node,left,mid,ql,qr,k);
    }
    else if(mid<ql){
        return query(2*node+1,mid+1,right,ql,qr,k);
    }
    else{
        int left_node=query(2*node,left,mid,ql,mid,k);
        int right_node=query(2*node+1,mid+1,right,mid+1,q
        ↳ r,k);
        return left_node+right_node;
    }
}
int main(){
    int n,ql,qr,pos,new_val;
    cin>>n;
    ar.resize(n+5);
    tree.resize(4*(n+5));
    for(int i=1;i<=n;i++){
        cin>>ar[i];
    }
    build(1,1,n);
    // int q;cin>>q;
    // while(q--){
    //     ll k;
    //     cin>>ql>>qr>>k;
    //     cout<<query(1,1,n,ql,qr,k)<<"\n";
    // }

    return 0;
}

```

Segmenttree Lazypropagation

Code in C++:

```

/// sl = segment left,sr = segment right, tre[nod] contain
    ↳ [sl-sr] range
#define ll long long
const int MAX_N =100007;
const int oo = 2e9+10;
int ar[MAX_N];
struct LazyTree{
    vector<int>tre,lazy;
    LazyTree(int sz){
        tre.assign((sz*4)+10,0);
        lazy.assign((sz*4)+10,0);
    }
    inline void lazyUpdate(int nod,int sl,int sr){

```

```

if(lazy[nod]==0)return;
//tre[nod] += lazy[nod];// change += or = // if we
↳ chaking for max,min
tre[nod] += lazy[nod]*(sr-sl+1);// change += or =
if(sl!=sr){
    int left_child = 2*nod , right_child =
        ↳ 2*nod+1;
    lazy[left_child] += lazy[nod],
    ↳ lazy[right_child] += lazy[nod];// change
    ↳ += or =
}
lazy[nod]=0;
}
void build(int nod,int sl,int sr){
    lazy[nod]=0;
    if(sl==sr){
        tre[nod]=ar[sr];// root node
        return;
    }
    int mid = (sl+sr)/2;
    int left_child = 2*nod , right_child = 2*nod+1;
    build(left_child , sl , mid);
    build(right_child , mid+1, sr);
    tre[nod] = tre[left_child] +
        ↳ tre[right_child];///change
}
ll query(int nod,int sl,int sr,int ql,int qr){
    lazyUpdate(nod,sl,sr);
    if(ql<=sl && sr<=qr){///fully overlaped
        return tre[nod];
    }
    if(qr<sl || sr<ql)return 0;/// out of the range
    ↳ ,0/-oo/oo;
    int mid = (sl+sr)/2;
    int left_child = 2*nod , right_child = 2*nod+1;
    return query(left_child,sl,mid,ql,qr)+query(right,
        ↳ _child,mid+1,sr,ql,qr);///change
}
void update(int nod,int sl,int sr,int ql,int qr,ll
    ↳ val){
    lazyUpdate(nod,sl,sr);
    if(ql<=sl && sr<=qr){///fully overlaped
        lazy[nod]+=val;
        lazyUpdate(nod,sl,sr);
        return;
    }
    if(qr<sl || sr<ql)return;/// position is out of
    ↳ the range
    int mid = (sl+sr)/2;
    int left_child = 2*nod , right_child = 2*nod+1;
    update(left_child,sl,mid,ql,qr,val);
    update(right_child,mid+1,sr,ql,qr,val);
    tre[nod]=tre[left_child]+tre[right_child];///chan
    ↳ ge
}
}
};

```

```

signed main(){
    int n,q,ql,qr,ty;
    int val;
    cin>>n;
    for(int i=1;i<=n;i++){
        cin>>ar[i];
    }
    LazyTree lt(n);
    lt.build(1,1,n);///lt.build(1,0,n-1);
    while(1){
        cin>>ty;
        if(ty==1){
            cin>>ql>>qr>>val;
            lt.update(1,1,n,ql,qr,val);
        }else if(ty==2){
            cin>>ql>>qr;
            cout<<lt.query(1,1,n,ql,qr)<<"\n";
        }else{
            break;
        }
    }
}

```

Segment Tree

Code in C++:

```

#include<bits/stdc++.h>
using namespace std;

const int Size=10000;
int ar[Size];
int tree[4*Size];
void build(int node,int left,int right){
    if(left==right){
        tree[node]=ar[left];
        return ;
    }
    int mid=(left+right)/2;
    build(node*2,left,mid);
    build(node*2+1,mid+1,right);
    tree[node]=tree[node*2]+tree[node*2+1];
    //tree[node]=max(tree[node*2],tree[node*2+1]);
    //tree[node]=min(tree[node*2],tree[node*2+1]);
}
int query(int node,int left,int right,int ql,int
    ↳ qr){///query left=ql,right=qr
    if(left>=ql && right<=qr){
        return tree[node];
    }
    int mid=(left+right)/2;
    if(qr<=mid){/// range is left of mid
        return query(2*node,left,mid,ql,qr);
    }
    else if(mid<ql){/// range is right of mid

```

```

        return query(2*node+1,mid+1,right,ql,qr);
    }
    else{/// range is partially overlap
        int left_node=query(2*node,left,mid,ql,mid);
        int right_node=query(2*node+1,mid+1,right,mid+1,q
            ↳ r);
        return left_node+right_node;
        //return max(left_node,right_node);
        //return min(left_node,right_node);
    }
}
void update(int node,int left,int right,int pos)
{
    if(left==pos && right==pos){
        tree[node]= ar[pos];
        return;
    }
    int mid = (left+right)/2;
    if(pos<=mid && pos>=left)///if pos in lower left
        update(node*2,left,mid,pos);
    else
        update(node*2+1,mid+1,right,pos);/// if pos in
        ↳ lower right
    tree[node] = tree[node*2] + tree[(node*2)+1];
    // tree[node] = min(tree[node*2],tree[(node*2)+1]);
    // tree[node] = max(tree[node*2],tree[(node*2)+1]);
}

int main(){
    //ios_base::sync_with_stdio(0); cin.tie(0);
    int n,ql,qr,pos,new_val;;
    while(cin>>n){
        for(int i=1;i<=n;i++){
            cin>>ar[i];
        }
        build(1,1,n);
        while(1){
            int qtype;cin>>qtype;
            if(qtype==1){///query
                cin>>ql>>qr;
                cout<<query(1,1,n,ql,qr)<<"\n";
            }else if(qtype==2){///update
                cin>>pos>>new_val;
                ar[pos]=new_val;
                update(1,1,n,pos);
            }else{
                break;
            }
        }
    }
    return 0;
}

```

Graph

Articulation Point

Code in C++:

```
void art_point_dfs(int node,int parent,int vis[],int
↳ &timer,int tin[],
    int tlow[],vector<int>adj[],set<int>&art_points){
    vis[node]=1;
    tin[node]=tlow[node]=timer;
    timer++;
    int child=0;
    for(auto v : adj[node]){
        if(v==parent)continue;
        if(vis[v]==0){
            art_point_dfs(v,node,vis,timer,tin,tlow,adj,a
↳ rt_points);
            tlow[node]=min(tlow[v],tlow[node]);
            if(tlow[v]>=tin[node] && parent!=-1){
                art_points.insert(node);
            }
            child++;
        }else{
            tlow[node]=min(tin[v],tlow[node]);
        }
    }
    if(child>1 && parent ==-1){
        art_points.insert(node);
    }
}

int main(){
    int V,E;
    while(cin>>V>>E){
        int vis[V+5]={0},tin[V+5],tlow[V+5];
        vector<int>adj[V+5];
        set<int>art_points;
        for(int i=0;i<E;i++){
            int u,v;
            cin>>u>>v;
            adj[u].push_back(v);
            adj[v].push_back(u);///undirected graph
        }
        int timer=1;
        for(int i=0;i<V;i++){///zero based;
            if(vis[i]==0)
                art_point_dfs(i,-1,vis,timer,tin,tlow,adj
↳ ,art_points);
        }
        for(auto it : art_points){
            cout<<it<<" ";
        }
        if(art_points.size()==0)
            cout<<"There is no Articulation Points";
        cout<<"\n";
    }
}
```

```
}
```

Bellman Ford

Code in C++:

```
struct Edge{
    int u,v,w;
};
vector<Edge>edgeList;
int dist[V_SZ];
int par[V_SZ];
int V,E,Source;
const int oo = (1<<25);

void init(){
    for(int i =1;i<=V;i++)
    {
        dist[i] = oo;
        par[i] = -1;
    }
    edgeList.clear();
}

bool bellmanFord_IsNegCyc(int Source){
    dist[s] = 0;
    bool isUpdated;
    ///bellmanford needs maximum V-1 iteration for update
    ↳ all
    ///nodes minimum distance from source .but why there
    ///is V iteration , because if its update a nodes
    ↳ distance
    ///after V-1 iteration that means it have negative
    ↳ cycle
    for(int i=1;i<=V;i++){
        isUpdated = false;

        for(auto edg: edgeList){
            if(dist[edg.v] > dist[edg.u] + edg.w){
                dist[edg.v] = dist[edg.u] + edg.w;
                par[edg.v] = edg.u;
                isUpdated = true;///if its update V'th
                ↳ iteration
                ///thats means it has
                ↳ negative cycle
            }
        }
    }
    return isUpdated;
}
```

Bipartite Graph Dfs

Code in C++:

```
vector<int>adj[SIZE];
int color[SIZE],V,E,u,v;
bool DFS(int u,int col){
    color[u]=col;
    for(auto v : adj[u]){
        if(color[v]==-1){
            if(DFS(v,!col)==false)///color[v]= reverse
            ↳ color[u]
                return false;
        }
        else if(color[v]==col){
            return false;
        }
    }
    return true;
}

signed main(){
    cin>>V>>E;
    for(int i=0;i<V+5;i++){
        color[i]=-1;
        adj[i].clear();
    }
    for(int i=0;i<E;i++){
        cin>>u>>v;
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    int flg=1;
    for(int i=1;i<=V;i++){///1 based
        if(color[i]==-1){
            if(DFS(i,0)==false){
                flg=0;
                break;
            }
        }
    }
    ///if graph has a cycle which is contain odd number of
    ↳ nodes
    ///in that case graph is not Bipartite Graph
    if(flg){
        cout<<"Yes\n";
    }
    else{
        cout<<"No\n";
    }
}
```

Bridges

Code in C++:

```
const int nodes=105;
int timer;
int vis[nodes],tin[nodes],tlow[nodes];
vector<int>adj[nodes];
```



```

vector<pair<int,int>>bridge;
void bridge_dfs(int node,int parent){
    vis[node]=1;
    tin[node]=tlow[node]=timer;
    timer++;
    for(auto v : adj[node]){
        if(v==parent)continue;
        if(vis[v]==0){
            bridge_dfs(v,node);
            tlow[node]=min(tlow[v],tlow[node]);
            if(tlow[v]>tin[node]){
                bridge.push_back({node,v});
            }
        }else{
            tlow[node]=min(tin[v],tlow[node]);
        }
    }
}
void init(int V){
    for(int i=0;i<V+5;i++){
        vis[i]=0;
        adj[i].clear();
    }
    timer=1;bridge.clear();
}

int main(){
    //zero based;
    int V,E;
    cin>>V>>E
    init(V);
    for(int i=0;i<E;i++){
        int u,v;cin>>u>>v;
        adj[u].push_back(v);
        adj[v].push_back(u);///undirected graph
    }
    for(int i=0;i<V;i++){///zero based;
        if(vis[i]==0)bridge_dfs(i,-1);
    }
    for(auto it : bridge){
        cout<<it.first<<"->"<<it.second<<"\n";
    }
    if(bridge.size()==0)cout<<"No Bridges\n";
    cout<<"\n";
    return 0;
}

```

Dfs

Code in C++:

```

const int WHITE = 0;
const int GRAY = 1;
const int BLACK = 2;
vector<int>g[V_SZ];
int col[V_SZ];

```

```

int par[V_SZ];
int startTime[V_SZ];
int finishTime[V_SZ];
int Flattening_tree[2*V_SZ];
int depth[V_SZ];
int height[V_SZ];
int subtree_sum[V_SZ];
vector<int>order;
int Time;
int V,E;
void init(){
    for(int i =1;i<=V;i++){
        col[i] = WHITE;
        par[i] = -1;
        g[i].clear();

        startTime[i] = finishTime[i] = -1;
        Flattening_tree[i]=Flattening_tree[V-i+1]=-1;

        height[i]=0;
        depth[i]=0;
        subtree_sum[i]=i;
    }
    Time = 1;
    order.clear();
}

void dfs(int u){
    startTime[u] = Time;
    Flattening_tree[Time]=u;
    Time++;
    col[u] = GRAY;

    for(auto v: g[u]){
        // if we solve tree problem then we can use
        // if(v!=par[u])
        //condition in this line because tree do not
        // contain cycle
        if(col[v]==WHITE){
            depth[v]=depth[u]+1;
            par[v] = u;
            dfs(v);
            height[u]=max(height[u],height[v]+1);
            subtree_sum[u]+=subtree_sum[v];
        }
    }
    col[u] = BLACK;
    order.push_back(u);
    finishTime[u] = Time;
    Flattening_tree[Time]=u;
    Time++;
}

int main(){
    // in tree problem E = V-1
    cin>>V>>E;
    init();
}

```

```

int u,v;
for(int i=0;i<E;i++){
    cin>>u>>v;
    g[u].push_back(v);
    g[v].push_back(u); ///then it will be nondirected
    // graph
}
for(int i=1;i<=V;i++){
    if(col[i]==WHITE)dfs(i);

    puts("Parent:");
    for(int i=1;i<=V;i++)printf("[%d:%d]", "i,
    // par[i]);printf("\n");
    puts("\nTime:");
    for(int i=1;i<=V;i++)printf("%d:[%d-%d]", "i,
    // startTime[i],finishTime[i]);
    puts("\nFlattening Tree :");
    for(int i=1;i<=2*V;i++)printf("%d,
    // ",Flattening_tree[i]);
    puts("\ndepth of all vertex:");
    for(int i=1;i<=V;i++){
        cout<<i<<" -> "<<depth[i]<<" ,";
    }
    puts("\n\nheight of all vertex:");
    for(int i=1;i<=V;i++){
        cout<<i<<" -> "<<height[i]<<" ,";
    }
    puts("\n\nSub tree sum:");
    for(int i=1;i<=V;i++){
        cout<<"["<<i<<":"<<subtree_sum[i]<<"] ,";
    }
    puts("\n\nFinal complete visited Order:");
    for(auto v: order) printf("%d", v); puts("");
}

```

Dfs Cycle Finder

Code in C++:

```

const ll mxn=2e5+10;
vector<ll>g[mxn+10],cyl[mxn+10];
ll par[mxn+10];
ll vis[mxn+10],cnt;
void cycle(ll snode,ll enode){
    cyl[cnt].push_back(enode);
    while(snode!=enode){
        cyl[cnt].push_back(snode);
        snode=par[snode];
    }
    cyl[cnt].push_back(enode);
    //reverse(cyl[cnt].begin(),cyl[cnt].end());///for
    // directed graph
}

void DFS(ll u){

```

```

vis[u]=1;
for(auto v:g[u]){
    if(vis[v]==0){
        par[v]=u;
        DFS(v);
    }
    else if(vis[v]==1&&v!=par[u]){///if(vis[v]==1) for
        ↳ directed graph
        ll snode=u;
        ll enode=v;
        cycle(snode,enode);
        cnt++;///number of cycle
    }
}
vis[u]=2;/// u nodes all adj nodes r visited
}

int main(){
    ///for undirected = minimum three nodes make a cycle
    ↳ for this code
    ///for directed = also one node can be make a cycle
    ↳ for this code
    ll V,E,u,v;
    while(cin>>V>>E){
        for(int i=0;i<=V+5;i++){
            vis[i]=0;
            par[i]=-1;
            g[i].clear();
            cyl[i].clear();
        }
        for(ll i=0; i<E; i++){
            cin>>u>>v;
            g[u].push_back(v);
            g[v].push_back(u);///off the line for directed
            ↳ graph
        }
        cnt=0;
        for(ll i=1;i<=V;i++){
            if(vis[i]==0)
                DFS(i);
        }
        for(ll i=0; i<cnt; i++){
            for(auto v:cyl[i])
                cout<<v<<" ";
            cout<<"\n";
        }
        if(cnt==0)cout<<"IMPOSSIBLE"<<"\n";
    }
}

```

Dijkstra Using Pq

Code in C++:

```

struct Nod{
    int u, dis;

```

```

    Nod(int iU, int iDis){
        u = iU;
        dis = iDis;
    }
    bool operator<(const Nod& b) const{
        return dis > b.dis;
    }
};
const int Vertex_N = 101;
const int oo = 1e8+0.5;
int dist[Vertex_N];
int par[Vertex_N];
vector<int>graph[Vertex_N];
vector<int>weight[Vertex_N];
void init(int n){
    for(int i=1;i<=n;i++){
        dist[i] = oo;
        par[i] = -1;
        graph[i].clear();
        weight[i].clear();
    }
}
int dijkstra(int source, int destination){
    priority_queue<Nod>pq;
    dist[source] = 0;
    pq.push(Nod(source, 0));///pq.push({source, 0});
    while(!pq.empty()){
        Nod cur = pq.top();
        pq.pop();

        int u = cur.u;
        int uDist = cur.dis;
        if(dist[u] < uDist) {
            continue;
        }
        for(int i=0;i<graph[u].size();i++){
            int v = graph[u][i];
            int edgeWeight = weight[u][i];
            if(dist[v] > uDist + edgeWeight){
                dist[v] = uDist + edgeWeight;
                par[v] = u;
                pq.push({v, dist[v]});
            }
        }
    }
    return dist[destination];
}
vector<int> getPaht(int source, int destination){
    int v = destination;
    vector<int>path;
    while(source != v){
        path.push_back(v);
        v = par[v];
    }
    path.push_back(source);
    reverse(path.begin(), path.end());
}

```

```

        return path;
    }

int main(){
    int V, E, S, D;///S=Point vertex,D=target vertex
    ↳ distance
    cin>>V>>E>>S>>D;
    init(V);
    for(int i=0;i<E;i++){
        int u,v,w;
        cin>>u>>v>>w;
        graph[u].push_back(v);
        weight[u].push_back(w);
        ///for undirected graph
        graph[v].push_back(u);
        weight[v].push_back(w);
    }
    int distance = dijkstra(S, D);
    printf("Distan: %d\n", distance);

    vector<int>path = getPaht(S, D);
    printf("Path: ");
    for(auto v: path) cout<<v<<" ";cout<<endl;
}

```

Floyd Warshall

Code in C++:

```

const int oo = 1e8;
const int Size = 100;
int dis[Size][Size],N,E;
cin>>N>>E;/// N=number of nodes,E=number of edges
for(int i=1;i<=N;i++){
    for(int j=1;j<=N;j++){
        dis[i][j]=oo;
        if(i==j)dis[i][j]=0;
    }
}
for(int i=0;i<E;i++){
    int u,v,w;
    cin>>u>>v>>w;
    dis[u][v]=w;/// directed graph;
}

for(int via=1;via<=N;via++){
    for(int u=1;u<=N;u++){
        for(int v=1;v<=N;v++){
            dis[u][v]=min(dis[u][v] ,
                ↳ dis[u][via]+dis[via][v]);
        }
    }
}
cout<<"All nodes distance matrix:\n";
for(int u=1;u<=N;u++){

```

```

for(int v=1;v<=N;v++){
    if(dis[u][v]==00){
        cout<<"00 ";
    }
    else
        cout<<dis[u][v]<< " ";
}
el;
}
// if any node dist[u][u]<0 then
// we call it has nagtive cycle

```

Kruskal Union By Size

Code in C++:

```

-----
struct Edge{
    int u,v,w;
    Edge(int ui,int vi,int wi){
        u=ui;v=vi;w=wi;
    }
};
vector<Edge>edgeList;
int parant[sz];
int compoSize[sz];
void disjoint(int V){
    edgeList.clear();
    for(int i=0;i<=V+3;i++){
        parant[i]=i; //call by make func in DSU
        compoSize[i]=1;
    }
}
// finding root node of this component and
// make root node is parant of the all nodes of this
// component
int FindRootParant(int node){
    if(node == parant[node])
        return node;
    return parant[node]=FindRootParant(parant[node]);
}
// joining two components
void join_components(int u,int v){ //union/makelink u
    // nodes component
    // to v nodes component
    // and
    // make them as a same
    // component

    int u_parant=FindRootParant(u); // finding u 's root
    // node
    int v_parant=FindRootParant(v); // finding v 's root
    // node

    if(u_parant==v_parant) //both r alrady joined

```

```

        return ;
    if(compoSize[u_parant]>compoSize[v_parant]){
        parant[v_parant]=u_parant;
        compoSize[u_parant]+=compoSize[v_parant];
    }
    else{
        parant[u_parant]=v_parant;
        compoSize[v_parant]+=compoSize[u_parant];
    }
}
bool com_by_waight(Edge a,Edge b){
    return a.w<b.w;
}
int kruskal(){
    int cost=0;
    sort(edgeList.begin(),edgeList.end(),com_by_waight);

    for(int i=0;i<edgeList.size();i++){
        //if two vertex or groups root parent r same
        //then it will be creat a cycle
        //Then we won't add them
        //else ↓
        if(FindRootParant(edgeList[i].u) !=
            FindRootParant(edgeList[i].v)){
            join_components(edgeList[i].u ,
                edgeList[i].v);
            cost+=edgeList[i].w;
            //connecting edges
            cout<<edgeList[i].u<<"<->"<<edgeList[i].v<<" =
                <<"<<edgeList[i].w<<el;
        }
    }
    return cost;
}

int main(){
    int V,E;cin>>V>>E;
    disjoint(V); //init
    for(int i=0;i<E;i++){
        int u,v,w;
        cin>>u>>v>>w;
        edgeList.push_back({u,v,w});
    }
    int MST_Cost = kruskal();
    cout<<"MST COST = "<<MST_Cost<<el;
}

```

Max Flow Dinics Algorithm

Code in C++:

```

-----
//O(V^2 E)
const long long inf = 1LL << 61;
struct Dinic {
    struct edge {

```

```

        int to, rev;
        long long flow, w;
        int id;
    };
    int n, s, t, mxid;
    vector<int> d, flow_through;
    vector<int> done;
    vector<vector<edge>> g;
    Dinic() {}
    Dinic(int _n) {
        n = _n + 10;
        mxid = 0;
        g.resize(n);
    }
    void add_edge(int u, int v, long long w, int id = -1) {
        edge a = {v, (int)g[v].size(), 0, w, id};
        edge b = {u, (int)g[u].size(), 0, 0, -2}; //for
        //bidirectional edges cap(b) = w
        g[u].emplace_back(a);
        g[v].emplace_back(b);
        mxid = max(mxid, id);
    }
    bool bfs() {
        d.assign(n, -1);
        d[s] = 0;
        queue<int> q;
        q.push(s);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (auto &e : g[u]) {
                int v = e.to;
                if (d[v] == -1 && e.flow < e.w) d[v] = d[u] + 1,
                    q.push(v);
            }
        }
        return d[t] != -1;
    }
    long long dfs(int u, long long flow) {
        if (u == t) return flow;
        for (int &i = done[u]; i < (int)g[u].size(); i++) {
            edge &e = g[u][i];
            if (e.w <= e.flow) continue;
            int v = e.to;
            if (d[v] == d[u] + 1) {
                long long nw = dfs(v, min(flow, e.w - e.flow));
                if (nw > 0) {
                    e.flow += nw;
                    g[v][e.rev].flow -= nw;
                    return nw;
                }
            }
            done[u]++;
        }
        return 0;
    }
}

```

```

long long max_flow(int _s, int _t) {
    s = _s;
    t = _t;
    long long flow = 0;
    while (bfs()) {
        done.assign(n, 0);
        while (long long nw = dfs(s, inf)) flow += nw;
    }
    flow_through.assign(mxid + 10, 0);
    //for(int i = 0; i <=n; i++) for(auto e : g[i])
    //    if(e.id >= 0) flow_through[e.id] = e.flow;
    return flow;
}
};
int main() {
    int n, m;
    cin >> n >> m;
    Dinic F(n + 1);
    for (int i = 1; i <= m; i++) {
        int u, v, w; // onse based
        cin >> u >> v >> w;
        F.add_edge(u, v, w);
        //F.add_edge(v, u, w); // bi directional
    }
    cout << F.max_flow(1, n) << '\n';
    return 0;
}

```

Stronglyconnectedcomponents

Code in C++:

```

struct node{
    int idx,st,fin;
};
node Time[Size];
vector<int>adj[Size];
vector<int>radj[Size];
vector<int>component[Size];
int vis[Size],scc[Size],ti,compo_no;
bool com(node a,node b){
    return a.fin>b.fin;
}
bool comidx(node a,node b){
    return a.idx<b.idx;
}
void dfs(int u){
    Time[u].st=ti++;
    vis[u]=1;
    for(int i=0;i<adj[u].size();i++){
        int v=adj[u][i];
        if(vis[v]==0){
            dfs(v);
        }
    }
    Time[u].fin=ti++;
}

```

```

}
void rdfs(int u,int compo_no){
    vis[u]=1;
    scc[u]=compo_no; //scc[u] is compo_no'th component who
    // is carring nod u
    component[compo_no].push_back(u);
    for(int i=0;i<radj[u].size();i++){
        int v=radj[u][i];
        if(vis[v]==0){
            rdfs(v,compo_no);
        }
    }
}
int main(){
    int V,E,u,v;cin>>V>>E;
    // SCC works only for directional graph
    for(int i=0;i<=V+5;i++){
        adj[i].clear();
        radj[i].clear();
        component[i].clear();
        vis[i]=0;
    }
    for(int i=1;i<=E;i++){
        cin>>u>>v;
        adj[u].push_back(v);
        radj[v].push_back(u); // for reverce edges
        // direction
    }
    ti=1;
    for(int i=1;i<=V;i++){ // 1 based graph
        Time[i].idx=i;
        if(vis[i]==0){
            dfs(i);
        }
    }
    // cout<<"[Start time,Finish Time]:\n";
    // for(int i=1;i<=V;i++){
    //     cout<<"Nod "<<i<<"
    //     :["<<Time[i].st<<","<<Time[i].fin<<"]\n";
    // }
    memset(vis,0,sizeof vis),compo_no=0; //compo_no = n'th
    // component[1 based]
    sort(&Time[1],&Time[V+1],com); //precedency by finish
    // time
    for(int i=1;i<=V;i++){
        if(vis[Time[i].idx]==0){
            compo_no++; // compo_no also compo
            // index which is 1 based
            rdfs(Time[i].idx,compo_no); //dfs traverce for
            // reverse direction
        }
    }
    //sort(&Time[1],&Time[V+1],comidx);
    for(int i=1;i<=compo_no;i++){ // number of component
        // is compo_no
    }
}

```

```

cout<<"SCC("<<scc[component[i][0]]<<")->
    //"; //component[i][0] is the 1st node of i'th
    // component
    for(auto v : component[i]){
        cout<<v<<" ";
        //cout<<"-> SCC("<<scc[v]<<") ,";
    }
    cout<<"\n";
}
cout<<"\n";
}
}

```

Topologicalsort Khans

Code in C++:

```

const int Size=105;
vector<int>adj[Size];
vector<int>TS; //Topological Sort
int indegree[Size],V,E;
queue<int>Q;
void init(){
    for(int i=0;i<V+5;i++){
        indegree[i]=0;
        adj[i].clear();
    }
    TS.clear();
}
void topo_BFS(){
    while(!Q.empty()){
        int u=Q.front();Q.pop();
        for(auto v : adj[u]){
            --indegree[v];
            if(indegree[v]==0){
                TS.emplace_back(v);
                Q.push(v);
            }
        }
    }
}
int main(){
    cin>>V>>E;
    init();int u,v;
    for(int i=0;i<E;i++){
        cin>>u>>v;
        adj[u].emplace_back(v);
        ++indegree[v];
    }
    for(int i=1;i<=V;i++){ //1 based
        if(indegree[i]==0){
            TS.emplace_back(i);
            Q.push(i);
        }
    }
    topo_BFS();
}

```

```

    if(TS.size()!=V){
        cout<<"CycleExist\n";
    }
    for(auto it : TS){
        cout<<it<<" ";
    }
    cout<<"\n";
}

```

Matrix

Matrix Exponential

Code in C++:

```

-----
vector<vector<ll>> matMulti(vector<vector<ll>>&a,
    ↪ vector<vector<ll>>&b, ll Mod){
    int r = a.size();
    int c = b[0].size();
    vector<vector<ll>> ans(r, vector<ll>(c, 0));
    for(int i = 0; i < r; i++) {
        for(int j = 0; j < c; j++) {
            for(int k = 0; k < a[0].size(); k++) {
                ans[i][j]=((ans[i][j]+(a[i][k]*b[k][j])%M_
                ↪ od)%Mod+Mod)%Mod;
            }
        }
    }
    return ans;
}

vector<vector<ll>> matExpo(vector<vector<ll>>& b, ll pw,
    ↪ ll Mod){
    int r = b.size();
    vector<vector<ll>> ans(r, vector<ll>(r, 0));
    for(int i = 0; i < r; ++i) {
        ans[i][i] = 1;
    }
    while(pw) {
        if(pw & 1) {
            ans = matMulti(ans, b, Mod);
        }
        b = matMulti(b, b, Mod);
        pw >>= 1;
    }
    return ans;
}

```