

# ICPC Asia Dhaka Regional 2025

**Team: BUBT\_Sunday\_Monday\_Close**

**Team Members:**

1. Md. Tuhin Hasnat
2. Amir Hamza Miraz
3. Rakin Absar Ratul

Generated: December 18, 2025

1	Utilities	1
1.1	Template	1
1.2	Sublime Build System	1
2	Number Theory	1
2.1	Bigmod	1
2.2	Derangement	1
2.3	Divisors Pre Clc	1
2.4	Prime Factor Sieve	1
2.5	Prime Factor Spf	2
2.6	Sieve	2
2.7	Cumulative Sum 2d	2
2.8	Divisors	2
2.9	Kadanes	2
2.10	Log B N	2
2.11	Ncr Npr Pre Calculation	2
2.12	Number Hashing Rng	3
2.13	Trailingzeroes Of Factorial Number	3
3	String Algorithm	3
3.1	Aho Corasick	3
3.2	Double Hashing	4
3.3	Kmp	4
3.4	Trie Tree	5
3.5	Hashing Longest Common Prefix	5
3.6	Hashing String Divisor	5
4	Backtracking	5
4.1	Combination	5
4.2	Nqueen	5
4.3	Permutation	6
5	Dynamic Programming	6
5.1	1 Knapsack	6
5.2	Edit Distance	6
5.3	Knight Tour	6
5.4	Lcs	7
5.5	Lcs Lexicography Minimum String	7
5.6	Lis Lower Bound	7
5.7	Lis Using Segment Tree	7
5.8	Mcm Burst Balloons	7
5.9	Coin Change Distinct Way	8
5.10	Coin Change Use One More Time Arbitrary Order	8
5.11	Longest Common Substring	8
5.12	Number Of Palindrome In Range Query	8

```
#include<bits/stdc++.h>
using namespace std;

//For Debugging
#define debug(a...) {cout<<__LINE__<<" #-->
    ↪ " ;dbg,a; cout<<endl;}
struct debugger
{
    template<typename T> debugger& operator , (const T v)
    {
        cout<<v<<" ";
        return *this;
    }
};
```

```
{
  "shell_cmd": "g++ -std=c++17 \"${file}\" -o
  ↳ \"${file_path}/${file_base_name}\" &&
  ↳ \"${file_path}/${file_base_name}\" <
  ↳ \"${file_path}/inputf.in\" >
  ↳ \"${file_path}/outputf.out\"",
  "working_dir": "${file_path}",
}
```

```

"selector": "source.cpp"
}

```

## Number Theory

### Bigmod

Code in C++:

```

ll mul(ll a, ll b, ll mod) { // a * b % mod
    return __int128(a) * b % mod;
}
ll power(ll a, ll b, ll mod) { // a^b % mod
    ll ans = 1 % mod;
    while (b) {
        if (b & 1) ans = mul(ans, a, mod);
        a = mul(a, a, mod);
        b >>= 1;
    }
    return ans;
}
ll inverse(ll a, ll mod) { // (1 / a) % mod
    return power(a, mod - 2, mod);
}

```

### Derangement

Code in C++:

```

ll der[MAXN];
void precalculate_derangements() {
    der[0]=1;der[1]=0;der[2]=1;
    for (int i = 3; i < MAXN; i++) {
        der[i]=(i-1)*(der[i-1]+der[i-2])%MOD;
    }
}

```

### Divisors Pre Clc

Code in C++:

```

///nlog(log(n))
vector<int>divisors[1000010];
void Divisor_pre_clc(){
    for(int div=1;div<=1000000;div++){
        for(int num=div;num<=1000000;num+=div)
            divisors[num].push_back(div);
    }
}

```

### Prime Factor Sieve

Code in C++:

```

#define SIZE_N 10000000 // 10^7
bool isprime[SIZE_N + 4];
vector<int> prime;
void sieve() {
    for(int i=3;i<=SIZE_N;i+=2)isprime[i]=true;
    isprime[2] = true;
    prime.push_back(2);
    for (ll i = 3; i <= SIZE_N; i += 2) {
        if (isprime[i]) {
            prime.push_back((int)i);
            if ((ll)SIZE_N / i >= i) {
                for (ll j = i * i; j <= SIZE_N; j += 2 * i)
                    isprime[j] = false;
            }
        }
    }
}
//it handle up to 10^14 with current sieve
void prime_factors(ll n) {
    for(int i=0;i<prime.size()&&(ll)prime[i]*prime[i]<=n;i++){
        while (n % prime[i] == 0) {
            cout << prime[i] << " ";
            n /= prime[i];
        }
    }
    if (n > 1) cout << n;
}
int main() {
    sieve();
    prime_factors(100000000000000LL); // 10^14
}

```

### Prime Factor Spf

Code in C++:

```

int spf[N];///smallest prime factor
void spf_pre_clc(){///nlog(log(n))
    for(int i=2;i<=N;i++){
        spf[i]=i;
    }
    for(int div=2;div<=N;div++){
        for(int i=div;i<=N;i+=div){
            spf[i]=min(spf[i],div);
        }
    }
}
void prime_factors(int n){///log(n)
    while(n>1){
        cout<<spf[n]<<" ";
        n/=spf[n];
    }
}
int32_t main() {

```

```

ios_base::sync_with_stdio(0);
cin.tie(0);
spf_pre_clc();
int n;
cin>>n;
prime_factors(n);
}

```

### Sieve

Code in C++:

```

///Nlog(N)
const int N = 1e7 + 9;
bitset<N> not_prime;
vector<int> primes;
void sieve(){
    not_prime[1] = true;
    for (int i = 2; i * i <= N; i++) {
        if (!not_prime[i]) {///prime
            for (int j = i * i; j <= N; j += i) {
                not_prime[j] = true;
            }
        }
    }
    for (int i = 2; i <= N; i++) {
        if (!not_prime[i]) { /// prime
            primes.push_back(i);
        }
    }
}

```

### Cumulative Sum 2d

Code in C++:

```

int r,c;
scanf("%d%d",&r,&c);
int ar[r+5][c+5],px[r+5][c+5];
for(int i=1;i<=r;i++)
    for(int j=1;j<=c;j++)
        cin>>ar[i][j];

for(int i=0;i<=r;i++)px[i][0]=0;
for(int j=0;j<=c;j++)px[0][j]=0;

px[1][1]=ar[1][1];
for(int i=2;i<=r;i++){
    px[i][1]=px[i-1][1]+ar[i][1];
}
for(int j=2;j<=c;j++){
    px[1][j]=px[1][j-1]+ar[1][j];
}
for(int i=2;i<=r;i++)
    for(int j=2;j<=c;j++){

```

```

        px[i][j]=px[i-1][j]+px[i][j-1]+ar[i][j]-px[i-1][j]
        -1];
    }
    cout<<"\n prefix sum array : "<<endl;
    for(int i=1;i<=r;i++){
        for(int j=1;j<=c;j++){
            cout<<px[i][j]<<" ";
        }
        cout<<"\n";
    }
    cout<<"Range of summation array (i1,j1)->(i2,j2)"<<endl;
    int i1,i2,j1,j2,ans;
    cin>>i1>>j1>>i2>>j2;
    if(i1>i2)swap(i1,i2);
    if(j1>j2)swap(j1,j2);

    ans=px[i2][j2]-px[i2][j1-1]-px[i1-1][j2]+px[i1-1][j1-1];

    cout<<"sum of range = "<<ans<<endl;

```

## Divisors

Code in C++:

```

void divisors(int n){
    vector<int> divs;
    for (int i=1;i<=n;i++){
        if (n%i==0){
            divs.push_back(i);
            if (i!=n/i)divs.push_back(n/i);
        }
    }
    sort(divs.begin(), divs.end());
    for (auto x: divs) cout << x << ' ';
}

```

## Kadanes

Code in C++:

```

cin>>n;
ll ar[n+6];
ll mx=-9999999999;
ll sum=0;
for(int i=1;i<=n;i++){
    cin>>ar[i];
    sum=max(ar[i],sum+ar[i]);
    mx=max(mx,sum);
}
cout<<mx<<"\n";

```

## Log B N

Code in C++:

```

int n,b;cin>>n>>b;
double ans;
ans=(log2(n)/log2(b));//logb(n)
cout<<ans<<"\n";

```

## Ncr Npr Pre Calculation

Code in C++:

```

template <typename T>
T INV(T base,T mod=1e9+7){//default mod=1e9+7
    return BIGMOD(base%mod,mod-2,mod)%mod;///base^-1
}

long long fact[N+10];
long long inv_fact[N+10];
void pre() {
    fact[0] = 1;
    for (long long i = 1; i <= N; i++)
        fact[i] = (fact[i - 1] * i)%MOD;

    inv_fact[N] = INV(fact[N]);
    for (long long i=N-1;i>=0;i--)
        inv_fact[i] = (inv_fact[i + 1]*(i+1))%MOD;
}

long long nCr(long long n, long long r) {
    if (r > n || r < 0) return 0;
    return fact[n] * inv_fact[r]%MOD*inv_fact[n-r]%MOD;
}

long long nPr(long long n, long long r) {
    if (r > n || r < 0) return 0;
    return fact[n] * inv_fact[n-r]%MOD;
}

signed main(){
    pre();
    int n,r;
    cin>>n>>r;
    cout<<nCr(n,r)<<" "<<nPr(n,r)<<"\n";
}

other way NCR
long long ncr(int n, int r){
    int res = 1;
    for (int i=0; i<r; i++){
        res *= (n-i);
        res /= (i+1);
    }
    return res;
}

```

## Number Hashing Rng

Code in C++:

```

struct custom_hash {
    static uint32_t splitmix32(uint32_t x) {//uint64_t
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }

    size_t operator()(uint32_t x) const {//uint64_t
        static const uint32_t FIXED_RANDOM =
            chrono::steady_clock::now().time_since_epoch().co_
            unt();
        return splitmix32(x + FIXED_RANDOM);
    }
};rng;//Random number generator
signed main(){
    int a=rng(1);
    int b=rng(2);
    int c=rng(3);
    cout<<a<<" "<<bitset<32>(a)<<"\n";
    cout<<b<<" "<<bitset<32>(b)<<"\n";
    cout<<c<<" "<<bitset<32>(c)<<"\n";
    /// if xor 1,2,3 then generally ans will be
        zero.because (1^2=3) ^ 3 =0
    /// if we this function then ans will never been zero
        because
    /// (rng(1)^rng(2) != rng(3)) ^ rng(3) = 0
    /// There can be only one way ans will be zero when we
        xor the same number with it.
    /// rng(num)^rng(num) = 0 //    rng(num)-rng(num)=0
}

```

## Trailing zeroes Of Factorial Number

Code in C++:

```

int findTrailingZeros(int n){
    int count = 0;
    for (int i = 5; n / i >= 1; i *= 5)
        count += n / i;
    return count;
}

```

## String Algorithm

### Aho Corasick

Code in C++:

```

//Time Complexity: O(n + l + z), where 'n' is the length
↳ of the text, 'l'(sum of all ptrns len) is the length
↳ of keywords, and 'z' is the number of matches.
const int MX_P = 100; // maximum number of patterns
struct AhoCorasick{
    int nod_no, ptrn_no;
    const int root = 0;
    vector<vector<int>>> next;
    vector<int> link; // suffix link/failure link
    vector<bitset<MX_P>>> output; // bitset points which
↳ which patterns output indicated by this state
    bitset<MX_P> zero; // zero
    vector<int> occr;

    AhoCorasick(): nod_no(0), ptrn_no(0){node();}

    int node(){
        next.emplace_back(26, 0);
        link.emplace_back(root); // all link initialize by
↳ root;
        output.emplace_back(zero); // each node initialize
↳ by 0 set bit
        occr.emplace_back(0); // each pattern occraance
↳ initialize by zero
        return nod_no++; // increase node count
    }

    void add_pattern(const string &s){ // trie building
        int currentState = root;
        for(auto c : s){
            int ch = c - 'a';
            if(!next[currentState][ch])
                next[currentState][ch] = node(); //
↳ node() = create a new node in this state
↳ and also next[currentState][ch] set
↳ with a state number
            currentState = next[currentState][ch];
        }
        output[currentState][ptrn_no] = 1; // this states
↳ end point of prth_no th pattern
        // output[currentState].set(ptrn_no, 1);
        ptrn_no++; // increase pattern count
    }

    void build_Automaton(){
        queue<int> Q;
        for(int ch = 0; ch < 26; ch++){
            if(next[root][ch]){
                int stat_lv1 = next[root][ch]; //
↳ stat_lv1 = state which connect with
↳ root
                link[stat_lv1] = root; // make level 1
↳ states failure link with root
                Q.push(stat_lv1);
            }
        }
    }
}

```

```

while(Q.size()){
    int currentState = Q.front(); Q.pop();
    for(int ch = 0; ch < 26; ch++){
        if(next[currentState][ch]){
            int child_state = next[currentState][ch];
            ↳ ;
            int failure = link[currentState];

            while(failure != root &&
                ↳ !next[failure][ch]) // finding
                ↳ failure node
                failure = link[failure];
            failure = next[failure][ch];

            link[child_state] = failure;
            output[child_state] |= output[failure];
            ↳ // a state also indicate
            ↳ failure states all outputs
            Q.push(child_state);
        }
    }
}

int find_NextState(int currentState, int ch){
    while(currentState != root &&
        ↳ !next[currentState][ch])
        currentState = link[currentState];

    return currentState = next[currentState][ch];
}

void searchWords(string pattern[], string &text){
    int currentState = root;
    for(int i = 0; i < text.size(); i++){
        int ch = text[i] - 'a';
        currentState = find_NextState(currentState, ch);
        if(output[currentState].any()) // chacking
            ↳ this state point any output
            for(int j = 0; j < ptrn_no; j++){
                if(output[currentState][j]) // if i'th
                    ↳ bit is on
                    cout << pattern[j] << " appears from
                    ↳ "<< i - pattern[j].size() + 1 << " to
                    ↳ "<< i << "\n";
                    occr[j]++; // increase j'th
                    ↳ patterns occurence
            }
        }
    }
}

int main(){
    int n; cin >> n;
    string pattern[n+1];
    string text;
}

```

```

AhoCorasick aho;
for(int i = 0; i < n; i++){
    cin >> pattern[i];
    aho.add_pattern(pattern[i]);
}
cin >> text;
aho.build_Automaton();
aho.searchWords(pattern, text);
for(int i = 0; i < n; i++){
    cout << pattern[i] << " occurs " << aho.occr[i] << "
    ↳ times\n";
}
}

```

## Double Hashing

Code in C++:

```

const int MAX = 1e6 + 10; // string max size
const ll MOD1 = 1e9 + 7;
const ll MOD2 = 1e9 + 9;
const ll base1 = 269; // 31, // 53
const ll base2 = 277; // 31, // 53
pair<ll, ll> pw[MAX], inv_pw[MAX];
void pow_clc(){
    ll rev_base1 = BIGMOD(base1, MOD1 - 2, MOD1); // base1^-1
    ll rev_base2 = BIGMOD(base2, MOD2 - 2, MOD2); // base2^-1
    pw[0] = {1, 1};
    inv_pw[0] = {1, 1};
    for(int i = 1; i < MAX; i++){
        pw[i].F = 1LL * pw[i-1].F * base1 % MOD1;
        inv_pw[i].F = 1LL * inv_pw[i-1].F * rev_base1 %
            ↳ MOD1;

        pw[i].S = 1LL * pw[i-1].S * base2 % MOD2;
        inv_pw[i].S = 1LL * inv_pw[i-1].S * rev_base2 %
            ↳ MOD2;
    }
}

ll compute_prehash(string const &s) // 0 (string size)
pair<ll, ll> hash_value = {0, 0};
for(int i = 0; i < s.size(); i++){
    hash_value.F = (hash_value.F +
        ↳ (s[i] * pw[i].F) % MOD1) % MOD1;
    hash_value.S = (hash_value.S +
        ↳ (s[i] * pw[i].S) % MOD2) % MOD2;
}
return {hash_value.F % MOD2 + hash_value.S};
}

vector<pair<ll, ll>> prehsh, sufsh;
int len;
void hashing(string const &s) // make a hash array in
↳ O(string size)
    len = s.size();
    prehsh.resize(len + 4);
    sufsh.resize(len + 4);
}

```

```

for(int i=0;i<len;i++){
    prehsh[i].F= (1LL*s[i]*pw[i].F) %MOD1;
    prehsh[i].S= (1LL*s[i]*pw[i].S) %MOD2;
    if(i){
        prehsh[i].F= (prehsh[i].F + prehsh[i-1].F)
        ↪ %MOD1;
        prehsh[i].S= (prehsh[i].S + prehsh[i-1].S)
        ↪ %MOD2;
    }
    sufhsh[i].F= (1LL*s[i]*pw[len-i-1].F) %MOD1;
    sufhsh[i].S= (1LL*s[i]*pw[len-i-1].S) %MOD2;
    if(i){
        sufhsh[i].F= (sufhsh[i].F + sufhsh[i-1].F)
        ↪ %MOD1;
        sufhsh[i].S= (sufhsh[i].S + sufhsh[i-1].S)
        ↪ %MOD2;
    }
}
}
ll substring_hash(int i,int j){///O(1)
    assert(i<=j);
    pair<ll,ll>hs({0,0});
    hs.F=prehsh[j].F;
    hs.S=prehsh[j].S;
    if(i){
        hs.F=(hs.F- prehsh[i-1].F +MOD1)%MOD1;
        hs.S=(hs.S- prehsh[i-1].S +MOD2)%MOD2;
    }
    hs.F= (1LL* hs.F * inv_pw[i].F)%MOD1;
    hs.S= (1LL* hs.S * inv_pw[i].S)%MOD2;
    return (hs.F*MOD2 + hs.S);
}
ll GetPrefixHash(int i,int j){
    return substring_hash(i, j);
}
ll GetSuffixHash(int i,int j){
    assert(i<=j);
    pair<ll,ll>hs({0,0});
    hs.F=sufhsh[j].F;
    hs.S=sufhsh[j].S;
    if(i){
        hs.F=(hs.F- sufhsh[i-1].F +MOD1)%MOD1;
        hs.S=(hs.S- sufhsh[i-1].S +MOD2)%MOD2;
    }
    hs.F= (1LL* hs.F * inv_pw[len-j-1].F)%MOD1;
    hs.S= (1LL* hs.S * inv_pw[len-j-1].S)%MOD2;
    return (hs.F*MOD2 + hs.S);
}
bool IsPallindrome(int l , int r) {
    return (GetPrefixHash(l , r) == GetSuffixHash(l , r));
}
void string_matching(string const &txt,string const
    ↪ &pat){///O(N)///Rabin Karp
    hashing(txt);
    ll pat_hsh=compute_prehash(pat);

```

```

int substr_len=pat.size();
vector<int>idx;
for(int i=0;i+substr_len-1<txt.size();i++){
    ll substr_hsh=substring_hash(i,i+substr_len-1);
    if(substr_hsh==pat_hsh)idx.push_back(i+1);
}
if(idx.size()){
    cout<<"pattern found at index : ";
    for(auto it: idx)cout<<it<<" ";
    cout<<"\n";
}else{
    cout<<"pattern not found\n";
}
}
int main() {
    pow_clc();
    string txt,pat;
    while(cin>>txt>>pat){
        hashing(txt);
        string_matching(txt,pat);
    }
    return 0;
}

```

## Kmp

Code in C++:

```

vector<int> failure_function(string &p){
    vector<int>failure_idx(p.size(),0);
    for(int i=1;i<p.size();i++){
        int j=failure_idx[i-1];
        while(j>0 && p[i]!=p[j]){
            j=failure_idx[j-1];
        }
        if(p[i]==p[j])failure_idx[i]=++j;
    }
    return failure_idx;
}
void KMP(string &txt,string &pat){
    vector<int>failure_idx=failure_function(pat);
    int j=0;
    for(int i=0;i<txt.size();i++){
        while(j>0 && txt[i]!=pat[j])j=failure_idx[j-1];
        if(txt[i]==pat[j]){
            j++;
            if(j==pat.size()){
                cout<<i-pat.size()+1<<" ";
                j=failure_idx[j-1];
            }
        }
    }
}

```

## Trie Tree

Code in C++:

```

struct node{
    bool End;
    vector<node*>next;
    node(){
        End=false;
        next.resize(26,nullptr);
    }
};
class Trie {
public:
    node* root;
    Trie() {
        root=new node();
    }
    void insert(string &word) {
        node*cur=root;
        for(auto ch : word){
            if(!cur->next[ch-'a'])cur->next[ch-'a']=new
                ↪ node();
            cur=cur->next[ch-'a'];
        }
        cur->End=true;
    }
    bool search(string &word) {
        node*cur=root;
        for(auto ch : word){
            if(!cur->next[ch-'a'])return false;
            cur=cur->next[ch-'a'];
        }
        return cur->End;
    }
    bool startsWith(string &prefix) {
        node*cur=root;
        for(auto ch : prefix){
            if(!cur->next[ch-'a'])return false;
            cur=cur->next[ch-'a'];
        }
        return true;
    }
};

```

## Hashing Longest Common Prefix

Code in C++:

```

void lcp(int i1,int j1,int i2,int j2){
    int l=1,r=min(j1-i1+1,j2-i2+1);/// minimum length of
    ↪ two string
    int ans=0;
    while(l<=r){

```

```

    int mid = l+r >>1;
    if(sub_hash(i1,i1+mid-1,txthsh)==sub_hash(i2,i2+
        mid-1,pathsh)){
        ans=mid;
        l=mid+1;
    }else{
        r=mid-1;
    }
}
cout<<ans<<"\n";
cout<<txt.substr(i1,ans)<<"\n";
}

```

## Hashing String Divisor

Code in C++:

```

void string_divisors(string const &s){/// nlog(n)
    hashing(s);
    int n=s.size();
    for(int len=1;len<=n;len++){
        bool ok=true;
        for(int i=0;i+len-1<n;i+=len){
            ok &= sub_hash(i,i+len-1)==sub_hash(0,len-1);

            if(i+len+len-1>=n && i+len<=n-1){///partial
                ok &= sub_hash(i+len,n-1)==sub_hash(0,n-1-i-len);
            }
        }
        if(ok==true){
            cout<<s.substr(0,len)<<"\n";
        }
    }
}

```

## Backtracking

### Combination

Code in C++:

```

int sto[20];
int N, R;
void bt(int start, int depth){
    if(depth == R){
        for(int i=0;i<R;i++){
            cout<<sto[i]<<" ";
            cout<<endl;
            return;
        }
        for(int i = start;i<=N;i++){
            sto[depth] = i;
            bt(i+1, depth+1);
        }
    }
}

```

```

    }
}
int main(){
    while(cin>>N>>R){
        bt(1, 0);
    }
}

```

## Nqueen

Code in C++:

```

int n;
vector<vector<string>>boards;
bool UnderAttack(int row,int col,vector<string>&board){
    int duprow = row;
    int dupcol = col;
    while(row>=0 && col>=0){
        if(board[row][col]=='Q'){
            return true;
        }
        --row,--col;
    }
    col = dupcol;
    row = duprow;
    while(row<n && col<=0){
        if(board[row][col]=='Q'){
            return true;
        }
        ++row,--col;
    }
    row = duprow;
    col = dupcol;
    while(col<=0){
        if(board[row][col]=='Q'){
            return true;
        }
        --col;
    }
    return false;
}
void res(int col,vector<string>&board){
    if(col==n){
        boards.push_back(board);
        return;
    }
    for(int row=0;row<n;row++){
        if(UnderAttack(row,col,board)){
            continue;
        }
        board[row][col]='Q';
        res(col+1,board);
        board[row][col]='.';
    }
}
int main(){

```

```

    cin>>n;
    vector<string>board(n,string(n,'.'));
    res(0,board);
    int w=0;
    for(auto ans : boards){
        cout<<"Possible Way : "<<w<<el;
        for(auto r : ans){
            cout<<r<<el;
        }
        cout<<el;
    }
    board.clear(),boards.clear();
}

```

}

## Permutation

Code in C++:

```

int n,r;
int color[S],sto[S];
void go(int depth){
    if(depth==r){
        for(int i=0;i<r;i++){
            printf("%d ",sto[i]);
        }
        printf("\n");
        return;
    }
    for(int i=1;i<=n;i++){
        if(color[i]==false){
            color[i]=true;
            sto[depth]=i;
            go(depth+1);
            color[i]=false;
        }
    }
}
int main(){
    while(cin>>n>>r){
        memset(color, false, sizeof color);
        go(0);
    }
}

```

## Dynamic Programming

### 1 Knapsack

Code in C++:



```

int knapSack(int i, int sto) {
    if (sto < 0) return INT_MIN;
    if (i < 0 || sto == 0) return 0;

    if(memo[i][sto] != -1) return memo[i][sto];

    int in = val[i] + knapSack(i-1, sto-wt[i]);
    int ex = knapSack(i-1, sto);
    return memo[i][sto] = max(in, ex);
}

void path(int i, int sto) {
    if(sto < 0) return;
    if(i < 0 || sto == 0) return;
    int in = memo[i-1][sto-wt[i]] + val[i];
    int ex = memo[i-1][sto];
    if(in > ex) {
        v.push_back(val[i]);
        path(i-1, sto-wt[i]);
    }
    else {
        path(i-1, sto);
    }
}

```

## Edit Distance

Code in C++:

```

int EditDistance(int i, int j) {
    if(i < 0) return j+1;
    if(j < 0) return i+1;

    if(memo[i][j] != -1) return memo[i][j];

    if(s1[i] == s2[j])
        return memo[i][j] = EditDistance(i-1, j-1);

    // any move cost 1
    int Insert = 1 + EditDistance(i, j-1);
    int Delete = 1 + EditDistance(i-1, j);
    int Remove = 1 + EditDistance(i-1, j-1);
    return memo[i][j] = min({Insert, Delete, Remove});
}

```

## Knight Tour

Code in C++:

```

typedef struct {int x, y;} co;
int dis[1006][1006], n;
int dp[1<<17][17];
int N, k;

```

```

co ic[20];
void BFS() {
    queue<co> q;
    int r, c, ur, uc,
    dr[] = {2, 2, 1, 1, -1, -1, -2, -2},
    dc[] = {1, -1, 2, -2, 2, -2, 1, -1};
    memset(dis, -1, sizeof(dis));
    dis[2][2] = 0;
    q.push({2, 2});

    while(!q.empty()) {
        ur = q.front().x;
        uc = q.front().y;
        q.pop();
        for(int i=0; i<8; i++) {
            r = ur + dr[i]; c = uc + dc[i];
            if(r >= 0 && c >= 0 && r <= 1002 && c <= 1002 &&
            dis[r][c] == -1) {
                q.push({r, c});
                dis[r][c] = dis[ur][uc] + 1;
            }
        }
    }
}

int DIS(co a, co b) {
    if(
        (a.x==1 && a.y==1 && b.x==2 && b.y==2) ||
        (a.x==2 && a.y==2 && b.x==1 && b.y==1) ||
        (a.x==n-1 && a.y==n-1 && b.x==n && b.y==n) ||
        (a.x==n && a.y==n && b.x==n-1 && b.y==n-1) ||
        (a.x==1 && a.y==n && b.x==2 && b.y==n-1) ||
        (a.x==2 && a.y==n-1 && b.x==1 && b.y==n) ||
        (a.x==n && a.y==1 && b.x==n-1 && b.y==2) ||
        (a.x==n-1 && a.y==2 && b.x==n && b.y==1)
    )
        return 4;
    return dis[abs(a.x-b.x)+2][abs(a.y-b.y)+2];
}

int go(int msk, int cur) {
    if(msk == ((1<<k)-1)) return DIS(ic[cur], ic[0]);
    int &rf = dp[msk][cur];
    if(rf != -1) return rf;
    rf = 1<<30;
    for(int i=0; i<k; i++) {
        if((msk & (1<<i)) == 0) {
            rf = min(rf, go((msk | (1<<i)), i) + DIS(ic[cur], ic[i]));
        }
    }
    return rf;
}

int main() {
    co s, a, b; int t, ks=0;
    BFS(); //pre
    cin >> t;

```

```

    while(t--){
        memset(dp, -1, sizeof dp);
        cin >> n >> k;
        for(int i=0; i<k; i++){
            cin >> ic[i].x >> ic[i].y;
        }
        cout << go(0, 0) << "\n";
    }
}

```

## Lcs

Code in C++:

```

int lcs(int t, int p) {
    if(t==n || p==m)
        return 0;
    if(memo[t][p] != -1) return memo[t][p];
    if(txt[t] == pat[p]) {
        memo[t][p] = 1 + lcs(t+1, p+1);
    }
    else {
        memo[t][p] = max(lcs(t+1, p), lcs(t, p+1));
    }
    return memo[t][p];
}

void path(int t, int p) {
    if(t==n || p==m) return;
    if(txt[t] == pat[p]) {
        ans += txt[t];
        path(t+1, p+1);
    }
    else if(memo[t+1][p] > memo[t][p+1]) {
        path(t+1, p);
    }
    else {
        path(t, p+1);
    }
}

```

## Lcs Lexicography Minimum String

Code in C++:

```

string dp[105][105];
bool vis[105][105];
string lcs(int i, int j) {
    if(i==n || j==m) return "";
    if(vis[i][j]) return dp[i][j];

    vis[i][j] = true;
    string ans = "";
    if(txt[i] == pat[j]) {
        ans = txt[i] + lcs(i+1, j+1);
    }
    else {

```



```

string a=lcs(i+1,j);
string b=lcs(i,j+1);
if(a.size()>b.size()){
    ans=a;
}else if(a.size()<b.size()){
    ans=b;
}else{
    ans=min(a,b);
}
}
dp[i][j]=ans;
return dp[i][j];
}

```

## Lis Lower Bound

Code in C++:

```

int LIS(vector<int>&a){
    vector<int>v;
    int ans=0;
    for(auto x : a){
        auto it =lower_bound(v.begin(),v.end(),x);
        ans=max(ans,(int)(it-v.begin()+1));
        if(it==v.end()){
            v.push_back(x);
        }else{
            *it=x;
        }
    }
    return ans;
}

```

## Lis Using Segment Tree

Code in C++:

```

void solve(){
    cin>>n;
    int ar[n+2];
    for(int i=0;i<n;i++){
        cin>>ar[i];
    }

    // segmenttree not working above 1e6 // needs to
    // compress values
    // coordinate compression, now all a[i] are 1 <= a[i]
    // <= n which is cute
    /**
    set<int>s;
    for(int i=0;i<n;i++)s.insert(ar[i]);
    int id=0;
    map<int,int>mp;
    for(auto it : s)mp[it]=++id;
    for(int i=0;i<n;i++)ar[i]=mp[ar[i]];
    */

```

```

*/
int max_value=n;// after compression max value will be
    ~ n or id
// segment tree on value
// MAX Segment Tree
st.build(1,1,max_value);
vector<int>dp(n+2,1);
int mx=1;
for(int i=0;i<n;i++){
    // for(int j=0;j<i;j++){
    //     if(ar[j]<ar[i]){
    //         dp[i]=max(dp[i],1+dp[j]);
    //     }
    // }
    // mx=max(dp[i],mx);
    dp[i]=max(dp[i],st.query(1,1,max_value,1,ar[i]-1)
    ~ +1);// MAX Segment
    ~ Tree
    st.update(1,1,max_value,ar[i],dp[i]);// MAX
    ~ Segment Tree update
    mx=max(mx,dp[i]);
}
cout<<mx<<"\n";
}

```

## Mcm Burst Balloons

Code in C++:

```

int go(int i,int j){
    if(i>j)return 0;
    int &rf=dp[i][j];
    if(rf!=-1)return rf;
    rf=-9999999;
    for(int idx=i;idx<=j;idx++){
        rf=max(rf,ar[i-1]*ar[idx]*ar[j+1]+go(i,idx-1)+go(
        ~ idx+1,j));
    }
    return rf;
}

```

## Coin Change Distinct Way

Code in C++:

```

memset(dp,0,sizeof dp);
dp[0]=1;
for(int i=0;i<n;i++){
    for(int j=0;j<=s;j++){
        if(j-c[i]>=0){
            dp[j]=dp[j]+dp[j-c[i]]%MOD;
        }
    }
}
cout<<dp[s]%MOD<<endl;

```

## Coin Change Use One More Time Arbitrary Order

Code in C++:

```

int way(int W) {
    if (W < 0) return INF;
    if (W == 0) return 0;

    int &rf=memo[W];
    if (rf != -1) {
        return rf;
    }
    rf = INF;
    for (int i = 0; i < NC; i++) {
        rf = min(rf, 1 + way(W - C[i]));
    }
    return rf;
}

```

## Longest Common Substring

Code in C++:

```

int lcs(string &s1, string &s2)
{
    int l1=s1.size(),l2=s2.size();
    vector<vector<int>>dp(l1+3,vector<int>(l2+3,0));
    int ans=0;
    for(int i=l1-1;i>=0;i--){
        for(int j=l2-1;j>=0;j--){
            if(s1[i]==s2[j]){
                dp[i][j]=1+dp[i+1][j+1];
            }else{
                dp[i][j]=0;
            }
            ans=max(ans,dp[i][j]);
        }
    }
    return ans;
}

```

## Number Of Palindrome In Range Query

Code in C++:

```

string s;int q;
int ispal[5010][5010];
int IsPalindrome(int l , int r) {

```

```

    if(l>r)return 1;
    if(ispal[l][r]!=-1)return ispal[l][r];
    return ispal[l][r]= s[l]==s[r] &
        ↪ IsPallindrome(l+1,r-1);
}
int dp[5010][5010];
int num_of_palin(int l,int r){
    if(l>r)return 0;
    if(dp[l][r]!=-1)return dp[l][r];
    return dp[l][r]=IsPallindrome(l,r)+
        num_of_palin(l+1,r)+num_of_palin(l,r-1)-num_of_pa
            ↪ lin(l+1,r-1);
}
int main() {
    cin>>s>>q;
    memset(dp,-1,sizeof dp);
    memset(ispal,-1,sizeof ispal);
    while(q--){
        int l,r;
        cin>>l>>r;
        l--,r--;
        cout<<num_of_palin(l,r)<<"\n";
    }
}

```

## Two Player Optimal Moves

Code in C++:

```

ll dp1[3005][3005];
bool vis1[3005][3005];
ll dp2[3005][3005];
bool vis2[3005][3005];
ll ar[3005];
ll first_player_optimal(int i,int j);//function prototype
ll second_player_optimal(int i,int j){

    if(i>j)return 0;

    if(vis2[i][j])return dp2[i][j];
    vis2[i][j]=true;

    ll left =first_player_optimal(i+1 ,j)-ar[i];
    ll right =first_player_optimal(i ,j-1)-ar[j];
    return dp2[i][j] = min(left,right);
}

ll first_player_optimal(int i,int j){

    if(i>j)return 0;

    if(vis1[i][j])return dp1[i][j];
    vis1[i][j]=true;

    ll left =second_player_optimal(i+1,j)+ar[i];
    ll right =second_player_optimal(i,j-1)+ar[j];
}

```

```

        return dp1[i][j] = max(left,right);
    }
}


```

## Geometry

### Formulas

### 2D Shapes

#### Triangle



$$\text{Area} = \frac{1}{2}bh = \sqrt{s(s-a)(s-b)(s-c)}$$

$$s = \frac{a+b+c}{2}$$

#### Sector



$$\text{Area} = \frac{1}{2}r^2\theta \text{ (rad)} = \pi r^2 \frac{\theta}{360}$$

$$\text{Arc } s = r\theta \text{ (rad)}$$

#### Polygon Area

$$A = \frac{1}{2} \left| \sum_{i=1}^n (x_i y_{i+1} - x_{i+1} y_i) \right|$$

#### Pick's Theorem

$$A = I + \frac{B}{2} - 1 \text{ (I: interior, B: boundary)}$$

### 3D Shapes

#### Sphere

$$V = \frac{4}{3}\pi r^3, \quad S = 4\pi r^2$$

#### Cylinder

$$V = \pi r^2 h, \quad S = 2\pi r(r + h)$$

#### Cone

$$V = \frac{1}{3}\pi r^2 h, \quad S = \pi r(r + \text{slant})$$

### Coordinate Geometry

#### Distance Slope

$$d = \sqrt{\Delta x^2 + \Delta y^2}, \quad m = \frac{\Delta y}{\Delta x} = \tan \theta$$

#### Rotation (CCW by $\theta$ )

$$x' = x \cos \theta - y \sin \theta$$

$$y' = x \sin \theta + y \cos \theta$$

### Trigonometry

$$\text{Sine Rule: } \frac{a}{\sin A} = \frac{b}{\sin B} = \frac{c}{\sin C} = 2R$$

$$\text{Cosine Rule: } c^2 = a^2 + b^2 - 2ab \cos C$$

$$\text{Area: } \frac{1}{2}ab \sin C$$

### Vectors

$$|A| = \sqrt{x^2 + y^2}, \quad A \cdot B = |A||B| \cos \theta$$

$$A \times B = |A||B| \sin \theta \Rightarrow x_1 y_2 - x_2 y_1$$

### Convex Hull

Code in C++:

```

struct P{
    double x,y;
};
P pvt;
P vec(P a,P b){return {b.x-a.x,b.y-a.y};}
double Cross(P a,P b){return a.x*b.y-a.y*b.x;}
double eDis(P a,P b){return
    ↪ sqrt(sqr(a.x-b.x)+sqr(a.y-b.y));}

bool comp(P a,P b)
{
    double c = Cross(vec(pvt,a),vec(pvt,b));

    if(c) return c>0;
    return eDis(pvt,a)<eDis(pvt,b);
}

vector<P> makeConvexHull(vector<P> p){
    int nConvex=p.size(),i,j;
    if(nConvex<2) return p;
    /** IF ALL POINTS ARE CO-LINER */
    // j=0;
    // for(i=2;i<nConvex;i++)
    //     if(Cross(vec(p[0],p[1]),vec(p[0],p[i]))==0)
    //         j++;
    // if(j+2==nConvex) return P
    pvt=p[0];
    for(int i=1;i<nConvex;i++){
        if(pvt.y>p[i].y) pvt=p[i];
        else if(pvt.y==p[i].y && pvt.x>p[i].x)
            ↪ pvt=p[i];
    }

    sort(all(p),comp);
    j=2;
    for(int i=2;i<nConvex;i++)
    {
}

```

```

//while(j>1 &&
↳ Cross(vec(p[j-2],p[j-1]),vec(p[j-2],p[i]))<=0)
↳ skip same line
while(j>1 &&
↳ Cross(vec(p[j-2],p[j-1]),vec(p[j-2],p[i]))<0)
↳ j--;
p[j++]=p[i];
}
p.resize(j);
return p;
}
void solve(int n) {
vector<P>v;
for(int i=0;i<n;i++){
double x,y;cin>>x>>y;
v.push_back({x,y});
}
double Perimeter=0;
if(n==1){
cout<<"("<<sp(v[0].x,1)<<" "<<sp(v[0].y,1)<<"")\n";
cout<<"Perimeter length =
↳ "<<sp(Perimeter,2)<<"\n";
return;
}
v=makeConvexHull(v);
reverse(all(v));
for(int i=0;i<v.size();i++){
cout<<"("<<sp(v[i].x,1)<<" "<<sp(v[i].y,1)<<"")-";
Perimeter+=(eDis(v[i],v[(i+1)%v.size()]));
}
cout<<"("<<sp(v[0].x,1)<<" "<<sp(v[0].y,1)<<"")\n";
cout<<"Perimeter length = "<<sp(Perimeter,2)<<"\n";
}

```

## Segment Intersect

Code in C++:

```

struct P{
double x,y;
};
P vec2d(P &a,P &b){
return{b.x - a.x, b.y - a.y};
}
double cross(P &A, P &B) {
return A.x * B.y - A.y * B.x;
}
bool onSegment(P &a,P &b, P &p) {
return min(a.x,b.x)-1e-9<=p.x<=max(a.x,b.x)+1e-9
&& min(a.y,b.y)-1e-9<=p.y<=max(a.y,b.y)+1e-9;
}
P getIntersectionPoint(P a, P b, P c, P d) {
P AB = vec2d(a, b);
P CD = vec2d(c, d);

```

```

P AC = vec2d(a, c);
double det = cross(AB, CD);
double t = cross(AC, CD) / det;
return {a.x + t * AB.x, a.y + t * AB.y};
}
bool segmentIntersect(P &a,P &b, P &c, P&d){
P AB=vec2d(a,b);
P AC=vec2d(a,c);
P AD=vec2d(a,d);
P CD=vec2d(c,d);
P CB=vec2d(c,b);
P CA=vec2d(c,a);

if(cross(AB,AC)*cross(AB,AD)<0 &&
↳ cross(CD,CB)*cross(CD,CA)<0)
return true;
if(cross(AB,AC)==0 && onSegment(a,b,c))return true;
if(cross(AB,AD)==0 && onSegment(a,b,d))return true;
if(cross(CD,CB)==0 && onSegment(c,d,b))return true;
if(cross(CD,CA)==0 && onSegment(c,d,a))return true;
return false;
}
void solve() {
P a,b,c,d;
cin>>a.x>>a.y>>b.x>>b.y>>c.x>>c.y>>d.x>>d.y;

if(segmentIntersect(a,b,c,d)){
YES
// Special case: check if lines are collinear
P AB = vec2d(a, b);
P CD = vec2d(c, d);
if(abs(cross(AB, CD))<1e-9){
cout<<"Segments are collinear"<<endl;
} else {
P it = getIntersectionPoint(a, b, c, d);
cout << "Point: " << it.x << " " << it.y <<
↳ endl;
}
}
}
}
}
}

```

## Tree Algos

### Diameter Of A Tree Dfs

Code in C++:

```

int depth[Size];
vector<int>graph[Size];
int max_depth;
int max_depth_node;

```

```

void init(int V){
for(int i=0;i<V+5;i++){
graph[i].clear();depth[i]=0;
}
max_depth=0;
}
int dfs(int u,int par=-1){
if(depth[u]>max_depth){
max_depth=depth[u];
max_depth_node=u;
}
for(auto v : graph[u]){
if(v==par)continue;
depth[v]=depth[u]+1;
dfs(v,u);
}
return max_depth_node;
}
int main(){
int V,u,v;cin>>V;
init(V);
int E=V-1;
for(int i=0;i<E;i++){
cin>>u>>v;
graph[u].push_back(v);
graph[v].push_back(u);
}
max_depth_node=dfs(1);///one based
memset(depth,0,sizeof depth);
max_depth=0;
max_depth_node=dfs(max_depth_node);
cout<<"Diameter of this Tree =
↳ "<<depth[max_depth_node]<<"\n";
}

```

## Lowest Common Ancestor Sparse Table

Code in C++:

```

///Complexity: O(NlgN,lgN)
int E,V;
int LVL[Size];
int par[Size];
int A[Size][20];
vector<int>adj[Size];
/// finding nodes tree level and parent
void leveling_dfs(int u){
for(auto v : adj[u]){
if(v==par[u])continue;
LVL[v]=LVL[u]+1;
par[v]=u;
leveling_dfs(v);
}
}

```

```

    }
}
void Sparse_Table(){
    for(int p=0;p<=log2(V)+1;p++){
        for(int i=1;i<=V;i++){
            if(p==0)
                A[i][p] = par[i];///2^p = 2^0 = 1'th
                ← parent
            else
                A[i][p] = A[A[i][p-1]][p-1];///A[i][p] =
                ← i'th nodes 2^p'th parant
        }
    }
}
int LCA(int u,int v){
    if(LVL[u]>LVL[v])
        swap(u,v);
    //Bring u and v in same level
    for(int i=log2(V)+1;i>=0;i--){
        int x = A[v][i];
        if(LVL[u]==LVL[x]){
            v=x;
            break;
        }
        if(LVL[u]<LVL[x])
            v = x;
    }
    if(u==v) return u;
    for(int i=log2(V)+1;i>=0;i--){
        if(A[u][i] != -1 && A[u][i] != A[v][i]){
            u = A[u][i];
            v = A[v][i];
        }
    }
    return par[u];
}
void build_LCA(int source){
    LVL[source]=1,par[source]=source;
    leveling_dfs(source);
    Sparse_Table();
}
int main(){
    //one based code
    int i,j,u,v,q;
    scanf("%d",&V);
    for(i=0;i<V+2;i++){
        adj[i].clear();
        for(j=0;j<=log2(V+1);j++){
            A[i][j] = -1;
        }
    }
    for(i=1;i<V;i++){
        scanf("%d%d",&u,&v);
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    int source=1;

```

```

    build_LCA(source);
    scanf("%d%d",&u,&v);
    printf("%d\n",LCA(u,v));
}

```

## Merge Sorttree Number Of Element Greater Than K

Code in C++:

```

-----
vector<ll>ar;
vector<vector<ll>>>tree;
vector<ll> marge(vector<ll>&a,vector<ll>&b){
    int n=a.size(),m=b.size();
    vector<ll>c;
    int i=0,j=0;
    while(i<n && j<m){
        if(a[i]<=b[j]){
            c.push_back(a[i]);
            i++;
        }else{
            c.push_back(b[j]);
            j++;
        }
    }
    while(i<n)c.push_back(a[i]),i++;
    while(j<m)c.push_back(b[j]),j++;
    return c;
}
void build(int node,int left,int right){
    if(left==right){
        tree[node].push_back(ar[left]);
        return ;
    }
    int mid=(left+right)/2;
    build(node*2,left,mid);
    build(node*2+1,mid+1,right);
    tree[node]=marge(tree[node*2],tree[node*2+1]);
}
int query(int node,int left,int right,int ql,int qr,ll
    ← k){///query left=ql,right=qr
    if(left>=ql && right<=qr){
        int ans= (int)tree[node].size()
        - (upper_bound(tree[node].begin(),tree[node].end(),
            ← ,k)-tree[node].begin());
        return ans;
    }
    int mid=(left+right)/2;
    if(qr<=mid){
        return query(2*node,left,mid,ql,qr,k);
    }
    else if(mid<ql){
        return query(2*node+1,mid+1,right,ql,qr,k);
    }
    else{
        int left_node=query(2*node,left,mid,ql,mid,k);

```

```

        int right_node=query(2*node+1,mid+1,right,mid+1,q
            ← r,k);
        return left_node+right_node;
    }
}
int main(){
    int n,ql,qr,pos,new_val;
    cin>>n;
    ar.resize(n+5);
    tree.resize(4*(n+5));
    for(int i=1;i<=n;i++){
        cin>>ar[i];
    }
    build(1,1,n);
    // int q;cin>>q;
    // while(q--){
    //     ll k;
    //     cin>>ql>>qr>>k;
    //     cout<<query(1,1,n,ql,qr,k)<<"\n";

    // }

    return 0;
}

```

## Segmenttree Lazypropagation

Code in C++:

```

-----
// sl = segment left,sr = segment right, tre[nod] contain
    ← [sl-sr] range
#define ll long long
const int MAX_N =100007;
const int oo = 2e9+10;
int ar[MAX_N];
struct LazyTree{
    vector<int>tre,lazy;
    LazyTree(int sz){
        tre.assign((sz*4)+10,0);
        lazy.assign((sz*4)+10,0);
    }
    inline void lazyUpdate(int nod,int sl,int sr){
        if(lazy[nod]==0)return;
        //tre[nod] += lazy[nod];// change += or = // if we
        ← chaking for max,min
        tre[nod] += lazy[nod]*(sr-sl+1);// change += or =
        if(sl!=sr){
            int left_child = 2*nod , right_child =
                ← 2*nod+1;
            lazy[left_child] += lazy[nod],
                ← lazy[right_child] += lazy[nod];// change
                ← += or =
        }
        lazy[nod]=0;
    }
}

```



```

    if(v==parent)continue;
    if(vis[v]==0){
        art_point_dfs(v,node,vis,timer,tin,tlow,adj,a,
            rt_points);
        tlow[node]=min(tlow[v],tlow[node]);
        if(tlow[v]>=tin[node] && parent!=-1){
            art_points.insert(node);
        }
        child++;
    }else{
        tlow[node]=min(tin[v],tlow[node]);
    }
}
if(child>1 && parent ==-1){
    art_points.insert(node);
}
}

int main(){
    int V,E;
    while(cin>>V>>E){
        int vis[V+5]={0},tin[V+5],tlow[V+5];
        vector<int>adj[V+5];
        set<int>art_points;
        for(int i=0;i<E;i++){
            int u,v;
            cin>>u>>v;
            adj[u].push_back(v);
            adj[v].push_back(u);//undirected graph
        }
        int timer=1;
        for(int i=0;i<V;i++){//zero based;
            if(vis[i]==0)
                art_point_dfs(i,-1,vis,timer,tin,tlow,adj,
                    rt_points);
        }
        for(auto it : art_points){
            cout<<it<<" ";
        }
        if(art_points.size()==0)
            cout<<"There is no Articulation Points";
        cout<<"\n";
    }
}

```

## Bellman Ford

Code in C++:

```

struct Edge{
    int u,v,w;
};
vector<Edge>edgeList;
int dist[V_SZ];
int par[V_SZ];

```

```

int V,E,Source;
const int oo = (1<<25);

void init(){
    for(int i =1;i<=V;i++)
    {
        dist[i] = oo;
        par[i] = -1;
    }
    edgeList.clear();
}

bool bellmanFord_IsNegCyc(int Source){
    dist[s] = 0;
    bool isUpdated;
    // bellmanford needs maximum V-1 iteration for update
    ↳ all
    //nodes minimum distance from source .but why there
    // is V iteration , because if its update a nodes
    ↳ distance
    // after V-1 iteration that means it have negative
    ↳ cycle
    for(int i=1;i<=V;i++){
        isUpdated = false;

        for(auto edg: edgeList){
            if(dist[edg.v] > dist[edg.u] + edg.w){
                dist[edg.v] = dist[edg.u] + edg.w;
                par[edg.v] = edg.u;
                isUpdated = true;// if its update V'th
                ↳ iteration
            }
        }
    }
    return isUpdated;
}

```

## Bipartite Graph Dfs

Code in C++:

```

vector<int>adj[SIZE];
int color[SIZE],V,E,u,v;
bool DFS(int u,int col){
    color[u]=col;
    for(auto v : adj[u]){
        if(color[v]==-1){
            if(DFS(v,!col)==false)// color[v]= reverse
                ↳ color[u]
            return false;
        }
        else if(color[v]==col){
            return false;
        }
    }
}

```

```

    }
}
return true;
}

signed main(){
    cin>>V>>E;
    for(int i=0;i<V+5;i++){
        color[i]=-1;
        adj[i].clear();
    }
    for(int i=0;i<E;i++){
        cin>>u>>v;
        adj[u].push_back(v);
        adj[v].push_back(u);
    }
    int flg=1;
    for(int i=1;i<=V;i++){//1 based
        if(color[i]==-1){
            if(DFS(i,0)==false){
                flg=0;
                break;
            }
        }
    }
    //if graph has a cycle which is contain odd number of
    ↳ nodes
    //in that case graph is not Bipartite Graph
    if(flg){
        cout<<"Yes\n";
    }
    else{
        cout<<"No\n";
    }
}
}

```

## Bridges

Code in C++:

```

const int nodes=105;
int timer;
int vis[nodes],tin[nodes],tlow[nodes];
vector<int>adj[nodes];
vector<pair<int,int>>bridge;
void bridge_dfs(int node,int parent){
    vis[node]=1;
    tin[node]=tlow[node]=timer;
    timer++;
    for(auto v : adj[node]){
        if(v==parent)continue;
        if(vis[v]==0){
            bridge_dfs(v,node);
            tlow[node]=min(tlow[v],tlow[node]);
            if(tlow[v]>tin[node]){

```





```

        cnt++;///number of cycle
    }
}
vis[u]=2;/// u nodes all adj nodes r visited
}

int main(){
    ///for undirected = minimum three nodes make a cycle
    ↪ for this code
    ///for directed = also one node can be make a cycle
    ↪ for this code
    ll V,E,u,v;
    while(cin>>V>>E){
        for(int i=0;i<=V+5;i++){
            vis[i]=0;
            par[i]=-1;
            g[i].clear();
            cyl[i].clear();
        }
        for(ll i=0; i<E; i++){
            cin>>u>>v;
            g[u].push_back(v);
            g[v].push_back(u);///off the line for directed
            ↪ graph
        }
        cnt=0;
        for(ll i=1;i<=V;i++){
            if(vis[i]==0)
                DFS(i);
        }
        for(ll i=0; i<cnt; i++){
            for(auto v:cyl[i])
                cout<<v<<" ";
            cout<<"\n";
        }
        if(cnt==0)cout<<"IMPOSSIBLE"<<"\n";
    }
}

```

## Dijkstra Using Pq

Code in C++:

```

struct Nod{
    int u, dis;
    Nod(int iU, int iDis){
        u = iU;
        dis = iDis;
    }
    bool operator<(const Nod& b) const{
        return dis > b.dis;
    }
};
const int Vertex_N = 101;
const int oo = 1e8+0.5;
int dist[Vertex_N];

```

```

int par[Vertex_N];
vector<int>graph[Vertex_N];
vector<int>weight[Vertex_N];
void init(int n){
    for(int i=1;i<=n;i++){
        dist[i] = oo;
        par[i] = -1;
        graph[i].clear();
        weight[i].clear();
    }
}
int dijkstra(int source, int destination){
    priority_queue<Nod>pq;
    dist[source] = 0;
    pq.push(Nod(source, 0));///pq.push({source, 0});
    while(!pq.empty()){
        Nod cur = pq.top();
        pq.pop();

        int u = cur.u;
        int uDist = cur.dis;
        if(dist[u] < uDist) {
            continue;
        }
        for(int i=0;i<graph[u].size();i++){
            int v = graph[u][i];
            int edgeWeight = weight[u][i];
            if(dist[v] > uDist + edgeWeight){
                dist[v] = uDist + edgeWeight;
                par[v] = u;
                pq.push({v, dist[v]});
            }
        }
        return dist[destination];
    }
}
vector<int> getPaht(int source, int destination){
    int v = destination;
    vector<int>path;
    while(source != v){
        path.push_back(v);
        v = par[v];
    }
    path.push_back(source);
    reverse(path.begin(), path.end());
    return path;
}

int main(){
    int V, E, S, D;///S=Point vertex,D=terget vertex
    ↪ distance
    cin>>V>>E>>S>>D;
    init(V);
    for(int i=0;i<E;i++){
        int u,v,w;
        cin>>u>>v>>w;
    }
}

```

```

graph[u].push_back(v);
weight[u].push_back(w);
///for undirected graph
graph[v].push_back(u);
weight[v].push_back(w);
}
int distance = dijkstra(S, D);
printf("Dstance: %d\n", distance);

vector<int>path = getPaht(S, D);
printf("Path: ");
for(auto v: path) cout<<v<<" ";cout<<endl;
}

```

## Floyd Warshall

Code in C++:

```

const int oo = 1e8;
const int Size = 100;
int dis[Size][Size],N,E;
cin>>N>>E;/// N=number of nodes,E=number of edges
for(int i=1;i<=N;i++){
    for(int j=1;j<=N;j++){
        dis[i][j]=oo;
        if(i==j)dis[i][j]=0;
    }
}
for(int i=0;i<E;i++){
    int u,v,w;
    cin>>u>>v>>w;
    dis[u][v]=w;/// directed graph;
}

for(int via=1;via<=N;via++){
    for(int u=1;u<=N;u++){
        for(int v=1;v<=N;v++){
            dis[u][v]=min(dis[u][v] ,
                ↪ dis[u][via]+dis[via][v]);
        }
    }
}
cout<<"All nodes distance matrix:\n";
for(int u=1;u<=N;u++){
    for(int v=1;v<=N;v++){
        if(dis[u][v]==oo){
            cout<<"oo ";
        }
        else
            cout<<dis[u][v]<<" ";
    }
    el;
}
/// if any node dist[u][u]<0 then
/// we call it has nagtive cycle

```

## Kruskal Union By Size

Code in C++:

```
-----
struct Edge{
    int u,v,w;
    Edge(int ui,int vi,int wi){
        u=ui;v=vi;w=wi;
    }
};
vector<Edge>edgeList;
int parant[sz];
int compoSize[sz];
void disjoint(int V){
    edgeList.clear();
    for(int i=0;i<=V+3;i++){
        parant[i]=i;///call by make func in DSU
        compoSize[i]=1;
    }
}
/// finding root node of this component and
/// make root node is parant of the all nodes of this
    component
int FindRootParant(int node){
    if(node == parant[node])
        return node;
    return parant[node]=FindRootParant(parant[node]);
}
/// joining two components
void join_components(int u,int v){///union/makelink u
    component
    /// to v nodes component
    and
    /// make them as a same
    component

    int u_parant=FindRootParant(u); /// finding u 's root
    node
    int v_parant=FindRootParant(v); /// finding v 's root
    node

    if(u_parant==v_parant)///both r alrady joined
        return ;
    if(compoSize[u_parant]>compoSize[v_parant]){
        parant[v_parant]=u_parant;
        compoSize[u_parant]+=compoSize[v_parant];
    }
    else{
        parant[v_parant]=u_parant;
        compoSize[v_parant]+=compoSize[u_parant];
    }
}
bool com_by_waight(Edge a,Edge b){
```

```

        return a.w<b.w;
    }
}
int kruskal(){
    int cost=0;
    sort(edgeList.begin(),edgeList.end(),com_by_waight);

    for(int i=0;i<edgeList.size();i++){
        ///if two vertex or groups root parent r same
        ///then it will be creat a cycle
        ///Then we won't add them
        ///else ↓
        if(FindRootParant(edgeList[i].u) !=
            FindRootParant(edgeList[i].v)){
            join_components(edgeList[i].u ,
                edgeList[i].v);
            cost+=edgeList[i].w;
            ///connecting edges
            cout<<edgeList[i].u<<"<->"<<edgeList[i].v<<" =
                <<"<<edgeList[i].w;el;
        }
    }
    return cost;
}

int main(){
    int V,E;cin>>V>>E;
    disjoint(V);///init
    for(int i=0;i<E;i++){
        int u,v,w;
        cin>>u>>v>>w;
        edgeList.push_back({u,v,w});
    }
    int MST_Cost = kruskal();
    cout<<"MST COST = "<<MST_Cost;el;
}
}
```

## Max Flow Dinics Algorithm

Code in C++:

```
-----
//O(V^2 E)
const long long inf = 1LL << 61;
struct Dinic {
    struct edge {
        int to, rev;
        long long flow, w;
        int id;
    };
    int n, s, t, mxid;
    vector<int> d, flow_through;
    vector<int> done;
    vector<vector<edge>> g;
    Dinic() {}
    Dinic(int _n) {
        n = _n + 10;
```

```

        mxid = 0;
        g.resize(n);
    }
    void add_edge(int u, int v, long long w, int id = -1) {
        edge a = {v, (int)g[v].size(), 0, w, id};
        edge b = {u, (int)g[u].size(), 0, 0, -2};///for
            bidirectional edges cap(b) = w
        g[u].emplace_back(a);
        g[v].emplace_back(b);
        mxid = max(mxid, id);
    }
    bool bfs() {
        d.assign(n, -1);
        d[s] = 0;
        queue<int> q;
        q.push(s);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (auto &e : g[u]) {
                int v = e.to;
                if (d[v] == -1 && e.flow < e.w) d[v] = d[u] + 1,
                    q.push(v);
            }
        }
        return d[t] != -1;
    }
    long long dfs(int u, long long flow) {
        if (u == t) return flow;
        for (int &i = done[u]; i < (int)g[u].size(); i++) {
            edge &e = g[u][i];
            if (e.w <= e.flow) continue;
            int v = e.to;
            if (d[v] == d[u] + 1) {
                long long nw = dfs(v, min(flow, e.w - e.flow));
                if (nw > 0) {
                    e.flow += nw;
                    g[v][e.rev].flow -= nw;
                    return nw;
                }
            }
        }
        return 0;
    }
    long long max_flow(int _s, int _t) {
        s = _s;
        t = _t;
        long long flow = 0;
        while (bfs()) {
            done.assign(n, 0);
            while (long long nw = dfs(s, inf)) flow += nw;
        }
        flow_through.assign(mxid + 10, 0);
        ///for(int i = 0; i <=n; i++) for(auto e : g[i])
            if(e.id >= 0) flow_through[e.id] = e.flow;
```

```

    return flow;
}
};
int main() {
    int n, m;
    cin >> n >> m;
    Dinic F(n + 1);
    for (int i = 1; i <= m; i++) {
        int u, v, w; // onse based
        cin >> u >> v >> w;
        F.add_edge(u, v, w);
        //F.add_edge(v, u, w); // bi directional
    }
    cout << F.max_flow(1, n) << '\n';
    return 0;
}

```

## Stronglyconnectedcomponents

Code in C++:

```

struct node{
    int idx,st,fin;
};
node Time[Size];
vector<int>adj[Size];
vector<int>radj[Size];
vector<int>component[Size];
int vis[Size],scc[Size],ti,compo_no;
bool com(node a,node b){
    return a.fin>b.fin;
}
bool comidx(node a,node b){
    return a.idx<b.idx;
}
void dfs(int u){
    Time[u].st=ti++;
    vis[u]=1;
    for(int i=0;i<adj[u].size();i++){
        int v=adj[u][i];
        if(vis[v]==0){
            dfs(v);
        }
    }
    Time[u].fin=ti++;
}
void rdfs(int u,int compo_no){
    vis[u]=1;
    scc[u]=compo_no; //scc[u] is compo_no'th component who
    // is carring nod u
    component[compo_no].push_back(u);
    for(int i=0;i<radj[u].size();i++){
        int v=radj[u][i];
        if(vis[v]==0){
            rdfs(v,compo_no);
        }
    }
}

```

```

}
}
int main(){
    int V,E,u,v;cin>>V>>E;
    // SCC works only for directional graph
    for(int i=0;i<=V+5;i++){
        adj[i].clear();
        radj[i].clear();
        component[i].clear();
        vis[i]=0;
    }
    for(int i=1;i<=E;i++){
        cin>>u>>v;
        adj[u].push_back(v);
        radj[v].push_back(u); // for reverce edges
        // direction
    }
    ti=1;
    for(int i=1;i<=V;i++){ // 1 based graph
        Time[i].idx=i;
        if(vis[i]==0){
            dfs(i);
        }
    }
    // cout<< "[Start time,Finish Time]:\n";
    // for(int i=1;i<=V;i++){
    //     cout<< "Nod "<<i<< "
    //     :["<<Time[i].st<<","<<Time[i].fin<<"]\n";
    // }
    memset(vis,0,sizeof vis),compo_no=0; //compo_no = n'th
    // component[1 based]
    sort(&Time[1],&Time[V+1],com); //precedency by finish
    // time
    for(int i=1;i<=V;i++){
        if(vis[Time[i].idx]==0){
            compo_no++; // compo_no also compo
            // index which is 1 based
            rdfs(Time[i].idx,compo_no); //dfs traverce for
            // reverse direction
        }
    }
    //sort(&Time[1],&Time[V+1],comidx);
    for(int i=1;i<=compo_no;i++){ // number of component
        // is compo_no
        cout<<"SCC("<<scc[component[i][0]]<<")<<")<< " ->
        // " ; //component[i][0] is the 1st node of i'th
        // component
        for(auto v : component[i]){
            cout<<v<<" ";
            //cout<<" -> SCC("<<scc[v]<<") ,";
        }
        cout<<"\n";
    }
    cout<<"\n";
}
}

```

## Topologicalsort Khans

Code in C++:

```

const int Size=105;
vector<int>adj[Size];
vector<int>TS; //Topological Sort
int indegree[Size],V,E;
queue<int>Q;
void init(){
    for(int i=0;i<V+5;i++){
        indegree[i]=0;
        adj[i].clear();
    }
    TS.clear();
}
void topo_BFS(){
    while(!Q.empty()){
        int u=Q.front();Q.pop();
        for(auto v : adj[u]){
            --indegree[v];
            if(indegree[v]==0){
                TS.emplace_back(v);
                Q.push(v);
            }
        }
    }
}
int main(){
    cin>>V>>E;
    init();int u,v;
    for(int i=0;i<E;i++){
        cin>>u>>v;
        adj[u].emplace_back(v);
        ++indegree[v];
    }
    for(int i=1;i<=V;i++){ //1 based
        if(indegree[i]==0){
            TS.emplace_back(i);
            Q.push(i);
        }
    }
    topo_BFS();
    if(TS.size()!=V){
        cout<<"CycleExist\n";
    }
    for(auto it : TS){
        cout<<it<<" ";
    }
    cout<<"\n";
}

```

## Matrix

## Matrix Exponential

Code in C++:

```
vector<vector<ll>> matMulti(vector<vector<ll>>&a,
    vector<vector<ll>>&b, ll Mod){
    int r = a.size();
    int c = b[0].size();
    vector<vector<ll>> ans(r, vector<ll>(c, 0));
    for(int i = 0; i < r; i++) {
        for(int j = 0; j < c; j++) {
            for(int k = 0; k < a[0].size(); k++) {
                ans[i][j] = ((ans[i][j] + (a[i][k] * b[k][j]) % M_
                    od) % Mod + Mod) % Mod;
            }
        }
    }
    return ans;
}

vector<vector<ll>> matExpo(vector<vector<ll>>& b, ll pw,
    ll Mod){
    int r = b.size();
    vector<vector<ll>> ans(r, vector<ll>(r, 0));
    for(int i = 0; i < r; ++i) {
        ans[i][i] = 1;
    }
    while(pw) {
        if(pw & 1) {
            ans = matMulti(ans, b, Mod);
        }
        b = matMulti(b, b, Mod);
        pw >>= 1;
    }
    return ans;
}
```