Pizza Sales Dashboard Oracle SQL Query:

A.KPI's Requirements

--Total Revenue:

select sum(total_price) Total_revenue from pizza_sales;

TOTAL_REVENUE
817860.05

--Average Order Value

select sum(total_price) / count(Distinct order_id) Avg_order_value from pizza_sales;

AVG_ORDER_VALUE
38.30726229508196721311475409836065573 77

--Total Pizzas Sold

select sum(quantity) as total_pizza_sold from pizza_sales;

TOTAL_PIZZA_SOLD
49574

--Total Orders

SELECT COUNT(DISTINCT order_id) AS Total_Orders FROM pizza_sales;

TOTAL_ORDERS
21350

--Average Pizzas Per Order

select round(sum(quantity)/count(distinct order_id),2)

as Avg_pizza_per_order

from pizza_sales;

AVG_PIZZA_PER_ORDER
2.32

--B. Daily Trend for Total Orders

```
select to_char(order_date,'Day') as order_day,
count(distinct order_id) total_orders from pizza_sales
group by to_char(order_date,'Day'),
    to_char(order_date,'D')
    order by to_char(order_date,'D') ;
```

ORDER_DAY	TOTAL_ORDERS
Sunday	2624
Monday	2794
Tuesday	2973
Wednesday	3024
Thursday	3239
Friday	3538
Saturday	3158

--C. Hourly Trend for Orders

```
select order_hours,count(distinct order_id) as total_orders from
(select extract(hour from to_timestamp(order_time,'HH24:MI:SS')) as order_hours,order_id from pizza_sales)
group by order_hours
order by order_hours;
```

ORDER_HOURS	TOTAL_ORDERS
9	1
10	8
11	1231
12	2520
13	2455
14	1472
15	1468
16	1920
17	2336
18	2399
19	2009
20	1642
21	1198
22	663
23	28

```
--D. % of Sales by Pizza Category
select pizza_size,
round(sum(total_price),2) total_revenue ,
round(sum(total_price)*100/
sum(sum(total_price)) over(),2) as pct from pizza_sales
group by pizza_size;
```

PIZZA_SIZE	TOTAL_REVENUE	PCT
M	249382.25	30.49
L	375318.7	45.89
S	178076.5	21.77
XL	14076	1.72
XXL	1006.6	0.12

```
--F. Total Pizzas Sold by Pizza Category
select pizza_category, sum(quantity) as total_quantity_sold from pizza_Sales
where extract(month from order_date)= 2
group by pizza_category
order by total_quantity_sold desc;
```

PIZZA_CATEGORY	TOTAL_QUANTITY_SOLD
Classic	1178
Supreme	964
Veggie	944
Chicken	875

```
--G. Top 5 Best Sellers by Total Pizzas Sold
select *
from ( select pizza_name,sum(quantity) as total_pizza_sold
from pizza_sales
group by pizza_name
order by total_pizza_sold desc
)
where rownum <=5;
```

PIZZA_NAME	TOTAL_PIZZA_SOLD
The Classic Deluxe Pizza	2453
The Barbecue Chicken Pizza	2432
The Hawaiian Pizza	2422
The Pepperoni Pizza	2418
The Thai Chicken Pizza	2371

--H. Bottom 5 Best Sellers by Total Pizzas Sold

```
select pizza_name,sum(quantity) as total_pizza_sold
from pizza_sales
group by pizza_name
order by  total_pizza_sold asc
fetch first 5 rows only;
```

PIZZA_NAME	TOTAL_PIZZA_SOLD
The Brie Carre Pizza	490
The Mediterranean Pizza	934
The Calabrese Pizza	937
The Spinach Supreme Pizza	950
The Soppressata Pizza	961