

Productname : INOX 200
Ref.Nr.: BDS001667_3_20221222 (EN)

Creationdate : 22.12.22 Version : 3.1
Replaces: BDS001667_20180705

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

INOX 200
Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Anti Corrosion Products

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom
Tel.: +44 1278 727200
Fax.: +44 1278 425644
E-mail : hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

| | |
|---|---|
| Physical: | Aerosols, category 1 Extremely flammable aerosol. Pressurised container: May burst if heated. |
| Classification is based on test data. | |
| Health: | Specific target organ toxicity - single exposure, category 3 May cause drowsiness or dizziness. |
| Classification based on calculation method. | |
| Environment: | Not classified |
| Classification based on calculation method. | |

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008



Productname : INOX 200
Ref.Nr.: BDS001667_3_20221222 (EN)

Creationdate : 22.12.22 Version : 3.1
Replaces: BDS001667_20180705

Product identifier: Contains:
n-butyl acetate

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s):
 H222 : Extremely flammable aerosol.
 H229 : Pressurised container: May burst if heated.
 H336 : May cause drowsiness or dizziness.

Precautionary statement(s):
 P102 : Keep out of reach of children.
 P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 : Do not spray on an open flame or other ignition source.
 P251 : Do not pierce or burn, even after use.
 P260 : Do not breathe dust/fume/gas/mist/vapours/spray.
 P271 : Use only outdoors or in a well-ventilated area.
 P410/412 : Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501-2 : Dispose of contents/container to an authorised waste collection point.

Supplemental Hazard information:
 Repeated exposure may cause skin dryness or cracking.
 Contains:
 nickel
 May produce an allergic reaction.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

| Hazardous ingredient | Registration number | CAS-nr. | EC-nr | w/w % | Hazard Class and Category | Hazard statement | Notes |
|--|---------------------|-----------|-----------|-------|---|---------------------|-------|
| dimethyl ether | 01-2119472128-37 | 115-10-6 | 204-065-8 | 50-75 | Flam. Gas 1, Press. Gas | H220,H280 | A |
| n-butyl acetate | 01-2119485493-29 | 123-86-4 | 204-658-1 | 10-25 | Flam. Liq. 3, STOT SE 3 | H226,H336 | |
| 2-methoxy-1-methylethyl acetate | 01-2119475791-29 | 108-65-6 | 203-603-9 | 5-10 | Flam. Liq. 3 | H226 | A |
| nickel | 01-2119438727-29 | 7440-02-0 | 231-111-4 | <0.5 | Carc. 2, STOT RE 1, Skin Sens. 1, Aquatic Chronic 3 | H351,H372,H317,H412 | B |
| Explanation notes | | | | | | | |
| A : substance with Community workplace exposure limit | | | | | | | |
| B : substance with national established workplace exposure limit | | | | | | | |

Productname : INOX 200
Ref.Nr.: BDS001667_3_20221222 (EN)

Creationdate : 22.12.22 Version : 3.1
Replaces: BDS001667_20180705

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|---|
| Contact with eyes : | If substance has got into eyes, immediately wash out with plenty of water If eye irritation persists: Get medical advice/attention. |
| Contact with skin : | Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. |
| Inhalation : | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| Ingestion : | If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-----------------------|--|
| Inhalation : | Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness |
| Ingestion : | After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. Symptoms : sore throat, abdominal pain, nausea, vomiting |
| Skin contact : | May cause irritation. Symptoms : redness and pain |
| Eye contact : | May cause irritation. Symptoms : redness and pain |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-------------------------|---|
| General Advice : | If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor |
|-------------------------|---|

SECTION 5: Firefighting measures

5.1. Extinguishing media

foam, carbon dioxide or dry agent
Do not use water jet extinguishing media, due to the risk of spreading fire.

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C
Forms hazardous decomposition products
CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes

Productname : INOX 200
Ref.Nr.: BDS001667_3_20221222 (EN)

Creationdate : 22.12.22 Version : 3.1
Replaces: BDS001667_20180705

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing and gloves.
In case of insufficient ventilation, wear suitable respiratory equipment.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
Keep out of reach of children.

7.3. Specific end use(s)

Anti Corrosion Products

SECTION 8: Exposure controls/personal protection

Productname : INOX 200
Ref.Nr.: BDS001667_3_20221222 (EN)

Creationdate : 22.12.22 Version : 3.1
Replaces: BDS001667_20180705

8.1. Control parameters

Exposure limits :

| Hazardous ingredient | CAS-nr. | method | |
|--|-----------|--------|-----------|
| EU established exposure limits: | | | |
| 2-methoxy-1-methylethyl acetate | 108-65-6 | TWA | 50 ppm |
| | | STEL | 100 ppm |
| dimethyl ether | 115-10-6 | TWA | 1000 ppm |
| National established exposure limits, United Kingdom | | | |
| 2-methoxy-1-methylethyl acetate | 108-65-6 | TWA | 50 ppm |
| | | STEL | 100 ppm |
| dimethyl ether | 115-10-6 | TWA | 400 ppm |
| | | STEL | 500 ppm |
| n-butyl acetate | 123-86-4 | TWA | 150 ppm |
| | | STEL | 200 ppm |
| National established exposure limits, Ireland | | | |
| 2-methoxy-1-methylethyl acetate | 108-65-6 | TWA | 50 ppm |
| | | STEL | 100 ppm |
| dimethyl ether | 115-10-6 | TWA | 1000 ppm |
| | | STEL | - |
| n-butyl acetate | 123-86-4 | TWA | 150 ppm |
| | | STEL | 200 ppm |
| nickel | 7440-02-0 | TWA | 0.5 mg/m3 |
| | | STEL | - |

8.2. Exposure controls

| | |
|-------------------------------------|--|
| Control procedures : | Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges |
| Personal protection : | Take precautions to avoid contact with skin and eyes when handling the product. It is good practice to wear gloves and to provide adequate ventilation whenever using the product. In all cases handle and use the product in accordance with good industrial hygiene practices. |
| Inhalation : | In case of insufficient ventilation, wear suitable respiratory equipment. |
| recommended respiratory protection: | (filter AXP2) |
| hands and skin : | Depending on amount and duration of use and the risk of contact with the product the gloves manufacturer can assist you in the selection of the right glove material and breakthrough time. |
| Recommended gloves: | Nitrile |
| eyes : | Wear safety eyewear according to EN 166. |
| Environmental protection: | Avoid release to the environment. Collect spillage. |

SECTION 9: Physical and chemical properties

| | | | |
|----------------------|---------------------------|-----------------------|------------------------|
| Productname : | INOX 200 | Creationdate : | 22.12.22 Version : 3.1 |
| Ref.Nr.: | BDS001667_3_20221222 (EN) | Replaces: | BDS001667_20180705 |

9.1. Information on basic physical and chemical properties

(for aerosols data for the product without propellant)

Appearance : physical state : DME propelled liquid.

colour : Grey.

odour : Solvent.

pH : Not applicable.

Melting point/range : Not applicable.

Boiling point/range : Not available.

flammability: Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Without adequate ventilation formation of explosive mixtures may be possible.

Flash point : - 40 °C (Closed Cup)

Evaporation rate : Not available.

Explosion limits : upper limit : Not available.

lower limit : Not available.

Vapour pressure : Not available.

Relative density : 0.793 g/cm³ (@ 20°C).

Solubility in water : Insoluble in water

Partition coefficient n-octanol/water: Not applicable.

Auto-ignition : 268 °C

Viscosity : 23 Sec (ASTM CF 4).

Particle characteristics: Not applicable.

9.2. Other information

VOC = volatile organic compounds 702 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

Productname : INOX 200
Ref.Nr.: BDS001667_3_20221222 (EN)

Creationdate : 22.12.22 Version : 3.1
Replaces: BDS001667_20180705

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO2

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|---|---|
| acute toxicity: | based on available data the classification criteria are not met |
| skin corrosion/irritation: | based on available data the classification criteria are not met |
| serious eye damage/irritation: | based on available data the classification criteria are not met |
| respiratory or skin sensitisation: | based on available data the classification criteria are not met |
| germ cell mutagenicity: | based on available data the classification criteria are not met |
| carcinogenicity: | based on available data the classification criteria are not met |
| toxicity for reproduction: | based on available data the classification criteria are not met |
| STOT-single exposure: | May cause drowsiness or dizziness. |
| STOT repeated exposure: | based on available data the classification criteria are not met |
| aspiration hazard: | based on available data the classification criteria are not met |

Information on likely routes of exposure:

| | |
|-----------------------|--|
| Inhalation : | Inhalation of solvent vapours may give rise to nausea, headaches and dizziness |
| Ingestion : | After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. |
| Skin contact : | Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis Repeated exposure may cause skin dryness or cracking. |
| Eye contact : | May cause irritation. |

Toxicological data :

| Hazardous ingredient | CAS-nr. | method | |
|---------------------------------|----------|-----------------|--------------|
| 2-methoxy-1-methylethyl acetate | 108-65-6 | LD50 oral rat | > 5000 mg/kg |
| | | LC50 inhal.rat | 10.8 mg/l |
| | | LD50 derm.rat | > 5000 mg/kg |
| | | LD50 derm.rabit | > 5000 mg/kg |
| dimethyl ether | 115-10-6 | LC50 inhal.rat | 309 mg/l |
| n-butyl acetate | 123-86-4 | LD50 oral rat | 10760 mg/kg |
| | | LC50 inhal.rat | > 20 mg/l |
| | | LD50 derm.rabit | > 1400 mg/kg |

11.2. Information on other hazards

Productname : INOX 200
Ref.Nr.: BDS001667_3_20221222 (EN)

Creationdate : 22.12.22 Version : 3.1
Replaces: BDS001667_20180705

No information available

SECTION 12: Ecological information

12.1. Toxicity

Not classified

Ecotoxicological data:

| Hazardous ingredient | CAS-nr. | method | |
|---------------------------------|----------|--------------|--------------|
| 2-methoxy-1-methylethyl acetate | 108-65-6 | LC50 fish | 100-180 mg/l |
| | | EC50 daphnia | > 400 mg/l |
| dimethyl ether | 115-10-6 | IC50 algae | 154.9 mg/l |
| | | LC50 fish | 4.1 mg/l |
| | | EC50 daphnia | 4.4 mg/l |
| n-butyl acetate | 123-86-4 | IC50 algae | 647 mg/l |
| | | LC50 fish | 18 mg/l |
| | | EC50 daphnia | 44 mg/l |

12.2. Persistence and degradability

No experimental data available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

Insoluble in water

12.5. Results of PBT and vPvB assessment

No information available

12.6. Endocrine disrupting properties

No information available

12.7. Other adverse effects

No experimental data available
GWP (global warming potential): 1

SECTION 13: Disposal considerations

Productname : INOX 200
Ref.Nr.: BDS001667_3_20221222 (EN)

Creationdate : 22.12.22 Version : 3.1
Replaces: BDS001667_20180705

13.1. Waste treatment methods

National regulations : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : 1950

14.2. UN proper shipping name

Proper shipping name: AEROSOLS

14.3. Transport hazard class(es)

Class: 2.1
ADR/RID - Classification code: 5F

14.4. Packing group

Packing group: Not applicable.

14.5. Environmental hazards

ADR/RID - Environmentally
hazardous: No
IMDG - Marine pollutant: No
IATA/ICAO - Environmentally
hazardous: No

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D)
IMDG - Ems: F-D, S-U
IATA/ICAO - PAX: 203
IATA/ICAO - CAO: 203

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.

Productname : INOX 200
Ref.Nr.: BDS001667_3_20221222 (EN)

Creationdate : 22.12.22 Version : 3.1
Replaces: BDS001667_20180705

Regulation (EC) No 1907/2006 (REACH)
Regulation (EC) No 1272/2008 (CLP)
Dir. 2013/10/EU, 2008/47/EC amendment of the aerosol dispenser directive 75/324/EEC.

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H220 : Extremely flammable gas.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H317 : May cause an allergic skin reaction.
H336 : May cause drowsiness or dizziness.
H351 : Suspected of causing cancer .
H372 : Causes damage to organs through prolonged or repeated exposure.
H412 : Harmful to aquatic life with long lasting effects.

acronyms and synonyms: TWA = time weight average
STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistant bioaccumulative toxic
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.