

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)
Product code	:	08934801
Unique Formula Identifier (UFI)	:	FGKC-C0R7-N002-GUAD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	:	Adhesives Professional use product
Recommended restrictions on use	:	Not applicable

1.3 Details of the supplier of the safety data sheet

Company	:	Adolf Wuerth GmbH & Co. KG Reinhold-Würth-Str. 12-17 74653 Künzelsau
Telephone	:	+49 794015 0
Telefax	:	+49 794015 10 00
E-mail address of person responsible for the SDS	:	isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements	:	H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H411	Toxic to aquatic life with long lasting effects.

Precautionary statements	:	Prevention:	
		P264	Wash skin thoroughly after handling.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ eye protection/ face protection.

Response:

P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P391	Collect spillage.

Hazardous components which must be listed on the label:

Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol	40216-08-8	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 90 - <= 100

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|----------------------------|--|
| General advice | : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| Protection of first-aiders | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| If inhaled | : If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|-------|---------------------------|
| Risks | : Causes skin irritation. |
|-------|---------------------------|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

Prevent spreading over a wide area (e.g. by containment or oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapours.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Gases

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to DIN EN 166

Hand protection

Material	: butyl-rubber
Break through time	: > 480 min
Glove thickness	: 0,8 mm
Directive	: Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

clothing (gloves, aprons, boots, etc).

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : light yellow

Odour : slight

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : > 200 °C

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 200 °C
Method: DIN 51758, Pensky-Martens closed cup

Auto-ignition temperature : No data available

Decomposition temperature : > 200 °C

pH : substance/mixture is non-soluble (in water)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

Viscosity
Viscosity, dynamic : 6.500 - 8.000 mPa.s (25 °C)

Viscosity, kinematic : No data available

Solubility(ies)
Water solubility : (20 °C)
practically insoluble

Partition coefficient: n-
octanol/water : Not applicable

Vapour pressure : < 0,000001 kPa (25 °C)

Relative density : 1,2

Density : 1,18 g/cm³ (25 °C)

Relative vapour density : No data available

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol:

Species : Rabbit
Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

Components:

Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol:

Exposure routes	: Skin contact
Species	: Guinea pig
Result	: positive

Assessment	: Probability or evidence of skin sensitisation in humans
------------	---

Germ cell mutagenicity

Not classified based on available information.

Components:

Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol:

Genotoxicity in vivo	: Test Type: Mammalian spermatogonial chromosome aberration test (in vivo) Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
----------------------	---

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 1 - 10 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 48 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	: EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 mg/l Exposure time: 72 h Remarks: Based on data from similar materials NOEC (Scenedesmus capricornutum (fresh water algae)): > 1 - 10 mg/l Exposure time: 72 h Remarks: Based on data from similar materials
Toxicity to microorganisms	: IC50 : > 100 mg/l Exposure time: 3 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 0,3 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

12.2 Persistence and degradability

Components:

Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 - 5 %
Exposure time: 28 d
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

Waste Code : The following Waste Codes are only suggestions:

used product
07 02 08, other still bottoms and reaction residues

unused product
07 02 08, other still bottoms and reaction residues

uncleaned packagings
15 01 10, packaging containing residues of or contaminated
by hazardous substances

Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-
hazardous products can be supplied to a system for the col-
lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: UN 3082
ADR	: UN 3082
RID	: UN 3082
IMDG	: UN 3082
IATA	: UN 3082

14.2 UN proper shipping name

ADN	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1- methylethylidene)bis[phenol] and phenol)
ADR	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1- methylethylidene)bis[phenol] and phenol)
RID	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1- methylethylidene)bis[phenol] and phenol)
IMDG	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1- methylethylidene)bis[phenol] and phenol)
IATA	: Environmentally hazardous substance, liquid, n.o.s.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

(Formaldehyde, polymer with (chloromethyl)oxirane, 4,4'-(1-methylethylidene)bis[phenol] and phenol)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 9	
ADR	: 9	
RID	: 9	
IMDG	: 9	
IATA	: 9	

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: M6
Hazard Identification Number	: 90
Labels	: 9
ADR	
Packing group	: III
Classification Code	: M6
Hazard Identification Number	: 90
Labels	: 9
Tunnel restriction code	: (-)
RID	
Packing group	: III
Classification Code	: M6
Hazard Identification Number	: 90
Labels	: 9
IMDG	
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 964
Packing instruction (LQ)	: Y964
Packing group	: III
Labels	: Miscellaneous
IATA (Passenger)	
Packing instruction (passenger aircraft)	: 964
Packing instruction (LQ)	: Y964
Packing group	: III
Labels	: Miscellaneous

14.5 Environmental hazards

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 3
--	--

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
---	------------------

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
---	------------------

Regulation (EU) 2019/1021 on persistent organic pollu-	: Not applicable
--	------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

tants (recast)

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2	ENVIRONMENTAL HAZARDS	Quantity 1 200 t	Quantity 2 500 t
----	-----------------------	---------------------	---------------------

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV §6(4)

TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:
Not applicable
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable
5.2.7.1.1: fibres:
Not applicable
5.2.7.1.2: Germ cell mutagens:
Not applicable
5.2.7.1.3: Substances toxic to reproduction:
Not applicable
5.2.7.2: Poorly degradable, easily enrichable and highly toxic organic substances:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Remarks: Not applicable

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



EPOXY RESIN FAST BONDING ADHESIVE ESK-50 - 50 ML (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 22.08.2023
5.5	11.04.2024	10635721-00011	Date of first issue: 25.11.2014

SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN