according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SILICONE REMOVER - 600 ML

Product code : 0893222600

Unique Formula Identifier

(UFI)

: H6J9-C01N-W00C-Y7UU

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cleaning agent, Detergent Professional use product

Recommended restrictions

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Specific target organ toxicity - single ex-

posure, Category 3

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated H372: Causes damage to organs through pro-

1/22

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

Version Revision Date: SDS Number: Date of last issue: 21.11.2023 8.15 26.03.2024 10672341-00013 Date of first issue: 11.06.2010

exposure, Category 1 longed or repeated exposure.

Long-term (chronic) aquatic hazard, Cat-H411: Toxic to aquatic life with long lasting effects.

egory 2

2.2 Label elements

Signal word

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Hazard statements H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated.

May cause drowsiness or dizziness. H336

H372 Causes damage to organs through prolonged or

repeated exposure.

Toxic to aquatic life with long lasting effects. H411

Supplemental Hazard

Statements

EUH066

Danger

Repeated exposure may cause skin dryness or

cracking.

Prevention: Precautionary statements

> P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition

source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

Avoid release to the environment. P273

Response:

P391 Collect spillage.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)				
	Index-No. Registration number						
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1 01-2119458049-33	Flam. Liq. 3; H226 STOT SE 3; H336 STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 90 - <= 100				
Substances with a workplace exposure limit :							
Carbon dioxide	124-38-9 204-696-9	Press. Gas Liquefied gas; H280	>= 1 - < 10				

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Gas reduces oxygen available for breathing.

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated

exposure.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Flash back possible over considerable distance.

Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Carbon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth- : Use extinguishing measures that are appropriate to local cir-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

ods cumstances and the surrounding environment.

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Remove all sources of ignition.

Ventilate the area.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

Version Revision Date: SDS Number: Date of last issue: 21.11.2023 8.15 26.03.2024 10672341-00013 Date of first issue: 11.06.2010

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventila-

tion.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe spray.

Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Do not spray on an open flame or other ignition source.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sun-

light.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases

Explosives Gases

Storage class (TRGS 510) : 2B

Storage period : 24 Months

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

Recommended storage tem- $\,$: $\,$ < 40 $^{\circ}$ C

perature

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis	
		of exposure)			
Hydrocarbons, C9-	64742-82-1	AGW	300 mg/m3	DE TRGS	
C12, n-alkanes,				900	
isoalkanes, cyclics,					
aromatics (2-25%)					
	Peak-limit: excursion factor (category): 2;(II)				
	Further information: Group exposure limit for hydrocarbon solvent mixtures				
Carbon dioxide	124-38-9	TWA	5.000 ppm	2006/15/EC	
			9.000 mg/m3		
	Further information: Indicative				
		AGW	5.000 ppm	DE TRGS	
			9.100 mg/m3	900	
	Peak-limit: excursion factor (category): 2;(II)				
		MAK	5.000 ppm	DE DFG MAK	
			9.100 mg/m3		
	Peak-limit: excursion factor (category): 2; II				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C9- C12, n-alkanes, isoal- kanes, cyclics, aro- matics (2-25%)	Workers	Inhalation	Long-term systemic effects	330 mg/m3
	Workers	Skin contact	Long-term systemic effects	44 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	71 mg/m3
	Consumers	Skin contact	Long-term systemic effects	26 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	26 mg/kg bw/day

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Please follow all applicable local/national requirements when

selecting protective measures for a specific workplace.

Wear the following personal protective equipment:

Safety glasses

Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Rate of permeability : > 480 min
Glove thickness : > 0,7 mm

Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change

gloves often!

Skin and body protection : Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

Propellant : Carbon dioxide

Colour : colourless

clear

Odour : hydrocarbon-like

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

130 - 180 °C (1.013 hPa) Method: DIN 51751

Extremely flammable aerosol.

Upper explosion limit / Upper

Flammability (solid, gas)

flammability limit

: 6,5 %(V)

Lower explosion limit / Lower

flammability limit

: 0,7 %(V)

Flash point : > 23 - < 40 °C

Flash point is only valid for liquid portion in the aerosol can.

Auto-ignition temperature : > 200 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : slightly soluble

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

Partition coefficient: n-

octanol/water

: log Pow: 3,7 - 6,4

Vapour pressure : 6,5 bar (20 °C)

9,0 bar (50 °C)

Density : 0,77 - 0,785 g/cm³ (15 °C)

Method: DIN 51757

Relative vapour density : Not applicable

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation exposure Skin contact

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Acute oral toxicity : LD50 (Rat): > 15.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 13,1 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 3.400 mg/kg

Carbon dioxide:

Acute inhalation toxicity : LC50 (Rat): 40000 - 50000 ppm

Exposure time: 30 min Test atmosphere: vapour

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Species : Rabbit

Method : OECD Test Guideline 405

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 105 weeks Result : negative

Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Exposure routes : Inhalation

Target Organs : Central nervous system

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Repeated dose toxicity

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Species : Rat

NOAEL : 1.056 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat

NOAEL : 3,950 mg/l LOAEL : 7,400 mg/l Application Route : Inhalation Exposure time : 90 Days

Aspiration toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Experience with human exposure

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Inhalation : Symptoms: central nervous system effects

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 10 - 22 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 4,1

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0,76

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

Version Revision Date: SDS Number: Date of last issue: 21.11.2023 8.15 26.03.2024 10672341-00013 Date of first issue: 11.06.2010

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,097 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Carbon dioxide:

Toxicity to fish : NOEC (Lepomis macrochirus (Bluegill sunfish)): > 100 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

NOEC (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Biodegradability : Result: Readily biodegradable.

Biodegradation: 75,9 % Exposure time: 31 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):

Partition coefficient: n-

octanol/water

: Pow: > 4

Carbon dioxide:

Partition coefficient: n-

octanol/water

log Pow: 0,83

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

Waste Code : The following Waste Codes are only suggestions:

used product

14 06 03, other solvents and solvent mixtures

unused product

14 06 03, other solvents and solvent mixtures

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

(Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aro-

matics (2-25%))

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADN
 : 2
 2.1

 ADR
 : 2
 2.1

 RID
 : 2
 2.1

IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

Version Revision Date: SDS Number: Date of last issue: 21.11.2023 8.15 26.03.2024 10672341-00013 Date of first issue: 11.06.2010

aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Flammable Gas Labels

IATA (Passenger)

Packing instruction (passen-203

ger aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Labels Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

Environmentally hazardous yes

Environmentally hazardous yes

IMDG

Marine pollutant yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

plete the ozone layer

Regulation (EC) No 1005/2009 on substances that de-

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EU) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

Not applicable

: Not applicable

Not applicable

Not applicable

Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

Version Revision Date: SDS Number: Date of last issue: 21.11.2023 8.15 26.03.2024 10672341-00013 Date of first issue: 11.06.2010

of dangerous chemicals

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

Quantity 1 Quantity 2 ENVIRONMENTAL 200 t 500 t

HAZARDS

P3b FLAMMABLE AEROSOLS 5.000 t 50.000 t

34 Petroleum products: (a) 2.500 t 25.000 t

gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water hazard class (Germa-

ny)

WGK 2 obviously hazardous to water

Code Number: 9.145 Remarks: self classification

Classification according to AwSV §6(4)

TA Luft List (Germany) : 5.2.1: Total dust:

Not applicable

5.2.2: Inorganic substances in powdered form:

Not applicable

5.2.4: Inorganic substances in gaseous form:

Not applicable

5.2.5: Organic Substances:

Not applicable

5.2.7.1.1: Carcinogenic substance:

Not applicable

5.2.7.1.1: Quartz fine dust PM4:

Not applicable

5.2.7.1.1: Formaldehyde:

Not applicable 5.2.7.1.1: fibres: Not applicable

5.2.7.1.2: Germ cell mutagens:

Not applicable

5.2.7.1.3: Substances toxic to reproduction:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

Version Revision Date: SDS Number: Date of last issue: 21.11.2023 8.15 26.03.2024 10672341-00013 Date of first issue: 11.06.2010

Not applicable

5.2.7.2: Poorly degradable, easily enrichable and highly toxic

organic substances: Not applicable

Volatile organic compounds : Directive 2004/42/EC

VOC content in g/l: 785 g/l

Product sub-category: Preparatory and cleaning products

Coatings: Preparatory products VOC limit level 1 (2007): 850 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 100 %, 785 g/l

Remarks: VOC content excluding water

Regulation (EC) No. 648/2004, as amended

30 % and more: Aliphatic hydrocarbons

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated. H304 : May be fatal if swallowed and enters airways.

H336 : May cause drowsiness or dizziness.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Flam. Lig. : Flammable liquids

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

Press. Gas : Gases under pressure

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure 2006/15/EC : Europe. Indicative occupational exposure limit values

DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2006/15/EC / TWA : Limit Value - eight hours

DE DFG MAK / MAK : MAK value

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

Sheet cy, http://echa.europa.eu/

Classification of the mixture:

Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment

STOT SE 3 H336 Calculation method

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



SILICONE REMOVER - 600 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 21.11.2023

 8.15
 26.03.2024
 10672341-00013
 Date of first issue: 11.06.2010

STOT RE 1 H372 Calculation method Aquatic Chronic 2 H411 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN