

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture ADHESIVE MP 100

Registration number -

Synonyms None.

Product code UDS000282AE

Issue date 18-November-2022

Version number 1.0

Revision date 13-January-2023

Supersedes date 18-November-2022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesives

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries UK Ltd.

Address Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom

Telephone +44 1278 727200

Fax +44 1278 425644

E-mail hse.uk@crcind.com

Website www.crcind.com

Company name CRC Industries Europe bv

Address Touwslagerstraat 1
9240 Zele
Belgium

Telephone +32(0)52/45.60.11

Fax +32(0)52/45.00.34

E-mail hse@crcind.com

Website www.crcind.com

1.4. Emergency telephone number Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Carcinogenicity	Category 2	H351 - Suspected of causing cancer.

2.2. Label elements**Label according to Regulation (EC) No. 1272/2008 as amended****Contains:** dichloromethane; methylene chloride**Hazard pictograms****Signal word**

Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H351 Suspected of causing cancer.
 H336 May cause drowsiness or dizziness.

Precautionary statements**Prevention**

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P281 Use personal protective equipment as required.

Response

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.**2.3. Other hazards**

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
dichloromethane; methylene chloride	20 - 50	75-09-2 200-838-9	01-2119480404-41	602-004-00-3	#
Classification: Skin Irrit. 2;H315, Eye Irrit. 2;H319, Carc. 2;H351, STOT SE 3;H336					
butanone; ethyl methyl ketone	0 - 2.5	78-93-3 201-159-0	01-2119457290-43	606-002-00-3	#
Classification: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).
 ATE: Acute toxicity estimate.
 M: M-factor
 PBT: persistent, bioaccumulative and toxic substance.
 vPvB: very persistent and very bioaccumulative substance.
 All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.**SECTION 4: First aid measures****General information**

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.
4.2. Most important symptoms and effects, both acute and delayed	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	Extremely flammable aerosol.
5.1. Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
For emergency responders	Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers.

6.4. Reference to other sections For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
---	---

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).
Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
butanone; ethyl methyl ketone (CAS 78-93-3)	STEL	899 mg/m3
		300 ppm
	TWA	600 mg/m3
dichloromethane; methylene chloride (CAS 75-09-2)	STEL	200 ppm
		706 mg/m3
	TWA	353 mg/m3
		100 ppm

Biological limit values

UK. EH40 Biological Monitoring Guidance Values (BMGVs)

Components	Value	Determinant	Specimen	Sampling Time
butanone; ethyl methyl ketone (CAS 78-93-3)	70 umol/l	Butan-2-one	Urine	*
dichloromethane; methylene chloride (CAS 75-09-2)	30 ppm	Carbon monoxide	end-tidal breath	*

* - For sampling details, please see the source document.

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General population

Components	Value	Assessment factor	Notes
butanone; ethyl methyl ketone (CAS 78-93-3)			
Long-term, Systemic, Dermal	412 mg/kg bw/day	2	Repeated dose toxicity
Long-term, Systemic, Inhalation	106 mg/m3	2	Repeated dose toxicity

Workers

Components	Value	Assessment factor	Notes
butanone; ethyl methyl ketone (CAS 78-93-3)			
Long-term, Systemic, Dermal	1161 mg/kg bw/day	1	Repeated dose toxicity
Long-term, Systemic, Inhalation	600 mg/m3	1	Repeated dose toxicity

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
butanone; ethyl methyl ketone (CAS 78-93-3)			
Freshwater	55.8 mg/l	1	Oral
Secondary poisoning	1000 mg/kg	30	
Sediment (freshwater)	284.74 mg/kg		
Soil	22.5 mg/kg	1	

Exposure guidelines

UK EH40 WEL: Skin designation

butanone; ethyl methyl ketone (CAS 78-93-3)	Can be absorbed through the skin.
dichloromethane; methylene chloride (CAS 75-09-2)	Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
Individual protection measures, such as personal protective equipment	
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.
Skin protection	
- Hand protection	When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Butyl rubber gloves are recommended. Suitable gloves can be recommended by the glove supplier.
- Other	Wear appropriate chemical resistant clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type AX)
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Colour	Brown.
Odour	Solvent.
Odour threshold	Not available.
pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	39 °C (102.2 °F)
Flash point	None
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	1.8 %
Explosive limit – upper (%)	19 %
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	1.22 g/cm ³ 25 °C
Solubility(ies)	
Solubility (water)	Partly soluble in water
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	605 °C (1121 °F)
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2. Other information

VOC

666 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid high temperatures. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
butanone; ethyl methyl ketone (CAS 78-93-3)		
Acute		
Dermal		
LD50	Rabbit	> 8000 mg/kg
Oral		
LD50	Rat	2300 - 3500 mg/kg
dichloromethane; methylene chloride (CAS 75-09-2)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Inhalation		
LC50	Rat	76000 mg/m3, 4 h 53 mg/l, 6 h
Oral		
LD50	Rat	2136 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

dichloromethane; methylene chloride (CAS 75-09-2) 2A Probably carcinogenic to humans.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Mixture versus substance information Not available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
dichloromethane; methylene chloride (CAS 75-09-2)			
<i>Acute</i>			
Other	EC50	Pseudokirchnerella subcapitata	> 500 mg/l, 72 h
			> 500 mg/l, 96 h
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	1532 - 1847 mg/l, 48 h
			190 mg/l, 48 h
Fish	LC50	Lepomis macrochirus	193 mg/l, 96 h
		Pimephales promelas	262 - 855 mg/l, 96 h
			140.8 - 277.8 mg/l, 96 h

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

butanone; ethyl methyl ketone	0.29
dichloromethane; methylene chloride	1.25

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.
GWP: 5

Substance Global Warming Potential per (Annex IV), Regulation 517/2014/EU on fluorinated greenhouse gases, as amended

dichloromethane; methylene chloride (CAS 75-09-2)	9
---	---

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable

14.3. Transport hazard class(es)

Class 2.1
Subsidiary risk -
Label(s) 2.1
Hazard No. (ADR) Not assigned.
Tunnel restriction code D
ADR/RID - Classification 5F
code:

14.4. Packing group Not assigned.

14.5. Environmental hazards No

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.
for user

RID

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable
name

14.3. Transport hazard class(es)

Class 2.1
Subsidiary risk -
Label(s) 2.1

14.4. Packing group Not assigned.

14.5. Environmental hazards No

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.
for user

ADN

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable
name

14.3. Transport hazard class(es)

Class 2.1
Subsidiary risk -
Label(s) 2.1

14.4. Packing group Not assigned.

14.5. Environmental hazards No

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.
for user

IATA

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable
name

14.3. Transport hazard class(es)

Class 2.1
Subsidiary risk -

14.4. Packing group Not assigned.

14.5. Environmental hazards No

ERG Code 10L

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.
for user

Other information

Passenger and cargo Allowed with restrictions.
aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable
name

14.3. Transport hazard class(es)

Class 2.1
Subsidiary risk -

14.4. Packing group Not assigned.

14.5. Environmental hazards

Marine pollutant No

EmS F-D, S-U

14.6. Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

dichloromethane; methylene chloride (CAS 75-09-2)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

butanone; ethyl methyl ketone (CAS 78-93-3)

dichloromethane; methylene chloride (CAS 75-09-2)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

butanone; ethyl methyl ketone (CAS 78-93-3)

Other regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.
 CEN: European Committee for Standardization.
 CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.
 GWP: Global Warming Potential.
 IATA: International Air Transport Association.
 IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
 IMDG: International Maritime Dangerous Goods.
 MAC: Maximum Allowed Concentration.
 MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).
 MARPOL: International Convention for the Prevention of Pollution from Ships.
 PBT: Persistent, bioaccumulative and toxic.
 REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation, Authorization and Restriction of Chemicals).
 RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
 STEL: Short term exposure limit.
 TLV: Threshold Limit Value.
 TWA: Time Weighted Average.
 VLE: Exposure Limit Value.
 VME: Exposure Average Value.
 VOC: Volatile organic compounds.
 vPvB: Very persistent and very bioaccumulative.
 STEL: Short-term Exposure Limit.
 Not available.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.