


Chapter 1: Introduction





Chapter 1: Introduction

- What Operating Systems Do
- Computer-System Organization
- Computer-System Architecture
- Operating-System Operations
- Resource Management
- Security and Protection
- Virtualization
- Distributed Systems
- Kernel Data Structures
- Computing Environments
- Free/Libre and Open-Source Operating Systems





Objectives

- Describe the general organization of a computer system and the role of interrupts
- Describe the components in a modern, multiprocessor computer system
- Illustrate the transition from user mode to kernel mode
- Discuss how operating systems are used in various computing environments
- Provide examples of free and open-source operating systems





What is an Operating System?

- A program that acts as an intermediary between a user of a computer and the computer hardware
- Operating system goals:
 - Execute user programs and make solving user problems easier
 - Make the computer system convenient to use
 - Use the computer hardware in an efficient manner






Computer System Structure

- Computer system can be divided into four components:
 - Hardware – provides basic computing resources
 - 4 CPU, memory, I/O devices
 - Operating system
 - 4 Controls and coordinates use of hardware among various applications and users
 - Application programs – define the ways in which the system resources are used to solve the computing problems of the users
 - 4 Word processors, compilers, web browsers, database systems, video games
 - Users
 - 4 People, machines, other computers





Abstract View of Components of Computer





What Operating Systems Do

- Depends on the point of view
- Users want convenience, **ease of use** and **good performance**
 - Don't care about **resource utilization**
- But shared computer such as **mainframe** or **minicomputer** must keep all users happy
 - Operating system is a **resource allocator** and **control program** making efficient use of HW and managing execution of user programs
- Users of dedicated systems such as **workstations** have dedicated resources but frequently use shared resources from **servers**
- Mobile devices like smartphones and tablets are resource poor, optimized for usability and battery life
 - Mobile user interfaces such as touch screens, voice recognition
- Some computers have little or no user interface, such as embedded computers in devices and automobiles
 - Run primarily without user intervention





Operating System Definition

- No universally accepted definition
- “Everything a vendor ships when you order an operating system” is a good approximation
 - But varies wildly
- “The one program running at all times on the computer” is the **kernel**, part of the operating system
- Everything else is either
 - A **system program** (ships with the operating system, but not part of the kernel) , or
 - An **application program**, all programs not associated with the operating system
- Today’s OSES for general purpose and mobile computing also include **middleware** – a set of software frameworks that provide additional services to application developers such as databases, multimedia, graphics






Overview of Computer System Structure





Computer System Organization

- Computer-system operation
 - One or more CPUs, device controllers connect through common **bus** providing access to shared memory
 - Concurrent execution of CPUs and devices competing for memory cycles





Computer-System Operation

- I/O devices and the CPU can execute concurrently
- Each device controller is in charge of a particular device type
- Each device controller has a local buffer
- Each device controller type has an operating system **device driver** to manage it
- CPU moves data from/to main memory to/from local buffers
- I/O is from the device to local buffer of controller
- Device controller informs CPU that it has finished its operation by causing an **interrupt**






Common Functions of Interrupts

- Interrupt transfers control to the interrupt service routine generally, through the **interrupt vector**, which contains the addresses of all the service routines
- Interrupt architecture must save the address of the interrupted instruction
- A **trap** or **exception** is a software-generated interrupt caused either by an error or a user request
- An operating system is **interrupt driven**





Interrupt Timeline






Interrupt Handling

- The operating system preserves the state of the CPU by storing the registers and the program counter
- Determines which type of interrupt has occurred:
- Separate segments of code determine what action should be taken for each type of interrupt





Interrupt-drive I/O Cycle





Computer Startup

- **Bootstrap program** is loaded at power-up or reboot
 - Typically stored in ROM or EPROM, generally known as **firmware**
 - Initializes all aspects of system
 - Loads operating system kernel and starts execution





Storage Structure






Storage Hierarchy

- Storage systems organized in hierarchy
 - Speed
 - Cost
 - Volatility
- **Caching** – copying information into faster storage system; main memory can be viewed as a cache for secondary storage
- **Device Driver** for each device controller to manage I/O
 - Provides uniform interface between controller and kernel






Storage-Device Hierarchy





How a Modern Computer Works



A von Neumann architecture





Direct Memory Access Structure

- Used for high-speed I/O devices able to transmit information at close to memory speeds
- Device controller transfers blocks of data from buffer storage directly to main memory without CPU intervention
- Only one interrupt is generated per block, rather than the one interrupt per byte





Operating-System Operations

- Bootstrap program – simple code to initialize the system, load the kernel
- Kernel loads
- Starts **system daemons** (services provided outside of the kernel)
- Kernel **interrupt driven** (hardware and software)
 - Hardware interrupt by one of the devices
 - Software interrupt (**exception** or **trap**):
 - 4 Software error (e.g., division by zero)
 - 4 Request for operating system service – **system call**
 - 4 Other process problems include infinite loop, processes modifying each other or the operating system





Multiprogramming (Batch system)

- Single user cannot always keep CPU and I/O devices busy
- Multiprogramming organizes jobs (code and data) so CPU always has one to execute
- A subset of total jobs in system is kept in memory
- One job selected and run via **job scheduling**
- When job has to wait (for I/O for example), OS switches to another job






Multitasking (Timesharing)

- A logical extension of Batch systems– the CPU switches jobs so frequently that users can interact with each job while it is running, creating **interactive** computing
 - **Response time** should be < 1 second
 - Each user has at least one program executing in memory □ **process**
 - If several jobs ready to run at the same time □ **CPU scheduling**
 - If processes don't fit in memory, **swapping** moves them in and out to run
 - **Virtual memory** allows execution of processes not completely in memory





Memory Layout for Multiprogrammed System






Dual-mode Operation

- **Dual-mode** operation allows OS to protect itself and other system components
 - **User mode** and **kernel mode**
- **Mode bit** provided by hardware
 - Provides ability to distinguish when system is running user code or kernel code.
 - When a user is running ☐ mode bit is “user”
 - When kernel code is executing ☐ mode bit is “kernel”
- How do we guarantee that user does not explicitly set the mode bit to “kernel”?
 - System call changes mode to kernel, return from call resets it to user
- Some instructions designated as **privileged**, only executable in kernel mode





Transition from User to Kernel Mode





Timer

- Timer to prevent infinite loop (or process hogging resources)
 - Timer is set to interrupt the computer after some time period
 - Keep a counter that is decremented by the physical clock
 - Operating system set the counter (privileged instruction)
 - When counter zero generate an interrupt
 - Set up before scheduling process to regain control or terminate program that exceeds allotted time





Computer System Architecture






Computer-System Architecture

- Most systems use a single general-purpose processor
 - Most systems have special-purpose processors as well
- **Multiprocessors** systems growing in use and importance
 - Also known as **parallel systems**, **tightly-coupled systems**
 - Advantages include:
 1. **Increased throughput**
 2. **Economy of scale**
 3. **Increased reliability** – graceful degradation or fault tolerance
 - Two types:
 1. **Asymmetric Multiprocessing** – each processor is assigned a specific task.
 2. **Symmetric Multiprocessing** – each processor performs all tasks





Symmetric Multiprocessing Architecture





Computer System Environments





Computing Environments

- Traditional
- Mobile
- Client Server
- Peer-to-Peer
- Cloud computing
- Real-time Embedded





Traditional

- Stand-alone general-purpose machines
- But blurred as most systems interconnect with others (i.e., the Internet)
- **Portals** provide web access to internal systems
- **Network computers (thin clients)** are like Web terminals
- Mobile computers interconnect via **wireless networks**
- Networking becoming ubiquitous – even home systems use **firewalls** to protect home computers from Internet attacks





Mobile


- Handheld smartphones, tablets, etc.
- What is the functional difference between them and a “traditional” laptop?
- Extra feature – more OS features (GPS, gyroscope)
- Allows new types of apps like *augmented reality*
- Use IEEE 802.11 wireless, or cellular data networks for connectivity
- Leaders are **Apple iOS** and **Google Android**





Client Server


- Client-Server Computing
 - Dumb terminals supplanted by smart PCs
 - Many systems now **servers**, responding to requests generated by **clients**
 - 4 **Compute-server system** provides an interface to client to request services (i.e., database)
 - 4 **File-server system** provides interface for clients to store and retrieve files





Peer-to-Peer

- Another model of distributed system
- P2P does not distinguish clients and servers
 - Instead all nodes are considered peers
 - May each act as client, server or both
 - Node must join P2P network
 - 4 Registers its service with central lookup service on network, or
 - 4 Broadcast request for service and respond to requests for service via *discovery protocol*
 - Examples include Napster and Gnutella, **Voice over IP (VoIP)** such as Skype





Cloud Computing

- Delivers computing, storage, even apps as a service across a network
- Logical extension of virtualization because it uses virtualization as the base for its functionality.
 - Amazon **EC2** has thousands of servers, millions of virtual machines, petabytes of storage available across the Internet, pay based on usage





Cloud Computing (Cont.)


- Many types
 - **Public cloud** – available via Internet to anyone willing to pay
 - **Private cloud** – run by a company for the company's own use
 - **Hybrid cloud** – includes both public and private cloud components
 - Software as a Service (**SaaS**) – one or more applications available via the Internet (i.e., word processor)
 - Platform as a Service (**PaaS**) – software stack ready for application use via the Internet (i.e., a database server)
 - Infrastructure as a Service (**IaaS**) – servers or storage available over Internet (i.e., storage available for backup use)





Cloud Computing (cont.)

- Cloud computing environments composed of traditional OSes, plus VMMs, plus cloud management tools
 - Internet connectivity requires security like firewalls
 - Load balancers spread traffic across multiple applications



End of Chapter 1

