

VOLUME 0 — PROJECT FOUNDATION

CHAPTER 0.3

Glossary

Shared Vocabulary for the Entire Project

Document Title	Glossary
Chapter Reference	0.3
Version	1.0
Status	Draft — Pending Approval
Owner	Faisal — Human Archive
Prepared With	Claude (Cowork)
Date	05 August 2026
Purpose	Ensure every later volume uses these terms with exactly one meaning.

This glossary is the authoritative definition of every recurring term used across Volumes 0–12. If a later document uses one of these words differently, the later document is wrong and must be corrected — not the other way around.

1. Technical Terms

Session	One complete recording event for a task, from tapping Record to the app marking it "Complete" — may consist of multiple chunks.
Chunk	A single 10-minute (or configured-length) video segment produced by splitting a session's raw footage after recording stops.
Chunking	The local process of splitting a finished recording into fixed-length chunks; occurs after Stop, never during active recording.
Upload Queue	The ordered, locally-persisted list of chunks waiting to be uploaded, including their retry state.
Resumable Upload	An upload mechanism (S3 multipart) that can pause and continue from where it left off, instead of restarting from zero after an interruption.
Background Upload	Upload activity that continues while the collector uses another part of the app (e.g. starts a new recording) or while the app is backgrounded.
Offline-first	An architecture approach where every core action works with no network connection, and syncing to the server happens opportunistically once connectivity returns.
Local Persistence	Data (chunk files, metadata, queue state) saved on-device so it survives app restarts, crashes, and connectivity loss.
Token Refresh	The silent renewal of an authentication session token before it expires, without interrupting the collector.
SSO (Single Sign-On)	Login via an organization's existing identity provider (e.g. SAML or OAuth) instead of an app-specific password.
State Management	The architectural approach used to hold and update in-app data (e.g. recording status, upload progress) consistently across screens.
Clean Architecture	A layered code structure separating data access, business logic (domain), and UI (presentation) so each can change independently.
Repository Pattern	A code pattern that hides where data actually comes from (local database, cache, or network) behind one consistent interface.
Dependency Injection	A coding technique for supplying a component's dependencies from outside itself, making the component easier to test and swap.
Feature Flag	A remotely toggleable switch that turns a feature or configuration value on/off without releasing a new app build.
Idempotent	Describes an operation (like an upload retry) that produces the same end result no matter how many times it is repeated.

2. Business Terms

Collector	The field worker or operator who uses the mobile app to record and submit video footage.
Client	An organization or team that owns a Project and consumes the resulting dataset (may be internal or an external customer).
Project	A top-level body of work assigned to one or more Collectors, containing one or more Tasks.
Task	A specific, instructed unit of recording work within a Project, including instructions, examples, and requirements.
Dataset	The full collection of footage and metadata produced across all Sessions for a Project, used downstream for AI/ML training.

Throughput	The volume of usable recorded footage (typically hours per day/week) produced by a Collector or across the fleet.
Fleet	All active Collectors and their devices, considered collectively for monitoring and analytics purposes.
QA (Quality Assurance)	The process of reviewing collected footage/metadata against task requirements before it is accepted into the dataset.
Rework Flag	A marker placed on a Session or Chunk during QA indicating it does not meet requirements and must be re-recorded.
Admin	A user role (via the future Web Admin Dashboard) responsible for creating Projects/Tasks and monitoring the Collector fleet.

3. Dataset Terminology

Sample	One usable unit of data extracted from the dataset for training or evaluation purposes (may correspond to a chunk, clip, or frame range).
Ground Truth	The verified, correct label or reference data associated with a sample, used to train or evaluate a model.
Annotation	Metadata or labels added to footage (by a human or automated process) describing what is present in the footage.
Metadata	Structured data describing a chunk or session — timestamps, GPS location, device info, task reference, duration, and similar attributes (Volume 5.7 — Metadata Generation).
Clip	A shorter extract taken from a chunk for review, QA sampling, or reference purposes.
Frame	A single still image within a video, the smallest visual unit that can be analyzed by a computer vision model.
Dataset Completeness	The proportion of assigned Tasks that have reached fully uploaded, QA-passed status.

4. Camera Terminology

Egocentric	First-person point of view — footage captured from the perspective of the person doing the recording, rather than looking at them.
Wide-Angle Lens	A camera lens with a wider field of view than a standard lens, capturing more of the scene at the same distance.
Ultra-Wide	The widest rear camera lens available on modern smartphones (commonly used from iPhone 11 onward), used here to approximate the same field of view as an Android wide lens.
Field of View (FOV)	The extent of the observable scene captured by the camera, usually measured in degrees.
Zoom Factor (0.5x / 0.6x)	A zoom-out multiplier relative to the phone's default "1x" lens, selecting the wide or ultra-wide physical lens instead of digitally cropping.
Rear-Facing Camera	The camera on the back of the device, used for all recording in this app (the app does not use the front/selfie camera in the MVP).
Bitrate	The amount of video data encoded per second of footage; higher bitrate generally means higher quality and larger file size.
Resolution	The pixel dimensions of the recorded video (e.g. 1920x1080), independent of the lens's field of view.
Frame Rate (fps)	The number of frames captured per second of video; common values are 24, 30, or 60 fps.
Codec	The video compression format used to encode footage (e.g. H.264/AVC or H.265/HEVC), affecting file size and compatibility.

Stabilization	Software or hardware correction applied to reduce shake in handheld or body-worn footage.
----------------------	---

5. AI Terminology

Computer Vision	The field of AI concerned with extracting understanding from images and video.
Embodied AI	AI systems (often robotic) that perceive and act within a physical environment, frequently trained using egocentric data like this app collects.
Training Data	The dataset used to teach a machine learning model to perform a task.
Model	A trained system that takes input data (e.g. video frames) and produces predictions or classifications.
Occlusion Detection	An automated check for whether part of the camera's view is blocked (e.g. by a hand or object), relevant to the future in-app QA feature.
Motion-Blur Detection	An automated check for excessive blur caused by camera movement during capture, relevant to the future in-app QA feature.
Multi-Modal	Combining more than one type of data (e.g. video plus location plus device sensor data) in a single dataset or model input.
Inference	The process of running a trained model on new data to produce a prediction, as opposed to training the model itself.
Annotation Pipeline	The end-to-end process by which raw footage is turned into labeled, model-ready training data.

End of Chapter 0.3 — Glossary