

ACI-CO Repository Architecture

Colombian Actuarial Climate Index (ACI-CO) pipeline

August 11, 2026

Abstract

This document is a LaTeX companion to `ARCHITECTURE.md` and `CLAUDE.md` at the repository root. It describes how the ACI-CO codebase is organized: the scientific target it computes, the actual data flow between scripts (as opposed to the README’s idealized version), where the repository’s documentation is authoritative versus stale, and how to read already-processed outputs from a notebook (e.g. Google Colab) using the `aci_lib` data-access library introduced alongside this document. It is a description of the codebase as it stands, not a specification – where the code and the docs disagree, the code wins.

Contents

1	What this repository is	1
2	The scientific target: ACI-CO	1
2.1	Extensions beyond the base ACI framework	2
2.2	Regions actually computed	2
3	Repository layout	2
4	Actual data flow	3
4.1	Two parallel “correctness check” implementations	4
4.2	Forecasting: two families plus shared modules	5
5	Documentation status	5
6	Discrepancies between README/docstrings and reality	6
7	The git tracking gap	6
7.1	Known secrets in the repository	6
8	The <code>aci_lib</code> data-access library	7
8.1	Why it exists	7
8.2	Important caveat: data is not in git	7
8.3	Quickstart in Google Colab	7
8.4	Scope	8
9	Benchmarking the pipeline in Colab	8
9.1	Why no script changes were needed	8
9.2	<code>src/drive_sync.py</code>	8
9.3	<code>aca_opt_benchmark.ipynb</code>	9
9.4	Verified, then partially reopened: Colab vs. local reproducibility	9

9.5	aca_opt_full_replication.ipynb	10
9.6	aca_opt_multi_region_monthly.ipynb	10
9.7	Performance: decode raw grib once per year, not once per region	11
9.8	Precipitation/drought: a real correctness hazard, not just a performance gap	11

10	Cleanup priorities (standing list)	12
----	------------------------------------	----

1 What this repository is

This is a research pipeline that builds the **Colombian Actuarial Climate Index (ACI-CO)** from ERA5(-Land) reanalysis data (1961–2024): a Colombian adaptation of the Actuaries Climate Index (ACI) framework, extended with ENSO calibration, a bootstrap uncertainty band, multi-dataset robustness checks, and validation against Colombia’s national disaster registry (UNGRD).

It is an active research codebase, not a packaged library: there is no test suite, several parallel/experimental implementations of the same pipeline stage coexist deliberately, and a non-trivial share of the *working* pipeline was never committed to git (Section 7).

Authoritative methodology source. The methodology (how T90, T10, Rx5day, CDD and WP are computed; how the composite, ENSO decomposition, and bootstrap bands work) is described in `articles/aci_co_submission/article1.tex`, §3–§7 – *not* the older root-level `articles/article1.tex` (a superseded LOWESS-based draft), and not the empty stubs in `docs/methodology.md` / `docs/results.md` / `docs/zones_description.md`.

2 The scientific target: ACI-CO

The ACI-CO composite is the unweighted mean of five signed, standardized components (divided by $K = 5$; an earlier draft divided by 6 for a placeholder sea-level component, since dropped for lack of tide-gauge coverage):

Component	Meaning	Sign	Threshold
T90	Fraction of days/month with temperature above the 1961–1990 baseline 90th percentile	+	Empirical P90 per grid cell × calendar month
T10	Fraction of days/month with temperature below the baseline 10th percentile	−	Empirical P10
Rx5day	Max 5-day precipitation total per month, z -scored vs. 1961–1990 climatology	+	z -score vs. monthly climatology
CDD	Annual max consecutive dry days (<1 mm), interpolated onto the monthly axis	+	—
WP	Wind-power ($\propto U^3$) exceedance	+	Empirical P90 (current); replaces an earlier parametric $\mu + 1.28\sigma$ threshold, discarded because WP is right-skewed

2.1 Extensions beyond the base ACI framework

- **ENSO-neutral decomposition** (§4): asymmetric ARIMAX regression per component/region on Niño-3.4 ($E^+ = \max(E, 0)$, $E^- = \min(E, 0)$) plus a linear trend and $\text{AR}(p)$ errors, separating secular warming from ENSO-driven variability.
- **Bootstrap uncertainty bands** (§4.4): block-resample ($L = 12$ mo) the 1961–1990 baseline composite into $B = 500$ (national) / $B = 200$ (regional) null-model replicates, testing whether the observed trend exceeds baseline-period variability. Replaced an earlier LOWESS residual-envelope approach.
- **Multi-dataset robustness** (§5): ERA5-Land vs. ERA5 standard vs. CHIRPS.
- **UNGRD validation** (§7): negative-binomial regression of disaster counts (floods, landslides, windthrow, vegetation fires – 49,734 events, 1998–2022) on ACI-CO components.

2.2 Regions actually computed

Despite the paper conceptually discussing 5 natural regions and 32 departments, the implementation aggregates **4 units**: national (area-weighted, all of Colombia) and 3 departments chosen for insurance relevance – **Antioquia**, **Cundinamarca-Bogotá**, and **Valle del Cauca**. Shapefiles also exist for Bogotá, Medellín, Cali, San Andrés/Providencia, Pacífico, and Amazonas, but the corresponding `data/processed/anomalias_{bogota,medellin,san_andres_providencia}/` directories are empty – never populated.

3 Repository layout

Path	Contents
<code>src/scripts/</code>	The original OPT pipeline: download, percentile, and anomaly-calculation scripts (<code>calcular_*</code> , <code>ecmwf_descarga.py</code> , <code>unir_archivos.py</code> , <code>graficas.py</code> , ...). Spanish-language docstrings dominate here.
<code>src/forecast_scripts/</code>	Two independent forecasting families (AutoTS ensembles vs. SARIMAX/ETS + ENSO) plus <code>common/</code> , the shared modules extracted from both (Section 4.2). English-language, newer code.
<code>src/dashboard/</code>	<code>app.py</code> – a read-only Streamlit dashboard that reads Stage 3/5 CSVs directly; not a pipeline stage.
<code>src/utils/</code>	Shared helpers (<code>get_available_years</code> , <code>get_cached_shapefile</code>), consolidated from near-identical copies previously duplicated across the <code>calcular_*</code> scripts.
<code>src/aci_lib/</code>	Read-only data-access library for notebooks (Section 8) – added alongside this document, not part of the original OPT/forecast pipeline.
<code>data/raw/</code> , <code>data/processed/</code> <code>articles/</code>	Pipeline inputs/outputs, entirely gitignored except for <code>.gitkeep</code> placeholders (Section 7). Three papers at different stages: the current submission (<code>aci_co_submission/</code>), a superseded LOWESS draft (<code>article1.tex</code>), and a separate forecasting report (<code>AnnualICAForecast_Report.tex</code>).

Path	Contents
docs/	Mostly empty stubs (<code>methodology.md</code> , <code>results.md</code> , <code>zones_description.md</code>); the one substantive file is <code>Diccionario.md</code> , a ~2400-line data-source vetting document.
tests/	Placeholder only (<code>test.txt</code>); there is no test suite or CI.

4 Actual data flow

The README describes an idealized 8-step flow; several of the scripts it names do not exist (Section 6). The flow below is reconstructed from what the scripts actually read and write.

Stage	Script(s)	Output
0. Download	<code>ecmwf_descarga.py</code> (canonical), <code>sst_descarga.py</code> , <code>get_aux_data.py</code> , IDEAM station data via <code>pyreadr</code>	<code>data/raw/era5/*.grib</code> , SST GRIB, <code>data/raw/auxiliary/</code> , <code>data/raw/ideam/*.rds</code>
1. Merge / resample	<code>unir_archivos.py</code> ; independently, the untracked <code>run_aci_colombia.py</code> re-merges raw GRIB into a from-scratch reimplementation	<code>era5_daily_combined_{tmp,rain, wind}.nc</code> ; <code>data/processed/aci_daily/</code> , <code>aci_colombia_1961_2024.csv</code>
2. Percentiles (1961–1990 baseline)	<code>calcular_percentil_- {temperatura,lluvia, viento}.py</code>	<code>era5*_percentil.nc</code> , <code>percentiles*.csv</code>
3. Anomalies, per region	<code>calcular_anomalias_- {temperatura,lluvia, viento}.py</code> , orchestrated by <code>calcular_anomalias_- regiones.py</code> over <code>data/shapefiles/*.shp</code>	<code>data/processed/anomalias_- <region>/anomalies_{temperature, precipitation,drought, wind}_combined.csv</code> (populated: <code>antioquia</code> , <code>cali</code> , <code>colombia</code> , <code>cundinamarca_bogota</code> , <code>valle_cauca</code> ; empty: <code>bogota</code> , <code>medellin</code> , <code>san_andres_providencia</code>)
4. Daily variants	<code>produce_daily_- anomalies.py</code> , <code>append_2025_2026.py</code> (untracked)	<code>data/processed/daily_- anomalies/*.xlsx</code>
5. ENSO / SST index	<code>anomalias_sst_daily.py</code> , <code>compareenso_flags.py</code>	<code>sst_index_colombia_pacific.csv</code> , <code>enso_flag_comparison.csv</code> , validated against NOAA CPC <code>oni.ascii.txt</code>
6. Downscaling	<code>downscale_era5_- temperature.py</code> , <code>downscale_era5_tp.py</code> (RandomForest, DEM/NDVI/IDEAM)	<code>data/processed/downscaled/</code> , validated in <code>data/processed/era5_- ideam_comparison/</code>

Stage	Script(s)	Output
7. Visualization / export	<code>graficas.py</code> , <code>generate_correlation_matrices.py</code>	<code>articles/graficas/<region>/*.png</code> , xlsx exports, correlation heatmaps
8. Forecasting	Two independent families – see Section 4.2	<code>articles/graficas/forecast_*/</code>

`data/indices/` and `data/zones/` exist but are effectively empty – no script currently writes to those exact paths.

Raw ERA5 .grib backup. `data/raw/era5/*.grib` is gitignored (Section 7) and not reproduced anywhere in version control. A backup copy of these raw downloads is kept on Google Drive: <https://drive.google.com/drive/folders/17SdbsxVJYnqjPz1lS4FFZ6MowfMcHfqW>.

4.1 Two parallel “correctness check” implementations

There are effectively two independent implementations of the core ACI algorithm in this repository:

- **The OPT pipeline** (`src/scripts/calcular_*`, tracked in git, the README’s documented flow) – the original project pipeline, per-region, percentile/anomaly based.
- `run_aci_colombia.py` (untracked) – a from-scratch reimplementaion of the ACI-Python reference algorithm directly on raw GRIB, used to cross-validate the OPT pipeline’s output. `compare_aci_colombia.py` and `compare_repos.py` (also untracked) diff the two and document the algorithmic differences.

Neither is “the old version” of the other – they are independent implementations kept deliberately in sync for cross-validation, and this comparison grounds the paper’s “validation against x-ACT” discussion (§8).

4.2 Forecasting: two families plus shared modules

Two independent forecasting families exist side by side and are *not* a superset/subset of each other:

- `forecast_ica_{monthly,daily}.py` – AutoTS ensembles.
- The `ETS(X)_*` family – statsmodels SARIMAX/ETS with an ENSO exogenous regressor.

`src/forecast_scripts/common/` holds logic that was byte-identical or near-identical across these scripts before consolidation:

Module	Extracted from	Used by
<code>data_loading.py</code>	Byte-identical in <code>forecast_ica_monthly.py</code> and <code>ETS_ica_forecast.py</code>	Both, via thin same-named wrapper methods
<code>climate_index.py</code>	Near-identical in all three monthly forecasters	All three

Module	Extracted from	Used by
<code>stationarity.py</code>	Near-identical in <code>ETS_ica_forecast.py</code> / <code>ETSX_ica_forecast.py</code>	Both
<code>diagnostics.py</code> (<code>ModelError-</code> <code>Diagnostics</code>)	Moved unchanged from the old <code>error_diagnostics.py</code>	Not currently called by anything

Deliberately *not* merged (structurally parallel, not literal duplicates): the `ONIDataHandler` / `ONIDataHandlerDaily` ENSO-fetching classes, the SARIMAX+Lasso fitting methods, the AutoTS setup (same shape, different hyperparameters), and all `visualize_forecasts`-style plotting methods (4 separate implementations, each with different overlays).

5 Documentation status

Document	Status
<code>docs/methodology.md</code> , <code>docs/results.md</code> , <code>docs/zones_-</code> <code>description.md</code>	Empty stubs. Methodology lives in <code>articles/aci_co_submission/article1.tex</code> instead.
<code>docs/explicacion_-</code> <code>excel.md</code>	One truncated sentence, no body.
<code>docs/data_dictionary.md</code>	Early, incomplete fragment (HUMBOLDT-only) of <code>docs/Diccionario.md</code> .
<code>docs/Diccionario.md</code>	The real, complete data-source vetting document (~2400 lines, 20 candidate sources evaluated). Canonical over <code>data_dictionary.md</code> .
<code>README.md</code>	Describes an idealized 8-step flow; two referenced scripts do not exist.

6 Discrepancies between README/docstrings and reality

- README step 1 says to run `descargar_datos.py` – it does not exist; `ecmwf_descarga.py` is the actual entry point.
- README step 6 says to run `sealevel.py` – does not exist. `sealevel2.py` exists but does not do sea-level analysis; it is a Mann-Kendall trend + Q-Q normality check on precipitation-like series with leftover Jupyter cell markers, suggesting it was pasted from a notebook and misnamed. Sea level is not part of the current ACI-CO methodology.
- `src/scripts/earthhub_descarga.py` has a whole-file indentation error and cannot run as-is, on top of embedding a live-looking credential (Section 7.1).
- `src/scripts/display.py` is not a plotting module – it is a Greece-precipitation download script (also embeds the same credential) that produced a 562 MB `.nc` file at the repo root as a side effect.
- Stale internal docstrings/comments: `era5datasets.py` says `""compare_land_only.py""`; `get_-aux_data.py`'s header says `get_auxiliary_data.py`. Trust the filename/git path.

- `graficas_altaresolucion.py` is a 4-line dead stub.
- `ETSX_seasonal_motif_forecast.py` (the “broken two-stage Lasso→ETS” approach `ETSX_daily_ica_forecast.py`’s docstring says it replaced) has been deleted – confirmed unused before removal.
- `example_grid_search_era5.py` imports `ONIDataHandler` from `ETSX_ica_forecast.py` expecting methods that do not exist on that class – a pre-existing break, unrelated to the `forecast_scripts` modularization.
- `articles/AnnualICAForecast_Report.tex` references `scripts/daily_forecast_to_annual.py` and `scripts/ar1_vs_ets_final.py` – neither exists anywhere in the repository. Treat that report’s pipeline as documented-but-unimplemented.

7 The git tracking gap

A significant portion of the *current, more-correct* pipeline exists only in the working tree and has never been git added: `run_aci_colombia.py`, `compare_aci_colombia.py`, `compare_repos.py`, `create_region_shapefiles.py`, `probe_2025.py`, `produce_daily_anomalies.py`, `append_2025_2026.py`, `reproduce.py`, `plot_repo_anomalies.py`, and most of `articles/` (the `aci_co-submission/` folder, `produce_paper_plots.py`, `build_validation_outputs.py`, etc.).

Conversely, things that *are* committed include generated junk (`presentation.aux/log/out`, `texput.log`, `output.log`, `comparison.png`, `storm_daniel.png`, `.vs/`, `proyecto-indices/`, root-level `.nc/.csv` data files) and a `.gitignore` that was itself accidentally overwritten with a PowerShell heredoc command instead of its output.

Untracked here often means “uncommitted work in progress,” not “disposable.” Do not delete untracked files without checking which side of this split they are on.

7.1 Known secrets in the repository

Two Earth Data Hub PAT tokens are hardcoded and **committed** in `src/scripts/display.py` (line 13) and `src/scripts/earthhub_descarga.py` (line 15) – the same token, duplicated. A CDS API key also appears in `GRID_SEARCH_AND_ERA5_GUIDE.md` (line 44). These require rotation/history-scrubbing independent of any code change. New download scripts should follow the pattern in `ecmwf_descarga.py` / `sst_descarga.py`: `cdsapi.Client()` reads credentials from the user’s local `~/.cdsapirc`, nothing embedded in source.

8 The `aci_lib` data-access library

`src/aci_lib/` is a small, dependency-light Python package that turns `data/processed/` into a browsable, loadable catalog, so that already-computed pipeline outputs can be pulled into a notebook (locally or in Google Colab) without knowing the directory’s internal layout by heart.

8.1 Why it exists

`data/processed/` mixes single tabular files, single gridded NetCDF files, and long runs of per-year or per-year-month NetCDF files that really form one logical time series (e.g. 768 files under `anomalias-colombia/anomalies_temperature_1961_1.nc` through `_2024_12.nc`). `aci_lib` groups the latter automatically and exposes a uniform three-function API:

- `list_datasets()` – a `DataFrame` of every dataset name, kind, file count, and (where known) a description sourced from this document’s data-flow tables.

- `describe(name)` – the underlying file list and kind for one dataset.
- `load(name)` – returns a `pandas.DataFrame` for CSV/XLSX datasets, an `xarray.Dataset` for single or multi-file NetCDF datasets (opened lazily via `xarray.open_mfdataset`), or a file path for images/raw text files.

8.2 Important caveat: data is not in git

`data/processed/` is entirely gitignored (Section 7) – only a `.gitkeep` placeholder is tracked. A plain git clone of this repository, including in Colab, brings the *code* in `src/aci_lib/` but *not* the data it reads. The data must be supplied separately: mount it from Google Drive, upload and unzip an archive of `data/processed/`, or copy it in via any other means available in the notebook environment.

8.3 Quickstart in Google Colab

```
# 1. Get the code (data/processed/ is gitignored, so this clone
# does NOT include the data -- only src/aci_lib/).
!git clone https://github.com/<org>/aca_indice_climatico_opt-main.git
import sys
sys.path.insert(0, "/content/aca_indice_climatico_opt-main/src")

# 2. Supply the data. Pick ONE of:
# (a) mount Drive, if data/processed/ was uploaded there beforehand:
from google.colab import drive
drive.mount("/content/drive")
DATA_DIR = "/content/drive/MyDrive/aca_data/processed"

# (b) upload + unzip a local copy:
# from google.colab import files
# files.upload() # e.g. processed.zip
# !unzip -q processed.zip -d /content/aci_data
# DATA_DIR = "/content/aci_data/processed"

import aci_lib
aci_lib.set_data_dir(DATA_DIR)

# 3. Browse and load.
catalog = aci_lib.list_datasets()
catalog.head(20)

national_composite = aci_lib.load(
    "anomalias_colombia/anomalies_temperature_combined"
) # -> pandas.DataFrame

gridded_series = aci_lib.load(
    "anomalias_colombia/anomalies_temperature"
) # -> xarray.Dataset, lazily concatenated from ~768 monthly files
```

Run locally, inside a checkout of this repository, `set_data_dir()` is unnecessary: `aci_lib.get_data_dir()` walks up from `src/aci_lib/` to find the repository root (marked by `CLAUDE.md`) and locates `data/processed/` on its own.

8.4 Scope

`aci_lib` currently covers everything under `data/processed/` only – it does not reach into `articles/*/graficas/paper_figures/` (the paper’s final figures/tables) or `data/raw/`. Both are reasonable follow-up extensions if a notebook workflow needs them, but were kept out of scope to keep the catalog’s grouping logic simple and its descriptions trustworthy.

9 Benchmarking the pipeline in Colab

Unlike `aci_lib` (read-only over already-computed `data/processed/`), this capability runs the actual pipeline *stages* – Stage 1 merge/resample, Stage 2 baseline percentiles, Stage 3 anomalies – against raw ERA5 `.grib`, to see how long they take on whatever compute a given Colab session provides.

9.1 Why no script changes were needed

`unir_archivos.py`, `calcular_percentil_temperatura.py`, and `calcular_anomalias_temperatura.py` already expose plain, parameterized functions (`process_yearly_data_tmp`, `calcular_percentiles`, `procesar_anomalias_temperatura`, ...) behind a thin `__main__` CLI wrapper that just supplies default repo-relative paths. **They were already importable as a library** – calling them directly from a notebook with explicit paths works without modification. This was verified by importing `unir_archivos` and timing `process_yearly_precipitation_data` against a real local `.grib` file before writing the Colab notebook described below.

9.2 `src/drive_sync.py`

A new, small helper module (not part of `aci_lib`) for pulling data out of the shared Google Drive folder (Section 7) into this repo’s `data/` layout, for use inside Colab. That folder (My Drive/2. Datos, confirmed from the Drive UI – it is a shortcut sitting directly in My Drive root; “Indice Climatico Actuarial”, seen in Drive’s breadcrumb/location panel, is the owner’s canonical path, not where the shortcut lives) is shared with specific named collaborators, not “anyone with the link” – confirmed from its “Who has access” panel, which is also why anonymous fetching (tested with `gdown`) returns HTTP 401. So `drive_sync.sync(...)` instead copies (or symlinks) from an already-mounted `google.colab.drive`, which authenticates as whoever is logged into that Colab session.

The full structure of 2. Datos is now confirmed (via `notebooks/explore_drive_structure.ipynb` in the `aca_aci_collab` repo): `shapefiles/` is flat (48 files, matches `data/shapefiles/`); `era5/completos/` is the flat raw archive (195 files, `era5_{rain,tmp,wind}_<year>.grib` – exactly what `data/raw/era5/` expects); `era5/union/` and `era5/Combined/<date>/` hold Stage 1 merged-daily outputs (differently named, or date-versioned, respectively – not a direct copy target); `era5/percentiles_nc/<date>/` holds dated Stage 2 baseline-percentile snapshots (names *do* match `data/processed/` exactly, but picking “current” means picking a date); `salidas_colombia/` and `salidas_cundinamarca-bogota/` are each a single `.zip`, not a flat folder; and `datos_indice/` is a dated personal archive (2024-12/, 2025-06/, 2025-12/) of `anomalias_<region>` CSVs that doesn’t map onto any one local directory.

`DEFAULT_MAPPING` accordingly only covers the three unambiguous cases – `shapefiles`, `era5/completos` (nested-path keys work: `sync()` just `os.path.join`s them), and the two `salidas_*` zips, which `sync()` detects and extracts automatically rather than copying the `.zip` itself. The dated/renamed subfolders (`union/`, `Combined/`, `percentiles_nc/`, `datos_indice/`) are deliberately left out – picking a date or renaming a file is a judgment call the module does not make for you; pass an explicit `mapping=` for those.

9.3 aca_opt_benchmark.ipynb

Lives in the `aca_aci_collab` companion repo's `notebooks/`, alongside `aci_lib_quickstart.ipynb`, but clones *this* pipeline repo rather than the companion repo, since that's what has the scripts to benchmark. It fetches one year of raw temperature `.grib` (not the whole ~13 GB archive) and times Stages 1–3 against just that year, then extrapolates linearly to a full 1961–2024 (64-year) run for Stages 1 and 3. Stage 2 (baseline percentiles) is timed against the same single year purely as a computational-shape proxy – the real pipeline computes it once over the fixed 30-year 1961–1990 baseline, not once per year, so its extrapolated figure isn't meaningful; multiply the single-year Stage 2 time by roughly 30 instead.

9.4 Verified, then partially reopened: Colab vs. local reproducibility

1-year smoke test (2026-08-10, year 1985, single process): Stage 1 took 31.8s in Colab vs. 22.1s locally, Stage 2 11.7s vs. 8.8s, Stage 3 30.8s vs. 26.6s – different hardware, same order of magnitude. The computed `t_90/t_10` anomaly values matched **bit-for-bit** between the two runs (−0.436035 / −0.737441 for December 1985, identical NaN pattern for the other 11 months). An unpinned Colab environment (`xarray==2026.7.0` vs. this repo's `xarray==2024.11.0`) silently dropped the `count_hot/count_cold` columns in this run; pinning every relevant package to `requirements.txt`'s exact versions (`xarray==2024.11.0`, `cf_grib==0.9.14.1`, `rioxarray==0.18.2`, `geopandas==1.0.1`, `netCDF4==1.7.2`, `eccodes==2.39.1`) appeared to resolve it at the time.

Full run (2026-08-10, 1961–2024, 30-year baseline, use_multiprocessing=True): with the same pinned versions, the `count_hot/count_cold` columns were *still* missing, and `t_90/t_10` no longer matched exactly (max abs. diff ≈ 0.02 , mean ≈ 0.001 , against the official `salidas_colombia` reference, 768/768 rows aligned). This contradicts the smoke test's pinning-fixes-it conclusion above – either the pin silently didn't take in that session, or version pinning was never the real cause. **Leading hypothesis, not yet confirmed:** the smoke test ran with `use_multiprocessing=False`; the full run (like the real pipeline's own default) used `multiprocessing.Pool`. `calcular_anomalias_temperatura.py` keeps a module-level `_percentiles_cache` dict wrapping lazily-loaded `xr.open_dataset()` handles – a known-fragile pattern under fork-based multiprocessing, where file handles duplicated across `fork()` can behave inconsistently. Re-running Stage 3 with `use_multiprocessing=False` at full scale would confirm or rule this out; not yet done. Treat both the missing columns and the `t_90/t_10` drift as **open, unresolved** until then – do not trust downstream (composite index, multi-region) results computed with `use_multiprocessing=True` without re-checking this.

9.5 aca_opt_full_replication.ipynb

Scales `aca_opt_benchmark.ipynb` up from a 1-year smoke test to the real thing: fetches all `era5-tmp_<year>.grib` files (1961–2024) rather than one, runs Stage 1/2 over the actual 30-year 1961–1990 baseline (not a 1-year proxy), Stage 3 over the full record, and then diffs the resulting `anomalies_temperature_combined.csv` against the official `salidas_colombia` output already on Drive (fetched into a separate `_official_reference/` path so it can't be overwritten by the fresh computation) – column-by-column max/mean absolute difference, not just a visual spot-check. Expected runtime is 45–90 minutes (network fetch of ~5.5 GB plus compute); not something to run casually, but the strongest available evidence that `aca_indice_climatico_opt` genuinely works as an importable library against Drive-sourced data end to end, not just for one hand-picked year.

9.6 aca_opt_multi_region_monthly.ipynb

Extends the replication from temperature-only to all four monthly components `calcular_anomalias_regiones.py`'s existing `procesar_anomalias_region()` already orchestrates per region – temperature

(T90/T10), wind power (WP), precipitation (Rx5day), and drought (CDD) – across the four regions this repo documents as actually populated (Section 2.2: national, Antioquia, Cundinamarca-Bogotá, Valle del Cauca). No new pipeline logic; this wires already-importable functions to Drive-sourced data across three raw variables (temperature, precipitation, wind) instead of one. Expected runtime is 2.5–3.5 hours for the default 4 regions – substantially longer than the temperature-only replication, since it triples the raw data fetched and runs three anomaly calculations per region.

Two implementation details surfaced while wiring this up, both pre-existing repo quirks, not new bugs:

- `unir_archivos.py`'s three `process_yearly_*_data` functions have **inconsistent parameter order**: `process_yearly_data_tmp` and `process_yearly_precipitation_data` take `(file_path, year, variable, output_dir)`, but `process_yearly_wind_data` takes `(file_path, year, output_dir, variable)` – `output_dir` and `variable` swapped. A generic wrapper assuming one order would silently misdirect wind's output; the notebook uses small per-variable adapters instead of "fixing" the scripts' order.
- `calcular_percentil_lluvia.py`'s `calcular_percentiles()` saves `era5_lluvia_percentil.nc` (singular), but `calcular_anomalias_lluvia.py` reads `era5_lluvias_percentil.nc` (plural) – confirmed as a real, pre-existing mismatch: this repo's own `data/processed/` contains *both* filenames side by side, evidently from someone working around it manually rather than fixing the source. The notebook copies the percentile output under both names rather than silently hiding the inconsistency; fixing the actual name mismatch in the two scripts would be a reasonable, separate follow-up.

A third issue found this way was an actual bug, not a quirk, and was fixed in the source (not worked around): `calcular_anomalias_lluvia.py`'s `process_year()` selected a year's grib file with `[f for f in files if str(year) in f and f.endswith(".grib")][0]` – no variable-name filter, unlike `calcular_anomalias_temperatura.py` and `calcular_anomalias_viento.py`, which both filter further ("`tmp`" in `f` / "`wind`" in `f`). As long as `data/raw/era5/` held only rain grib this never mattered; once this notebook fetched all three variables into one directory, it started picking temperature or wind files for most years, failing with "No variable named '`tp`'". Caught live during an actual Colab run (2026-08-11); the missing "`rain`" in `f` filter was added directly to the script (matching the existing pattern in the other two), verified against real data before pushing. The already-published `salidas_colombia` reference was unaffected (768/768 rows present, confirmed by row count) – it was evidently computed back when `data/raw/era5/` held only rain grib, before temperature/wind were added.

9.7 Performance: decode raw grib once per year, not once per region

The first version of this notebook called `procesar_anomalias_region()` once per region, and each call independently re-decoded the same raw grib from scratch – 4 regions × 3 variables × 64 years = 768 redundant grib-decode passes, identical until the final shapefile clip – understandably frustrating given how long a run was taking, since multiprocessing across years does not fix redundant work, and GPU/TPU runtimes provide *zero* benefit here (nothing in this stack – `xarray/cfgrib/ pandas` – is CUDA-aware).

Temperature and wind both expose a clean split – `load_annual_grid_data / load_annual_grid_data_safe` take an *optional* `shapefile_path`, decoding unclipped data when it's `None` – so the notebook now decodes each year once and clips that one decode to all 4 regions via plain `rioxarray` (`.rio.write_crs(...).rio.clip(...)`), calling `calcular_anomalias/calcular_anomalias_viento` per region-month against the shared decode. Multiprocessing still parallelizes over years (unchanged from before), so this combines with, not replaces, the existing 7-worker parallelism. **Verified bit-for-**

bit identical against the original per-region code path (year 1985, Colombia, both temperature and wind) before shipping – same values, roughly a 4x reduction in redundant decode work.

9.8 Precipitation/drought: a real correctness hazard, not just a performance gap

Precipitation is *not* sped up the same decode-once way temperature and wind are, and drought could not safely be either, for a reason more serious than "not yet done": `calcular_anomalias_lluvia.py`'s `calcular_interpolacion()` (the CDD/drought calculation) reads the **previous year's** saved `datos_maximos_{year-1}.nc` to compute the current year's value, and writes its own for the next year – a sequential, year-over-year dependency. `procesar_anomalias_lluvia()`'s own default is `use_multiprocessing=True`, parallelizing over years via `multiprocessing.Pool` – which does not guarantee execution order. Any year whose predecessor has not yet been written when it runs silently falls back to a cruder approximation (except `FileNotFoundError` in `calcular_interpolacion`) instead of the proper interpolation. **This is a pre-existing risk in this script's own default behavior, not something introduced by this notebook** – and it is plausible, not yet confirmed, that some official reference output was affected, since `use_multiprocessing=True` is the default a plain call would use.

(`load_grid_data`'s `shapefile` parameter was still made properly optional – its docstring already said "if a shapefile is provided, clips the data," but the implementation clipped unconditionally with no `None` guard. That part was a real, narrow, worth-fixing gap; the CDD ordering issue is a different, larger one.)

Given that, `aca_opt_multi_region_monthly.ipynb` parallelizes precipitation/drought across **regions** instead of years: each region gets its own worker process running `procesar_anomalias_lluvia(..., use_multiprocessing=False)` – sequential and therefore correct within that region – with up to 4 regions running concurrently. Real parallelism (up to 4x, one region per core) without touching the ordering question above. Verified by calling the worker function directly (not through `Pool`, since Windows' `spawn` multiprocessing model does not reliably reflect Colab's Linux `fork` model for local testing) against two regions – distinct, plausible output for both, no cross-region collisions.

This leaves the CDD ordering issue itself unresolved – a legitimate follow-up would be making `calcular_interpolacion` not depend on sequential file I/O at all (e.g. computing each year's raw dry-day count independently and doing the cross-year blend as a separate, explicitly ordered pass), which is a real redesign, not something to bundle into a performance-motivated notebook change.

This changes performance only for temperature/wind, and the region- vs. year-level parallelization choice only for precipitation/drought – the open multiprocessing-correctness question from Section 9.4 (the `count_hot/count_cold` and `t_90/t_10` drift, specific to temperature) is unaffected by any of this and remains open regardless of which version of this notebook is run.

10 Cleanup priorities (standing list)

Ordered roughly by urgency/impact; see `ARCHITECTURE.md` for the canonical, living version of this list.

1. **Secrets**: rotate the Earth Data Hub PAT tokens and the CDS key (Section 7.1); scrub from git history if the two committed copies need to be fully removed.
2. **Commit the real pipeline**: the untracked files listed in Section 7.
3. **Purge committed generated junk**: build artifacts and data files committed at the repo root instead of under `data/`.
4. **Fix .gitignore**: currently wraps the real ignore rules in a literal PowerShell heredoc command that got committed instead of its output.

5. **Delete disk-only bloat** (not committed, safe to remove locally): environment archives, unrelated test data, `__pycache__`/.
6. **Consolidate duplicated helpers** into `src/utils/` (mostly done – see `get_available_years`, `get_cached_shapefile`).
7. **Resolve naming/content mismatches**: `display.py`, `sealevel2.py`, stale internal docstrings.
8. **Decide the fate of superseded scripts**: `graficas_altaresolucion.py`, `docs/data_dictionary.md`, root `articles/article1.tex`.
9. **Fill or drop the empty doc stubs** in `docs/`.
10. **Populate or drop** the empty `data/processed/anomalias_{bogota,medellin,san_andres_providencia}/` directories and the unused `data/indices/`, `data/zones/` locations.

Confirm scope with a maintainer before acting on any of these – several things that look like dead scratch code are load-bearing work that simply never got committed (Section 7).