Lab Guide 2

Pods:

Q.1 Create a Pod using httpd image and name of POD should be pod1.

Q.2 Create a Pod using nginx image and name of POD should be pod2.

Q.3 Create a Pod using yaml method, and use nginx image and name of POD should be yamlpod1.

Q.4 Create a Pod using yaml method, and use mdhack/myserver image and name of POD should be yamlpod2

Ans: 1

kubectl run pod1 --image httpd

kubectl get pods

```
root@master:~# kubectl run pod1 --image  httpd
pod/pod1 created
```

```
root@master:~# kubectl get pods
NAME                      READY   STATUS    RESTARTS   AGE
mayank-6c949d7dc7-64pzk   1/1     Running   0          3m11s
pod1                      1/1     Running   0          28s
root@master:~#
```

Ans: 2

kubectl run pod2 --image nginx

kubectl get pods pod2

```
root@master:~# kubectl run pod2 --image  nginx
pod/pod2 created
root@master:~# kubectl get pods pod2
NAME    READY   STATUS    RESTARTS   AGE
pod2    1/1     Running   0          7s
root@master:~#
```

Ans 3:

kubectl run yamlpod1 --image nginx --dry-run -o yaml

kubectl run yamlpod1 --image nginx --dry-run -o yaml > pod1.yaml

cat pod1.yaml

kubectl create -f pod1.yaml

kubectl get pods

```
root@master:~# kubectl run yamlpod1 --image nginx --dry-run  -o yaml
W0503 16:53:02.360955    8624 helpers.go:636] --dry-run is deprecated and can be replaced with --dry-run=client.
apiVersion: v1
kind: Pod
metadata:
  creationTimestamp: null
  labels:
    run: yamlpod1
  name: yamlpod1
spec:
  containers:
  - image: nginx
    name: yamlpod1
    resources: {}
  dnsPolicy: ClusterFirst
  restartPolicy: Always
status: {}
root@master:~# kubectl run yamlpod1 --image nginx --dry-run  -o yaml  > pod1.yaml
W0503 16:53:09.096610    8665 helpers.go:636] --dry-run is deprecated and can be replaced with --dry-run=client.
root@master:~# cat pod1.yaml
apiVersion: v1
kind: Pod
metadata:
  creationTimestamp: null
  labels:
    run: yamlpod1
  name: yamlpod1
spec:
  containers:
  - image: nginx
    name: yamlpod1
    resources: {}
  dnsPolicy: ClusterFirst
  restartPolicy: Always
status: {}
root@master:~# kubectl create  -f pod1.yaml
pod/yamlpod1 created
```

```
root@master:~# kubectl get pods yamlpod1
NAME       READY   STATUS    RESTARTS   AGE
yamlpod1   1/1     Running   0          3m21s
root@master:~# kubectl get pods
NAME                        READY   STATUS    RESTARTS   AGE
mayank-6c949d7dc7-64pzk     1/1     Running   0          10m
pod1                        1/1     Running   0          7m27s
pod2                        1/1     Running   0          5m44s
yamlpod1                    1/1     Running   0          3m21s
```

Ans: 4

kubectl run yamlpod2 --image mdhack/myserver --dry-run -o yaml

kubectl run yamlpod2 --image mdhack/myserver --dry-run -o yaml > pod2.yaml

cat pod2.yaml

kubectl create -f pod2.yaml

kubectl get pods

```
root@master:~# kubectl run yamlpod2 --image mdhack/myserver  --dry-run  -o yaml
W0503 16:57:55.412383    9943 helpers.go:636] --dry-run is deprecated and can be replaced with --dry-run=client.
apiVersion: v1
kind: Pod
metadata:
  creationTimestamp: null
  labels:
    run: yamlpod2
  name: yamlpod2
spec:
  containers:
  - image: mdhack/myserver
    name: yamlpod2
    resources: {}
  dnsPolicy: ClusterFirst
  restartPolicy: Always
status: {}
root@master:~# kubectl run yamlpod2 --image mdhack/myserver  --dry-run  -o yaml  > pod2.yaml
W0503 16:58:00.262563    9980 helpers.go:636] --dry-run is deprecated and can be replaced with --dry-run=client.
root@master:~# cat pod2.yaml
apiVersion: v1
kind: Pod
metadata:
  creationTimestamp: null
  labels:
    run: yamlpod2
  name: yamlpod2
spec:
  containers:
  - image: mdhack/myserver
    name: yamlpod2
    resources: {}
  dnsPolicy: ClusterFirst
  restartPolicy: Always
status: {}
root@master:~# kubectl create  -f pod2.yaml
pod/yamlpod2 created
```

```
root@master:~# kubectl get pods
NAME                        READY   STATUS    RESTARTS   AGE
mayank-6c949d7dc7-64pzk     1/1     Running   0          12m
pod1                        1/1     Running   0          9m48s
pod2                        1/1     Running   0          8m5s
yamlpod1                    1/1     Running   0          5m42s
yamlpod2                    1/1     Running   0          51s
root@master:~# kubectl get pods yamlpod2
NAME       READY   STATUS    RESTARTS   AGE
yamlpod2   1/1     Running   0          53s
root@master:~#
```

<u>Clean up your Environment</u>

kubectl delete all --all –force

kubectl get pods

```
root@master:~# kubectl delete  all --all --force
warning: Immediate deletion does not wait for confirmation that the running resource has been terminated. The resource may continue to run on the clu
ster indefinitely.
pod "mayank-6c949d7dc7-64pzk" force deleted
pod "pod1" force deleted
pod "pod2" force deleted
pod "yamlpod1" force deleted
pod "yamlpod2" force deleted
service "mayank" force deleted
deployment.apps "mayank" force deleted
replicaset.apps "mayank-6c949d7dc7" force deleted
root@master:~# kubectl get pods
No resources found in learning namespace.
root@master:~#
```