Implementation Guide for CDA Release 2 ONC/HL7/IHE Consolidation Project Results Section (working draft)



DRAFT: FOR DEVELOPMENT USE ONLY (Consolidated Developer Documentation)

2 Implementation Guide for CDA Release 2 Introduction						

Contents

Ackn	owledgments	5
Cons	olidated Results	7
	Diagnostic Results Section	
	Procedure	
	Result	.10
	External Reference	. 12
CCD	Results	13
	Results Section	. 13
	Result Organizer	14
	Result Observation	

4 Implementation Guide for CDA Release 2 TOC

Acknowledgments

©2010 ANSI. This material may be copied without permission from ANSI only if and to the extent that the text is not altered in any fashion and ANSI's copyright is clearly noted.

SNOMED CT® is the registered trademark of the International Health Terminology Standard Development Organization (IHTSDO).

This material contains content from LOINC® (http://loinc.org). The LOINC table, LOINC codes, and LOINC panels and forms file are copyright © 1995-2010, Regenstrief Institute, Inc. and the Logical Observation Identifiers Names and Codes (LOINC) Committee and available at no cost under the license at http://loinc.org/terms-of-use.

Certain materials contained in this Interoperability Specification are reproduced from Health Level Seven (HL7) HL7 Implementation Guide: CDA Release 2 – Continuity of Care Document (CCD), HL7 Implementation Guide for CDA Release 2: History and Physical (H&P) Notes, HL7 Implementation Guide for CDA Release 2: Consult Notes, or HL7 Implementation Guide for CDA Release 2: Operative Notes with permission of Health Level Seven, Inc. No part of the material may be copied or reproduced in any form outside of the Interoperability Specification documents, including an electronic retrieval system, or made available on the Internet without the prior written permission of Health Level Seven, Inc. Copies of standards included in this Interoperability Specification may be purchased from the Health Level Seven, Inc. Material drawn from these standards is credited where used.


6 Implementation Guide for CDA Release 2 Acknowledgments						
DRAFT HHS CONFIDENTIAL						

Consolidated Results

Diagnostic Results Section

[Section: templateId 2.16.840.1.113883.3.88.11.83.122]

This CCD diagram will be updated to show all consolidated constraints from IHE and HITSP.



The Diagnostic Results Section contains information about the results from diagnostic procedures the patient received.

- 1. SHALL conform to CDA Section
- **2. SHALL** conform to *IHE Coded Results Section* template (templateId: 1.3.6.1.4.1.19376.1.5.3.1.3.28)
- **3.** [IHE] **SHALL** contain [1..1] code/@code = "30954-2" *STUDIES SUMMARY* (CodeSystem: 2.16.840.1.113883.6.1 LOINC STATIC)
- 4. [IHE] SHALL contain [1..*] procedureEntry, such that it
 - a. contains IHE Procedure Entry
- 5. [IHE] **SHOULD** contain [1..*] entry, such that it
 - a. contains IHE External Reference (templateId: 1.3.6.1.4.1.19376.1.5.3.1.4.4)
- **6.** [IHE] **MAY** contain [0..*] entry, such that it
 - **a.** contains *IHE Simple Observation* (templateId: 1.3.6.1.4.1.19376.1.5.3.1.4.13)
- 7. [HITSP] **SHALL** contain [1..*] entry, such that it
 - **a.** contains *HITSP Procedure* (templateId: 2.16.840.1.113883.3.88.11.83.17) (C83-[CT-122-2])
- 8. [HITSP] SHALL contain [1..*] entry, such that it
 - **a.** contains *HITSP Result* (templateId: 2.16.840.1.113883.3.88.11.83.15) (C83-[CT-122-2])

```
<?xml version="1.0" encoding="UTF-8"?>
<ClinicalDocument xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="urn:hl7-org:v3" xsi:schemaLocation="urn:hl7-org:v3 CDA.xsd">
        <component>
```

```
<structuredBody>
      <component>
        <section>
          <templateId root="1.3.6.1.4.1.19376.1.5.3.1.3.28"</pre>
 assigningAuthorityName="IHE Coded Results Section"/>
          <templateId root="2.16.840.1.113883.3.88.11.83.122"</pre>
 assigningAuthorityName="HITSP Diagnostic Results Section"/>
          <code code="30954-2" codeSystem="2.16.840.1.113883.6.1"</pre>
 codeSystemName="LOINC" displayName="STUDIES SUMMARY"/>
          <title>STUDIES SUMMARY</title>
          <entry>
            <templateId root="2.16.840.1.113883.10.20.1.29"/>
              <templateId root="1.3.6.1.4.1.19376.1.5.3.1.4.19"/>
              <templateId root="2.16.840.1.113883.3.88.11.83.17"</pre>
 assigningAuthorityName="HITSP Procedure"/>
              <id root="86c1463f-526e-42b6-ad9b-d0d0cd31aa3f"/>
              <code/>
              <text/>
              <statusCode code="completed"/>
              <effectiveTime>
                <low value="1972"/>
                <high value="2008"/>
              </effectiveTime>
              <approachSiteCode/>
              <targetSiteCode codeSystem="2.16.840.1.113883.6.96"</pre>
 codeSystemName="SNOMEDCT"/>
            </procedure>
          </entry>
          <entry>
            <observation classCode="OBS" moodCode="EVN">
              <templateId root="2.16.840.1.113883.10.20.1.31"</pre>
 assigningAuthorityName="CCD Result Observation"/>
              <templateId root="1.3.6.1.4.1.19376.1.5.3.1.4.13"</pre>
 assigningAuthorityName="IHE Simple Observation"/>
              <templateId root="2.16.840.1.113883.3.88.11.83.15"</pre>
 assigningAuthorityName="HITSP Result"/>
              <id root="1d186cd1-8285-4b05-8abd-084214b1cb8d"/>
              <code/>
              <statusCode code="completed"/>
              <effectiveTime>
                <low value="1972"/>
                <high value="2008"/>
              </effectiveTime>
              <interpretationCode/>
              <methodCode/>
            </observation>
          </entry>
        </section>
      </component>
    </structuredBody>
  </component>
</ClinicalDocument>
```

Figure 1: Diagnostic Results Section example

Procedure

[Procedure: templateId 2.16.840.1.113883.3.88.11.83.17]

Defines a coded entry describing a procedure performed on a patient.

1. SHALL conform to *IHE Procedure Entry*

- 2. SHALL conform to CCD Procedure Activity
- 3. SHALL conform to CDA Clinical Statement
- 4. SHALL conform to CDA Procedure
- **5. SHALL** conform to *CCD Procedure Activity Procedure* template (templateId: 2.16.840.1.113883.10.20.1.29)
- **6. SHALL** conform to *IHE Procedure Entry Procedure Activity Procedure* template (templateId: 1.3.6.1.4.1.19376.1.5.3.1.4.19)
- 7. [CDA] Contains [1..1] @classCode, where its data type is ActClass
- 8. [CDA] Contains [1..1] @moodCode, where its data type is x_DocumentProcedureMood
- 9. [IHE] SHALL contain [1..*] id
- 10. [IHE] SHALL contain [1..1] statusCode
 - The <statusCode> element shall be present when used to describe a procedure event. It shall have the value 'completed' for procedures that have been completed, and 'active' for procedures that are still in progress. Procedures that were stopped prior to completion shall use the value 'aborted', and procedures that were cancelled before being started shall use the value 'cancelled'.
- 11. [IHE] SHOULD contain [1..1] effectiveTime
- 12. [IHE] SHALL contain [1..1] code
 - Contains a code describing the type of procedure.
- 13. [IHE] MAY contain [0..*] approachSiteCode
 - This element may be present to indicate the procedure approach.
- **14.** [HITSP] **SHOULD** contain [1..1] targetSiteCode, which **SHOULD** be selected from ValueSet 2.16.840.1.113883.3.88.12.3221.8.9 Body Site Value Set STATIC 2 (C83-[DE-17-CDA-3])
- 15. [IHE] SHALL contain [1..1] text
- 16. [IHE] SHALL satisfy: The <text> element shall contain a reference to the narrative text describing the procedure.
 - [OCL]: not self.text.reference.oclIsUndefined()
- **17.** [IHE] **MAY** satisfy: entryRelationship with typeCode='COMP' may be present to point to the encounter in which the procedure was performed, and shall contain an internal reference to the encounter.
- **19.** [HITSP] **SHOULD** satisfy: The code/@code attribute is present.
 - [OCL]: not self.code.code.oclIsUndefined()
- **20.** [HITSP] **SHALL** satisfy: The code/originalText/reference/@value is present.
 - [OCL]: not self.code.originalText.reference.value.oclIsUndefined()
- **21.** [HITSP] **SHOULD** satisfy: Contains the procedure provider in performer / assignedEntity.
 - [OCL]: self.performer->forAll(perf : cda::Performer2 | not perf.oclIsUndefined() and perf.assignedEntity->size() > 0)

```
<code/>
              <text/>
              <statusCode code="completed"/>
               <effectiveTime>
                <low value="1972"/>
                <high value="2008"/>
              </effectiveTime>
               <approachSiteCode/>
              <targetSiteCode codeSystem="2.16.840.1.113883.6.96"</pre>
 codeSystemName="SNOMEDCT"/>
            </procedure>
          </entry>
        </section>
      </component>
    </structuredBody>
  </component>
</ClinicalDocument>
```

Figure 2: Procedure example

Result

```
[Observation: templateId 2.16.840.1.113883.3.88.11.83.15]
```

This module contains current and relevant historical result observations for the patient. The scope of "observations" is broad with the exception of "vital signs" which are contained in the Vital Signs section.

- 1. SHALL conform to *IHE Simple Observation* template (templateId: 1.3.6.1.4.1.19376.1.5.3.1.4.13)
- 2. SHALL conform to CDA Clinical Statement
- 3. SHALL conform to CDA Observation
- **4. SHALL** conform to *CCD Result Observation* template (templateId: 2.16.840.1.113883.10.20.1.31)
- 5. [CDA] Contains [1..1] @classCode, where its data type is ActClassObservation
- **6.** [CCD] **SHALL** contain [1..1] @moodCode = "EVN" (CONF-408)
- 7. [CCD] **SHALL** contain [1..*] id (CONF-409)
- 8. [CCD] SHALL contain [1..1] statusCode (CONF-410)
- 9. [HITSP] SHALL contain [1..1] code
- 10. [HITSP] SHALL contain [1..1] effectiveTime
- 11. [CCD] MAY contain [0..1] methodCode (CONF-414)
 - Included if the method isn't inherent in code or if there is a need to further specialize the method in code.
- **12.** [CCD] **SHOULD** contain [0..*] interpretationCode (CONF-418)
 - Can be used to provide a rough qualitative interpretation of the observation, such as 'N' (normal), 'L' (low), 'S' (susceptible), etc. Interpretation is generally provided for numeric results where an interpretation range has been defined, or for antimicrobial susceptibility test interpretation.
- 13. [HITSP] SHALL contain [1..1] value
 - The Result value records the desired result in a goal or recorded event, and will not present when recording an intent, request or proposal to measure a result.
- **14.** [CCD] **SHOULD** satisfy: The value for 'code' SHOULD be selected from LOINC (codeSystem 2.16.840.1.113883.6.1) or SNOMED CT (codeSystem 2.16.840.1.113883.6.96), and MAY be selected from CPT-4 (codeSystem 2.16.840.1.113883.6.12). (CONF-413)
- 15. [CCD] SHALL satisfy: The methodCode SHALL NOT conflict with the method inherent in code (CONF-415)
- **16.** [CCD] **SHALL** satisfy: Where value is a physical quantity, the unit of measure SHALL be expressed using a valid Unified Code for Units of Measure (UCUM) expression. (CONF-417)
- **17.** [CCD] **SHOULD** satisfy: Contain one or more referenceRange to show the normal range of values for the observation result (CONF-419)
 - [OCL]: not self.referenceRange->isEmpty()

- **18.** [CCD] **SHALL** satisfy: SHALL NOT contain referenceRange / observationRange / code, as this attribute is not used by the HL7 Clinical Statement or Lab Committee models. (CONF-420)
 - [OCL]: self.referenceRange->forAll(range : cda::ReferenceRange | range.observationRange.code.code.oclIsUndefined())
- 19. [CCD] SHALL satisfy: Contains one or more sources of information. (CONF-421)

```
• [OCL]: not self.informant->isEmpty()
or not self.getSection().informant->isEmpty()
or not self.getClinicalDocument().informant->isEmpty()
or self.reference->exists(ref : cda::Reference | ref.typeCode =
    vocab::x_ActRelationshipExternalReference::XCRPT)
or (self.entryRelationship->exists(rel : cda::EntryRelationship |
    rel.typeCode = vocab::x_ActRelationshipEntryRelationship::REFR
    and rel.observation.code.code = '48766-0'))
```

- **20.** [HITSP] **SHOULD** satisfy: Result Type SHOULD be selected from LOINC (codeSystem 2.16.840.1.113883.6.1) or SNOMED CT (codeSystem 2.16.840.1.113883.6.96) (C154-[DE-15.03-1])
- **21.** [HITSP] **SHOULD** satisfy: Result Type for laboratory results SHOULD be coded as specified in HITSP/C80 Section 2.2.3.6.1 Laboratory Observations. (C154-[DE-15.03-2])
- **22.** [HITSP] **SHALL** satisfy: Result Value SHALL be present when the observation/@moodCode is EVN or GOL, and SHALL NOT be present when observation/@moodCode is INT or PRP. (C83-[DE-15.05-CDA-1])

```
(OCL]: (self.moodCode = vocab::x_ActMoodDocumentObservation::EVN or
self.moodCode = vocab::x_ActMoodDocumentObservation::EVN)
  implies (not self.value->isEmpty()) and
  (self.moodCode = vocab::x_ActMoodDocumentObservation::INT or
  self.moodCode = vocab::x_ActMoodDocumentObservation::PRP)
  implies (self.value->isEmpty())
```

```
<?xml version="1.0" encoding="UTF-8"?>
<ClinicalDocument xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"</pre>
xmlns="urn:hl7-org:v3" xsi:schemaLocation="urn:hl7-org:v3 CDA.xsd">
  <component>
    <structuredBody>
      <component>
        <section>
          <entry>
            <observation classCode="OBS" moodCode="EVN">
              <templateId root="2.16.840.1.113883.10.20.1.31"</pre>
 assigningAuthorityName="CCD Result Observation"/>
              <templateId root="1.3.6.1.4.1.19376.1.5.3.1.4.13"</pre>
 assigningAuthorityName="IHE Simple Observation"/>
              <templateId root="2.16.840.1.113883.3.88.11.83.15"</pre>
 assigningAuthorityName="HITSP Result"/>
              <id root="2a072630-9878-47eb-b807-f06ca2f67da4"/>
              <code/>
              <statusCode code="completed"/>
              <effectiveTime>
                <low value="1972"/>
                 <high value="2008"/>
              </effectiveTime>
              <interpretationCode/>
              <methodCode/>
            </observation>
          </entry>
        </section>
      </component>
    </structuredBody>
  </component>
</ClinicalDocument>
```

Figure 3: Result example

External Reference

[Act: templateId 1.3.6.1.4.1.19376.1.5.3.1.4.4]

- 1. SHALL conform to CDA Clinical Statement
- 2. SHALL conform to CDA Act
- **3.** [IHE] **SHALL** contain [1..1] @classCode = "ACT"
- **4.** [IHE] **SHALL** contain [1..1] @moodCode = "EVN"
- 5. [CDA] Contains [1..1] code, where its data type is CD


```
<?xml version="1.0" encoding="UTF-8"?>
<ClinicalDocument xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"</pre>
xmlns="urn:hl7-org:v3" xsi:schemaLocation="urn:hl7-org:v3 CDA.xsd">
 <component>
   <structuredBody>
      <component>
        <section>
          <entry>
            <act classCode="ACT" moodCode="EVN">
              <templateId root="1.3.6.1.4.1.19376.1.5.3.1.4.4"</pre>
assigningAuthorityName="IHE External Reference"/>
            </act>
          </entry>
        </section>
      </component>
    </structuredBody>
 </component>
</ClinicalDocument>
```

Figure 4: External Reference example

CCD Results

Results Section

[Section: templateId 2.16.840.1.113883.10.20.1.14]



This section contains the results of observations generated by laboratories, imaging procedures, and other procedures. The scope includes hematology, chemistry, serology, virology, toxicology, microbiology, plain x-ray, ultrasound, CT, MRI, angiography, cardiac echo, nuclear medicine, pathology, and procedure observations. The section may contain all results for the period of time being summarized, but should include notable results such as abnormal values or relevant trends.

Lab results are typically generated by laboratories providing analytic services in areas such as chemistry, hematology, serology, histology, cytology, anatomic pathology, microbiology, and/or virology. These observations are based on analysis of specimens obtained from the patient, submitted to the lab.

Imaging results are typically generated by a clinician reviewing the output of an imaging procedure, such as where a cardiologist reports the left ventricular ejection fraction based on the review of a cardiac echo.

Procedure results are typically generated by a clinician wanting to provide more granular information about component observations made during the performance of a procedure, such as where a gastroenterologist reports the size of a polyp observed during a colonoscopy.

- 1. SHALL conform to CDA Section
- 2. [CCD] SHALL contain [1..1] code/@code = "30954-2" Relevant diagnostic tests and/or laboratory data (CodeSystem: 2.16.840.1.113883.6.1 LOINC STATIC) (CONF-389)
- **3.** [CCD] **SHALL** contain [1..1] title (CONF-391)
- 4. [CCD] SHOULD contain [1..*] entry, such that ita. contains CCD Result Organizer (templateId: 2.16.840.1.113883.10.20.1.32) (CONF-388)
- **5.** [CCD] **SHALL** contain [1..1] text (CONF-388)

```
<structuredBody>
      <component>
        <section>
          <templateId root="2.16.840.1.113883.10.20.1.14"</pre>
 assigningAuthorityName="CCD Results Section"/>
          <code code="30954-2" codeSystem="2.16.840.1.113883.6.1"</pre>
 codeSystemName="LOINC" displayName="Relevant diagnostic tests and/or
 laboratory data"/>
          <title>Relevant diagnostic tests and/or laboratory data</title>
          <entry>
            <organizer moodCode="EVN">
              <templateId root="2.16.840.1.113883.10.20.1.32"</pre>
 assigningAuthorityName="CCD Result Organizer"/>
              <id root="d27aae29-c29e-44c9-8dff-68c7336892cf"/>
              <code/>
              <statusCode/>
            </organizer>
          </entry>
        </section>
      </component>
    </structuredBody>
  </component>
</ClinicalDocument>
```

Figure 5: Results Section example

Result Organizer

[Organizer: templateId 2.16.840.1.113883.10.20.1.32]

The result organizer identifies an observation set, contained with the result organizer as a set of result observations. It contains information applicable to all of the contained result observations.

Results in ASTM CCR and CCD are structured similarly to the HL7 Version 2 ORU Observation message, where there is an outer result organizer (templateId 2.16.840.1.113883.10.20.1.32), analogous to the HL7 Version 2 OBR Observation Result Segment, which contains one or more result observations (templateId 2.16.840.1.113883.10.20.1.31), analogous to the HL7 Version 2 OBX Observation/Result Segment.

- 1. SHALL conform to CDA Clinical Statement
- 2. SHALL conform to CDA Organizer
- 3. [CDA] Contains [1..1] @classCode, where its data type is x_ActClassDocumentEntryOrganizer
- **4.** [CCD] **SHALL** contain [1..1] @moodCode = "EVN" (CONF-394)
- 5. [CCD] SHALL contain [1..1] statusCode (CONF-396)
- **6.** [CCD] **SHALL** contain [1..*] component, such that it
 - **a.** contains *CCD Result Observation* (templateId: 2.16.840.1.113883.10.20.1.31) (CONF-405)
- 7. [CCD] SHOULD contain [1..*] specimen, such that it
 - a. contains CDA Specimen (CONF-399)
 - Should be included if the specimen isn't inherent in code value.
- **8.** [CCD] **SHALL** contain [1..*] id (CONF-395)
- **9.** [CCD] **SHALL** contain [1..1] code (CONF-397)
- 10. [CCD] SHOULD satisfy: The value for 'code' in a result organizer SHOULD be selected from LOINC (codeSystem 2.16.840.1.113883.6.1) or SNOMED CT (codeSystem 2.16.840.1.113883.6.96), and MAY be selected from CPT-4 (codeSystem 2.16.840.1.113883.6.12) or ValueSet 2.16.840.1.113883.1.11.20.16 ResultTypeCode STATIC. (CONF-398)
- 11. [CCD] **SHALL** satisfy: The specimen element SHALL NOT conflict with the specimen inherent in code (CONF-400)
- **12.** [CCD] **SHOULD** satisfy: specimen / specimenRole / id SHOULD be set to equal a Procedure / specimen / specimenRole / id to indicate that the Results and the Procedure are referring to the same specimen. (CONF-401)

- **13.** [CCD] **SHALL** satisfy: Contains one or more component (CONF-402)
 - [OCL]: not self.component->isEmpty()
- **14.** [CCD] **MAY** satisfy: The target of one or more result organizer component relationships MAY be a procedure, to indicate the means or technique by which a result is obtained, particularly if the means or technique isn't inherent in code or if there is a need to further specialize the code value. (CONF-403)
- **15.** [CCD] **MAY** satisfy: A result organizer component / procedure MAY be a reference to a procedure described in the Procedure section. (CONF-404)
- 16. [CCD] SHALL satisfy: Contains one or more sources of information. (CONF-406)

```
[OCL]: not self.informant->isEmpty()
    or not self.getSection().informant->isEmpty()
    or not self.getClinicalDocument().informant->isEmpty()
    or self.reference->exists(ref : cda::Reference | ref.typeCode =
     vocab::x_ActRelationshipExternalReference::XCRPT)
<?xml version="1.0" encoding="UTF-8"?>
<ClinicalDocument xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"</pre>
xmlns="urn:hl7-org:v3" xsi:schemaLocation="urn:hl7-org:v3 CDA.xsd">
  <component>
    <structuredBody>
      <component>
        <section>
          <entry>
            <organizer moodCode="EVN">
              <templateId root="2.16.840.1.113883.10.20.1.32"</pre>
 assigningAuthorityName="CCD Result Organizer"/>
              <id root="ccbc483f-0939-4c0b-8135-488ba5faa4c3"/>
              <code/>
              <statusCode/>
              <component>
                <observation classCode="OBS" moodCode="EVN">
                  <templateId root="2.16.840.1.113883.10.20.1.31"</pre>
 assigningAuthorityName="CCD Result Observation"/>
                  <id root="018ef4cd-35ed-47b3-a99b-018a863e8dc0"/>
                  <code/>
                  <statusCode/>
                  <effectiveTime>
                     <low value="1972"/>
                     <high value="2008"/>
                  </effectiveTime>
                  <interpretationCode/>
                  <methodCode/>
                </observation>
              </component>
            </organizer>
          </entry>
        </section>
      </component>
    </structuredBody>
  </component>
</ClinicalDocument>
```

Figure 6: Result Organizer example

Result Observation

[Observation: templateId 2.16.840.1.113883.10.20.1.31]

- 1. SHALL conform to CDA Clinical Statement
- 2. SHALL conform to CDA Observation
- 3. [CDA] Contains [1..1] @classCode, where its data type is ActClassObservation

- **4.** [CCD] **SHALL** contain [1..1] @moodCode = "EVN" (CONF-408)
- **5.** [CCD] **SHALL** contain [1..1] code (CONF-412)
- **6.** [CCD] **SHALL** contain [1..*] id (CONF-409)
- 7. [CCD] **SHOULD** contain [1..1] effectiveTime (CONF-411)
 - Represents the biologically relevant time (e.g. time the specimen was obtained from the patient).
- 8. [CCD] SHALL contain [1..1] statusCode (CONF-410)
- 9. [CCD] MAY contain [0..1] methodCode (CONF-414)
 - Included if the method isn't inherent in code or if there is a need to further specialize the method in code.
- 10. [CCD] SHOULD contain [0..*] interpretationCode (CONF-418)
 - Can be used to provide a rough qualitative interpretation of the observation, such as 'N' (normal), 'L' (low), 'S' (susceptible), etc. Interpretation is generally provided for numeric results where an interpretation range has been defined, or for antimicrobial susceptibility test interpretation.
- **11.** [CCD] **SHALL** contain [1..1] value (CONF-416)
- **12.** [CCD] **SHOULD** satisfy: The value for 'code' SHOULD be selected from LOINC (codeSystem 2.16.840.1.113883.6.1) or SNOMED CT (codeSystem 2.16.840.1.113883.6.96), and MAY be selected from CPT-4 (codeSystem 2.16.840.1.113883.6.12). (CONF-413)
- 13. [CCD] SHALL satisfy: The methodCode SHALL NOT conflict with the method inherent in code (CONF-415)
- **14.** [CCD] **SHALL** satisfy: Where value is a physical quantity, the unit of measure SHALL be expressed using a valid Unified Code for Units of Measure (UCUM) expression. (CONF-417)
- **15.** [CCD] **SHOULD** satisfy: Contain one or more referenceRange to show the normal range of values for the observation result (CONF-419)
 - [OCL]: not self.referenceRange->isEmpty()

• [OCL]: not self.informant->isEmpty()

- **16.** [CCD] **SHALL** satisfy: SHALL NOT contain referenceRange / observationRange / code, as this attribute is not used by the HL7 Clinical Statement or Lab Committee models. (CONF-420)
 - [OCL]: self.referenceRange->forAll(range : cda::ReferenceRange | range.observationRange.code.code.oclIsUndefined())
- 17. [CCD] SHALL satisfy: Contains one or more sources of information. (CONF-421)

<observation classCode="OBS" moodCode="EVN">

assigningAuthorityName="CCD Result Observation"/>

<low value="1972"/>
<high value="2008"/>

<code/>

<statusCode/>
<effectiveTime>

</effectiveTime>
<interpretationCode/>

<methodCode/>

<templateId root="2.16.840.1.113883.10.20.1.31"</pre>

<id root="3dfebf60-e3b4-4236-be7b-a6200f31865f"/>

Figure 7: Result Observation example