# HFITS: Heat Flux Measurements using Infrared Thermography and a Plate Sensor

*Software Manual (Version 0.1)*

**Parham Dehghani**
**Matthew J. DiDomizio**

Fire Safety Research Institute
UL Research Institutes
Columbia, MD 21045

July 3, 2024

In no event shall UL be responsible to anyone for whatever use or non-use is made of the information contained in this report and in no event shall UL, its employees, or its agents incur any obligation or liability for damages including, but not limited to, consequential damage arising out of or in connection with the use or inability to use the information contained in this report. Information conveyed by this report applies only to the specimens actually involved in these tests. UL has not established a Factory Follow-Up Service Program to determine the conformance of subsequently produced material, nor has any provision been made to apply any registered mark of UL to such material. The issuance of this report in no way implies Listing, Classification, or Recognition by UL and does not authorize the use of UL Listing, Classification, Recognition Marks, or other reference to UL on or in connection with the product or system.

i

# Summary

HFITS [1] is a software tool that supports experiment measurements of heat flux over planar surfaces using infrared thermography. This technique enables spatially and temporally resolved heat flux measurements at a greater resolution than arrays of traditional point sensors. The target audience is researchers and engineers in thermal engineering disciplines. Developed in Python with a graphical front end, the software is accessible both to advanced users as well as to users with a more fundamental knowledge of complex thermogram manipulation and heat transfer analysis methods. HFITS consists of two main components: pre-processing of infrared thermograms (obtained from heat transfer experiments), and inverse heat transfer analysis (to deduce heat flux over the planar surface in those experiments). The software offers comprehensive functionalities, including support for custom thermogram formats, metadata handling, a graphical interface for selection of regions of interest, the ability to import additional temperature measurements to enhance convective heat transfer estimates, and the exporting of both computed field data and contour videos. This open-source software broadens access to advanced experimental and analytical techniques to support thermal analyses in a wide range of engineering and research applications.

In this 0.1 version of the software manual, the authors provide basic instructions to configure and run HFITS.

# 1 Software Overview

The intended use of HFITS is to calculate the heat flux to a planar surface over time from sequential thermograms recorded with an IR camera in heat transfer experiments. The user should export the sequence of recorded thermograms to CSV files. HFITS then employs a two-step process for calculating heat flux to the surface:

1. Thermogram pre-processing (to rectify and crop thermograms to the region of interest).
2. Inverse heat transfer analysis (calculate heat flux over the region of interest).

To begin, ensure that the following software and dependencies are installed on the host system. Python packages may be installed by typing 'pip install <package>' in a terminal.

1. Python 3.6+ and a terminal environment (we suggest running HFITS with VSCode).
2. Dependencies:
   * opencv-python
   * ffmpeg-python
   * numpy
   * pandas
   * matplotlib
   * scipy
   * tqdm
   * fdm
   * h5py
   * seaborn

Next, organize the source data:

1. Clone the repository.
2. Create a root working directory (e.g., IHT).
3. Create subdirectories to organize data (e.g., T_source, T_proc, and Q_proc).
4. Copy CSV thermograms (exported from the IR camera software) into T_source.

Next, pre-process the thermograms:

1. Run HFITS_GUI.py (if it's not already running).
2. Select the first tab in the GUI, 'Image Processing'.
3. Select the source (T_source) and destination (T_proc) directories.
4. Adjust the default values in the configuration fields as needed.
5. Select a CSV thermogram from which the rectangular region of interest will be identified.
6. Select 'Run' to crop and rectify the thermogram sequence:
   * Select reference points on the sample thermogram (each of the four corners of the region of interest, and then the approximate middle of each edge of the region of interest).

- Examine the processed sample thermogram for accuracy. Either proceed with processing the entire sequence or cancel to return to the GUI and select a different thermogram or reference points.

Finally, perform inverse heat transfer analysis:

1. Run `HFITS_GUI.py` (if it's not already running).
2. Select the second tab in the GUI, 'Inverse Heat Transfer'.
3. Select the source (`T_proc`) and destination (`Q_proc`) directories.
4. Adjust the default values in the configuration fields as needed.
5. Select 'Run' next to 'Apply Inverse Model' to perform inverse heat transfer calculations.
6. Select 'Run' next to 'Export PNG' to create contour images of the computed heat flux field at each time instance.
7. Select 'Run' next to 'Export Video' to create a video of the entire sequence of computed heat flux fields.

# References

[1] Parham Dehghani and Matthew J. DiDomizio. HFITS: Heat Flux Measurements using Infrared Thermography and a Plate Sensor. [Code repository], Github. https://github.com/ulfsri/HFITS, 2024.