

# Hands-on Lab: String Patterns, Sorting and Grouping

Estimated time needed: 35 minutes

In this lab, you will go through some SQL practice problems that will provide hands-on experience with string patterns, sorting result sets and grouping result sets.

### Software Used in this Lab

In this lab, you will use an IBM Db2 Database. Db2 is a Relational Database Management System (RDBMS) from IBM, designed to store, analyze and retrieve data efficiently.

To complete this lab you will utilize a Db2 database service on IBM Cloud. If you did not already complete this lab task earlier in this module, you will not yet have access to Db2 on IBM Cloud, and you will need to follow the lab below first:

• Hands-on Lab: Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console

### Database Used in this Lab


The database used in this lab is an internal database. You will be working on a sample HR database. This HR database schema consists of 5 tables called **EMPLOYEES**, **JOB\_HISTORY**, **JOBS**, **DEPARTMENTS** and **LOCATIONS**. Each table has a few rows of sample data. The following diagram shows the tables for the HR database:

#### SAMPLE HR DATABASE TABLES

EMP_ID	F_NAME	L_NAME	SSN	B_DATE	SEX	ADDRESS	JOB_ID	SALARY	MANAGER_ID	DEP_ID
E1001	John	Thomas	123456	1976-01-09	М	5631 Rice, OakPark,IL	100	100000	30001	2
E1002	Alice	James	123457	1972-07-31	F	980 Berry In, Elgin,IL	200	80000	30002	5
E1003	Steve	Wells	123458	1980-08-10	М	291 Springs, Gary, IL	300	50000	30002	5

JOB_HISTORY				
EMPL_ID	START_DATE	JOBS_ID	DEPT_ID	
E1001	2000-01-30	100	2	
E1002	2010-08-16	200	5	
E1003	2016-08-10	300	5	

IOBS					
JOB_IDENT	JOB_TITLE	MIN_SALARY	MAX_SALARY		
100	Sr. Architect	60000	100000		
200	Sr.SoftwareDeveloper	60000	80000		
300	Jr.SoftwareDeveloper	40000	60000		



LOCATIONS				
DEP_ID_LOC				
2				
5				
7				

**NOTE:** This lab requires you to have all 5 of these tables of the HR database populated with sample data on Db2. If you didn't complete the earlier lab in this module, you won't have the tables above populated with sample data on Db2, so you will need to go through the lab below

• Hands-on Lab: Create tables using SQL scripts and Load data into tables

### **Objectives**

After completing this lab, you will be able to:

- Simplify a SELECT statement by using string patterns, ranges, or sets of values
- Sort the result set in either ascending or descending order and identify which column to use for the sorting order
- Eliminate duplicates from a result set and further restrict a result set

### **NOTE**: Make sure that you are using the CSV file and datasets from the same instruction file.

### **Instructions**

When you approach the exercises in this lab, follow the instructions to run the queries on Db2:

- Go to the Resource List of IBM Cloud by logging in where you can find the Db2 service instance that you created in a previous lab under Services section. Click on the Db2-xx service. Next, open the Db2 Console by clicking on Open Console button. Click on the 3-bar menu icon in the top left corner and go to the Run SQL page. The Run SQL tool enables you to run SQL statements.
  - o If needed, follow Hands-on Lab: Sign up for IBM Cloud, Create Db2 service instance and Get started with the Db2 console

## **Exercise 1: String Patterns**

In this exercise, you will go through some SQL problems on String Patterns.

1. Problem:

Retrieve all employees whose address is in Elgin, IL.

- ▶ Hint
- ▼ Solution

```
SELECT F_NAME , L_NAME
FROM EMPLOYEES
WHERE ADDRESS LIKE '%Elgin,IL%';
```

- Output
- 2. Problem:

Retrieve all employees who were born during the 1970's.

- ▶ Hint
- ▼ Solution

```
SELECT F_NAME , L_NAME
FROM EMPLOYEES
WHERE B_DATE LIKE '197%';
```

- ▶ Output
- 3. Problem:

Retrieve all employees in department 5 whose salary is between 60000 and 70000.

- ► Hint
- ▼ Solution

```
SELECT *
FROM EMPLOYEES
WHERE (SALARY BETWEEN 60000 AND 70000) AND DEP_ID = 5;
```

▶ Output

# **Exercise 2: Sorting**

In this exercise, you will go through some SQL problems on Sorting.

1. Problem:

Retrieve a list of employees ordered by department ID.

- ▶ Hint
- ▼ Solution

```
SELECT F_NAME, L_NAME, DEP_ID
FROM EMPLOYEES
ORDER BY DEP_ID;
```

Output

#### 2. Problem:

Retrieve a list of employees ordered in descending order by department ID and within each department ordered alphabetically in descending order by last name.

- ▶ Hint
- **▼** Solution

```
SELECT F_NAME, L_NAME, DEP_ID
FROM EMPLOYEES
ORDER BY DEP_ID DESC, L_NAME DESC;
```

▶ Output

#### 3. (Optional) Problem:

In SQL problem 2 (Exercise 2 Problem 2), use department name instead of department ID. Retrieve a list of employees ordered by department name, and within each department ordered alphabetically in descending order by last name.

- Hint
- ▼ Solution

```
SELECT D.DEP_NAME , E.F_NAME, E.L_NAME
FROM EMPLOYEES as E, DEPARTMENTS as D
WHERE E.DEP_ID = D.DEPT_ID_DEP
ORDER BY D.DEP_NAME, E.L_NAME DESC;
```

In the SQL Query above, D and E are aliases for the table names. Once you define an alias like D in your query, you can simply write D.COLUMN\_NAME rather than the full form DEPARTMENTS.COLUMN\_NAME.

► Output

## **Exercise 3: Grouping**

In this exercise, you will go through some SQL problems on Grouping.

NOTE: The SQL problems in this exercise involve usage of SQL Aggregate functions AVG and COUNT. COUNT has been covered earlier. AVG is a function that can be used to calculate the Average or Mean of all values of a specified column in the result set. For example, to retrieve the average salary for all employees in the EMPLOYEES table, issue the query: SELECT AVG(SALARY) FROM EMPLOYEES;. You will learn more about AVG 4/21/23, 11:18 AM  $https://cf-courses-data.s3.us.cloud-object-storage.appdomain.cloud/IBMDeveloperSkillsNetwork-DB0201EN-SkillsNetwork/labs/Labs\_Coursera\_V5/labs/Lab-String Patterns - Sorting - Grouping \dots \\$ and other aggregate functions later in the lecture **Built-in Database Functions**.

1. Problem:

For each department ID retrieve the number of employees in the department.

- ► Hint
- **▼** Solution

```
SELECT DEP_ID, COUNT(*)
FROM EMPLOYEES
GROUP BY DEP_ID;
```

► Output

#### 2. Problem:

For each department retrieve the number of employees in the department, and the average employee salary in the department..

- ► Hint
- **▼** Solution

```
SELECT DEP_ID, COUNT(*), AVG(SALARY)
FROM EMPLOYEES
GROUP BY DEP_ID;
```

- ▶ Output
- 3. Problem:

Label the computed columns in the result set of SQL problem 2 (Exercise 3 Problem 2) as NUM\_EMPLOYEES and AVG\_SALARY.

- ► Hint
- ▼ Solution

```
SELECT DEP_ID, COUNT(*) AS "NUM_EMPLOYEES", AVG(SALARY) AS "AVG_SALARY"
FROM EMPLOYEES
GROUP BY DEP_ID;
```

▶ Output

#### 4. Problem:

In SQL problem 3 (Exercise 3 Problem 3), order the result set by Average Salary..

- ► Hint
- Solution

```
SELECT DEP_ID, COUNT(*) AS "NUM_EMPLOYEES", AVG(SALARY) AS "AVG_SALARY"
FROM EMPLOYEES
GROUP BY DEP_ID
ORDER BY AVG_SALARY;
```

- Output
- 5. Problem:

In SQL problem 4 (Exercise 3 Problem 4), limit the result to departments with fewer than 4 employees.

- ► Hint
- ▼ Solution

```
SELECT DEP_ID, COUNT(*) AS "NUM_EMPLOYEES", AVG(SALARY) AS "AVG_SALARY"
FROM EMPLOYEES
GROUP BY DEP_ID
HAVING count(*) < 4</pre>
ORDER BY AVG_SALARY;
```

▶ Output

## Solution Script

If you would like to run all the solution queries of the SQL problems of this lab with a script, download the script below. Upload the script to the Db2 console and run. Follow Hands-on Lab: Create tables using SQL scripts and Load data into tables on how to upload a script to Db2 console and run it.

• StringPattern-Sorting-Grouping Solution Script.sql

Congratulations! You have completed this lab, and you are ready for the next topic.

# Author(s)

- Rav Ahuja
- Sandip Saha Joy

### Changelog

Date	Version	Changed by	Change Description
2020-12-24	2.1	Steve Ryan	ID Reviewed
2020-12-08	2.0	Sandip Saha Joy	Created revised version from DB0201EN
2020	1.0	Rav Ahuja	Created initial version

© IBM Corporation 2020. All rights reserved.