

API Reference Documentation

Health Check API

This document provides reference documentation for the Health Check API. The API retrieves the results of the cronjob that deletes PII data based on TTL (Time-To-Live) settings, providing details of the recent cronjob execution status in the last 24 hours.

Document Type	API Reference
Version	1.0
Method	GET
Auth Required	Yes — Central Auth Token
Date	July 2026

1. Overview

The Health Check API retrieves the results of the cronjob that deletes PII data based on TTL settings. It provides details of the recent cronjob execution status in the last 24 hours, including information about deleted PII data.

Note: This endpoint reflects only the last 24 hours of cronjob activity. If no job has run in that window, the response will reflect the most recently stored record rather than a live execution.

2. Authentication

To access the Health Check API, users must have an **API Key** and **Secret Key** for authentication. These keys are created per company by executing the following curl command in the central auth management service.

Warning: API keys are created per company. Store the returned API Key and Secret Key securely. They cannot be retrieved after creation — only regenerated.

2.1 Generating an API Key

Run the following command, replacing <company-id> with the actual company ID:

```
curl --location --request POST \  
'http://<auth-service-host>/api/v1/companies/api-key' \  
--header 'Content-Type: application/json' \  
--data-raw '{ "company": "<company-id>" }'
```

The command returns a new API Key and Secret Key.

2.2 Configuring Environment Variables

Store the returned keys in the pipeline environment variables before deployment:

```
process.env.AUTH_KEY_ID # API Key  
process.env.AUTH_KEY_SECRET # Secret Key
```

For the full setup walkthrough, refer to the internal company setup guide, **Step 3: Creating API key for company**.

2.3 Using the Token

A **Central Auth token** is required to access the API. Pass it in the Authorization header as a Bearer token:

```
Authorization: Bearer <central-auth-token>
```

3. Endpoint

Method	Endpoint
GET	/ttl-health-check

Returns the status of the most recent PII deletion cronjob execution within the last 24 hours. No request body is required.

Note: The base URL is environment-specific and is configured during deployment. The path `/ttl-health-check` is constant across all environments.

4. Request Headers

Header	Required	Value	Description
Authorization	Required	Bearer <token>	Central Auth token derived from your API Key and Secret Key.
Content-Type	Optional	application/json	Recommended. The response is always JSON.

There are no query parameters or request body fields for this endpoint.

5. API Responses

The API returns three distinct response states depending on the outcome of the most recent PII deletion cronjob execution.

5.1 Successful Deletion — 200 OK

The most recent cronjob completed successfully and deleted PII data as expected. The `deleteCount` field reflects the number of form records removed.

```
{
  "success": true,
  "data": {
    "_id": "a1b2c3d4-e5f6-7890-ab12-cd34ef567890",
    "statusCode": 200,
    "message": "Forms deleted successfully",
    "deleteCount": 1,
    "fileDeleteCount": 0,
    "createdAt": "2026-03-15T09:12:44.379Z",
    "expiresAt": "2026-04-14T09:12:44.380Z",
    "__v": 0
  }
}
```

5.2 No Data Scheduled — 304 Not Modified

The cronjob ran but found no PII records that had exceeded their TTL. No deletions were performed. This is a normal operational state — it means there is currently no expired PII data in the system. Both `deleteCount` and `fileDeleteCount` will be 0.

```
{
  "success": true,
  "data": {
    "_id": "f9e8d7c6-b5a4-3210-fe98-dc76ba543210",
    "statusCode": 304,
    "message": "Not modified",
    "deleteCount": 0,
    "fileDeleteCount": 0,
    "createdAt": "2026-03-15T09:10:28.784Z",
    "expiresAt": "2026-04-14T09:10:28.785Z",
    "__v": 0
  }
}
```

5.3 Cron Job Down — 503 Service Unavailable

The PII deletion cronjob has failed or is not running. The `success` field returns `false`. No deletion was performed. Immediate investigation is required — PII data that has exceeded its TTL has not been purged, which may constitute a compliance risk.

```
{
  "success": false
}
```

Warning: When `success` is `false`, no additional fields are returned. Check the monitoring dashboards for deletion job failure alerts and verify the cronjob is active.

6. Response Fields

The following fields are present in the data object when `success` is `true`.

Field	Type	Description	Example
<code>success</code>	boolean	Top-level flag. <code>true</code> if the API call succeeded. <code>false</code> if the cronjob is down.	<code>true</code>
<code>data._id</code>	string (UUID)	Unique identifier for this execution record.	<code>a1b2c3d4-e5f6-...</code>
<code>data.statusCode</code>	number	200 = deletion performed. 304 = no expired PII found.	200

Field	Type	Description	Example
data.message	string	Human-readable status message from the cronjob.	"Forms deleted successfully"
data.deleteCount	number	Number of form records deleted. 0 if no TTL-expired records were found.	1
data.fileDeleteCount	number	Number of file records deleted. 0 if no file attachments were purged.	0
data.createdAt	string ISO 8601	Timestamp when the cronjob ran and this record was created.	"2026-03-15T09:12:44.379Z"
data.expiresAt	string ISO 8601	Timestamp when this record expires (typically 30 days after createdAt).	"2026-04-14T09:12:44.380Z"
data.__v	number	Internal document version key. Can be safely ignored by API consumers.	0

7. Code Examples

Replace `<base-url>` with your environment-specific host and `<token>` with the Central Auth Bearer token generated from your API Key and Secret Key.

7.1 curl

```
curl --location --request GET \  
'https://<base-url>/ttl-health-check' \  
--header 'Authorization: Bearer <token>' \  
--header 'Content-Type: application/json'
```

7.2 JavaScript — fetch

```
const response = await fetch(  
  'https://<base-url>/ttl-health-check',  
  {  
    method: 'GET',  
    headers: {  
      'Authorization': `Bearer ${process.env.AUTH_KEY_ID}:${process.env.AUTH_KEY_SECRET}`,  
      'Content-Type': 'application/json'  
    }  
  }  
);  
const result = await response.json();  
if (!result.success) {  
  // Cron job is down – investigate immediately  
} else if (result.data.statusCode === 200) {  
  // Deletion successful
```

```
} else if (result.data.statusCode === 304) {  
  // No expired PII data found  
}
```