

# Lecture 9: Priority Queues and Heaps

Michael Dinitz

September 23, 2025

601.433/633 Introduction to Algorithms

# Introduction

Priority Queues / Heaps: Like a queue/stack, but instead of FIFO/LIFO, by priority

- ▶  $\text{Insert}(H, x)$ : insert element  $x$  into heap  $H$ .
- ▶  $\text{Extract-Min}(H)$ : remove and return an element with smallest key
- ▶  $\text{Decrease-Key}(H, x, k)$ : decrease the key of  $x$  to  $k$ .
- ▶  $\text{Meld}(H_1, H_2)$ : replace heaps  $H_1$  and  $H_2$  with their union

Extra Operations:

- ▶  $\text{Find-Min}(H)$ : return the element with smallest key
- ▶  $\text{Delete}(H, x)$ : delete element  $x$  from heap  $H$

Min-Heap, but can also do Max-Heap.

# Introduction

Priority Queues / Heaps: Like a queue/stack, but instead of FIFO/LIFO, by priority

- ▶  $\text{Insert}(H, x)$ : insert element  $x$  into heap  $H$ .
- ▶  $\text{Extract-Min}(H)$ : remove and return an element with smallest key
- ▶  $\text{Decrease-Key}(H, x, k)$ : decrease the key of  $x$  to  $k$ .
- ▶  $\text{Meld}(H_1, H_2)$ : replace heaps  $H_1$  and  $H_2$  with their union

Extra Operations:

- ▶  $\text{Find-Min}(H)$ : return the element with smallest key
- ▶  $\text{Delete}(H, x)$ : delete element  $x$  from heap  $H$

Min-Heap, but can also do Max-Heap.

Note:  $x$  is a *pointer* to an element. No way to lookup, so need a pointer to an element to change it.

# Obvious Approaches

	Insert	Extract-Min	Decrease-Key	Meld
Linked List				

## Obvious Approaches

	Insert	Extract-Min	Decrease-Key	Meld
Linked List	$O(1)$	$O(n)$	$O(1)$	$O(1)$

## Obvious Approaches

	Insert	Extract-Min	Decrease-Key	Meld
Linked List	$O(1)$	$O(n)$	$O(1)$	$O(1)$
Sorted Array				

## Obvious Approaches

	Insert	Extract-Min	Decrease-Key	Meld
Linked List	$O(1)$	$O(n)$	$O(1)$	$O(1)$
Sorted Array	$O(n)$	$O(1)$	$O(n)$	$O(n)$

## Obvious Approaches

	Insert	Extract-Min	Decrease-Key	Meld
Linked List	$O(1)$	$O(n)$	$O(1)$	$O(1)$
Sorted Array	$O(n)$	$O(1)$	$O(n)$	$O(n)$
Balanced Search Tree				



## Obvious Approaches

	Insert	Extract-Min	Decrease-Key	Meld
Linked List	$O(1)$	$O(n)$	$O(1)$	$O(1)$
Sorted Array	$O(n)$	$O(1)$	$O(n)$	$O(n)$
Balanced Search Tree	$O(\log n)$	$O(\log n)$	$O(\log n)$	$O(n)$

## Obvious Approaches

	Insert	Extract-Min	Decrease-Key	Meld
Linked List	$O(1)$	$O(n)$	$O(1)$	$O(1)$
Sorted Array	$O(n)$	$O(1)$	$O(n)$	$O(n)$
Balanced Search Tree	$O(\log n)$	$O(\log n)$	$O(\log n)$	$O(n)$

Goal: get as many of these to  $O(1)$  as possible

## Obvious Approaches

	Insert	Extract-Min	Decrease-Key	Meld
Linked List	$O(1)$	$O(n)$	$O(1)$	$O(1)$
Sorted Array	$O(n)$	$O(1)$	$O(n)$	$O(n)$
Balanced Search Tree	$O(\log n)$	$O(\log n)$	$O(\log n)$	$O(n)$

Goal: get as many of these to  $O(1)$  as possible

**Question:** Can we make Insert and Extract-Min both  $O(1)$ , even amortized?

## Obvious Approaches

	Insert	Extract-Min	Decrease-Key	Meld
Linked List	$O(1)$	$O(n)$	$O(1)$	$O(1)$
Sorted Array	$O(n)$	$O(1)$	$O(n)$	$O(n)$
Balanced Search Tree	$O(\log n)$	$O(\log n)$	$O(\log n)$	$O(n)$

Goal: get as many of these to  $O(1)$  as possible

**Question:** Can we make Insert and Extract-Min both  $O(1)$ , even amortized?

**No!** Sorting lower bound. But maybe can make one  $O(1)$ , other  $O(\log n)$ ?

# Today and State of the Art

State of the art: *strict Fibonacci Heaps*.


- ▶ Too complicated for this class, not practical. See CLRS 19 for Fibonacci Heaps.

Today: binary heaps (should be review), then binomial heaps

- ▶ Binomial heaps not quite as complicated as Fibonacci heaps, many of same core ideas


# Binary Heaps

- ▶ Complete binary tree, except possibly at bottom level.
- ▶ Heap order: key of any node no larger than key of its children.



# Binary Heaps

- ▶ Complete binary tree, except possibly at bottom level.
- ▶ Heap order: key of any node no larger than key of its children.



## Properties:

- ▶ Since (almost) complete binary tree, depth  $\Theta(\log n)$
- ▶ Min must be at root


## Representation:

- ▶ Pointers to root and rightmost leaf
- ▶ Every node has pointers to parent and children

## Insert( $H, x$ )

Preserve heap *structure*: insert  $x$  into next open spot (bottom right, or left of new level if bottom level full)

- ▶ Might violate heap *order*!







## Insert( $H, x$ )

Preserve heap *structure*: insert  $x$  into next open spot (bottom right, or left of new level if bottom level full)

- ▶ Might violate heap *order*!




"Swim up": as long as  $x$  smaller than its parent, swap with parent




## Insert( $H, x$ )

Preserve heap *structure*: insert  $x$  into next open spot (bottom right, or left of new level if bottom level full)

- ▶ Might violate heap *order*!



"Swim up": as long as  $x$  smaller than its parent, swap with parent



Running time:  $O(\log n)$  worst case (also amortized) via depth


## Extract-Min( $H$ )

Min is definitely at root. How to remove it while still have binary tree?

## Extract-Min( $H$ )

Min is definitely at root. How to remove it while still have binary tree?


- ▶ Swap root with final heap element, remove former root.
- ▶ Sink down: swap root with smaller of its children until heap order restored



## Extract-Min( $H$ )

Min is definitely at root. How to remove it while still have binary tree?

- ▶ Swap root with final heap element, remove former root.
- ▶ Sink down: swap root with smaller of its children until heap order restored



Running time:  $O(\log n)$  worst case (via depth). Amortized:  $O(1)$  (not obvious)

## Decrease-Key( $H, x, k$ )

Decrease key of  $x$  to  $k$ , “swim up” until heap order restored.

Running time:  $O(\log n)$  (depth)

## Meld( $H_1, H_2$ )

Assume both heaps have size  $n$ .

- ▶ Obvious approach: insert each element of  $H_2$  into  $H_1$ . Time:  $O(n \log n)$

## Meld( $H_1, H_2$ )

Assume both heaps have size  $n$ .

- ▶ Obvious approach: insert each element of  $H_2$  into  $H_1$ . Time:  $O(n \log n)$

Better:

- ▶ Insert all elements of  $H_2$  all at once (not fixing heap order)
- ▶ Instead of fixing by swimming up: iterate from bottom up and sink down to fix heap.



## Meld( $H_1, H_2$ )

Assume both heaps have size  $n$ .

- ▶ Obvious approach: insert each element of  $H_2$  into  $H_1$ . Time:  $O(n \log n)$

Better:

- ▶ Insert all elements of  $H_2$  all at once (not fixing heap order)
- ▶ Instead of fixing by swimming up: iterate from bottom up and sink down to fix heap.

**Correctness:** ends up in heap order (induction, or contradiction)

## Meld( $H_1, H_2$ )

Assume both heaps have size  $n$ .

- ▶ Obvious approach: insert each element of  $H_2$  into  $H_1$ . Time:  $O(n \log n)$

Better:

- ▶ Insert all elements of  $H_2$  all at once (not fixing heap order)
- ▶ Instead of fixing by swimming up: iterate from bottom up and sink down to fix heap.

**Correctness:** ends up in heap order (induction, or contradiction)

**Running Time:**

- ▶ Inserting:  $O(n)$  total

## Meld( $H_1, H_2$ )

Assume both heaps have size  $n$ .

- ▶ Obvious approach: insert each element of  $H_2$  into  $H_1$ . Time:  $O(n \log n)$

Better:

- ▶ Insert all elements of  $H_2$  all at once (not fixing heap order)
- ▶ Instead of fixing by swimming up: iterate from bottom up and sink down to fix heap.

**Correctness:** ends up in heap order (induction, or contradiction)

**Running Time:**

- ▶ Inserting:  $O(n)$  total
- ▶ Sinking down:
  - ▶ Nodes at height  $h$  might have to sink down  $h$ .
  - ▶ At most  $n/2^h$  nodes at height  $h$

## Meld( $H_1, H_2$ )

Assume both heaps have size  $n$ .

- ▶ Obvious approach: insert each element of  $H_2$  into  $H_1$ . Time:  $O(n \log n)$

Better:

- ▶ Insert all elements of  $H_2$  all at once (not fixing heap order)
- ▶ Instead of fixing by swimming up: iterate from bottom up and sink down to fix heap.

**Correctness:** ends up in heap order (induction, or contradiction)

**Running Time:**

- ▶ Inserting:  $O(n)$  total
- ▶ Sinking down:
  - ▶ Nodes at height  $h$  might have to sink down  $h$ .
  - ▶ At most  $n/2^h$  nodes at height  $h$

$$\sum_{h=0}^{\log n} h \left( \frac{n}{2^h} \right) = n \sum_{h=0}^{\log n} \frac{h}{2^h} \leq O(n)$$

# Amortized Extract-Min

Weights:  $w(x) = \text{depth of } x$

- ▶ Root has weight **0**, its children have weight **1**, etc.

Potential:  $\Phi(H) = \sum_x w(x)$

## Amortized Extract-Min

Weights:  $w(x)$  = depth of  $x$

- ▶ Root has weight **0**, its children have weight **1**, etc.

Potential:  $\Phi(H) = \sum_x w(x)$

Insert:  $\Delta\Phi = O(\log n) \implies$  amortized cost  $\leq O(\log n) + O(\log n) = O(\log n)$

# Amortized Extract-Min

Weights:  $w(x) = \text{depth of } x$

- ▶ Root has weight **0**, its children have weight **1**, etc.

Potential:  $\Phi(H) = \sum_x w(x)$

Insert:  $\Delta\Phi = O(\log n) \implies \text{amortized cost} \leq O(\log n) + O(\log n) = O(\log n)$

Extract-Min:

- ▶ True cost: height  $h = \Theta(\log n)$  of tree, plus  $O(1)$  (for initial swap).
- ▶  $\Delta\Phi$ : one less node at depth  $h \implies \Delta\Phi = -h$
- ▶ Amortized cost:  $h + O(1) - h = O(1)$ .

# Amortized Extract-Min

Weights:  $w(x) = \text{depth of } x$

- ▶ Root has weight **0**, its children have weight **1**, etc.

Potential:  $\Phi(H) = \sum_x w(x)$

Insert:  $\Delta\Phi = O(\log n) \implies \text{amortized cost} \leq O(\log n) + O(\log n) = O(\log n)$

Extract-Min:

- ▶ True cost: height  $h = \Theta(\log n)$  of tree, plus  $O(1)$  (for initial swap).
- ▶  $\Delta\Phi$ : one less node at depth  $h \implies \Delta\Phi = -h$
- ▶ Amortized cost:  $h + O(1) - h = O(1)$ .

Uses Inserts to “pay for” Extract-Mins.



# Improvements

Downsides of binary heaps:

- ▶ Do at least as many Inserts as Extract-Mins! Want  $O(1)$  Insert,  $O(\log n)$  Extract-Min
- ▶ Meld in  $O(n)$  is better than trivial, but still not great.

# Improvements

Downsides of binary heaps:

- ▶ Do at least as many Inserts as Extract-Mins! Want  $O(1)$  Insert,  $O(\log n)$  Extract-Min
- ▶ Meld in  $O(n)$  is better than trivial, but still not great.

Binomial Heaps:

- ▶ Get Insert down to  $O(1)$  (amortized)
- ▶ Meld in  $O(\log n)$  (worst-case and amortized)
- ▶ Downside:  $O(\log n)$  Extract-Min,  $O(\log n)$  Find-Min

# Improvements

Downsides of binary heaps:

- ▶ Do at least as many Inserts as Extract-Mins! Want  $O(1)$  Insert,  $O(\log n)$  Extract-Min
- ▶ Meld in  $O(n)$  is better than trivial, but still not great.

Binomial Heaps:

- ▶ Get Insert down to  $O(1)$  (amortized)
- ▶ Meld in  $O(\log n)$  (worst-case and amortized)
- ▶ Downside:  $O(\log n)$  Extract-Min,  $O(\log n)$  Find-Min

Fibonacci Heaps:

- ▶ Everything  $O(1)$  (amortized) except  $O(\log n)$  Extract-Min (amortized)


# Binomial Heaps

Not based on binary tree anymore! Based on *binomial tree*.

# Binomial Heaps

Not based on binary tree anymore! Based on *binomial tree*.

- ▶  $B_0$  = single node.
- ▶  $B_k$  = one  $B_{k-1}$  linked to another  $B_{k-1}$ .




# Structure Lemma

## Lemma

The order  $k$  binomial tree  $B_k$  has the following properties:

1. Its height is  $k$ .
2. It has  $2^k$  nodes
3. The degree of the root is  $k$
4. If we delete the root, we get  $k$  binomial trees  $B_{k-1}, \dots, B_0$ .




# Binomial Heap

## Definition

A *binomial heap* is a collection of binomial trees so that each tree is heap ordered, and there is exactly **0** or **1** tree of order  **$k$**  for each integer  **$k$** .

Keep roots of trees in linked list, from smallest order (not key!) to largest




# Binomial Heap

## Definition

A *binomial heap* is a collection of binomial trees so that each tree is heap ordered, and there is exactly **0** or **1** tree of order  **$k$**  for each integer  **$k$** .

Keep roots of trees in linked list, from smallest order (not key!) to largest



With  **$n$**  items, no choices about which binomial trees exist in heap!

- ▶ Write  **$n$**  in binary:  **$b_a b_{a-1} \dots b_1 b_0$** .
- ▶ Tree  **$B_k$**  exists if and only if  **$b_k = 1$**




# Binomial Heap

## Definition

A *binomial heap* is a collection of binomial trees so that each tree is heap ordered, and there is exactly **0** or **1** tree of order  **$k$**  for each integer  **$k$** .

Keep roots of trees in linked list, from smallest order (not key!) to largest



With  **$n$**  items, no choices about which binomial trees exist in heap!

- ▶ Write  **$n$**  in binary:  **$b_a b_{a-1} \dots b_1 b_0$** .
- ▶ Tree  **$B_k$**  exists if and only if  **$b_k = 1$**

$\implies$  at most  **$\log n$**  trees, and by lemma each has height  $\leq \log n$

## Analysis: Beginning

Analyze all operations both worst-case and amortized.

# Analysis: Beginning

Analyze all operations both worst-case and amortized.

Potential function:  $\Phi(H) = \# \text{ trees in } H$

- ▶ Initially **0**
- ▶ Never negative

# Analysis: Beginning

Analyze all operations both worst-case and amortized.

Potential function:  $\Phi(H) = \# \text{ trees in } H$

- ▶ Initially **0**
- ▶ Never negative

Find-Min(***H***):

## Analysis: Beginning

Analyze all operations both worst-case and amortized.

Potential function:  $\Phi(H) = \# \text{ trees in } H$

- ▶ Initially **0**
- ▶ Never negative

Find-Min( $H$ ): Scan through roots of trees in  $H$ , return min

## Analysis: Beginning

Analyze all operations both worst-case and amortized.

Potential function:  $\Phi(H) = \# \text{ trees in } H$

- ▶ Initially **0**
- ▶ Never negative

Find-Min( $H$ ): Scan through roots of trees in  $H$ , return min

- ▶ Correct: each tree heap-ordered, so global min one of the roots

## Analysis: Beginning

Analyze all operations both worst-case and amortized.

Potential function:  $\Phi(H) = \# \text{ trees in } H$

- ▶ Initially **0**
- ▶ Never negative

Find-Min( $H$ ): Scan through roots of trees in  $H$ , return min

- ▶ Correct: each tree heap-ordered, so global min one of the roots
- ▶ Worst-case:  **$O(\log n)$**
- ▶ Amortized: doesn't change potential, also  **$O(\log n)$** .

## Meld( $H_1, H_2$ ): Link

Key operation: we'll use Meld to do Insert and Extract-Min



## Meld( $H_1, H_2$ ): Link

Key operation: we'll use Meld to do Insert and Extract-Min

Warmup:  $H_1, H_2$  both single trees of same order  $k$ .


- ▶ Union has size  $2^k + 2^k = 2^{k+1}$ : just a single  $B_{k+1}$
- ▶ Easy to make a  $B_{k+1}$  out of two  $B_k$ 's!

## Meld( $H_1, H_2$ ): Link

Key operation: we'll use Meld to do Insert and Extract-Min

Warmup:  $H_1, H_2$  both single trees of same order  $k$ .

- ▶ Union has size  $2^k + 2^k = 2^{k+1}$ : just a single  $B_{k+1}$
- ▶ Easy to make a  $B_{k+1}$  out of two  $B_k$ 's!




## Meld( $H_1, H_2$ ): Link

Key operation: we'll use Meld to do Insert and Extract-Min

Warmup:  $H_1, H_2$  both single trees of same order  $k$ .

- ▶ Union has size  $2^k + 2^k = 2^{k+1}$ : just a single  $B_{k+1}$
- ▶ Easy to make a  $B_{k+1}$  out of two  $B_k$ 's!




*Link* of two trees.

- ▶ Worst-case time:  $O(1)$  (create a single link). Normalize: call 1
- ▶  $\Delta\Phi$ : two trees to one:  $-1$
- ▶ Amortized cost:  
 $1 - 1 = 0 = O(1)$ .

# Meld( $H_1, H_2$ ): General Case

(Almost) just like binary addition!



## Meld( $H_1, H_2$ ): Analysis

Easy to prove correct (exercise for home).

Running time:

- ▶ Worst case:  $O(1)$  per “order”  $k \implies \leq O(\log n)$
- ▶ Amortized: Potential does not go up, but could stay the same  
 $\implies O(\log n)$  amortized

## Insert( $H, x$ )

Use Meld:

- ▶ Create new heap  $H'$  with one  $B_0$  consisting of just  $x$
- ▶ Meld( $H, H'$ )

Correctness: Obvious

## Insert( $H, x$ )

Use Meld:

- ▶ Create new heap  $H'$  with one  $B_0$  consisting of just  $x$
- ▶ Meld( $H, H'$ )

Correctness: Obvious

Running Time:

- ▶ Worst case:  $O(\log n)$  (via Meld)

## Insert( $H, x$ )

Use Meld:

- ▶ Create new heap  $H'$  with one  $B_0$  consisting of just  $x$
- ▶ Meld( $H, H'$ )

Correctness: Obvious

Running Time:

- ▶ Worst case:  $O(\log n)$  (via Meld)
- ▶ Amortized:
  - ▶ Like incrementing a binary counter!



## Insert( $H, x$ )

Use Meld:

- ▶ Create new heap  $H'$  with one  $B_0$  consisting of just  $x$
- ▶ Meld( $H, H'$ )

Correctness: Obvious

Running Time:

- ▶ Worst case:  $O(\log n)$  (via Meld)
- ▶ Amortized:
  - ▶ Like incrementing a binary counter!
  - ▶ If we link  $k$  trees, potential goes down by  $k - 1$
  - ▶ Cost = # links plus 1 (for making new heap)
  - ▶ Amortized cost =  $k + 1 + \Delta\Phi = k + 1 - (k - 1) = 2 = O(1)$

## Extract-Min( $H$ )

Use Meld again!

- ▶  $O(\log n)$  to Find-Min: one of the roots.
- ▶ Delete and return this root: tree turns into a new heap!
- ▶ Meld with original heap (minus the tree)

Correctness: Obvious

## Extract-Min( $H$ )

Use Meld again!

- ▶  $O(\log n)$  to Find-Min: one of the roots.
- ▶ Delete and return this root: tree turns into a new heap!
- ▶ Meld with original heap (minus the tree)

Correctness: Obvious

Running Time:

- ▶ Worst-Case:  $O(\log n)$  from creating new heap, Meld
- ▶ Amortized:
  - ▶ Potential can go up! But by at most  $\log n$
  - ▶ Amortized time at most  $O(\log n) + \log n = O(\log n)$