

All You Ever Wanted to Know About Dynamic Taint Analysis and Forward Symbolic Execution

(but might have been afraid to ask)

Matteo Di Pirro

BSc in Computer Science
Department of Mathematics

University of Padova

December 7, 2016



UNIVERSITÀ
DEGLI STUDI
DI PADOVA



Outline

Introduction

The language

Static and Dynamic Analysis

► Static Analysis

- Examines a program's text to derive properties that hold for all executions
- Program-centric analysis

► Dynamic Analysis

- Examines the running program to derive properties hold for one or more executions
- Detect violations of stated properties
- Provide useful information about the behavior of the program
- Input-centric analysis



Dynamic Analysis

There are two essential questions about the input analysis:



Dynamic Analysis

There are two essential questions about the input analysis:

1. **Is the final value affected by user input?**
 - **Dynamic Taint Analysis!**
 - Tracks information flow between sources and sinks

Dynamic Analysis

There are two essential questions about the input analysis:

1. **Is the final value affected by user input?**
 - **Dynamic Taint Analysis!**
 - Tracks information flow between sources and sinks
2. **What input will make execution reach this line of code?**
 - **Forward Symbolic Execution**
 - Allows us to reason about the behavior of a program on many different inputs



Use cases

The number of security applications utilizing these two techniques is enormous:



Use cases

The number of security applications utilizing these two techniques is enormous:

1. **Unknown Vulnerability Detection:** monitor whether user input is executed

Use cases

The number of security applications utilizing these two techniques is enormous:

1. **Unknown Vulnerability Detection:** monitor whether user input is executed
2. **Automatic Input Filter Generation:** detect and remove exploits from the input stream

Use cases

The number of security applications utilizing these two techniques is enormous:

1. **Unknown Vulnerability Detection:** monitor whether user input is executed
2. **Automatic Input Filter Generation:** detect and remove exploits from the input stream
3. **Forward Symbolic Execution:** analyze how information flows through a malware binary

Use cases

The number of security applications utilizing these two techniques is enormous:

1. **Unknown Vulnerability Detection:** monitor whether user input is executed
2. **Automatic Input Filter Generation:** detect and remove exploits from the input stream
3. **Forward Symbolic Execution:** analyze how information flows through a malware binary
4. **Test Case Generation:** automatically generate inputs to test programs



SimplIL

Designed to demonstrate the critical aspects of this analysis.

program ::= *stmt**

stmt s ::= *var* := *exp* | *store*(*exp*, *exp*)
| *goto* *exp* | *assert* *exp*
| *if* *exp* *then* *goto* *exp*
| *else* *goto* *exp*

exp e ::= *load*(*exp*) | *exp* \diamond_b *exp* | \diamond_u *exp*
| *var* | *get_input*(*src*) | *v*

\diamond_b ::= typical binary operators

\diamond_u ::= typical unary operators

value v ::= 32-bit unsigned integer

SimplIL Grammar

Designed to demonstrate the critical aspects of this analysis.

- **Each** statement rule of the operational semantic is like:

$$\frac{\text{computation}}{\langle \text{current state} \rangle, \text{stmt} \rightarrow \langle \text{end state} \rangle, \text{stmt}}$$

- The state is composed of:
 - Program statements (Σ)
 - Current memory state (μ)
 - Current values for variables (Δ)
 - Program counter (pc)
 - Current statement (i)



UNIVERSITÀ
DEGLI STUDI
DI PADOVA

THANK YOU FOR ALLOWING ME
TO
TAINT YOUR PRECIOUS TIME!



DIPARTIMENTO
MATEMATICA