CIS 263 Introduction to Data Structures and Algorithms

Graph Coloring

Graph coloring

Given a Graph, we have color its nodes in a way that no two adjacent nodes have the same color (i.e. each edge ends at different color vertices)



Graph coloring

Given a Graph, we have color its nodes in a way that no two adjacent nodes have the same color (i.e. each edge ends at different color vertices)

Traversal seq

A	B	C	D	E



Graph coloring

Greedy Algorithm



Traversal seq

A	B	C	D	E

Graph coloring

Greedy Algorithm

- Ordered list of colors



Traversal seq

A	B	C	D	E



Graph coloring

Greedy Algorithm

- Ordered list of colors
- **Starting node: color with the initial index**



Traversal seq

	B	C	D	E



Graph coloring

Greedy Algorithm

- Ordered list of colors
- Starting node: color with the initial index
- **Go to the next neighbour, color it**
  - **with the minimum available index (non replaceable) exclusive to the already labeled (colored) neighbor's indices**
  - **Iterate**



Traversal seq





Graph coloring

Greedy Algorithm

- Ordered list of colors
- Starting node: color with the initial index
- **Go to the next neighbour, color it**
  - **with the minimum available index (non replaceable) exclusive to the already labeled (colored) neighbor's indices**
  - **Iterate**



Traversal seq



Graph coloring

Greedy Algorithm

- Ordered list of colors
- Starting node: color with the initial index
- **Go to the next neighbour, color it**
  - **with the minimum available index (non replaceable) exclusive to the already labeled (colored) neighbor's indices**
  - **Iterate**



Traversal seq





Graph coloring

Greedy Algorithm

- Ordered list of colors
- Starting node: color with the initial index
- **Go to the next neighbour, color it**
  - **with the minimum available index (non replaceable) exclusive to the already labeled (colored) neighbor's indices**
  - **Iterate**



Traversal seq



Graph coloring

Greedy Algorithm

- Ordered list of colors
- Starting node: color with the initial index
- Go to the next neighbour, color it
  - with the minimum available index (non replaceable) exclusive to the already labeled (colored) neighbor's indices
  - Iterate
- **Solution: 4 colours (chromatic number) graph**



Traversal seq





Revisit one more ..

Graph coloring applications

- No two states have the same color
  - Whiteboarding
- Old days printing

Summary

- **Given a Graph**, we used a **Greedy Algorithm** to perform graph coloring.