

Deep Learning Model for Detecting and Diagnosing Plant Disease

Nazmun Nessa Moon
Department of Computer Science and Engineering
Daffodil International University
Dhaka, Bangladesh
moon@daffodilvarsity.edu.bd

Ms. Shayla Sharmin
Department of Computer Science and Engineering
Daffodil International University
Dhaka, Bangladesh
shayla.cse@diu.edu.bd

Refath Ara Hossain
Department of Computer Science and Engineering
Daffodil International University
Dhaka, Bangladesh
refath.cse@diu.edu.bd

Israt Jahan
Department of Computer Science and Engineering
Daffodil International University
Dhaka, Bangladesh
isratjahan.cse@diu.edu.bd

Fernaz Narin Nur
Department of Computer Science and Engineering
Notre Dam University
Dhaka, Bangladesh
fernazcse@ndub.edu.bd

Md. Mosfikur Rahman
Department of Computer Science and Engineering
Daffodil International University
Dhaka, Bangladesh
mdmosfikurrahman.cse@gmail.com

Abstract—This work deals with some plant disease detection like Potato, Pepper, and Tomato, Rice, etc. based on CNN image processing Technology. An enormous improvement has been made in the field of picture preparation and AI and its application in different parts of designing. The authors have entered the time of digitization. The authors have caught pictures with the assistance of an advanced camera. All the clearer the pictures are better and produce the outcomes. In this report, the authors have done the arrangement of sickness-free, somewhat infected, and sick leaves. The information related to plant features is especially useful for its applications in plant growth modeling, agricultural research, and on-farm production. Traditional direct measurement methods are generally simple and reliable, but they are time-consuming, laborious, and cumbersome. In contrast, the proposed vision-based methods are efficient in detecting and observing the exterior disease features. In the present investigation, CNN image processing algorithms are developed to detect disease by identifying the color feature of the defected area. Subsequently, the rotted area was segmented from an image, and the area of the rotted leaf portion was deduced from the Pepper and tomato plant feature data. The results showed a promising performance of this automatic vision-based system it is found 94% accuracy average in practice with easy validation in a large amount of data.

Keywords—Disease, Image Processing, Plant, Technology, Pictures

I. INTRODUCTION

In 2020 there are around 5 billion cell phone clients on the planet [1]. Of this, one billion clients are situated in India and a further one billion are found in Africa. As indicated by Statista, these figures have reliably risen each year for the most recent decade. With these realities as a main priority, it is accepted that AI applications will play a significant job in molding the eventual fate of cultivating.

The utilization of CNNs in plant disease arrangement has accomplished superb outcomes as of late. Due to the continuous rise of predominant outcomes, the multi-layered administered network has gotten positive among specialists. Since the arrival of Le-Net, CNN structures have changed significantly. Complex capacities, for example, Re-Lu

nonlinearity and covering pooling, have become a pervasive element in present-day design. Such advancements have assisted with lessening preparation time and mistake rate. Most importantly, the advancement of engineering has been a fundamental interest of enormous and complex 21st-century datasets [3].

One ongoing design; Res-Net presented further weighty capacities. This fuses dynamic skip associations just as weighty bunch standardization. This permit preparing to happen at a lot higher learning rate. In 2019, Wu et al., contrasted Res-Net with VGG-Net, Google-Le-Net, and Dense-Net, finding that Res-Net delivered the best outcomes in ordering grape leaf diseases. In current exploration; architectures including Alex-Net, Le-Net, and Google-Net, are ordinarily fused into the foundation of custom forms. Wall-Elgin proposed such a construct; in light of Le-Net, in his examination of Soybean disease order. The model comprised of three convolution layers, one max-pooling layer, and a completely associated MLP with Re-Lu actuation and accomplished a 91% accuracy rate [1].

Information pre-preparing is significantly critical to a model's execution. Viral, bacterial, and contagious diseases can be hard to recognize, regularly sharing a cover of indications. These manifestations can be any quantifiable contrast in shading, shape, or capacity which results as the plant reacts to the microbe. In light of this multifaceted nature, it is desirable to use RGB information. This produces clear, commotion-free pictures which may take longer than greyscale information to prepare, yet generally speaking, are more appropriate for plant disease distinguishing proof models.

More modest datasets or unvaried information can influence a model's dependability. This can be overseen severally, by utilizing procedures, for example, growth or move to learn. Enlarging preparing pictures cannot just decrease overfitting yet, can improve a model's general execution. This can be performed by adding capacities, for example, zoom, pivot, adding shading changes, or differentiation changes. The changed pictures should, nonetheless, mirror the assumptions of the approval dataset.

When improperly applied, a classifier's accuracy can deteriorate notwithstanding the additional information created.

The strategy for move learning has additionally demonstrated very fruitful when working with more modest datasets. This includes adjusting the loads of a pre-prepared model. The ImageNet information base is normally utilized for this reason and contains over 14 million pictures.

In 2016, Mohan-ty et al. uncovered these benefits in an examination that zeroed in on harvest disease arrangement. Here, unrivaled outcomes were recorded utilizing move learning ImageNet, contrasted with a model worked without any preparation. As ImageNet contains pictures superfluous to a plant explicit assignment, it is flawed whether pre-preparing on an herbal information base all things being equal may upgrade execution. Ebb and flow research recommends that pre-preparing on ImageNet may sum up better, in any case pre-preparing on a plant explicit assignment may lessen overfitting. These assertions, be that as it may, are uncertain. Due to the nonappearance of enormous organic datasets, the subject is generally neglected. Growth can likewise be applied to pertained models. Because of the information previously achieved by a particular model nonetheless, the impacts are more prominent when applied to un-prepared CNNs. The quality and sort of preparing information enormously impact the model's abilities. At the point when prepared on symbolism which contains plain foundation information, a classifier's accuracy gets subject to this creation. In this manner, it is prone to be untrustworthy when tried with in-field photography. A considerable lot of the accessible plant disease datasets including, the dataset, don't contain in-field symbolism [2]. The requirement for such a dataset is featured intensely in the examination.

Segmentation for this situation can demonstrate successful, by isolating a leaf from its experience. This strategy can besides be utilized in circumstances where the classifier requires scene mindfulness. For instance, this may include understanding the degree of microbe harm around the tainted tissue, instead of simply the contaminated tissue. Segmentation is certainly not another idea and has been applied to disease grouping undertakings since the 1990s. Indeed, even at this early stage, great outcomes were accounted for. Early examinations were moreover supportive in distinguishing the restrictions, demonstrating that the strategy couldn't beat helpless picture quality. Accordingly, focusing on the significance of cautious information assortment and preprocessing. The pertinence of segmentation proceeds into 2020 [1]. There is a lot of examination potential in joining this with particular symbolism.

The kind of preparing information utilized likewise figures out what stage of disease, location is conceivable. For early disease recognition, explicit symbolism should be utilized.

Chlorophyll fluorescent (CFI), infrared thermography (IRT), hyperspectral (HSI) and multispectral (MSI) symbolism have explicit capacities to distinguish manifestations that are not yet noticeable to the unaided eye. These can be utilized alone or joined where suitable. For the model, IRT has the remarkable capacity to recognize an expansion in temperature. This has been effective in

diagnosing crop diseases remembering fleece mold for roses and FHB in wheat, days before indications were noticeable. This subject of early location is moderately neglected due to the restricted accessibility of such information. The innovation expected to catch this particular symbolism is getting more moderate, with a developing scholastic premium in the region. At this stage, in any case, it's anything but an available instrument for distant ranchers. Accordingly, it is ridiculous to remember it for an undertaking expected for such clients.

II.LITERATURE REVIEW

Sardogan, M. et al shows a good farming depends on early disease diagnosis in agriculture. There are several diseases that influence the quality of tomato crops, such as bacterial spot, late bloom, septoria leaf spot, and yellow curled leaf disease. According to this article, tomato leaf disease detection and classification may be done using Convolutional Neural Network models based on Learning Vector Quantization (LVQ) algorithms. [8]

Researchers are working on ways to improve real-time illness diagnosis using Convolutional Neural Networks (CNN) so that suitable nutrients may be applied to avoid additional plant damage from pathogenic viruses. On a TensorFlow framework, new mathematical activation functions are constructed and compared with current activation functions. The suggested optimizer improves the training time of the CNN model by 83 percent when implemented in an ARM processor. [9]

As a result of inadequate diagnosis and failure to recognize the indications of such diseases, Shrestha, G. et al offers many crops perish each year. This study provides a detailed overview of plant disease detection using different methods. On sample images, for example, a study of temporal complexity and an analysis of the size of the infected zone are done. The exam has an accuracy of 88.80 percent. For each, there is a unique set of performance indicators. [10]

As smartphone penetration and computer vision models have grown in popularity, agricultural picture categorization has become possible. Images may be quickly and accurately diagnosed using Convolutional Neural Networks (CNNs), which are regarded the state-of-the-art in image identification. On average 97.2 percent accurate, the suggested approach achieves an F1 score over 95 percent. Using CNNs to classify plant diseases is technically feasible. [11]

Menon, V. et al shows India's agriculture has been the country's economic engine for centuries, and it has witnessed remarkable development and expansion throughout the years. Today, plant diseases are a major obstacle in agricultural production today. Plant tissue or specimens are traditionally examined by a specialist for disease severity, however this approach is wasteful and inconvenient. [12]

III.METHODOLOGY

A. Data Collection

More modest datasets or unvaried information can influence a model's unwavering quality. This can be overseen severally, by utilizing procedures, for example, expansion or move to learn. Increasing preparation pictures can diminish overfitting as well as can improve a model's

general execution. The quality and sort of preparing information hugely impact the model's abilities. At the point when prepared on symbolism which contains plain foundation information, a classifier's accuracy gets reliant on this structure. Consequently, it is probably going to be temperamental when tried with in-field photography. A considerable lot of the accessible plant disease datasets including, the Plant Village dataset [3], and added an enormous number of pictures information for better accuracy. Try not to contain in-field symbolism. The requirement for such a dataset is featured intensely in the examination.

B. Model selection

Model determination is the most significant part and probably the hardest piece of an exploration project. The accomplishment of any examination depends on the Data set and Model determination. On the off chance that the authors can pick the model effectively, there should be a positive result soon. Then again picking an awful one may prompt disappointment as a definite truth. For this, the authors have tried a few models with test information looking for the most reasonable one for the exploration project. In any case, from that whole inquiry, the authors have arrived at the resolution that Naive Byes Classifier calculation is the most effortless and the best one for us. At the point when the authors have discovered that it gives a simple to utilize the library, the authors comprehended that the classifier work would be simpler. Along these lines, the authors finished this model for utilization in the undertaking.

C. Image Pre-Processing and labeling

a) Data labeling is additionally a most significant part for makes code so quicker. It was the main piece of this work. Since it makes code quicker to run and less tedious for information preparation. The authors use Label Encoder in Python for naming information. Pictures downloaded from the Internet were in different arrangements alongside various goals and quality.

b) To improve highlight extraction, the last pictures planned to be utilized as the dataset for profound neural organization classifier were preprocessed to pick up consistency. Moreover, the method of picture preprocessing included trimming of the relative multitude of pictures physically, making the square around the leaves, feature the district of interest (plant leaves). During the period of gathering the pictures for the dataset, pictures with more modest goals and measurements under 500px were not considered as substantial pictures for the dataset. In that manner, it was guaranteed that pictures contain all the required data for highlight learning. Pictures utilized for the dataset were picture resized to lessen the hour of preparing, which was consequently processed by composing content in Python, utilizing the Open-CV system.

c) Numerous assets can be found via looking across the Internet, however, their pertinence is frequently temperamental. In light of a legitimate concern for affirming the accuracy of classes in the dataset, at first gathered by a watchwords search, agricultural specialists analyzed leaf pictures and marked all the pictures with suitable disease abbreviation. In this stage, copied pictures that were left after the underlying emphasis of social occasion and gathering pictures into classes depicted in Section 4.2 were

eliminated from the dataset, the input data of this project Fig.1, Fig.2, and Fig.3.




Fig.1. Pre-Processed Input Data Example Phase One - padding mode (reflection).




Fig.2. Pre-Processed Input Data Example Phase Two- brightness changes (0.4, 0.7).




Fig.3. Pre-Processed Rise Leaf Input Data Example Phase One.

D. Experimental Setup

This segment portrays the means engaged with making and sending the classifier. Order by CNN is partitioned into three stages that tackle separate assignments. All work engaged with this exploration was finished on one machine, with particulars recorded in Hardware & Software are Memory 8.0GB Processor Intel(R) Core™ i5-9300H CPU @ 2.40GHz Graphics NVIDIA GeForce RTX 2060 6GB GDDR6 Operating system Windows 10 Home 64.

E. Information Acquisition

All Potato and Tomato symbolism get from The Plant Village Dataset, an open-access store that contains altogether 12569 pictures and the authors added more data total train 19772 data. All Rice symbolism begins from the Rice Diseases Image Dataset [3]. For every species, a select number of classes are picked, with subtleties distinguishable in Table 4.2. To get to this, a test dataset containing 50 pictures, sourced from Google is set up. These pictures contain extra plant life structures, in-field foundation information, and fluctuating phases of the disease.

TABLE I. FINAL DATASET USED FOR CALCIFICATION.

Species	Class	No. of Images
Pepper	Pepper Bell	997
Pepper	Healthy	1478
Potato	Early Blight	986
Potato	Late Blight	989
Potato	Healthy	145
Tomato	Bacterial Spot	2115
Tomato	Leaf Mold	942
Tomato	Mosaic Virus	373
Tomato	Healthy	1581
Tomato	Target Spot	1404
Species	Class	No. of Images
Tomato	Curl Virus	3190
Tomato	Bacterial Spot	2117
Tomato	Early Blight	991
Early blight	Late Blight	1901
Rice	Brown Spot	204
Rice	Leaf Blast	164

F. Information Pre-Processing

The dataset is separated into 80% for preparing and 20% for approval. To begin with, increase settings are applied to the preparing information. These are created 'on the fly', with each activity conveying a weighted likelihood of showing up in every age. The settings applied incorporate flipping (arbitrary), cushioning mode (reflection) and zoom with crop (scale = (1.0, 1.5)). 'Zoom with crop' was later overlooked after finding that it had improperly trimmed zones of a contaminated leaf. At last, all pictures are re-sized and standardized. Resizing is completed utilizing a pack work, to 256 x 256. As a pre-prepared model is utilized, the RGB

ImageNet measurements are utilized to standardize. An example of the last pre-handled pictures is perceptible in Fig.1.

G. Arrangement by CNN

1) Phase One – Trialing of Image size: Stage one intends to explore the impact that picture size has on model execution. Altogether, five pictures estimated are tried going from 256 x 256 to 150 x 150. To start, the Resnet34 pre-prepared loads are downloaded. As a default of move learning, all layers with the besides of the last two layers are frozen. These contain new loads and are explicit to the plant disease order task.

Freezing permits these layers to be disease independently prepared, without back-propagating the angles. In precisely thusly, the 1cycle strategy is utilized to prepare the last layers. With this total, the leftover layers are delivered. To help the adjusting cycle, a plot showing learning rate versus misfortune is created and broke down. From this, reasonable learning is chosen, and the model is run. All means stay predictable in every preliminary including the learning rate. And the convolutional Operation processing in Fig 4. This info from CNN Calcification Model [5].




Fig 4. Input image processes by a convolutional layer

2) Phase Two – Model Optimization

Utilizing the most appropriate picture size, the ResNet34 model is enhanced. To additionally improve the model's presentation, extra growth settings are added. Activities incorporate splendor changes (0.4, 0.7) and twist (0.5). Next, the last two layers are disengaged and prepared at the default learning rate. With this total, tweaking is performed, running numerous preliminaries to test a progression of learning rates and the number of ages.

The Convolutional Operation:

Here are the three components that go into the convolution activity:

- Input image
- Feature detector
- Feature map

As should be obvious, the info picture is a similar smiley face picture that The authors had in the past instructional exercise. Once more, if you investigate the example of the 1's and 0's, you will have the option to make out the smiley face in there.

Once in a while a 5x5 or a 7x7 lattice is utilized as an element finder, however the more ordinary one, and that is the one that the authors will be working with, is a 3x3 grid. The component identifier is regularly alluded to as a "piece" or a "channel," which you may appear to be you dive into

other material on the point. It is smarter to recall the two terms to save yourself the disarray. They all allude to something very similar and are utilized conversely, remembering for this course. The convolutional operation is shown in Fig.5.




Fig.5. The Convolutional Operation

The authors can consider the component indicator a window comprising of 9 (3x3) cells. It's significant not to confound the component map with the other two components. The cells of the component guide can contain any digit, not exclusively 1's and 0's.

In the wake of going over each pixel in the information picture in the model above, the authors would wind up with these outcomes in Fig.6.

- The authors place it over the info picture starting from the upper left corner inside the lines the authors see separated above, and afterward, you include the number of cells in which the element locator coordinates the information picture.
- The quantity of coordinating cells is then embedded in the upper-left cell of the element map.
- The authors at that point move the element finder one cell to one side and do something very similar. This development is known and since the authors are moving the element indicator one cell at the time that would be known as a step of one pixel.

After you have experienced the entire first line, you would then be able to move it over to the following column and experience a similar cycle.




Fig.6. The Convolutional Operation Feature Map

Incidentally, much the same as highlight locator can likewise be alluded to as a bit of a channel, an element map is otherwise called an initiation map and the two terms are additionally exchangeable.

H. Full Connection

Here's the place where artificial neural networks and convolutional neural networks crash as the authors add the previous to last mentioned. It is here that the way toward

making a convolutional neural organization starts to take a more unpredictable and modern turn. How convolutional full connection work is shown in Fig.7. As The authors see from the picture beneath, the authors have three layers in the full association step:

- Input layer
- Fully-connected layer
- Output layer




Fig.7. The Convolutional Full Connection

The figure above fig.5., Fig.6., Fig.7. and Fig.8. are the information of the CNN Model [5].

IV.RESULT

A. Results & Analysis

The authors have run their dataset to create a model from the given data. It provided us with the desired output. Then, the authors have a validation column that gave us 95% accuracy in large-scale data. Then again, comparison between small scales averages in 90% accuracy. Besides, a comparison of age with the time and pass column was 94% accurate.

B. Effect of result Phase Two

The authors find the expected output by the code as appeared in Fig .8. The model predicts any of the classes from the class referenced previously.

```

model = Sequential()
model.add(Convolution2D(32, 3, 3, input_shape=(img_width, img_height,3)))
model.add(Activation('relu'))
model.add(MaxPooling2D(pool_size=(2, 2)))

model.add(Convolution2D(32, 3, 3))
model.add(Activation('relu'))
model.add(MaxPooling2D(pool_size=(2, 2)))

model.add(Convolution2D(64, 3, 3))
model.add(Activation('relu'))

model.add(Flatten())
model.add(Dense(64))
model.add(Activation('relu'))
model.add(Dropout(0.5))
model.add(Dense(1))
model.add(Activation('sigmoid'))

[ ] #Creating our main CNN model to augment images
from tensorflow.keras.layers import Dense, Conv2D, Flatten, Dropout, MaxPooling2D
model = Sequential([
    Conv2D(16, 3, padding='same', activation='relu', input_shape=(img_width, img_height, 3)),
    MaxPooling2D(),

    Conv2D(32, 3, padding='same', activation='relu'),
    MaxPooling2D(),

    Conv2D(64, 3, padding='same', activation='relu'),
    MaxPooling2D(),

    Flatten(),
    Dense(512, activation='relu'),

    Dense(1)
])

```

Fig.8. The Convolutional Model Code

Here the test output that the authors have given is plants leaf with leaf spot Phase Two Model Optimization Analysis on Fig.9., Fig.10., and Fig.11..




Fig.9. Plant Leaf Phase Two Model Optimization Analysis Test One




Fig.10. Plant Leaf Phase Two Model Optimization Analysis Test Two




Fig.11. Plant Leaf Phase Two Model Optimization Analysis Test Three

Hear in result analysis The authors can see the four data measurement figures are Fig.9., Fig.10., Fig.11.. Training the last layers ($lr=1e-3$) before tweaking the model accomplished an accuracy of 0.9465 and an F1 score of 0.9359. Learning rate Used to manage the tweaking cycle. As the learning rate increments past $1e-04$, an emotional expansion in misfortune is capable Fig 4.6. Fine-tuning the model, learning rate range = $1e-05$, $1e-04$ Signs of underfitting evident. The last advanced model, learning rate range = $1e-05$, $1e-04$. Preceding tweaking, the model accomplished an accuracy of 0.9465 and an F1 score of 0.9359 in (Fig 4.7). To help to adjust, a plot portraying learning rate (logarithmic scale) vs misfortune was examined (Fig.10.).

This shows a generally low misfortune between learning rates $1e-06$ to $1e-04$. As the learning rate increments past $1e-04$ be that as it may, an emotional expansion in misfortune is

capable. By tweaking this hyperparameter, a slight expansion inaccuracy (1.5%) and F1-Score (1.3%) were cultivated. On the last age, in any case, the end preparing and approval esteems demonstrate that the model might be marginally underfitting (Fig 4.8). To address this, the number of ages was expanded efficiently. At Approximately the tenth age, there was a clear improvement to the attack of the mode. The last perusing introduced a general improvement of 2.8% in accuracy and 3.1 % in F1-score (Fig 4.8). As expressed before, the approval dataset comprises of an unmistakable creation; one leaf and a plain foundation. For a precise perusing, much the same as those expressed in this part, utilization of the classifier should imitate this picture design. Now The authors provide the result table below Table II.

TABLE II. GENERAL RESULT PHASE ONE (10 EPOCHS, MAX_LR ($1E-05$, $1E-04$))

Test	Image size	Train Loss	Valid Loss	Accuracy	F1 Score
1	150	0.1550	0.1243	0.9604	0.9543
2	185	0.1574	0.1345	0.9422	0.9386
3	215	0.1775	0.1145	0.9729	0.9657
4	235	0.1285	0.1045	0.9341	0.9123
5	256	0.1553	0.1242	0.9232	0.9363

V.DISCUSSION

To forestall misfortunes, little holder ranchers are subject to an opportune and precise harvest disease finding. In this investigation, a pre-prepared Convolutional Neural Network was adjusted, what's more, the model was sent on the web. The eventual outcome was a plant disease identification application. This administration is free, simple to utilize, what's more, requires only a PDA and web association. Consequently, the client's necessities as characterized in this paper have been satisfied. A careful examination uncovered the capacities and constraints of the model. Generally, when approved in a controlled climate, an accuracy of 94.2% is introduced. This accomplished accuracy relies upon various components counting the phase of the disease, disease type, and foundation information also, object synthesis. Because of this, a bunch of client rules would be needed for business use, to guarantee the expressed accuracy is conveyed. As the model was prepared to utilize a plain foundation and solitary leaf, impersonation of these highlights is best. Enlargement and move learning for this situation, demonstrated gainfulness to the model, assisting the CNN with summing up additional dependability. While this improved the model's capacity to extricate highlights r, it was insufficient when the model was given 'in the field' symbolism. For this situation, the classifier positioned an accuracy of only 44% above every one of them, this Features the significance of enhancing the preparation dataset to incorporate elective foundation information, extra plant life structures, and fluctuating phases of the disease. Generally speaking, this investigation is definitive in exhibiting how CNNs might be applied to engage little holder ranchers in their battle against plant disease. Later on, work ought to be centered on differentiating preparing datasets and in testing comparative web applications, in actuality, circumstances. Without such turns of events, the battle against plant disease will proceed.

VII.CONCLUSION

To forestall misfortunes, little holder ranchers are subject to an opportune and precise harvest disease finding. In this modern era technology e.g. IoT [13-17], Cybersecurity[18], Machine Learning [19-24] and so on plays a vital role where in this investigation, a pre-prepared Convolutional Neural Network was adjusted, what's more, the model was sent on the web. The eventual outcome was a plant disease identification application. This administration is free, simple to utilize, what's more, requires only a PDA and web association. Consequently, the client's necessities as characterized in this paper have been satisfied. A careful examination uncovered the capacities and constraints of the model. Generally, when approved in a controlled climate, an accuracy of 94.2% is introduced. This accomplished accuracy relies upon various components counting the phase of the disease, disease type, and foundation information also, object synthesis. Because of this, a bunch of client rules would be needed for business use, to guarantee the expressed accuracy is conveyed. As the model was prepared to utilize a plain foundation and solitary leaf, impersonation of these highlights is best. Enlargement and move learning for this situation, demonstrated gainfulness to the model, assisting the CNN with summing up additional dependability. While this improved the model's capacity to extricate highlights r, it was insufficient when the model was given 'in the field' symbolism. For this situation, the classifier positioned an accuracy of only 44% above every one of them, this Features the significance of enhancing the preparation dataset to incorporate elective foundation information, extra plant life structures, and fluctuating phases of the disease. Generally speaking, this investigation is definitive in exhibiting how CNNs might be applied to engage little holder ranchers in their battle against plant disease. Later on, work ought to be centered on differentiating preparing datasets and in testing comparative web applications, in actuality, circumstances. Without such turns of events, the battle against plant disease will proceed.

REFERENCES

- [1] Plant Disease Detection using CNN, Emma Harte School of Computing National College of Ireland Mayor Street, IFSC, Dublin 1, Dublin, Ireland. Published by ComputerTechScience Team, Sunday, Sep 28, 2020.
- [2] Y.Toda and F. Okura, "How Convolutional Neural Networks Diagnose Plant Disease", *Plant Phenomics*, vol. 2019, pp. 1-14, 2019. Available: 10.34133/2019/9237136.
- [3] Huy Minh Do "Rice Diseases Image Dataset", Kaggle.com, 2020. [Online]. Available: <https://www.kaggle.com/minhhuy2810/ricediseases-image-dataset>. [Accessed: 26- Apr- 2020].
- [4] S.Bharath1, K.Vishal Kumar2, R.Pavithran3, CSE, SRM Institute of Science and Technology, Chennai, India. T.Malathi4, e-ISSN: 2395-0056 Volume: 07 Issue: 05 May 2020 www.irjet.net p-ISSN: 2395-0072.
- [5] The Ultimate Guide to Convolutional Neural Networks (CNN), Published by SuperDataScience Team Monday, Aug 27, 2018.
- [6] Yosuke Toda, and Fumio Okura, *Plant Phenomics* Volume 2019, Article ID 9237136, 14 pages <https://doi.org/10.34133/2019/9237136>, Received 22 November 2018; Accepted 11 February 2019; Published 26 March 2019.
- [7] Convolutional Neural Networks for Sentence Classification, Published by researchgate August 2014 DOI: 10.3115/v1/D14-1181 Source: arXiv.
- [8] Sardogan, M., Tuncer, A., & Ozen, Y. (2018, September). Plant leaf disease detection and classification based on CNN with LVQ algorithm. In 2018 3rd International Conference on Computer Science and Engineering (UBMK) (pp. 382-385). IEEE.
- [9] Yadhav, S. Y., Senthilkumar, T., Jayanthi, S., & Kovilpillai, J. J. A. (2020, July). Plant disease detection and classification using cnn model with optimized activation function. In 2020 International Conference on Electronics and Sustainable Communication Systems (ICESC) (pp. 564-569). IEEE.
- [10] Shrestha, G., Das, M., & Dey, N. (2020, October). Plant Disease Detection Using CNN. In 2020 IEEE Applied Signal Processing Conference (ASPCON) (pp. 109-113). IEEE.
- [11] Harte, E. (2020). Plant disease detection using CNN (Doctoral dissertation, Ph. D. thesis).
- [12] Menon, V., Ashwin, V., & Deepa, R. K. (2021, June). Plant Disease Detection using CNN and Transfer Learning. In 2021 International Conference on Communication, Control and Information Sciences (ICCIIS) (Vol. 1, pp. 1-6). IEEE.
- [13] Mohd. Saifuzzaman, Ashraf Hossain Khan, Nazmun Nessa Moon and Fernaz Narin Nur "Smart Security for an Organization Based on IoT" on International Journal of Computer Applications (IJCA), Volume 165, Number 10, May 2017, New York, USA.
- [14] Mohd. Saifuzzaman, Nazmun Nessa Moon & Fernaz Narin Nur, "IoT Based Street Lighting and Traffic Management System" on IEEE Region 10 Humanitarian Technology Conference (R10-HTC), 2018, BUET, Dhaka, Bangladesh.
- [15] Mohd. Saifuzzaman, Syeda Farjana Shetu, Nazmun Nessa Moon, Fernaz Narin Nur and Mohammad Hanif Ali "IoT Based Street Lighting Using Dual Axis Solar Tracker and Effective Traffic Management System Using Deep Learning: Bangladesh Context" on 11th International Conference on Computing, Communication And Networking Technologies (ICCCNT 2020), July 1-3, 2020, IIT Kharagpur, West Bengal, India.
- [16] Rakib Hasan, Sajedul Islam, Md. Habibur Rahman, Mohd. Saifuzzaman, Syeda Farjana Shetu and Nazmun Nessa Moon, "Implementation of Low Cost Real-time Attendance Management System: A Comparative Study" on IEEE 8TH International Conference on Reliability, Infocom Technologies and Optimization (ICRITO'2020), MARCH 5-6, 2020 / AMITY UNIVERSITY, NOIDA, INDIA.
- [17] Mahadi Hasan, Dipto Saha, Jannatul Ferdosh, Nazmun Nessa Moon, Mohd. Saifuzzaman, Fernaz Narin Nur, "BSSID based Monitoring Class Attendance System Using WiFi" on 3rd International conference on I-SMAC (IoT in Social, Mobile, Analytics and Cloud) (I-SMAC 2019), The IEEE provides SCOPUS with all of the IEEE Xplore digital library, 12-14, DECEMBER 2019, Palladam, India.
- [18] Syeda Farjana Shetu, Mohd. Saifuzzaman, Nazmun Nessa Moon and Fernaz Narin Nur "A Survey of Botnet in Cyber Security" on 2nd International Conference On Intelligent Communication and Computational Techniques (ICCT-2019), IEEE Conference, Manipal University, Jaipur, India.
- [19] Shetu, S.F., Jahan, I., Islam, M.M., Hossain, R.A., Moon, N.N. and Nur, F.N. (2021). Predicting Satisfaction of Online Banking System in Bangladesh by Machine Learning. 2021 International Conference on Artificial Intelligence and Computer Science Technology (ICAICST), 29th - 30th June 2021, Tangerang Selatan, Indonesia | Online Zoom. Indexing: IEEE Xplore Digital Library.
- [20] Saifuzzaman, M., Parvin, M., Jahan, I., Moon, N.N., Nur, F.N. and Shetu, S.F. (2021). Machine Learning Approach to Predict SGPA and CGPA. 2021 International Conference on Artificial Intelligence and Computer Science Technology (ICAICST), 29th - 30th June 2021, Tangerang Selatan, Indonesia | Online Zoom. Indexing: IEEE Xplore Digital Library.
- [21] Mohd. Saifuzzaman, Md Mosfikur Rahman, Syeda Farjana Shetu, Nazmun Nessa Moon (2021) "COVID-19 and Bangladesh: Situation Report, Comparative Analysis, and Case Study" on Current Research in Behavioral Sciences, Elsevier, 100034. doi: <https://doi.org/10.1016/j.crbeha.2021.100034>
- [22] Syeda Farjana Shetu, Md Mosfikur Rahman, Akash Ahmed, Mahfuja Ferdousi Mahin, Md Abtab Uddin Akib, Mohd. Saifuzzaman (2021) "Impactful E-Learning Framework: A New Hybrid Form of Education" Current Research in Behavioral Sciences, Elsevier, 100038. doi: <https://doi.org/10.1016/j.crbeha.2021.100038>
- [23] Md Mosfikur Rahman, Mohd. Saifuzzaman, Akash Ahmed, Mahfuja Ferdousi Mahin, Syeda Farjana Shetu (2021) "Impact of COVID-19 on Mental Health: A Quantitative Analysis of Anxiety and Depression Based on Regular Life and Internet Use" Current

Research in Behavioral Sciences, Elsevier, 100037.
doi: <https://doi.org/10.1016/j.crbeha.2021.100037>

- [24] Saif Mahmud Khan Durjoy, Abu Mohammed Rabbani Rafi, Zerine Nasrin Tumpa and Mohd. Saifuzzaman, "A Comparative Study on

Prediction of Dengue Fever Using Machine Learning Algorithm" on The First International Conference on Advances in Distributed Computing and Machine Learning(ICADCML-2020) on 30th and 31st January 2020