



Cataloguing and visualizing big Geodata

Final report

Martín Domínguez Durán¹

1. Wageningen University & Research, Wageningen, The Netherlands



Registration number: 1254246

Period of Internship: 2024-04-08 - 2024-08-08

Date final report: 2024-07-31

Telephone number student: +31651120353

Name of Company: Satelligence B.V.

Host supervisor: Luca Foresta

MGI supervisor: Lukasz Grus

Table of contents

1	Introduction	1
1.1	Internship organization background	1
1.2	Context and justification of research	1
1.2.1	Significance of the topic	1
1.2.2	Added value of this research	3
1.3	Research questions	4
2	Methodology	5
2.1	Data and processing code familiarization	6
2.1.1	Cloud services familiarization	6
2.2	Baseline scenario definition	6
2.3	Data integration	6
2.3.1	Local STAC creation and browsing	6
2.3.2	Organization of main STAC structure & extensions per asset . . .	7
2.3.3	Build main STAC v.0.1	8
2.3.4	Set up STAC browser on GCP	9
2.3.5	Automate processes via CI pipeline	9
2.4	Performance assessment	9
3	Discussion	10
4	Future work	11
5	Internship planning	12
5.1	Gantt chart	12
6	References	14

List of Figures

2.1	Internship flowchart	5
2.2	Initial proposed STAC structure	8

1 Introduction

1.1 Internship organization background

Satelligence is a company founded in 2016 that specializes in providing satellite-based actionable information by monitoring environmental risks in commodity supply chains and financial investment planning (Satelligence, n.d.). More specifically, the company processes terabytes of satellite imagery to detect environmental risks and presents this information to their clients in a web application to assist them in the migration towards more sustainable sourcing models and the compliance with deforestation-free regulations, such as the EUDR (Satelligence, 2023).

1.2 Context and justification of research

Satelligence currently employs cloud computing, specifically Kubernetes, to process extensive volumes of satellite imagery amounting to terabytes. While this processing workflow currently runs smoothly, the company's data team faces challenges when going deeper into the analysis and accessing intermediate results due to the big nature of this data (Satelligence, 2023). Scholars have defined big data as datasets characterized by their high Volume, Velocity, and Variety, which makes it paramount to use advanced processing and analytics techniques to derive relevant insights (Giri and Lone, 2014). In the specific case of Satelligence, their datasets can be categorized as big data due to their: High volume (Terabytes of satellite images processed every day), high velocity (Near – real time processing of these images) and high variety (Imagery coming from different sensors and regions). All these datasets are a specific case of big data: Big Geodata.

1.2.1 Significance of the topic

In the past decades there has been a rapid increase in the amount and size of geospatial information that can be accessed. Nowadays, more than 150 satellites orbit the earth collecting thousands of images every single day (Zhao et al., 2021). This has made data handling and the introduction of spatial data infrastructures (SDIs) paramount when working with such big datasets.

1 Introduction

Traditionally, SDIs have served to ease the accessibility, integration and analysis of spatial data (Rajabifard and Williamson, 2001). However, in practice SDIs have been built upon technologies that focus on data preservation rather than accessibility (Durbha et al., 2023). Due to this, an important shift is underway towards more cloud-based SDIs. These platforms need the emergence of new technologies that prioritize seamless access to cloud-stored data, efficient discovery services that ensure the easy location of extensive spatial data, and data visualization interfaces where multiple datasets can be depicted.

1.2.1.1 Cloud-based data storage

Spatial data, just like any other type of data, can be catalogued into structured and unstructured data. Structured datasets are often organized and follow a specific structure (i.e. A traditional table with rows (objects) and columns (features)). On the other hand, unstructured data does not have a predefined structure (e.g. Satellite imagery and Time series data) (Mishra and Misra, 2017). The management of structured data has witnessed substantial advancements, making it straightforward to handle it systematically using, for instance, relational databases (i.e. With the help of Structured Query Language (SQL)) (Kaufmann and Meier, 2023). In contrast, due to the additional challenges associated with the handling of unstructured data, the developments in this area have taken a longer time to appear.

The emergence of cloud-based archives has been one of the main advancements for unstructured data management during the last decades. In the specific case of geo-spatial data, it has allowed to store terabytes of unstructured data (i.e. Satellite imagery) on the cloud and access it through the network. However, the necessity transmitting data across networks to access it makes it essential to develop new data formats suited for such purposes (Durbha et al., 2023).

Cloud-Optimized GeoTIFFs (COGs) are an example of data formats that have been created to ease the access of data stored in the cloud. They improve the readability by including the metadata in the initial bytes of the file stored and storing different image tiles for different scales. These characteristics make COGs heavier than traditional image formats, however, they also greatly enhance accessibility by enabling the selective transfer of only the necessary tiles (Durbha et al., 2023).

Another cloud native data format that has gained popularity recently is Zarr. This data format and python library focuses on the cloud-optimization of n-dimensional arrays. Zarr differently than COGs store the metadata separately from the data chunks. Normally, using external JSON files (Durbha et al., 2023).

1.2.1.2 Data discovery services

A discovery service widely used for the exploration of big geodata (e.g. COGs) is Spatio-Temporal Asset Catalog (STAC). Through the standardization of spatial data, STAC

1 Introduction

simplifies the management and discovery of big geodata (Brodeur et al., 2019). This service works by organizing the data into catalogs, collections, items, and assets that will only be read when a computation is required (Durbha et al., 2023). This feature optimizes workflows by reducing unnecessary data loading.

1.2.1.2.1 STAC fundamentals

A Catalog built under STAC specifications is composed by:

Table 1.1: STAC components

STAC components	Description
<i>Assets</i>	An asset can be any type of data with a spatial and a temporal component.
<i>Items</i>	An item is a GeoJSON feature with some specifications like: Time, Link to the asset (e.g. Google bucket)
<i>Collections</i>	Defines a set of common fields to describe a group of Items that share properties and metadata
<i>Catalogs</i>	Contains a list of STAC collections, items or can also contain child catalogs.

1.2.1.3 Visualization interfaces

The visualization of spatial data brings with it a series of challenges due to its big nature. Dynamic tiling libraries such as *TiTiler* have tackled multiple of these challenges by dynamically generating PNG/JPEG image tiles only when requested without reading the entire source file into memory (*TiTiler*, n.d.). This feature optimizes rendering of images since PNG and JPEG image file formats are more easily transferred through the web.

1.2.2 Added value of this research

This research aims to develop a STAC catalog to facilitate the discovery of diverse big geospatial datasets created by different teams within the company. Depending on the time available for the thesis, data visualization functionalities may be integrated. Moreover, the research will explore tools to efficiently manage a STAC catalog containing both static and dynamic datasets.

1.3 Research questions

- What are the current challenges, practices, and user experiences related to data discovery and data visualization in the company?
- How does the integration of cloud-optimized data formats, cloud services and SpatioTemporal Asset Catalog (STAC) specifications influence the process and experiences of discovering big spatial data?
- To what extent do dynamic tiling services can perform in visualizing different cloud-optimized data formats?

2 Methodology

To address the proposed research questions, a series of activities and the deliverables expected from them are presented on Figure 2.1. Additionally, a detailed description of each activity is presented in the following subsections.




Figure 2.1: Internship flowchart

2.1 Data and processing code familiarization

In this step, I will familiarize myself with the current tools used for the processing of the images and its storage. This step will include the understanding of cloud services and internal image processing tools and the main datasets to be referenced on the catalog (STAC data). Moreover, in this step an initial description of the STAC data metadata will be performed.

2.1.1 Cloud services familiarization

An overview of the cloud services used by the company will be described. This will be mainly with the objective to understand, but not limited to:

- Who access the data?
- What are the costs of accessing it?
- How often certain data is updated?
- How is the data updated?

2.2 Baseline scenario definition

The baseline scenario was defined as the set of methods currently being used by members of different teams at Satelligence to find, retrieve and visualize spatial data. This baseline scenario was evaluated qualitatively by interviewing four members of two different teams in the company (i.e. The data and the operations team). To keep a balance regarding experience of the study subjects, both the newest member of each team and a member with at least three years in the company were interviewed.

The questions asked during the interviews were oriented towards two main topics that were covered during this internship: Spatial data discovery and spatial data visualization. For both topics, the questions were divided into questions related to raster and vector datasets. The questions included in the interview can be found in appendix ### and were meant to be open questions with multiple possible answers.

2.3 Data integration

2.3.1 Local STAC creation and browsing

This step will mainly be focused on the set up of the developing environment to both create a local STAC catalog and browse through it. This will include:

2 Methodology

1. Creation of a virtual environment or Docker container with all the required packages to create a STAC catalog.
2. Creation of Local STAC using sample data from the company.
3. Browse through the STAC catalog using tools like STAC browser.

The **deliverable** of this step will be a GitLab repository with code to create a catalog, add assets from a local directory and browse through them locally using STAC browser.

2.3.2 Organization of main STAC structure & extensions per asset

In this step the structure of the STAC catalog will be defined. This will involve the selection of datasets that will be referenced on the catalog, the definition of subcatalogs and/or collections to group items with similar metadata. An initial idea of the structure of the main STAC catalog can be seen on Figure 2.2. Initially, the creation of two different subcatalogs is proposed to keep the static and dynamic dataset separated. Moreover, the selection of the STAC extensions¹ used for each dataset will be defined in this step.

¹STAC extensions are additional metadata properties that can be added to a dataset. (e.g. Classes, bands, sensor-type, etc.)

2 Methodology




Figure 2.2: Initial proposed STAC structure

2.3.3 Build main STAC v.0.1

This step will focus on the building of the initial version of the main STAC catalog, once the datasets and the overall structure has been defined. It will involve the population of the catalog with STAC components following the defined structure on Section 2.3.2. Furthermore, on this step a series of validation tools will be used to check that the STAC catalog created follows the STAC specification. These tools are part of the python package `stac-tools`.

The **deliverable** of this step will be a GitLab repository with code to create a catalog, create collections, add assets from a directory on the cloud and update them.

2.3.4 Set up STAC browser on GCP

In this step a version of the STAC Browser application will be deployed using the tools from Google Cloud Platform (GCP). This application will allow users to browse and interact with the STAC catalog through a user-friendly interface. Additionally, this step will involve the definition of resources and tools from GCP that will be employed to deploy the application. For instance, the decision of doing it through a virtual machine or on a containerized way will be made.

The **deliverable** of this step will be a the STAC browser application running on GCP.

2.3.5 Automate processes via CI pipeline

Finally, the code to create, modify and/or deploy the STAC catalog will be merged into a continuous integration pipeline that will allow the integration of this catalog with other tools from the company. For instance, the Distributed Processing Framework (DPROF), which is satelligence’s Satellite Data Processing engine.

2.4 Performance assessment

The assessment of the performance of the new Data Catalog will be measured using the baseline scenario established at the beginning of the internship and the Speed Up metric proposed by (Durbha et al., 2023):

$$SpeedUp = \frac{t_{baseline}}{t_{catalog}}$$

This metric explains how much the process to access data has sped up thanks to the integration of cloud-based storage, the data catalog and the browsing interface.

3 Discussion

4 Future work

5 Internship planning

Internship duration: 08/04/2024 - 08/08/2024 (4 months)

5.1 Gantt chart

%%| fig-width: 100% gantt title Internship Gantt Chart dateFormat DD-MM-YYYY
excludes weekends todayMarker off axisFormat %d-%m

section Proposal

Writing & reviewing :active, 08-04-2024, 29-04-2024

section Data & Code familiarization

General code :29-04-2024, 4d

Cloud servives :01-05-2024, 4d

section Baseline scenario determination

Define the components of a baseline scenario : 06-05-2024, 1d

Test the baseline times : 07-05-2024, 3d

section Data integration

Local STAC creation & Browsing : done, 08-04-2024, 25-04-2024

Main STAC structure : main_s, 10-05-2024, 2d

Build main STAC v0.1 : after main_s, 21d

Set up STAC browser : stac_b, 28-05-2024, 15d

Automation via CI pipeline : end_data_int, after stac_b, 15d

Refinement : after end_data_int, 21d

section Performance assessment

Evaluate new discovery times : after stac_b, 2d

section Report writing

Writing : 29-04-2024, 19-07-2024

Review : 19-07-2024, 26-07-2024

Reflection paper writing : 26-07-2024, 07-08-2024

5 *Internship planning*

section Important dates

Midterm evaluation

:milestone, 10-06-2024, 24h

Submission of report

:milestone, 26-07-2024, 24h

Final examination

:milestone, 22-08-2024, 24h

“ —>

6 References

- Brodeur, J., Coetzee, S., Danko, D., Garcia, S. and Hjelmager, J. (2019). Geographic Information Metadata—An Outlook from the International Standardization Perspective. *ISPRS International Journal of Geo-Information*, 8(6), 280. p. <https://doi.org/10.3390/ijgi8060280>
- Durbha, S. S., Sanyal, J., Yang, L., S Chaudhari, S., Bhangale, U., Bharambe, U. and Kurte, K. (2023). *Advances in Scalable and Intelligent Geospatial Analytics: Challenges and Applications* (1st ed.). CRC Press. <https://doi.org/10.1201/9781003270928>
- Giri, K. and Lone, T. (2014). Big Data -Overview and Challenges. *International Journal of Advanced Research in Computer Science and Software Engineering*, 4.
- Kaufmann, M. and Meier, A. (2023). Database Management. In M. Kaufmann and A. Meier (Eds.), *SQL and NoSQL Databases: Modeling, Languages, Security and Architectures for Big Data Management* (1–24. pp.). Springer Nature Switzerland. https://doi.org/10.1007/978-3-031-27908-9_1
- Mishra, S. and Misra, A. (2017). Structured and Unstructured Big Data Analytics. *2017 International Conference on Current Trends in Computer, Electrical, Electronics and Communication (CTCEEC)*, 740–746. pp. <https://doi.org/10.1109/CTCEEC.2017.8454999>
- Rajabifard, A. and Williamson, I. P. (2001). *Spatial data infrastructures: Concept, SDI hierarchy and future directions*. <http://hdl.handle.net/11343/33897>
- Satelligence. (n.d.). Home - Satelligence - Sustainability monitoring simplified. In *Satelligence*. Retrieved February 5, 2024, from <https://satelligence.com/>
- Satelligence. (2023). *Internship: Cataloguing and visualizing big geodata*.
- TiTiler. (n.d.). Retrieved February 19, 2024, from <https://developmentseed.org/titiler/>
- Zhao, Y., Yang, X. and Vatsavai, R. R. (2021). A Scalable System for Searching Large-scale Multi-sensor Remote Sensing Image Collections. *2021 IEEE International Conference on Big Data (Big Data)*, 3780–3783. pp. <https://doi.org/10.1109/BigData52589.2021.9671679>