
Web Services (POST and Error Handling) in VUE

Objectives

- Make POST, PUT, and DELETE requests using Axios
- Catch and handle errors using Axios
- Explain what Cross-Origin Resource Sharing is and how it works
- Explain the cross-origin request process
- Explain why developers might encounter CORS errors when testing APIs on localhost

POST, PUT, & DELETE

HTTP Methods



Axios Post

```
axios
   .post("https://pokeapi.co/api/v2/pokedex/kanto/")
   .then(response => {
     this.pokemon = response.data;
})
   .catch(err => {
     console.log(err);
});
```

Axios Put

```
let userData = {
  firstName: 'Fredrick',
  lastName: 'Smith'
};

axios.put('/users/23', userData)
  .then((response) => {
    console.log(response);
  });
```

Axios Delete

```
axios.delete(process.env.VUE_APP_BASE_URL + 'api/users/1/', config)
   .then(function (response) {
     console.log(response)
   })
   .catch(function (error) {
     console.log(error)
   })
```

Axios Verbs

```
getItem(id) {
  return http.get(`/items/${id}`);
},
update(myItem) {
  return http.put(`/items/${myItem.id}`, myItem);
},
create(myItem) {
  return http.post('/items', myItem);
},
delete(myItem) {
  return http.delete(`/items/${myItem.id}`);
```

Let's look at the code!



Promise Error Handling

.catch method


Runs if:

- Server responds with no 2xx response code (2xx codes are "success" messages)
- Server fails to respond due to error
- Something happened that triggered an error.

Services


```
1 import axios from 'axios';
 3 // Create our Axios instance used to communicate with the server
 4 const http = axios.create({
 5 baseURL: 'https://some.url.net'
6 });
 8 export default { // This object is what other files will import via the import keyword
      getAllItems() {
10
         return <a href="http.get('/items');">http.get('/items');</a> // This is added to the end of baseURL specified above
12
      },
13
      getItem(id) {
       return http.get(`/items/${id}`);
15
16
      },
17
      update(myItem) {
19
       return http.put(`/items/${myItem.id}`, myItem);
20
      },
21
22
      create(myItem) {
       return http.post('/items', myItem);
24
      },
25
26
      delete(myItem) {
27
        return http.delete(`/items/${myItem.id}`);
28
29
30 };
```

Let's Code!




Your code can't crash if you never run it





Access-Control-Allow-Origin: https://github.com




CORS (Cross-Origin Resource Sharing): A mechanism that allows a website on one url to request data from a different url.






BUT WAIT, THERE'S MORE!



BUT WAIT, THERE'S MORE!



memegenerator.ne

Handling CORS on Java Backend


```
import javax.validation.Valid;

@RestController

@CrossOrigin

public class AuthenticationController {

private final TokenProvider tokenProvider;
 private final AuthenticationManagerBuilder authenticationManagerBuilder;
 private UserDAO userDAO;
```



The CORS mechanism supports secure cross-origin requests and data transfers between browsers and servers. Modern browsers use CORS in APIs such as XMLHttpRequest or <u>Fetch</u> to mitigate the risks of cross-origin HTTP requests.

https://developer.mozilla.org/en-US/docs/Web/HTTP/CORS

https://auth0.com/blog/cors-tutorial-a-guide-to-cross-origin-resource-sharing/

Objectives

- Make POST, PUT, and DELETE requests using Axios
- Catch and handle errors using Axios
- Explain what Cross-Origin Resource Sharing is and how it works
- Explain the cross-origin request process
- Explain why developers might encounter CORS errors when testing APIs on localhost