RAJALAKSHMI ENGINEERING COLLEGE

Mohammed Riyan M 250701436-2025-CSE

M2

| | |
|---|---|
| **Started on** | Monday, 5 October 2026, 8:19 AM |
| **State** | Finished |
| **Completed on** | Monday, 5 October 2026, 8:44 AM |
| **Time taken** | 24 mins 37 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

| | | | | | | |
|---|---|---|---|---|---|---|
| s1 | a | g | **g** | **t** | **a** | **b** |
| s2 | **g** | x | **t** | **x** | **a** | **y** | **b** |

**The length is 4**

Solveing it using Dynamic Programming

**For example:**

| Input | Result |
|---|---|
| aab<br>azb | 2 |

**Answer:** (penalty regime: 0 %)

```c
#include <stdio.h>
#include <string.h>

int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    char s1[100], s2[100];
    int dp[101][101];
    int n, m, i, j;

    scanf("%s", s1);
    scanf("%s", s2);

    n = strlen(s1);
    m = strlen(s2);


    for (i = 0; i <= n; i++)
        dp[i][0] = 0;

    for (j = 0; j <= m; j++)
        dp[0][j] = 0;


    for (i = 1; i <= n; i++) {
        for (j = 1; j <= m; j++) {
            if (s1[i - 1] == s2[j - 1]) {
                dp[i][j] = dp[i - 1][j - 1] + 1;
            } else {
                dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
            }
        }
    }

    printf("%d\n", dp[n][m]);

    return 0;
}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | aab<br>azb | 2 | 2 | ✔ |
| ✔ | ABCD<br>ABCD | 4 | 4 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course