

Lambda functions

INTERMEDIATE PYTHON FOR DEVELOPERS



George Boorman

Curriculum Manager, DataCamp

Simple functions

```
def average(values):  
    average_value = sum(values) / len(values)  
    return average_value
```

Lambda functions

- `lambda` keyword
 - Represents an *anonymous function*

`lambda`

Lambda functions

- `lambda` keyword
 - Represents an *anonymous function*

`lambda` argument(s)

Lambda functions

- `lambda` keyword
 - Represents an *anonymous function*

`lambda` argument(s):

Lambda functions

- `lambda` keyword
 - Represents an *anonymous function*
 - **Can** store as a variable and call it

```
lambda argument(s): expression
```

- Convention is to use `x` for a single argument
- The `expression` is the equivalent of the function body
- No `return` statement is required

Creating a lambda function

```
# Lambda average function  
lambda x: sum(x) / len(x)
```

```
<function __main__.<lambda>(x)>
```

```
# Custom average function  
def average(x):  
    return sum(x) / len(x)
```

```
average
```

```
<function __main__.average(x)>
```

Using lambda functions

```
# Get the average  
(lambda x: sum(x) / len(x))
```


Using lambda functions

```
# Get the average  
(lambda x: sum(x) / len(x))([3, 6, 9])
```

```
6.0
```

Storing and calling a lambda function

```
# Store lambda function as a variable
average = lambda x: sum(x) / len(x)

# Call the average function
average([3, 6, 9])
```

```
6.0
```

Multiple parameters

```
# Lambda function with two arguments  
(lambda x, y: x**y)(2, 3)
```

8

Lambda functions with iterables

- `map()` applies a function to **all** elements in an iterable

```
names = ["john", "sally", "leah"]  
# Apply a lambda function inside map()  
capitalize = map(lambda x: x.capitalize(), names)  
print(capitalize)
```

```
<map object at 0x7fb200529c10>
```

```
# Convert to a list  
list(capitalize)
```

```
['John', 'Sally', 'Leah']
```

Custom vs. lambda functions

Scenario	Function Type
Complex task	Custom
Same task several times	Custom
Simple task	Lambda
Performed once	Lambda

Let's practice!

INTERMEDIATE PYTHON FOR DEVELOPERS

Introduction to errors


INTERMEDIATE PYTHON FOR DEVELOPERS



George Boorman
Curriculum Manager, DataCamp

What is an error?

- Code that violates one or more rules
- Error = Exception
- Cause our code to terminate!



¹ <https://docs.python.org/3/library/exceptions.html#exception-hierarchy>

TypeError

- Incorrect data type

```
"Hello" + 5
```

```
-----  
TypeError
```

```
Traceback (most recent call last)
```

```
Cell In[1], line 1
```

```
----> 1 "Hello" + 5
```

```
TypeError: can only concatenate str (not "int") to str
```

ValueError

```
float("Hello")
```

```
-----  
ValueError                                Traceback (most recent call last)  
Cell In[2], line 1  
----> 1 float("Hello")  
  
ValueError: could not convert string to float: 'Hello'
```

- The value is not acceptable in an acceptable range

```
float("2")
```

```
2.0
```

Tracebacks

ValueError

Cell In[2], line 1

----> 1 float("Hello")


ValueError: could not convert string to float: 'Hello'

Traceback (most recent call last)



Tracebacks

```
-----  
ValueError                                Traceback (most recent call last)  
Cell In[2], line 1  
----> 1 float("Hello")  
  
ValueError: could not convert string to float: 'Hello'
```



Tracebacks

ValueError

Traceback (most recent call last)

Cell In[2], line 1

----> 1 float("Hello")

ValueError: could not convert string to float: 'Hello'

Code in packages

- Packages contain other people's code e.g., custom functions
- Known as source code
- `pip install <package>` downloads source code to our local environment
- The pandas' `pd.read_csv()` function executes the code written for that custom function behind the scenes

Tracebacks from packages

```
# Import pandas package
import pandas as pd

# Create pandas DataFrame
products = pd.DataFrame({"ID": "ABC1",
                        "price": 29.99})

# Try to access the non-existent "tag" column
products["tag"]
```

Tracebacks from packages

```

KeyError                                Traceback (most recent call last)
File /usr/local/lib/python3.8/dist-packages/pandas/core/indexes/base.py:3803, in Index.get_loc(self, key, method, tolerance)
    3802 try:
-> 3803     return self._engine.get_loc(casted_key)
    3804 except KeyError as err:

File /usr/local/lib/python3.8/dist-packages/pandas/_libs/index.pyx:138, in pandas._libs.index.IndexEngine.get_loc()

File /usr/local/lib/python3.8/dist-packages/pandas/_libs/index.pyx:165, in pandas._libs.index.IndexEngine.get_loc()

File pandas/_libs/hashtable_class_helper.pxi:5745, in pandas._libs.hashtable.PyObjectHashTable.get_item()

File pandas/_libs/hashtable_class_helper.pxi:5753, in pandas._libs.hashtable.PyObjectHashTable.get_item()

KeyError: 'tag'

The above exception was the direct cause of the following exception:

KeyError                                Traceback (most recent call last)
Cell In[5], line 9
      5 products = pd.DataFrame({"ID": ["ABC1", "ABC2", "ABC3"],
      6                        "price": [29.99, 39.95, 51.25]})
      8 # Try to access the non-existent "tag" column
----> 9 products["tag"]

File /usr/local/lib/python3.8/dist-packages/pandas/core/frame.py:3804, in DataFrame.__getitem__(self, key)
    3802 if self.columns.nlevels > 1:
    3803     return self._getitem_multilevel(key)
-> 3804 indexer = self.columns.get_loc(key)
    3805 if is_integer(indexer):
    3806     indexer = [indexer]

File /usr/local/lib/python3.8/dist-packages/pandas/core/indexes/base.py:3805, in Index.get_loc(self, key, method, tolerance)
    3803     return self._engine.get_loc(casted_key)
    3804 except KeyError as err:
-> 3805     raise KeyError(key) from err
    3806 except TypeError:
    3807     # If we have a listlike key, _check_indexing_error will raise
    3808     # InvalidIndexError. Otherwise we fall through and re-raise
    3809     # the TypeError.
    3810     self._check_indexing_error(key)

KeyError: 'tag'
```


Tracebacks from packages

```
-----
KeyError                                Traceback (most recent call last)
File /usr/local/lib/python3.8/dist-packages/pandas/core/indexes/base.py:3803, in Index.get_loc(self, key, method, tolerance)
    3802 try:
-> 3803     return self._engine.get_loc(casted_key)
    3804 except KeyError as err:

File /usr/local/lib/python3.8/dist-packages/pandas/_libs/index.pyx:138, in pandas._libs.index.IndexEngine.get_loc()

File /usr/local/lib/python3.8/dist-packages/pandas/_libs/index.pyx:165, in pandas._libs.index.IndexEngine.get_loc()

File pandas/_libs/hashtable_class_helper.pxi:5745, in pandas._libs.hashtable.PyObjectHashTable.get_item()

File pandas/_libs/hashtable_class_helper.pxi:5753, in pandas._libs.hashtable.PyObjectHashTable.get_item()

KeyError: 'tag'

The above exception was the direct cause of the following exception:
```

Tracebacks from packages

```
KeyError                                Traceback (most recent call last)
Cell In[5], line 9
      5 products = pd.DataFrame({"ID": ["ABC1", "ABC2", "ABC3"],
      6                          "price": [29.99, 39.95, 51.25]})
      8 # Try to access the non-existent "tag" column
----> 9 products["tag"]
```

Tracebacks from packages

```
File /usr/local/lib/python3.8/dist-packages/pandas/core/frame.py:3804, in DataFrame.__getitem__(self, key)
    3802 if self.columns.nlevels > 1:
    3803     return self._getitem_multilevel(key)
-> 3804 indexer = self.columns.get_loc(key)
    3805 if is_integer(indexer):
    3806     indexer = [indexer]

File /usr/local/lib/python3.8/dist-packages/pandas/core/indexes/base.py:3805, in Index.get_loc(self, key, method, tolerance)
    3803     return self._engine.get_loc(casted_key)
    3804 except KeyError as err:
-> 3805     raise KeyError(key) from err
    3806 except TypeError:
    3807     # If we have a listlike key, _check_indexing_error will raise
    3808     # InvalidIndexError. Otherwise we fall through and re-raise
    3809     # the TypeError.
    3810     self._check_indexing_error(key)

KeyError: 'tag'
```

Let's practice!

INTERMEDIATE PYTHON FOR DEVELOPERS

Error handling

INTERMEDIATE PYTHON FOR DEVELOPERS



George Boorman

Curriculum Manager, DataCamp

Pandas traceback

```
File /usr/local/lib/python3.8/dist-packages/pandas/core/indexes/base.py:3805, in Index.get_loc(self, key, method, tolerance)
    3803     return self._engine.get_loc(casted_key)
    3804 except KeyError as err:
-> 3805     raise KeyError(key) from err
    3806 except TypeError:
    3807     # If we have a listlike key, _check_indexing_error will raise
    3808     # InvalidIndexError. Otherwise we fall through and re-raise
    3809     # the TypeError.
    3810     self._check_indexing_error(key)

KeyError: 'tag'
```

- `except` , `raise`
- Try to anticipate how errors might occur

Design-thinking

- How might people use our custom function?
- Test these different approaches
- Find what errors occur



¹ Image credit: <https://www.flickr.com/photos/140641142@N05/>

Error handling in custom functions

```
def average(values):  
    # Calculate the average  
    average_value = sum(values) / len(values)  
    return average_value
```


Where might they go wrong?

- Provide more than one argument
- Use the wrong data type

Where might they go wrong?

```
sales_dict = {"cust_id": ["JL93", "MT12", "IY64"],
              "order_value": [43.21, 68.70, 82.19]}

average(sales_dict)
```

```
-----
TypeError                                Traceback (most recent call last)
Cell In[5], line 4
      1 sales_dict = {"cust_id": ["JL93", "MT12", "IY64"],
      2                 "order_value": [43.21, 68.70, 82.19]}
----> 4 average(sales_dict)

Cell In[4], line 3, in average(values)
      1 def average(values):
      2     # Calculate the average
----> 3     average_value = sum(values) / len(values)
      4     return average_value

TypeError: unsupported operand type(s) for +: 'int' and 'str'
```

Error-handling techniques

- Control flow `if` , `elif` , `else`
- Docstrings

try-except

```
def average(values):  
    try:  
        # Code that might cause an error  
        average_value = sum(values) / len(values)  
        return average_value  
    except:  
        # Code to run if an error occurs  
        print("average() accepts a list or set. Please provide a correct data type.")  
  
average(sales_dict)
```

```
average() accepts a list or set. Please provide a correct data type.
```

raise

```
def average(values):  
    # Check data type  
    if type(values) in ["list", "set"]:  
        # Run if appropriate data type was used  
        average_value = sum(values) / len(values)  
        return average_value
```

raise

```
def average(values):  
    # Check data type  
    if type(values) in ["list", "set"]:  
        # Run if appropriate data type was used  
        average_value = sum(values) / len(values)  
        return average_value  
    else:  
        # Run if an Exception occurs  
        raise
```

raise TypeError

```
def average(values):  
    # Check data type  
    if type(values) in ["list", "set"]:  
        # Run if appropriate data type was used  
        average_value = sum(values) / len(values)  
        return average_value  
    else:  
        # Run if an Exception occurs  
        raise TypeError("average() accepts a list or set, please provide a correct data type.")
```

raise TypeError output

```
average(sales_dict)
```

```
-----  
TypeError                                Traceback (most recent call last)  
Cell In[19], line 11  
      7     else:  
      8         # Run if an Exception occurs  
      9         raise TypeError("average() accepts a list or set, please provide a correct data type.")  
--> 11 average(sales_dict)  
  
Cell In[19], line 9, in average(values)  
      6     return average_value  
      7 else:  
      8     # Run if an Exception occurs  
----> 9     raise TypeError("average() accepts a list or set, please provide a correct data type.")  
  
TypeError: average() accepts a list or set, please provide a correct data type.
```


try-except vs. raise

try - except

- Avoid errors being produced
- Still execute subsequent code

raise


- Will produce an error
- Avoid executing subsequent code

Let's practice!

INTERMEDIATE PYTHON FOR DEVELOPERS

Congratulations

INTERMEDIATE PYTHON FOR DEVELOPERS



George Boorman

Curriculum Manager, DataCamp

Chapter 1 recap

- Built-in functions
 - `print()` , `help()` , `type()`
 - `max()` , `min()` , `sum()`
 - `len()` , `round()` , `sorted()`
- Modules
 - `collections` , `string` ,
 - `os` , `logging` , `subprocess`
- Packages
 - `pandas`

Chapter 2 recap

```
# Create a custom function
def average(values):
    # Calculate the average
    average_value = sum(values) / len(values)

    # Round the results
    rounded_average = round(average_value, 2)

    # Return rounded_average as an output
    return rounded_average
```

Chapter 2 recap

```
# Create a custom function
def average(values, rounded=False):
    # Round average to two decimal places if rounded is True
    if rounded == True:
        average_value = sum(values) / len(values)
        rounded_average = round(average_value, 2)
        return rounded_average
    # Otherwise, don't round
    else:
        average_value = sum(values) / len(values)
        return average_value
```

Chapter 2 recap

```
def average(values):  
    """  
    Find the mean in a sequence of values and round to two decimal places.  
  
    Args:  
        values (list): A list of numeric values.  
  
    Returns:  
        rounded_average (float): The mean of values, rounded to two decimal places.  
    """  
    average_value = sum(values) / len(values)  
    rounded_average = round(average_value, 2)  
    return rounded_average
```

Chapter 2 recap

```
# Use arbitrary positional arguments
```

```
def average(*args):  
    average_value = sum(values) / len(values)  
    rounded_average = round(average_value, 2)  
    return rounded_average
```

```
# Use arbitrary keyword arguments
```

```
def average(**kwargs):  
    average_value = sum(kwargs.values()) / len(kwargs.values())  
    rounded_average = round(average_value, 2)  
    return rounded_average
```


Chapter 3 recap

- `lambda argument(s): expression`

```
names = ["john", "sally", "leah"]

# Apply a lambda function inside map()
capitalize = map(lambda x: x.capitalize(), names)

# Convert to a list
list(capitalize)
```

```
['John', 'Sally', 'Leah']
```

Chapter 3 recap

```
-----  
ValueError                                Traceback (most recent call last)  
Cell In[2], line 1  
----> 1 float("Hello")  
  
ValueError: could not convert string to float: 'Hello'
```

Chapter 3 recap

- `try`
- `except`
- `raise`

Next steps

- Additional built-in functions
 - `zip()`
 - `input()`
 - `reduce()`
 - `filter()`
- More packages and modules
 - `time`
 - `venv`
 - `requests`
 - `fastapi`
- Object-oriented programming

Congratulations!

INTERMEDIATE PYTHON FOR DEVELOPERS