Understanding Support Vector Machines: A Comparative Analysis of Kernel Functions on Classification Performance

GitHub Repository (Code): https://github.com/mdsajidhasan510/MLNN_SVM_Tutorial.git

Name: Md Sajid Hasan | **Student ID:** 24156348 | Institution: University of Hertfordshire

---

1. Introduction

A popular class of supervised machine learning techniques for classification and regression applications is Support Vector Machines (SVMs). They are renowned for their capacity to create strong decision boundaries and are especially successful in high-dimensional feature spaces.

The main objective of SVM is to identify an optimal separating hyperplane that maximizes the margin between different classes. However, the efficacy of basic linear models is limited since real-world datasets are frequently not linearly separable.

The analysis of how various kernel functions impact SVM model performance is the main goal of this tutorial. In particular, the study contrasts three widely utilized kernels:

- Linear kernel
- Polynomial kernel
- Radial Basis Function (RBF) kernel

In addition to assessing performance, the goal is to comprehend how each kernel modifies the feature space and affects decision boundaries.

---

2. Theoretical Background

2.1 Maximum Margin Classifier

Finding a hyperplane that maximizes the margin between classes is how SVM works. The gap between the nearest data points from each class and the hyperplane is known as the margin. Increasing this margin lowers the chance of overfitting and enhances generalization.

2.2 Support Vectors

The crucial data points that are closest to the decision border are known as support vectors. The hyperplane's orientation and location are established by these points. SVM does not rely on the complete dataset, in contrast to other algorithms, but simply on some crucial data points.

2.3 The Kernel Trick

In their original feature space, many datasets cannot be linearly separated. SVM may map data into a higher-dimensional space where linear separation is feasible because to the kernel trick. Without explicitly calculating new coordinates, this transformation is accomplished effectively.

---

3. Kernel Functions and Their Characteristics

3.1 Linear Kernel

The linear kernel tries to divide classes using a straight line without altering the data.

Advantages:

- Effective in computation
- Suitable for data that is linearly separable

Limitations:

• Unable to depict intricate interactions

3.2 Polynomial Kernel

By taking into account polynomial combinations of characteristics, the polynomial kernel introduces non-linearity.

Advantages:

- Captures patterns that are substantially non-linear
- Adaptable based on the degree parameter

Limitations:

- Able to overfit at high degrees
- A higher level of computational complexity

3.3 Kernel of the Radial Basis Function (RBF)

The RBF kernel allows for extremely flexible decision boundaries by mapping data into an infinite-dimensional space.

Advantages:

• Manages intricate non-linear relationships
• Generally excellent results across datasets

Limitations:

• Hyperparameter sensitivity (gamma and C)
• Increased computational expenses

---

4. Dataset Description

Because of its ease of use and suitability for classification tasks, the Iris dataset was chosen for this lesson.
It has 150 samples in three different classes:

- Setosa
- Versicolor
- Virginica

Four numerical characteristics that describe floral measurements are present in each sample. Only the first two attributes were chosen for visualization, allowing decision boundaries to be clearly shown graphically.

---

5. Methodology

A structured pipeline was used in the experiment:
The Iris dataset was loaded using Scikit-learn

1. Select two features for visualization
2. Split data into training (80%) and testing (20%) sets
3. Train SVM models using different kernels
4. Evaluate performance using classification accuracy
5. Visualize decision boundaries for qualitative analysis

To ensure reproducibility, a fixed random state was used during data splitting

---

6. Results

6.1 Quantitative Evaluation

Kernel	Accuracy (Typical Range)
Linear	0.83 – 1.00
Polynomial	0.85 – 1.00
RBF	0.90 – 1.00

6.2 Qualitative Analysis

The visualization of decision boundaries provides insight into how each kernel behaves.



Figure 1: Iris dataset scatter plot with two chosen characteristics. A sample colored in accordance with its class label is represented by each point.

The dataset shows partial overlaps between classes, as seen in Figure 1, suggesting that linear separation might not be enough. This is why non-linear kernels are used.



Figure 2: A linear kernel SVM was used to produce the decision boundary.

A straightforward straight-line boundary is produced by the linear kernel, which may underfit complicated data distributions.



Figure 3: A polynomial kernel (degree = 3) was used to produce the decision boundary.

Compared to the linear kernel, the polynomial kernel adds curvature, which enables the model to capture more intricate patterns.



Figure 4: An RBF kernel SVM was used to produce the decision boundary.

The RBF kernel improves classification performance by creating a very flexible border that closely resembles data distribution.

---

7. Discussion

The findings demonstrate a trade-off between generalization and model complexity:

- While simpler models (linear kernel) are less likely to overfit, they might not be able to capture intricate patterns.
- Higher accuracy is attained by more adaptable models (RBF kernel), but careful parameter tweaking is necessary.

It's crucial to note that improved generalization is not always ensured by increasing model complexity. Overly complicated models may fit noise rather than significant patterns in tiny datasets like Iris. Thus, the following should serve as guidance when selecting a kernel:

- Nature of the dataset
- Dimensionality
- Computational constraints

8. Ethical and Practical Considerations

Despite SVM's strength, the quality of the data it uses determines how well it performs.

Potential concerns include:

- Unfair predictions due to bias in training data
- Limited interpretability as contrast to more straightforward models
- Overfitting because of incorrect parameter choice

Transparency, fairness assessment, and appropriate validation are necessary for the responsible application of machine learning.

9. Conclusion

This lesson showed how various kernel functions affect Support Vector Machine performance.

Key findings include:

- Model performance is greatly impacted by kernel selection.
- Simple datasets can benefit from linear kernels.
- For complex data, RBF kernels offer greater flexibility.
- A crucial component of comprehending model behavior is visualization.

Performance, complexity, and interpretability must all be balanced while choosing the right kernel.

10. References

Cortes, C. and Vapnik, V. (1995) 'Support-vector networks', *Machine Learning*, 20(3), pp. 273–297.

Bishop, C.M. (2006) *Pattern Recognition and Machine Learning*. Springer.

Pedregosa, F. et al. (2011) 'Scikit-learn: Machine Learning in Python', *Journal of Machine Learning Research*, 12, pp. 2825–2830.