



AULA PRÁTICA 2 – CSS

Aqui basta criar um arquivo para praticar:

Exemplo 1: CSS

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-
Compatible" content="IE=edge">
  <meta name="viewport" content="width=d
evice-width, initial-scale=1.0">
  <title>CSS</title>
  <style>
    .central_geral{
      text-align:center;
    }
    p.central{
      text-align:center;
    }
    h1,h2,h3{
```

```
        border-
bottom: 6px double gold;
    }
    ul ol{
        color: red;
    }
    ol ol{
        color: green;
    }
</style>
</head>
<body>
    <p>Texto do parágrafo</p>
    <p class='central'>Texto do P para cen
tralizar</p>
    <h4 class='central'>Texto do H4 que nã
o vai centralizar</h4>
    <h4 class='central_geral'>Texto do H4
que vai centralizar</h4>
    <hr>
    <h1>Titulo 1 geral</h1>
    <h2>Titulo 2 geral</h2>
    <h3>Titulo 3 geral</h3>
    <ul>
        <ol type='I'>
            <li>HTML</li>
            <li>CSS</li>
            <ol type='A'>
                <li>Border</li>
```

```
        <li>Shadow</li>
    </ol>
    <li>Javascript</li>
</ol>
</ul>
</body>
</html>
```

Exemplo 2:

Usei gerador de lero-lero: lorem-ipsuim para os parágrafos. <https://www.lipsum.com/>

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-
Compatible" content="IE=edge">
    <meta name="viewport" content="width=d
evice-width, initial-scale=1.0">
    <title>Document</title>
    <style>
        .base{
            position:absolute;
            z-index: 5;
            top: 10px;
            left: 10px;
```

```
    }
    .quadro{
        position: absolute;
        z-index: 10;
        top: 40px;
        left: 30px;
        width: 100px;
        height:100px;
        box-
shadow: 5px 5px 5px 3p gray;
        border-radius: 20px;
        background-color: white;
    }
    .topo{
        position: absolute;
        z-index: 15;
        top: 70px;
        left: 50px;
        color: blue;
        background-color: gray;
    }
</style>
</head>
<body>
    <p class="base">
```

It is a long established fact that a reader will be distracted by the readable content of a page when looking at its layout. The point of using Lorem Ipsum is t

<div class="quadro">It is a long established fact that a reader will be distracted by the readable content of a page when looking at its layout. The point of using Lorem Ipsum is that it has a more-or-less normal distribution of letters, as opposed to using 'Content here, content here', making it look like readable English. Many desktop publishing packages and web page editors now use Lorem Ipsum as their default model text, and a search for 'lorem ipsum' will uncover many web sites still in their infancy. Various versions have evo

lved over the years, sometimes by accident
, sometimes on purpose (injected humour and
the like).

</div>

<p class="topo">

It is a long established fact that
a reader will be distracted by the readable
content of a page when looking at its layout.
The point of using Lorem Ipsum is that
it has a more-or-

less normal distribution of letters, as opposed
to using 'Content here, content here', making
it look like readable English. Many desktop
publishing packages and web page editors
now use Lorem Ipsum as their default model
text, and a search for 'lorem ipsum' will
uncover many web sites still in their infancy.
Various versions have evolved over the years,
sometimes by accident, sometimes on purpose
(injected humour and the like).

</p>

</body>

</html>

Exemplo 3:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-
Compatible" content="IE=edge">
  <meta name="viewport" content="width=d
evice-width, initial-scale=1.0">
  <title>Document</title>
  <style>
    p{
      border-radius: 20px;
      box-
shadow: 10px 10px 15px gray;
      background-color: slategray;
      position: absolute;
      padding: 10px;
      top: 50px;
      left: 10px;
      width: 150px;
      height: 100px;
    }
    p:hover{
      //transform: translate(-
.5rem, -1rem) rotate(3deg);
      transform: rotate(360deg);
      transition: transform .8s;
```

```

        }
        h1: hover {
            box-
shadow: 10px 10px 15px gray;
            transform: translate(-.1rem, -
1rem) rotate(1deg);
            transition: transform .5s;
        }
    </style>

</head>
<body>
    <p><span style='color: gold'>Atenção:</
span>Teste de leitura</p>
    <br>
    <!--
    <h1>Promoção: aproveite!!!!</h1>
    -->
</body>
</html>

```

Exemplo 4:

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-
Compatible" content="IE=edge">

```



```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Document</title>
<style>
  p{
    margin-left:20px;

  }

  table.td{
    border: 1px solid black;
    border-collapse: collapse;
  }

  .destaque:hover{
    text-align: 1PX 1PX 3PX GRAY;
    background: burlywood;
    text-align: center;
  }
  .titulo:hover{
    color:red;
    font-size: 1.3em;
  }
</style>
</head>
<body>
  <table border="2">
    <caption>Tabela de Frutas</caption
  >
```

```

        <tr class="destaque">
            <td>Nome</td><td>Qtde</td><td>Valor</td>
        </tr>

        <tr class="destaque">
            <td>Banana</td><td>40</td><td>5,00</td>
        </tr>
        <tr class="destaque">
            <td>Acerola</td><td>7</td><td>9,00</td>
        </tr>
        <tr class="destaque">
            <td>Abacaxi</td><td>4</td><td>10,00</td>
        </tr>
    </table>

    <h1 class="titulo">Texto a ser destacado</h1>
</body>
</html>

```

Exemplo 5:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta http-equiv="X-UA-
Compatible" content="IE=edge">
  <meta name="viewport" content="width=d
evice-width, initial-scale=1.0">
  <title>Document</title>
  <link rel="stylesheet" href="https://m
axcdn.bootstrapcdn.com/bootstrap/4.5.2/css
/bootstrap.min.css">
  <script src="https://ajax.googleapis.com
/ajax/libs/jquery/3.5.1/jquery.min.js"></s
cript>
  <script src="https://cdnjs.cloudflare.co
m/ajax/libs/popper.js/1.16.0/umd/popper.mi
n.js"></script>
  <script src="https://maxcdn.bootstrapcdn
.com/bootstrap/4.5.2/js/bootstrap.min.js">
</script>
</head>
<div style="width: 400px;">

  <form>
    <div class="custom-control custom-
switch">
```

```

        <input type="checkbox" class="
custom-control-input" id="editar">
        <label class="custom-control-
label" for="editar">Editar</label>
    </div>
    <label for="temperatura">Temperatu
ra: </label>
        <input type="range" class="custom-
range" min="0" max="10" id="tempertura" na
me="temperatura">
    </form>
</div>
<!--
- colocar em src="nome completo de uma ima
gem, que deverá estar salva na mesma pasta
onde você salvou o arquivo, por exemplo]:
flor.png ou flor.jpg" -->

<br>
<br>
<!-- Modal-->

<button type="button" class="btn btn-
primary" data-toggle="modal" data-
target="#janela"> >Atenção</button>

<!-- Cria pop up-->
<div class="modal" id="janela">

```



```
</html>
```