

CprE 419 Lab 9:

Standard Operators in Streams Processing Language (SPL)

Shuo Wang

Figure 1 shows the streams dataflow graph for my code.




FIGURE 1 Streams Dataflow Graph

TCPSource generates raw data

Custom_4 and FileSink_6 write the raw data in “SourceData.txt”. The schema is:

{date, time, CallerID, CalleeID, Duration, CallStartTime in seconds, CallStartTime in minutes, CallEndTime in seconds}

Where $\text{CallEndTime in seconds} = \text{hour} * 3600 + \text{minute} * 60 + \text{second}$

(e.g. 11:13:09 => $11 * 3600 + 13 * 60 + 9 = 40389$)

$\text{CallStartTime in seconds} = \text{CallEndTime in seconds} - \text{Duration}$

$\text{CallStartTime in minutes} = \text{rounddown}(\text{CallStartTime in seconds} / 60)$

Recording “SourceData.txt” is for debugging and checking purpose.

Functor_6 calculated CallStartTime in seconds, CallStartTime in minutes and CallEndTime in seconds. (similar to what Custom_4 does)

Custom_3 checks the suspect type A and B. Custom_7 checks the suspect type C.

Custom_8 combines the stream from Custom_3 and Custom_7.

FileSink_5 archives the historical suspect alerts in “SuspectRecords.txt”, for debugging and checking purpose.

Punc9 adds punctuation to the stream after a certain time. (the time point needs to be specified manually in the code)

Custom_... aggregates all the suspect alerts by each CallerID and makes output at punctuation.

FileSink_10 writes the final suspect list in “suspects.txt”

I run the code for 47 minutes from 21:43 to 22:30 April 7, 2015, and the final suspect list is:

Number of Suspects 4

239769310 C

239788154 BCA

239793121 B

239718753 BA

Appendix: files in submission .zip

1. lab9.spl is the IBM Infosphere code for lab 9
2. "SouceData.txt" is the archived stream data, as described above.
3. "SuspectRecords.txt" is the archived historical suspect alerts, as described above.
4. "suspects.txt" is the final list for the police.