

# NLP\_C3\_W1\_lecture\_nb\_01\_trax\_intro

December 16, 2023

## 1 Trax : Ungraded Lecture Notebook

In this notebook you'll get to know about the Trax framework and learn about some of its basic building blocks.

### 1.1 Background

#### 1.1.1 Why Trax and not TensorFlow or PyTorch?

TensorFlow and PyTorch are both extensive frameworks that can do almost anything in deep learning. They offer a lot of flexibility, but that often means verbosity of syntax and extra time to code.

Trax is much more concise. It runs on a TensorFlow backend but allows you to train models with 1 line commands. Trax also runs end to end, allowing you to get data, model and train all with a single terse statements. This means you can focus on learning, instead of spending hours on the idiosyncrasies of big framework implementation.

#### 1.1.2 Why not Keras then?

Keras is now part of Tensorflow itself from 2.0 onwards. Also, trax is good for implementing new state of the art algorithms like Transformers, Reformers, BERT because it is actively maintained by Google Brain Team for advanced deep learning tasks. It runs smoothly on CPUs,GPUs and TPUs as well with comparatively lesser modifications in code.

#### 1.1.3 How to Code in Trax

Building models in Trax relies on 2 key concepts:- **layers** and **combinators**. Trax layers are simple objects that process data and perform computations. They can be chained together into composite layers using Trax combinators, allowing you to build layers and models of any complexity.

#### 1.1.4 Trax, JAX, TensorFlow and Tensor2Tensor

You already know that Trax uses Tensorflow as a backend, but it also uses the JAX library to speed up computation too. You can view JAX as an enhanced and optimized version of numpy.

Watch out for assignments which import `import trax.fastmath.numpy as np`. If you see this line, remember that when calling `np` you are really calling Trax's version of numpy that is compatible with JAX.

As a result of this, where you used to encounter the type `numpy.ndarray` now you will find the type `jax.interpreters.xla.DeviceArray`.

Tensor2Tensor is another name you might have heard. It started as an end to end solution much like how Trax is designed, but it grew unwieldy and complicated. So you can view Trax as the new improved version that operates much faster and simpler.

### 1.1.5 Resources

- Trax source code can be found on Github: [Trax](#)
- JAX library: [JAX](#)

## 1.2 Installing Trax

Trax has dependencies on JAX and some libraries like JAX which are yet to be supported in [Windows](#) but work well in Ubuntu and MacOS. We would suggest that if you are working on Windows, try to install Trax on WSL2.

Official maintained documentation - [trax-ml](#) not to be confused with this [TraX](#)

```
[ ]: #!pip install trax==1.3.9 Use this version for this notebook
```

## 1.3 Imports

```
[ ]: import numpy as np  # regular ol' numpy

from trax import layers as tl  # core building block
from trax import shapes  # data signatures: dimensionality and type
from trax import fastmath  # uses jax, offers numpy on steroids
```

```
[ ]: # Trax version 1.3.9 or better
!pip list | grep trax
```

## 1.4 Layers

Layers are the core building blocks in Trax or as mentioned in the lectures, they are the base classes. They take inputs, compute functions/custom calculations and return outputs.

You can also inspect layer properties. Let me show you some examples.

### 1.4.1 Relu Layer

First let's see how to build a relu activation function as a layer. A layer like this is one of the simplest types. Notice there is no object initialization so it works just like a math function.

**Note:** Activation functions are also layers in Trax, which might look odd if you have been using other frameworks for a longer time.

```
[ ]: # Layers
# Create a relu trax layer
relu = tl.Relu()

# Inspect properties
print("-- Properties --")
print("name :", relu.name)
print("expected inputs :", relu.n_in)
print("promised outputs :", relu.n_out, "\n")

# Inputs
x = np.array([-2, -1, 0, 1, 2])
print("-- Inputs --")
print("x :", x, "\n")

# Outputs
y = relu(x)
print("-- Outputs --")
print("y :", y)
```

### 1.4.2 Concatenate Layer

Now let's check how to build a layer that takes 2 inputs. Notice the change in the expected inputs property from 1 to 2.

```
[ ]: # Create a concatenate trax layer
concat = tl.Concatenate()
print("-- Properties --")
print("name :", concat.name)
print("expected inputs :", concat.n_in)
print("promised outputs :", concat.n_out, "\n")

# Inputs
x1 = np.array([-10, -20, -30])
x2 = x1 / -10
print("-- Inputs --")
print("x1 :", x1)
print("x2 :", x2, "\n")
```

```
# Outputs
y = concat([x1, x2])
print("-- Outputs --")
print("y :", y)
```

## 1.5 Layers are Configurable

You can change the default settings of layers. For example, you can change the expected inputs for a concatenate layer from 2 to 3 using the optional parameter `n_items`.

```
[ ]: # Configure a concatenate layer
concat_3 = tl.Concatenate(n_items=3) # configure the layer's expected inputs
print("-- Properties --")
print("name :", concat_3.name)
print("expected inputs :", concat_3.n_in)
print("promised outputs :", concat_3.n_out, "\n")

# Inputs
x1 = np.array([-10, -20, -30])
x2 = x1 / -10
x3 = x2 * 0.99
print("-- Inputs --")
print("x1 :", x1)
print("x2 :", x2)
print("x3 :", x3, "\n")

# Outputs
y = concat_3([x1, x2, x3])
print("-- Outputs --")
print("y :", y)
```

**Note:** At any point, if you want to refer the function help/ look up the [documentation](#) or use help function.

```
[ ]: #help(tl.Concatenate) #Uncomment this to see the function docstring with
    ↪ explanation
```

## 1.6 Layers can have Weights

Some layer types include mutable weights and biases that are used in computation and training. Layers of this type require initialization before use.

For example the `LayerNorm` layer calculates normalized data, that is also scaled by weights and biases. During initialization you pass the data shape and data type of the inputs, so the layer can initialize compatible arrays of weights and biases.

```
[ ]: # Uncomment any of them to see information regarding the function
# help(tl.LayerNorm)
# help(shapes.signature)

[ ]: # Layer initialization
norm = tl.LayerNorm()
# You first must know what the input data will look like
x = np.array([0, 1, 2, 3], dtype="float")

# Use the input data signature to get shape and type for initializing weights,
→and biases
norm.init(shapes.signature(x)) # We need to convert the input datatype from
→usual tuple to trax ShapeDtype

print("Normal shape:",x.shape, "Data Type:",type(x.shape))
print("Shapes Trax:",shapes.signature(x),"Data Type:",type(shapes.signature(x)))

# Inspect properties
print("-- Properties --")
print("name :", norm.name)
print("expected inputs :", norm.n_in)
print("promised outputs :", norm.n_out)
# Weights and biases
print("weights :", norm.weights[0])
print("biases :", norm.weights[1], "\n")

# Inputs
print("-- Inputs --")
print("x :", x)

# Outputs
y = norm(x)
print("-- Outputs --")
print("y :", y)
```

## 1.7 Custom Layers

This is where things start getting more interesting! You can create your own custom layers too and define custom functions for computations by using `tl.Fn`. Let me show you how.

```
[ ]: # help(tl.Fn) # Uncomment to see information regarding the function

[ ]: # Define a custom layer
# In this example you will create a layer to calculate the input times 2

def TimesTwo():
```

```

    layer_name = "TimesTwo" #don't forget to give your custom layer a name to
    ↪identify

    # Custom function for the custom layer
    def func(x):
        return x * 2

    return tl.Fn(layer_name, func)

# Test it
times_two = TimesTwo()

# Inspect properties
print("-- Properties --")
print("name :", times_two.name)
print("expected inputs :", times_two.n_in)
print("promised outputs :", times_two.n_out, "\n")

# Inputs
x = np.array([1, 2, 3])
print("-- Inputs --")
print("x :", x, "\n")

# Outputs
y = times_two(x)
print("-- Outputs --")
print("y :", y)

```

## 1.8 Combinators

You can combine layers to build more complex layers. Trax provides a set of objects named combinator layers to make this happen. Combinators are themselves layers, so behavior commutes.

### 1.8.1 Serial Combinator

This is the most common and easiest to use. For example could build a simple neural network by combining layers into a single layer using the `Serial` combinator. This new layer then acts just like a single layer, so you can inspect inputs, outputs and weights. Or even combine it into another layer! Combinators can then be used as trainable models. *Try adding more layers*

**Note:** As you must have guessed, if there is serial combinator, there must be a parallel combinator as well. Do try to explore about combinator layers and other layers from the trax documentation and look at the repo to understand how these layers are written.

```
[ ]: # Uncomment any of them to see information regarding the function
# help(tl.Serial)
# help(tl.Parallel)

[ ]: # Serial combinator
serial = tl.Serial(
    tl.LayerNorm(),          # normalize input
    tl.Relu(),               # convert negative values to zero
    times_two,               # the custom layer you created above, multiplies
    ↪ the input recieved from above by 2

    ### START CODE HERE
#     tl.Dense(n_units=2),   # try adding more layers. eg uncomment these lines
#     tl.Dense(n_units=1),   # Binary classification, maybe? uncomment at your
    ↪ own peril
#     tl.LogSoftmax()        # Yes, LogSoftmax is also a layer
    ### END CODE HERE
)

# Initialization
x = np.array([-2, -1, 0, 1, 2]) #input
serial.init(shapes.signature(x)) #initialising serial instance

print("-- Serial Model --")
print(serial, "\n")
print("-- Properties --")
print("name :", serial.name)
print("sublayers :", serial.sublayers)
print("expected inputs :", serial.n_in)
print("promised outputs :", serial.n_out)
print("weights & biases:", serial.weights, "\n")

# Inputs
print("-- Inputs --")
print("x :", x, "\n")

# Outputs
y = serial(x)
print("-- Outputs --")
print("y :", y)
```

## 1.9 JAX

Just remember to lookout for which numpy you are using, the regular ol' numpy or Trax's JAX compatible numpy. Both tend to use the alias np so watch those import blocks.

**Note:** There are certain things which are still not possible in fastmath.numpy which

can be done in numpy so you will see in assignments we will switch between them to get our work done.

```
[ ]: # Numpy vs fastmath.numpy have different data types
# Regular ol' numpy
x_numpy = np.array([1, 2, 3])
print("good old numpy : ", type(x_numpy), "\n")

# Fastmath and jax numpy
x_jax = fastmath.numpy.array([1, 2, 3])
print("jax trax numpy : ", type(x_jax))
```

## 1.10 Summary

Trax is a concise framework, built on TensorFlow, for end to end machine learning. The key building blocks are layers and combinators. This notebook is just a taste, but sets you up with some key intuitions to take forward into the rest of the course and assignments where you will build end to end models.