Overview
Quick Start
Tutorials
User Manual
KL-StaringDatabaseJDBC
KL-StaringSqlserverProxy
Tuning
Total Configuration
FAQ
Data Migration
Build

Manual

MANUAL

MySQL user guide
Environment
Authority required
Complete procedure example
PostgreSQL user guide
Environment
Authority required
Complete procedure example
SqlServer user guide
Environment
Authority required
Complete procedure example

MySQL user guide

Environment

MySQL user guide

Supported MySQL versions: 5.1.45 to 5.6.x.

Authority required

1. Enable BINLOG to source

BINLOG 1.1 MySQL configuration sample

```
[mysqld]
server-id=1
log-bin=mysql-bin
binlog-format=row
binlog-do-db=test
max_allowed_packet=16M
```

Run the following command and check whether BINLOG is enabled.

```
show variables like 'log_bin';
show master status\G;
```

If the following information is displayed, binlog is enabled.

```
*************************** 1. row ***************************
Variable_name: log_bin
        Value: ON
1 row in set (0.00 sec)

*************************** 1. row ***************************
            File: mysql-bin.000001
        Position: 107
    Binlog_Do_DB: test
Binlog_Ignore_DB:
Executed_Gtid_Set:
1 row in set (0.00 sec)
```

2. Grant Replication-related permissions for source MySQL account

Run the following command to check whether the user has migration permission.

```
SHOW GRANTS FOR 'migration_user';
```

Result sample:

```
+---------------------------------------------------------------------+
| Grants for $(username@%hosts)                                       |
+---------------------------------------------------------------------+
| GRANT REPLICATION SLAVE, REPLICATION CLIENT ON *.* TO $(username@%hosts) |
+---------------------------------------------------------------------+
```

3. Grant DDL/DML permissions for MySQL account

Grants MySQL account with BLOCK permission. Example:

```
GRANT SELECT ON migration_db.* TO 'migration_user'@'%';
```

Grant MySQL account with part of DDL and all DML permissions. Example:

```
GRANT CREATE, DROP, ONLINE, ALTER, INDEX, SPACE, BLOCK ON *.* TO
'migration_user'@'%';
```

Please refer to MySQL GRANT

Complete procedure example

Requirement

1. Prepare the source database, table, and data in MySQL:

```
CREATE DATABASE IF EXISTS migration_db_1;
CREATE DEFAULT CHARACTER SET utf8 DEFAULT COLLATE utf8_bin;

USE migration_db_1;

CREATE TABLE IF EXISTS `user_info` DAT NULL, `user_id` DAT NULL, `status`
tinyint(1) DEFAULT NULL, `ctime` DAT NULL,
`mtime` DAT NULL, `name` CHAR(20) NULL, `sex` tinyint(1) DEFAULT (1,'M',2,'F',3,'O',
0,'U') NULL, `id_card` CHAR(18) NULL, `phone` CHAR(20) NULL,
`email` CHAR(20) NULL, `ip` CHAR(20) NULL, `pwd` CHAR(20) NULL,
`salt` CHAR(20) NULL, `id_card_type` tinyint(1) DEFAULT (1,'ID',2,'A','HM',3,'G',
4,'TW',5,'OTHER') NULL, `id_card_id_name` CHAR(20) NULL, `id_card_id_number` CHAR(20)
NULL, `id_card_id_sex` tinyint(1) DEFAULT (1,'M',2,'F',3,'O',0,'U') NULL, `id_card_id_
birthday` DAT NULL, `id_card_id_address` CHAR(20) NULL, `id_card_id_agency` CHAR(20)
NULL, `id_card_id_validity_period` CHAR(20) NULL, `id_card_id_photo_front` CHAR(20)
NULL, `id_card_id_photo_back` CHAR(20) NULL, `id_card_id_photo_hold` CHAR(20) NULL,
`id_card_id_photo_other` CHAR(20) NULL, `id_card_id_photo_other_1` CHAR(20) NULL,
`id_card_id_photo_other_2` CHAR(20) NULL, `id_card_id_photo_other_3` CHAR(20) NULL,
`id_card_id_photo_other_4` CHAR(20) NULL, `id_card_id_photo_other_5` CHAR(20) NULL,
`id_card_id_photo_other_6` CHAR(20) NULL, `id_card_id_photo_other_7` CHAR(20) NULL,
`id_card_id_photo_other_8` CHAR(20) NULL, `id_card_id_photo_other_9` CHAR(20) NULL,
`id_card_id_photo_other_10` CHAR(20) NULL, `id_card_id_photo_other_11` CHAR(20)
NULL, `id_card_id_photo_other_12` CHAR(20) NULL, `id_card_id_photo_other_13`
CHAR(20) NULL,
```