

Workshop Email Server (Debian 10/Buster)

Oleh:

Idris Winarno




Server DNS

- Buat Server DNS untuk server email (buka PPT untuk pertemuan minggu ke-2)

```
;
; BIND data file for local loopback interface
;
$TTL      604800
@         IN      SOA      idris.my.id. root.idris.my.id. (
                        2      ; Serial
                        604800 ; Refresh
                        86400  ; Retry
                        2419200 ; Expire
                        604800 ) ; Negative Cache TTL
;
@         IN      NS       idris.my.id.
@         IN      A        10.252.108.200
@         IN      AAAA     ::1
@         IN      MX       10 mail.idris.my.id
mail      IN      A        10.252.108.200
```

Instalasi MTA (postfix)

- # apt-get install postfix




Konfigurasi MTA (postfix)

postconf -e "myhostname=com0.c307.eepis-its.edu"

```
root@debian:/var/cache/bind# postconf -e "home_mailbox=Maildir/"
root@debian:/var/cache/bind# postconf -e "mailbox_command="
root@debian:/var/cache/bind# /etc/init.d/postfix restart
[ ok ] Restarting postfix (via systemctl): postfix.service.
root@debian:/var/cache/bind#
```

Instalasi MDA (courier)

- # apt-get install courier-imap



Konfigurasi MDA (courier)

- # apt-get install courier-imap

```
root@debian:~# cd /etc/skel/
root@debian:/etc/skel# maildirmake Maildir
root@debian:/etc/skel# ls
Maildir
root@debian:/etc/skel# adduser coba
Adding user `coba' ...
Adding new group `coba' (1003) ...
Adding new user `coba' (1003) with group `coba' ...
Creating home directory `/home/coba' ...
Copying files from `/etc/skel' ...
Enter new UNIX password:
Retype new UNIX password:
passwd: password updated successfully
Changing the user information for coba
Enter the new value, or press ENTER for the default
    Full Name []:
    Room Number []:
    Work Phone []:
    Home Phone []:
    Other []:
Is the information correct? [Y/n]
root@debian:/etc/skel#
```

Ujicoba MDA (courier)

```
root@debian:/etc/skel# telnet localhost 143
Trying ::1...
Connected to localhost.
Escape character is '^]'.
* OK [CAPABILITY IMAP4rev1 UIDPLUS CHILDREN NAMESPACE THREAD=ORDEREDSUBJECT THREAD=REFERENCES SORT QUOTA IDLE ACL ACL2=UNION] Courier-IMAP ready. Copyright 1998-2011 Double Precision, Inc. See COPYING for distribution information.
a login coba coba
* OK [ALERT] Filesystem notification initialization error -- contact your mail administrator (check for configuration errors with the FAM/Gamin library)
a OK LOGIN Ok.
a logout
* BYE Courier-IMAP server shutting down
a OK LOGOUT completed
Connection closed by foreign host.
root@debian:/etc/skel#
```


Instalasi MUA (Roundcube)




Sebelum melakukan instalasi roundcube pastikan MySQL/Mariadb sudah berjalan/terinstal.

- # apt-get install mariadb-server
- # systemctl restart mariadb
- # apt-get install roundcube
- # vim /etc/roundcube/apache2.conf
hapus tanda # pada Alias /roundcube
- # vim /etc/roundcube/config.inc.php
 - default_host = 'domain.com'
 - smtp_user = " & smtp_pass = "
- # systemctl restart apache2

Pastikan mail server telah menggunakan DNS yang telah dibuat

Ujicoba

- <http://domain/roundcube>



TERIMA KASIH