

MySQL Shell 8.0.46

Copyright (c) 2016, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates.

Other names may be trademarks of their respective owners.

Type 'help' or '?' for help; \quit to exit.

```
MySQL JS > /sql
```

Expected an operand but found / (SyntaxError)

```
MySQL JS > \sql
```

Switching to SQL mode... Commands end with ;

```
MySQL SQL > SHOW DATABASES;
```

ERROR: Not connected.

```
MySQL SQL > \connect root@localhost
```

Creating a session to 'root@localhost'

Fetching global names for auto-completion... Press ^C to stop.

Your MySQL connection id is 8 (X protocol)

Server version: 8.0.46 MySQL Community Server - GPL

No default schema selected; type \use <schema> to set one.

```
MySQL localhost:33060+ ssl SQL > SHOW DATABASES;
```

```
+-----+
```

```
| Database      |
```

```
+-----+
```

```
| information_schema |
```

```
| lab_dbms       |
```

```
| my_first_db    |
```

```
| mysql          |
```

```
| performance_schema |
```

```
| sakila         |
```

```
| sys            |
```

```
| unilabon       |
```

```
| world          |
```

```
| yousuf         |
```

```
+-----+
```

10 rows in set (0.0023 sec)

```
MySQL localhost:33060+ ssl SQL > CREATE DATABASE dbms_lab_test_prac;
```

Query OK, 1 row affected (0.0219 sec)

```
MySQL localhost:33060+ ssl SQL > use dbms_lab_test_prac;
```

Default schema set to `dbms\_lab\_test\_prac`.

Fetching global names, object names from `dbms\_lab\_test\_prac` for auto-completion...

Press ^C to stop.

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > CREATE TABLE c1student(
```

```
-> student_id CHAR(5) PRIMARY KEY,
```

```
-> student_name VARCHAR(100) NOT NULL,
```

```
-> age INT,
```

```
-> cgpa DECIMAL(3,2),
```

```
-> gender ENUM ('male','female'),
```

```
-> active BOOLEAN
```

->);

Query OK, 0 rows affected (0.0640 sec)

MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > SHOW c1student;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'c1student' at line 1

MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > describe c1student;

Field	Type	Null	Key	Default	Extra
student_id	char(5)	NO	PRI	NULL	
student_name	varchar(100)	NO		NULL	
age	int	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
gender	enum('male','female')	YES		NULL	
active	tinyint(1)	YES		NULL	

6 rows in set (0.0062 sec)

MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create table(

-> ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '(' at line 1

MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create table teachers(

-> tea_id CHAR(5) PRIMARY KEY,

-> tea_name VARCHAR(100),

-> salary DOUBLE,

-> experince FLOAT,

-> joining_date DATE,

-> loging_time Time,

-> create_at DATETIME,

-> updated-at TIMESTAMP

->);

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '-at TIMESTAMP

)' at line 9

MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > CREATE TABLE Teachers(

-> teacher_id CHAR(5) PRIMARY KEY,

-> teacher_name VARCHAR(100),

-> salary DOUBLE,

-> experience FLOAT,

-> joining_date DATE,

-> login_time TIME,

-> created_at DATETIME,

-> updated_at TIMESTAMP

->);

Query OK, 0 rows affected (0.0429 sec)

MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > DESC Teachers;

Field	Type	Null	Key	Default	Extra
-------	------	------	-----	---------	-------

Field	Type	Null	Key	Default	Extra
teacher_id	char(5)	NO	PRI	NULL	
teacher_name	varchar(100)	YES		NULL	
salary	double	YES		NULL	
experience	float	YES		NULL	
joining_date	date	YES		NULL	
login_time	time	YES		NULL	
created_at	datetime	YES		NULL	
updated_at	timestamp	YES		NULL	

8 rows in set (0.0052 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create table deparments(
    -> dp_id char(5) primary key,
    -> dp_name varchar(100) unique,
    -> tota_stu smallint,
    -> total_buget bigint,
    -> dept_code mediumint,
    -> estbi year,
    -> status bit(1)
    -> );
```

Query OK, 0 rows affected (0.0519 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > deca deparments;
ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'deca deparments' at line 1
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > desc deparments
    -> ;
```

Field	Type	Null	Key	Default	Extra
dp_id	char(5)	NO	PRI	NULL	
dp_name	varchar(100)	YES	UNI	NULL	
tota_stu	smallint	YES		NULL	
total_buget	bigint	YES		NULL	
dept_code	mediumint	YES		NULL	
estbi	year	YES		NULL	
status	bit(1)	YES		NULL	

7 rows in set (0.0052 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create table course(
    -> c_id char(5) primary key,
    -> c_name varchar(100),
    -> description text .
    -> ,
    -> syl mediumtext,
    -> notes longtext,
    -> thumbnail blob,
    -> course-file longblob,
    -> metadata json
```

->);

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '.

,
syl mediumtext,
notes longtext,
thumbnail blob,
course-file longblob,
metada' at line 4

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > CREATE TABLE Courses(  
->   course_id CHAR(5) PRIMARY KEY,  
->   course_name VARCHAR(100),  
->   description TEXT,  
->   syllabus MEDIUMTEXT,  
->   notes LONGTEXT,  
->   thumbnail BLOB,  
->   course_file LONGBLOB,  
->   metadata JSON  
-> );
```

Query OK, 0 rows affected (0.0583 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > desc Courses;
```

Field	Type	Null	Key	Default	Extra
course_id	char(5)	NO	PRI	NULL	
course_name	varchar(100)	YES		NULL	
description	text	YES		NULL	
syllabus	mediumtext	YES		NULL	
notes	longtext	YES		NULL	
thumbnail	blob	YES		NULL	
course_file	longblob	YES		NULL	
metadata	json	YES		NULL	

8 rows in set (0.0114 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create table enroollments(  
->   en_id INT AUTO_INCREMENT PRIMARY KEY,  
->   s_id CHAR(5),  
->   c_id CHAR(5),  
->   semester VARCHAR(20) DEFAULT'spring',  
->   grad CHAR(3),  
->   fee DECIMAL(10,2) NOT NULL,  
->   UNIQUE(s_id,c_id),  
->   FOREIGN KEY (s_id) REFERENCES  
  
c1student(student_id),  
  
->   FOREIGN KEY(c_id) REFERENCES Courses  
  
(course_name)  
-> );
```

ERROR: 1822: Failed to add the foreign key constraint. Missing index for constraint 'enrollments_ibfk_2' in the referenced table 'courses'

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > CREATE TABLE enrollments(
->   en_id INT AUTO_INCREMENT PRIMARY KEY,
->   s_id CHAR(5),
->   c_id CHAR(5),
->   semester VARCHAR(20) DEFAULT 'spring',
->   grade CHAR(3),
->   fee DECIMAL(10,2) NOT NULL,
->   UNIQUE(s_id, c_id),
->   FOREIGN KEY (s_id) REFERENCES
c1student(student_id),
->   FOREIGN KEY (c_id) REFERENCES
Courses(course_id)
-> );
```

Query OK, 0 rows affected (0.0681 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > desc enrollments;
```

Field	Type	Null	Key	Default	Extra
en_id	int	NO	PRI	NULL	auto_increment
s_id	char(5)	YES	MUL	NULL	
c_id	char(5)	YES	MUL	NULL	
semester	varchar(20)	YES		spring	
grade	char(3)	YES		NULL	
fee	decimal(10,2)	NO		NULL	

6 rows in set (0.0088 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create d(
->   dpid int auto_increment not null unique,
-> );
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'd(dpid int auto_increment not null unique,' at line 1

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create table d(
->   dpid int auto_increment not null unique,
->   dp_name varchar(50)
-> );
```

Query OK, 0 rows affected (0.0430 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create table s(
->   si int auto_increment primary key,
->   name varchar(50) not null,
->   age int check (age >= 15),
->   cgpa decimal(3,2) default 0.00,
->   deid int ,
->   email varchar(50) unique,
->   foreign key (deid) references d(dpid)
-> );
```

Query OK, 0 rows affected (0.0553 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create table ss(
-> si int auto_increment primary key;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near " at line 2

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > create table ss9
-> si int auto_increment primary key,
-> name varchar(50) not null,
-> dpar_id int,
-> foreign key (dpar_id) references d(dpid),
-> on delete cascade,
-> on update cascade,
-> on delete set null
-> );
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'si int auto_increment primary key,

name varchar(50) not null,
dpar_id int,
forei' at line 2

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > CREATE TABLE ss9(
-> si INT AUTO_INCREMENT PRIMARY KEY,
-> name VARCHAR(50) NOT NULL,
-> dpar_id INT NULL,
-> FOREIGN KEY (dpar_id)
-> REFERENCES d(dpid)
-> ON DELETE SET NULL
-> ON UPDATE CASCADE
-> );
```

Query OK, 0 rows affected (0.0439 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > SHOW DATABASES;
```

```
+-----+
| Database      |
+-----+
| dbms_lab_test_prac |
| dbms_lab_test_prac3 |
| dms_lab_test_prac2 |
| information_schema |
| lab_dbms        |
| my_first_db     |
| mysql           |
| performance_schema |
| sakila          |
| sys             |
| unilabon        |
| world           |
| yousuf          |
+-----+
```

13 rows in set (0.0082 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > CREATE DATABASE  
DBMS_F_PARC;
```

Query OK, 1 row affected (0.0089 sec)

```
MySQL localhost:33060+ ssl dbms_lab_test_prac SQL > USE DBMS_F_PARC;  
Default schema set to `DBMS_F_PARC`.
```

Fetching global names, object names from `dbms\_f\_parac` for auto-completion... Press ^C to stop.

```
MySQL localhost:33060+ ssl dbms_f_parac SQL > CREATE TABLE Students(  
-> student_id INT AUTO_INCREMENT PRIMARY KEY,  
-> student_code CHAR(6) UNIQUE NOT NULL,  
-> first_name VARCHAR(50) NOT NULL,  
-> last_name VARCHAR(50),  
-> gender ENUM('Male','Female'),  
-> age TINYINT,  
-> cgpa DECIMAL(3,2),  
-> email VARCHAR(100) UNIQUE,  
-> phone VARCHAR(15),  
-> active BOOLEAN DEFAULT TRUE  
-> );
```

Query OK, 0 rows affected (0.0609 sec)

```
MySQL localhost:33060+ ssl dbms_f_parac SQL > CREATE TABLE Departments(  
-> dept_id SMALLINT AUTO_INCREMENT PRIMARY KEY,  
-> dept_code CHAR(5) UNIQUE,  
-> dept_name VARCHAR(100) NOT NULL,  
-> building VARCHAR(50),  
-> established YEAR,  
-> total_students MEDIUMINT,  
-> budget DOUBLE,  
-> description TEXT  
-> );
```

Query OK, 0 rows affected (0.0434 sec)

```
MySQL localhost:33060+ ssl dbms_f_parac SQL > CREATE TABLE Teachers(  
-> teacher_id INT AUTO_INCREMENT PRIMARY KEY,  
-> dept_id SMALLINT,  
-> teacher_name VARCHAR(100),  
-> salary DECIMAL(10,2),  
-> experience FLOAT,  
-> joining_date DATE,  
-> login_time TIME,  
-> created_at DATETIME,  
-> updated_at TIMESTAMP DEFAULT  
CURRENT_TIMESTAMP,  
->  
-> FOREIGN KEY(dept_id)  
-> REFERENCES Departments(dept_id)  
-> );
```

Query OK, 0 rows affected (0.0500 sec)

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > CREATE TABLE Courses(
->   course_id INT AUTO_INCREMENT PRIMARY KEY,
->   dept_id SMALLINT,
->   teacher_id INT,
->
->   course_code CHAR(8) UNIQUE,
->   course_name VARCHAR(100),
->
->   credit DECIMAL(2,1),
->
->   semester ENUM('Spring','Summer','Fall'),
->
->   syllabus MEDIUMTEXT,
->
->   notes LONGTEXT,
->
->   course_image BLOB,
->
->   pdf_file LONGBLOB,
->
->   course_info JSON,
->
->   FOREIGN KEY(dept_id)
->   REFERENCES Departments(dept_id),
->
->   FOREIGN KEY(teacher_id)
->   REFERENCES Teachers(teacher_id)
-> );

```

Query OK, 0 rows affected (0.0637 sec)

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > CREATE TABLE Enrollments(
->
->   enroll_id BIGINT AUTO_INCREMENT PRIMARY KEY,
->
->   student_id INT,
->
->   course_id INT,
->
->   enroll_date DATE,
->
->   fee DECIMAL(10,2) NOT NULL,
->
->   grade CHAR(2),
->
->   remarks VARCHAR(200)
->   DEFAULT 'Pending',
->
->   attendance INT
->   CHECK(attendance>=0),

```



```

->
-> UNIQUE(student_id,course_id),
->
-> FOREIGN KEY(student_id)
-> REFERENCES Students(student_id),
->
-> FOREIGN KEY(course_id)
-> REFERENCES Courses(course_id)
->
-> );

```

Query OK, 0 rows affected (0.0710 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > DESC Students;

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES	1		

10 rows in set (0.0208 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > insert into Students

```

->
(student_code,first_name,last_name,gender,age,cgpa,email,phone,active)
-> values
->
('s000','y','h','Male',20,4.00,'yousuf@gmail.com','0124356',true)
-> ;

```

Query OK, 1 row affected (0.0252 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > select* from Students;

student_id	student_code	first_name	last_name	gender	age	cgpa	email	phone	active
1	s000	y	h	Male	20	4.00	yousuf@gmail.com	0124356	1

1 row in set (0.0032 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > insert into Students values

```

->
('ST0004','Mahi','Hasan','Male',20,3.55,'mah@gmail.com','01744444444',FALSE);
ERROR: 1136: Column count doesn't match value count at row 1

```

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > INSERT INTO Students
-> VALUES
->
('ST0004','Mahi','Hasan','Male',20,3.55,'mahi@gmail.com','01744444444',FALSE,NOW());
```

ERROR: 1366: Incorrect integer value: 'ST0004' for column 'student_id' at row 1

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > INSERT INTO Students
-> VALUES
->
(NULL,'ST0004','Mahi','Hasan','Male',20,3.55,'mahi@gmail.com','01744444444',FALSE);
```

Query OK, 1 row affected (0.0079 sec)

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > insert into Students values
->
```

```
(3,'ST0005','Nabila','Akter','Female',21,3.95,'nabila@gmail.com','01755555555',TRUE);
```

Query OK, 1 row affected (0.0076 sec)

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > select* from Students;
```

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
| student_id | student_code | first_name | last_name | gender | age | cgpa | email          |
| phone      | active |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
|      1 | s000      | y          | h          | Male   | 20 | 4.00 | yousuf@gmail.com | 0124356 |
| 1 |
|      2 | ST0004     | Mahi       | Hasan      | Male   | 20 | 3.55 | mahi@gmail.com   |
| 01744444444 | 0 |
|      3 | ST0005     | Nabila     | Akter       | Female | 21 | 3.95 | nabila@gmail.com |
| 01755555555 | 1 |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
```

3 rows in set (0.0014 sec)

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > desc Depatments;
```

ERROR: 1146: Table 'dbms_f_parce.depatments' doesn't exist

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > desc Departments;
```

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra      |
+-----+-----+-----+-----+-----+-----+
| dept_id    | smallint  | NO   | PRI | NULL    | auto_increment |
| dept_code  | char(5)   | YES  | UNI | NULL    |              |
| dept_name  | varchar(100) | NO   |     | NULL    |              |
| building   | varchar(50) | YES  |     | NULL    |              |
| established | year      | YES  |     | NULL    |              |
| total_students | mediumint | YES  |     | NULL    |              |
| budget     | double    | YES  |     | NULL    |              |
| description | text      | YES  |     | NULL    |              |
+-----+-----+-----+-----+-----+-----+
```

8 rows in set (0.0071 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into Departments
(dept_id,dept_code,dept_name,building,established,total_students,budget,description)values
s

-> (1,'sss','cse','1k',2004,500,100.00,'hello');

Query OK, 1 row affected (0.0087 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into

-> Departments values

-> (2,'BBA01','Business

Administration','C',2012,450,2000000,'BBA Department');

Query OK, 1 row affected (0.0075 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select* from Departments;

```
+-----+-----+-----+-----+-----+-----+-----+
+
| dept_id | dept_code | dept_name          | building | established | total_students | budget | description |
+-----+-----+-----+-----+-----+-----+-----+
+
| 1 | sss | cse | 1k | 2004 | 500 | 100 | hello |
| 2 | BBA01 | Business Administration | C | 2012 | 450 | 2000000 | BBA
Department |
+-----+-----+-----+-----+-----+-----+-----+
+
2 rows in set (0.0017 sec)
```

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc Teachers;

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default      | Extra      |
+-----+-----+-----+-----+-----+-----+
| teacher_id | int       | NO   | PRI | NULL         | auto_increment |
| dept_id    | smallint  | YES  | MUL | NULL         |               |
| teacher_name | varchar(100) | YES  |     | NULL         |               |
| salary     | decimal(10,2) | YES  |     | NULL         |               |
| experience  | float     | YES  |     | NULL         |               |
| joining_date | date      | YES  |     | NULL         |               |
| login_time  | time      | YES  |     | NULL         |               |
| created_at  | datetime  | YES  |     | NULL         |               |
| updated_at  | timestamp | YES  |     | CURRENT_TIMESTAMP |
DEFAULT_GENERATED |
+-----+-----+-----+-----+-----+-----+
9 rows in set (0.0082 sec)
```

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into Teachers

-> (

teacher_id,dept_id,teacher_name,salary,experience,joining_data,login_time,created_at,updated_at)

-> values

-> (1,101,'y',100000,10.5,'2017-05-09','07:05:00','2017-05-09

07:05:00','2017-05-09 07:05:00');

ERROR: 1054: Unknown column 'joining_data' in 'field list'

MySQL localhost:33060+ ssl dbms_f_parcs SQL > INSERT INTO Teachers

```
-> (teacher_id, dept_id, teacher_name, salary, experience,
joining_date, login_time, created_at, updated_at)
```

```
-> VALUES
```

```
-> (1, 101, 'y', 100000, 10.5, '2017-05-09', '07:05:00',
```

```
'2017-05-09 07:05:00', '2017-05-09 07:05:00');
```

```
ERROR: 1452: Cannot add or update a child row: a foreign key constraint fails
(`dbms_f_parc`.`teachers`, CONSTRAINT `teachers_ibfk_1` FOREIGN KEY (`dept_id`)
REFERENCES `departments` (`dept_id`))
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > INSERT INTO Teachers
```

```
-> (teacher_id, dept_id, teacher_name, salary, experience,
joining_date, login_time, created_at, updated_at)
```

```
-> VALUES
```

```
-> (1, 101, 'y', 100000, 10.5, '2017-05-09', '07:05:00',
```

```
'2017-05-09 07:05:00', '2017-05-09 07:05:00');
```

```
ERROR: 1452: Cannot add or update a child row: a foreign key constraint fails
(`dbms_f_parc`.`teachers`, CONSTRAINT `teachers_ibfk_1` FOREIGN KEY (`dept_id`)
REFERENCES `departments` (`dept_id`))
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > SELECT dept_id, dept_name
```

```
-> FROM Departments;
```

```
+-----+-----+
| dept_id | dept_name |
```

```
+-----+-----+
| 1 | cse |
```

```
| 2 | Business Administration |
```

```
+-----+-----+
```

```
2 rows in set (0.0012 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > INSERT INTO Teachers
```

```
-> (teacher_id, dept_id, teacher_name, salary, experience,
joining_date, login_time, created_at, updated_at)
```

```
-> VALUES
```

```
-> (1, 1, 'y', 100000, 10.5, '2017-05-09', '07:05:00', '2017-05-09
07:05:00', '2017-05-09 07:05:00');
```

```
Query OK, 1 row affected (0.0075 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > insert into Teachers values
```

```
-> INSERT INTO Teachers (teacher_id, dept_id, teacher_name,
salary, experience, joining_date, login_time, created_at, updated_at) VALUES (1, 1, 'y',
100000, 10.5, '2017-05-09', '07:05:00', '2017-05-09 07:05:00', '2017-05-09 07:05:00');
```

```
ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'INSERT INTO Teachers
(teacher_id, dept_id, teacher_name, salary, experience, joi' at line 2
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > insert into Teachers values
```

```
-> (2, 2, 'y', 100000, 10.5, '2017-05-09', '07:05:00', '2017-05-09
07:05:00', '2017-05-09 07:05:00');
```

```
Query OK, 1 row affected (0.0073 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > select * from Teachers;
```

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+
```

teacher_id	dept_id	teacher_name	salary	experience	joining_date	login_time	created_at	updated_at
1	1	y	100000.00	10.5	2017-05-09	07:05:00	2017-05-09 07:05:00	2017-05-09 07:05:00
2	2	y	100000.00	10.5	2017-05-09	07:05:00	2017-05-09 07:05:00	2017-05-09 07:05:00

2 rows in set (0.0014 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > desc Courses;

Field	Type	Null	Key	Default	Extra
course_id	int	NO	PRI	NULL	auto_increment
dept_id	smallint	YES	MUL	NULL	
teacher_id	int	YES	MUL	NULL	
course_code	char(8)	YES	UNI	NULL	
course_name	varchar(100)	YES		NULL	
credit	decimal(2,1)	YES		NULL	
semester	enum('Spring','Summer','Fall')	YES		NULL	
syllabus	mediumtext	YES		NULL	
notes	longtext	YES		NULL	
course_image	blob	YES		NULL	
pdf_file	longblob	YES		NULL	
course_info	json	YES		NULL	

12 rows in set (0.0093 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > insert into courses

->

(course_id,dept_id,teacher_id,course_name,credit,semester,syllabus,notes,course_image,pdf_file,course_info)

-> values

-> (1,1,1,'c','c1',3.1,'Summer','hello1','she

good',null,null,'{"level":"Beginner",language":"e"}'

->);

ERROR: 1136: Column count doesn't match value count at row 1

MySQL localhost:33060+ ssl dbms_f_parc SQL > MySQL localhost:33060+ ssl dbms_f_parc SQL > desc Courses;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'MySQL localhost:33060+ ssl dbms_f_parc SQL > desc Courses' at line 1

MySQL localhost:33060+ ssl dbms_f_parc SQL >

Field	Type	Null	Key	Default	Extra

```

->
+-----+-----+-----+-----+-----+
auto_increment | -> | course_id | int | NO | PRI | NULL |
|
| -> | dept_id | smallint | YES | MUL | NULL |
|
| -> | teacher_id | int | YES | MUL | NULL |
|
| -> | course_code | char(8) | YES | UNI | NULL
|
| -> | course_name | varchar(100) | YES | | NULL
|
| -> | credit | decimal(2,1) | YES | | NULL |
|
| -> | semester | enum('Spring','Summer','Fall') | YES | |
NULL |
| -> | syllabus | mediumtext | YES | | NULL |
|
| -> | notes | longtext | YES | | NULL |
|
| -> | course_image | blob | YES | | NULL |
|
| -> | pdf_file | longblob | YES | | NULL |
|
| -> | course_info | json | YES | | NULL |
|
->

```

```

+-----+-----+-----+-----+-----+
-> 12 rows in set (0.0093 sec)
-> MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert
into courses
->
->
(course_id,dept_id,teacher_id,course_name,credit,semester,syllabus,notes,course_image,p
df_file,course_info)
->
-> values
->
(1,1,1,'c','c1',3.1,'Summer','hello1','she good',null,null,'{"level":"Beginner",language":"e"}'
-> );

```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near

```

'+-----+-----+-----+-----+-----+' at line 1
MySQL localhost:33060+ ssl dbms_f_parcs SQL > ERROR: 1136: Column count doesn't
match value count at row 1

```

```

'> MySQL localhost:33060+ ssl dbms_f_parcs SQL ;
'> ;
'> ;^C
MySQL localhost:33060+ ssl dbms_f_parcs SQL > INSERT INTO Courses

```

```

-> (dept_id, teacher_id, course_code, course_name, credit,
semester, syllabus, notes, course_image, pdf_file, course_info)
-> VALUES
-> (
-> 1,
-> 1,
-> 'CSE101',
-> 'Database',
-> 3.1,
-> 'Summer',
-> 'hello1',
-> 'she good',
-> NULL,
-> NULL,
-> '{"level":"Beginner","language":"e"}'
-> );

```

Query OK, 1 row affected (0.0076 sec)

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > INSERT INTO Courses
-> (course_id, dept_id, teacher_id, course_code, course_name,
credit, semester, syllabus, notes, course_image, pdf_file, course_info)
-> VALUES
-> (2, 2, 2, 'CSE101', 'c', 3.1, 'Summer', 'hello1', 'she good',

```

```

NULL, NULL, '{"level":"Beginner","language":"e"}');

```

ERROR: 1062: Duplicate entry 'CSE101' for key 'courses.course_code'

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > INSERT INTO Courses
-> (course_id, dept_id, teacher_id, course_code, course_name,
credit, semester, syllabus, notes, course_image, pdf_file, course_info)
-> VALUES

```

```

-> INSERT INTO Courses (course_id, dept_id, teacher_id,
course_code, course_name, credit, semester, syllabus, notes, course_image, pdf_file,
course_info) VALUES (2, 2, 2, 'CSE101', 'c', 3.1, 'Summer', 'hello1', 'she good', NULL, NULL,
'{"level":"Beginner","language":"e"}');

```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'INSERT INTO Courses (course_id, dept_id, teacher_id, course_code, course_name, c' at line 4

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > INSERT INTO Courses
-> (course_id, dept_id, teacher_id, course_code, course_name,
credit, semester, syllabus, notes, course_image, pdf_file, course_info)
-> VALUES

```

```

-> (2, 2, 2, 'CSE102', 'c', 3.1, 'Summer', 'hello1', 'she good',
NULL, NULL, '{"level":"Beginner","language":"e"}');

```

Query OK, 1 row affected (0.0069 sec)

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > select * from Courses;

```

```

+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| course_id | dept_id | teacher_id | course_code | course_name | credit | semester | syllabus |
notes | course_image | pdf_file | course_info |

```

```

+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+
| 1 | 1 | 1 | CSE101 | Database | 3.1 | Summer | hello1 | she good |
NULL | NULL | {"level": "Beginner", "language": "e"} |
| 2 | 2 | 2 | CSE102 | c | 3.1 | Summer | hello1 | she good | NULL
| NULL | {"level": "Beginner", "language": "e"} |
+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+

```

2 rows in set (0.0018 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc Enrollments;

```

+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| enroll_id | bigint | NO | PRI | NULL | auto_increment |
| student_id | int | YES | MUL | NULL | |
| course_id | int | YES | MUL | NULL | |
| enroll_date | date | YES | | NULL | |
| fee | decimal(10,2) | NO | | NULL | |
| grade | char(2) | YES | | NULL | |
| remarks | varchar(200) | YES | | Pending | |
| attendance | int | YES | | NULL | |
+-----+-----+-----+-----+-----+-----+

```

8 rows in set (0.0109 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into Enrollments

->

(enroll_id,student_id,course_id,enroll_date,fee,grade,remarks,attendance)

-> values

-> (1011,1,1,'12-6-2004',10000.23,'A','good',5);

ERROR: 1292: Incorrect date value: '12-6-2004' for column 'enroll_date' at row 1

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into Enrollments

->

(enroll_id,student_id,course_id,enroll_date,fee,grade,remarks,attendance)

-> values

-> (1011,1,1,'2004-6-12',10000.23,'A','good',5);

'>

'> ;

'> ^C

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into Enrollments

->

(enroll_id,student_id,course_id,enroll_date,fee,grade,remarks,attendance)

-> values

-> (1011,1,1,'2004-6-12',10000.23,'A','good',5);

Query OK, 1 row affected (0.0070 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select * from Enrollments;

```

+-----+-----+-----+-----+-----+-----+-----+-----+
| enroll_id | student_id | course_id | enroll_date | fee | grade | remarks | attendance |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 1011 | 1 | 1 | 2004-06-12 | 10000.23 | A | good | 5 |

```



```
+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.0018 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > desc Students;
```

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES	1		

```
+-----+-----+-----+-----+-----+-----+-----+
10 rows in set (0.0150 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > ALTER TABLE Students
-> ADD yous_phone VARCHAR(20);
```

```
Query OK, 0 rows affected (0.0747 sec)
```

```
Records: 0 Duplicates: 0 Warnings: 0
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > desc Students;
```

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES	1		
yous_phone	varchar(20)	YES		NULL	

```
+-----+-----+-----+-----+-----+-----+-----+
11 rows in set (0.0051 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table Students
-> add yousuf_king varchar(50);
```

```
Query OK, 0 rows affected (0.0391 sec)
```

```
Records: 0 Duplicates: 0 Warnings: 0
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table Students
-> add yousu_two varchar(100);
```

```
Query OK, 0 rows affected (0.0294 sec)
```

Records: 0 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table students
-> modify phone varchar(500);

Query OK, 3 rows affected (0.1312 sec)

Records: 3 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parc SQL > desc students;

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(500)	YES		NULL	
active	tinyint(1)	YES	1		
yous_phone	varchar(20)	YES		NULL	
yousuf_king	varchar(50)	YES		NULL	
yousu_two	varchar(100)	YES		NULL	

13 rows in set (0.0039 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table students
-> modify phone varchar(15);

Query OK, 3 rows affected (0.1164 sec)

Records: 3 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parc SQL > desc students;

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES	1		
yous_phone	varchar(20)	YES		NULL	
yousuf_king	varchar(50)	YES		NULL	
yousu_two	varchar(100)	YES		NULL	

+-----+-----+-----+-----+-----+

13 rows in set (0.0045 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table Students
-> modify cgpa int;

Query OK, 3 rows affected (0.1225 sec)

Records: 3 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc students;

+-----+-----+-----+-----+-----+

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	int	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES	1		
yous_phone	varchar(20)	YES		NULL	
yousuf_king	varchar(50)	YES		NULL	
yousu_two	varchar(100)	YES		NULL	

+-----+-----+-----+-----+-----+

13 rows in set (0.0039 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table students
-> modify cgpa float;

Query OK, 3 rows affected (0.1150 sec)

Records: 3 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table students
-> modify cgpa decimal(3,2);

Query OK, 3 rows affected (0.1000 sec)

Records: 3 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc students;

+-----+-----+-----+-----+-----+

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	

phone	varchar(15)	YES	NULL	
active	tinyint(1)	YES	1	
yous_phone	varchar(20)	YES	NULL	
yousuf_king	varchar(50)	YES	NULL	
yousu_two	varchar(100)	YES	NULL	

13 rows in set (0.0046 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table students
-> change yous_phone yp varchar(20);
Query OK, 0 rows affected (0.0339 sec)

Records: 0 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parc SQL > desc students;

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES	1		
yp	varchar(20)	YES		NULL	
yousuf_king	varchar(50)	YES		NULL	
yousu_two	varchar(100)	YES		NULL	

13 rows in set (0.0034 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table students
-> change yousuf_king yk varchar(50);
Query OK, 0 rows affected (0.0394 sec)

Records: 0 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parc SQL > desc students;

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	

phone	varchar(15)	YES	NULL	
active	tinyint(1)	YES	1	
yp	varchar(20)	YES	NULL	
yk	varchar(50)	YES	NULL	
yousu_two	varchar(100)	YES	NULL	

13 rows in set (0.0046 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table students
-> change yousu_two yt varchar(100);
Query OK, 0 rows affected (0.0411 sec)

Records: 0 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc students;

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES		1	
yp	varchar(20)	YES		NULL	
yk	varchar(50)	YES		NULL	
yt	varchar(100)	YES		NULL	

13 rows in set (0.0054 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table stuedents
-> drop column yp;

ERROR: 1146: Table 'dbms_f_parcs.students' doesn't exist

MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table students
-> drop column yp;

Query OK, 0 rows affected (0.0449 sec)

Records: 0 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc students;

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	

age	tinyint	YES		NULL		
cgpa	decimal(3,2)	YES		NULL		
email	varchar(100)	YES	UNI	NULL		
phone	varchar(15)	YES		NULL		
active	tinyint(1)	YES		1		
yk	varchar(50)	YES		NULL		
yt	varchar(100)	YES		NULL		

+-----+-----+-----+-----+-----+-----+
12 rows in set (0.0039 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table students
-> drop column yk;

Query OK, 0 rows affected (0.0381 sec)

Records: 0 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parc SQL > desc students;

Field	Type	Null	Key	Default	Extra	
student_id	int	NO	PRI	NULL	auto_increment	
student_code	char(6)	NO	UNI	NULL		
first_name	varchar(50)	NO		NULL		
last_name	varchar(50)	YES		NULL		
gender	enum('Male','Female')	YES		NULL		
age	tinyint	YES		NULL		
cgpa	decimal(3,2)	YES		NULL		
email	varchar(100)	YES	UNI	NULL		
phone	varchar(15)	YES		NULL		
active	tinyint(1)	YES		1		
yt	varchar(100)	YES		NULL		

+-----+-----+-----+-----+-----+-----+
11 rows in set (0.0040 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table students
-> drop column yt;

Query OK, 0 rows affected (0.0412 sec)

Records: 0 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parc SQL > desc students;

Field	Type	Null	Key	Default	Extra	
student_id	int	NO	PRI	NULL	auto_increment	
student_code	char(6)	NO	UNI	NULL		
first_name	varchar(50)	NO		NULL		
last_name	varchar(50)	YES		NULL		
gender	enum('Male','Female')	YES		NULL		
age	tinyint	YES		NULL		
cgpa	decimal(3,2)	YES		NULL		
email	varchar(100)	YES	UNI	NULL		

```

| phone      | varchar(15)      | YES | | NULL | |
| active     | tinyint(1)       | YES | | 1    | |
+-----+-----+-----+-----+-----+-----+
10 rows in set (0.0039 sec)
MySQL localhost:33060+ ssl dbms_f_parc SQL > select * from students;
+-----+-----+-----+-----+-----+-----+-----+-----+
--+
| student_id | student_code | first_name | last_name | gender | age | cgpa | email          |
| phone      | active |
+-----+-----+-----+-----+-----+-----+-----+-----+
--+
|      1 | s000      | y      | h      | Male | 20 | 4.00 | yousuf@gmail.com | 0124356      |
1 |
|      2 | ST0004     | Mahi     | Hasan   | Male | 20 | 4.00 | mahi@gmail.com   | 01744444444 | 0 |
|      3 | ST0005     | Nabila   | Akter   | Female | 21 | 4.00 | nabila@gmail.com | 01755555555 | 1 |
+-----+-----+-----+-----+-----+-----+-----+-----+
--+
3 rows in set (0.0021 sec)
MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table students
-> add constraint cek_age check(age >=15);
Query OK, 3 rows affected (0.1365 sec)

```

Records: 3 Duplicates: 0 Warnings: 0

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > desc students;

```

```

+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra          |
+-----+-----+-----+-----+-----+-----+
| student_id | int           | NO   | PRI | NULL    | auto_increment |
| student_code | char(6)       | NO   | UNI | NULL    |                |
| first_name  | varchar(50)   | NO   |    | NULL    |                |
| last_name   | varchar(50)   | YES  |    | NULL    |                |
| gender      | enum('Male','Female') | YES  |    | NULL    |                |
| age         | tinyint       | YES  |    | NULL    |                |
| cgpa        | decimal(3,2)  | YES  |    | NULL    |                |
| email       | varchar(100)  | YES  | UNI | NULL    |                |
| phone       | varchar(15)   | YES  |    | NULL    |                |
| active      | tinyint(1)    | YES  |    | 1       |                |
+-----+-----+-----+-----+-----+-----+
10 rows in set (0.0041 sec)
MySQL localhost:33060+ ssl dbms_f_parc SQL > select * from students;
+-----+-----+-----+-----+-----+-----+-----+-----+
--+
| student_id | student_code | first_name | last_name | gender | age | cgpa | email          |
| phone      | active |
+-----+-----+-----+-----+-----+-----+-----+-----+
--+

```


MySQL localhost:33060+ ssl dbms_f_parc SQL > show create table students;

```
+-----+-----+
| Table | Create Table
|
+-----+-----+
| students | CREATE TABLE `students` (
  `student_id` int NOT NULL AUTO_INCREMENT,
  `student_code` char(6) NOT NULL,
  `first_name` varchar(50) NOT NULL,
  `last_name` varchar(50) DEFAULT NULL,
  `gender` enum('Male','Female') DEFAULT NULL,
  `age` tinyint DEFAULT NULL,
  `cgpa` decimal(3,2) DEFAULT NULL,
  `email` varchar(100) DEFAULT NULL,
  `phone` varchar(15) DEFAULT NULL,
  `active` tinyint(1) DEFAULT '1',
  PRIMARY KEY (`student_id`),
  UNIQUE KEY `student_code` (`student_code`),
  UNIQUE KEY `email` (`email`),
  CONSTRAINT `cek_age` CHECK ((`age` >= 15))
) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4_0900_ai_ci |
+-----+-----+
```

1 row in set (0.0017 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > show create table students;

```
+-----+-----+
| Table | Create Table
|
+-----+-----+
```

```

+-----+-----+
|
|
|
|
|
|
|-----+
| students | CREATE TABLE `students` (
|   `student_id` int NOT NULL AUTO_INCREMENT,
|   `student_code` char(6) NOT NULL,
|   `first_name` varchar(50) NOT NULL,
|   `last_name` varchar(50) DEFAULT NULL,
|   `gender` enum('Male','Female') DEFAULT NULL,
|   `age` tinyint DEFAULT NULL,
|   `cgpa` decimal(3,2) DEFAULT NULL,
|   `email` varchar(100) DEFAULT NULL,
|   `phone` varchar(15) DEFAULT NULL,
|   `active` tinyint(1) DEFAULT '1',
|   PRIMARY KEY (`student_id`),
|   UNIQUE KEY `student_code` (`student_code`),
|   UNIQUE KEY `email` (`email`),
|   CONSTRAINT `cek_age` CHECK ((`age` >= 15))
| ) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=utf8mb4
| COLLATE=utf8mb4_0900_ai_ci |
+-----+-----+
|
|
|
|
|
|-----+
1 row in set (0.0014 sec)
MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table students
      -> drop constraint cek_age;
ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'cek_age' at line 2
MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table students
      -> add constraint c_k check(age>=10);
ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'c_k check(age>=10)' at line 2
MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table students
      -> add constraint c_k check (age >= 10);;
Query OK, 3 rows affected (0.0802 sec)

Records: 3 Duplicates: 0 Warnings: 0
ERROR: 1065: Query was empty
MySQL localhost:33060+ ssl dbms_f_parcs SQL > show create table students;
+-----+-----+
|
|
|
|
|
|

```

```
-----+
| Table | Create Table
|
+-----+
```

```
-----+
| students | CREATE TABLE `students` (
  `student_id` int NOT NULL AUTO_INCREMENT,
  `student_code` char(6) NOT NULL,
  `first_name` varchar(50) NOT NULL,
  `last_name` varchar(50) DEFAULT NULL,
  `gender` enum('Male','Female') DEFAULT NULL,
  `age` tinyint DEFAULT NULL,
  `cgpa` decimal(3,2) DEFAULT NULL,
  `email` varchar(100) DEFAULT NULL,
  `phone` varchar(15) DEFAULT NULL,
  `active` tinyint(1) DEFAULT '1',
  PRIMARY KEY (`student_id`),
  UNIQUE KEY `student_code` (`student_code`),
  UNIQUE KEY `email` (`email`),
  CONSTRAINT `c_k` CHECK ((`age` >= 10)),
  CONSTRAINT `cek_age` CHECK ((`age` >= 15))
) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4_0900_ai_ci |
+-----+
```

```
-----+
1 row in set (0.0018 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table students
-> drop constraint c_k;
```

```
Query OK, 0 rows affected (0.0291 sec)
```

```
Records: 0 Duplicates: 0 Warnings: 0
```

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > show create table students;
```

```
-----+
```

1

[illegible]

Query OK, 0 rows affected (0.0215 sec)

Handwriting practice lines with dashed midlines and solid top/bottom lines. The first line has a '+' sign at the start, and the last line has a '+' sign at the end.

i

```

-----+
| students | CREATE TABLE `students` (
  `student_id` int NOT NULL AUTO_INCREMENT,
  `student_code` char(6) NOT NULL,
  `first_name` varchar(50) NOT NULL,
  `last_name` varchar(50) DEFAULT NULL,
  `gender` enum('Male','Female') DEFAULT NULL,
  `age` tinyint DEFAULT NULL,
  `cgpa` decimal(3,2) DEFAULT NULL,
  `email` varchar(100) DEFAULT NULL,
  `phone` varchar(15) DEFAULT NULL,
  `active` tinyint(1) DEFAULT '1',
  PRIMARY KEY (`student_id`),
  UNIQUE KEY `student_code` (`student_code`),
  UNIQUE KEY `email` (`email`)
) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4_0900_ai_ci |
-----+
-----+
-----+
-----+
-----+
-----+

```

1 row in set (0.0014 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > RENAME TABLE STUDENTS TO S1;
Query OK, 0 rows affected (0.0412 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > rename table s1 to students;
Query OK, 0 rows affected (0.0323 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table rename students to s1;
ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'rename students to s1' at line 1

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table stuents rename students to
s1;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'to s1' at line 1

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table students rename to s1;
Query OK, 0 rows affected (0.0434 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > rename table s1 to students;
Query OK, 0 rows affected (0.0410 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > rename table students to s1;
Query OK, 0 rows affected (0.0426 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > alter table s1 rename to students;
Query OK, 0 rows affected (0.0381 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > rename table student to s;
ERROR: 1146: Table 'dbms_f_parc.student' doesn't exist

MySQL localhost:33060+ ssl dbms_f_parc SQL > rename tablw students to s;
ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'tablw students to s' at line 1

```

MySQL localhost:33060+ ssl dbms_f_parce SQL > rename table students to s;
Query OK, 0 rows affected (0.0407 sec)
MySQL localhost:33060+ ssl dbms_f_parce SQL > alter table s rename to students;
Query OK, 0 rows affected (0.0436 sec)
MySQL localhost:33060+ ssl dbms_f_parce SQL > alter table students rename to s;
Query OK, 0 rows affected (0.0644 sec)
MySQL localhost:33060+ ssl dbms_f_parce SQL > alter table s rename to students;
Query OK, 0 rows affected (0.0596 sec)
MySQL localhost:33060+ ssl dbms_f_parce SQL > rename table students to s;
Query OK, 0 rows affected (0.0405 sec)
MySQL localhost:33060+ ssl dbms_f_parce SQL > truncate table students;
ERROR: 1146: Table 'dbms_f_parce.students' doesn't exist
MySQL localhost:33060+ ssl dbms_f_parce SQL > TRUNCATE TABLE S;
ERROR: 1701: Cannot truncate a table referenced in a foreign key constraint
('dbms_f_parce`.`enrollments`, CONSTRAINT `enrollments_ibfk_1`)
MySQL localhost:33060+ ssl dbms_f_parce SQL > truncate table Courses;
ERROR: 1701: Cannot truncate a table referenced in a foreign key constraint
('dbms_f_parce`.`enrollments`, CONSTRAINT `enrollments_ibfk_2`)
MySQL localhost:33060+ ssl dbms_f_parce SQL > drop table Courses;
ERROR: 3730: Cannot drop table 'courses' referenced by a foreign key constraint
'enrollments_ibfk_2' on table 'enrollments'.
MySQL localhost:33060+ ssl dbms_f_parce SQL > create table y(
    -> id int,
    -> name char(5)
    -> );
Query OK, 0 rows affected (0.0580 sec)
MySQL localhost:33060+ ssl dbms_f_parce SQL > desc y;
+-----+-----+-----+-----+-----+-----+
| Field | Type  | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id    | int   | YES  |     | NULL    |       |
| name  | char(5) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
2 rows in set (0.0254 sec)
MySQL localhost:33060+ ssl dbms_f_parce SQL > truncate table y;
Query OK, 0 rows affected (0.0738 sec)
MySQL localhost:33060+ ssl dbms_f_parce SQL > create table y(
    -> id int,
    -> name char(5)
    -> );
ERROR: 1050: Table 'y' already exists
MySQL localhost:33060+ ssl dbms_f_parce SQL > create table y1(
    -> id int ,
    -> name char(5)
    -> );
Query OK, 0 rows affected (0.0584 sec)
MySQL localhost:33060+ ssl dbms_f_parce SQL > truncate table y1;
Query OK, 0 rows affected (0.0750 sec)

```

MySQL localhost:33060+ ssl dbms_f_parcs SQL > drop table y1;

Query OK, 0 rows affected (0.0456 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc y1;

ERROR: 1146: Table 'dbms_f_parcs.y1' doesn't exist

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc y;

```
+-----+-----+-----+-----+-----+-----+
| Field | Type   | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| id    | int    | YES  |     | NULL    |       |
| name  | char(5)| YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
```

2 rows in set (0.0036 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > drop table y;

Query OK, 0 rows affected (0.0514 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc y;

ERROR: 1146: Table 'dbms_f_parcs.y' doesn't exist

MySQL localhost:33060+ ssl dbms_f_parcs SQL > INSERT INTO TopStudents (student_id,
name, cgpa)

-> desc y;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'desc y' at line 2

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into students(cgpa)

-> select cgpa,age from studnets where cgpa > 3.7;

ERROR: 1146: Table 'dbms_f_parcs.students' doesn't exist

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into s (cgpa,age)

-> select cgpa,age from s

-> where cgpa >3.7;

ERROR: 1364: Field 'student_code' doesn't have a default value

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc s;

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra      |
+-----+-----+-----+-----+-----+-----+
| student_id | int           | NO   | PRI | NULL    | auto_increment |
| student_code | char(6)       | NO   | UNI | NULL    |               |
| first_name  | varchar(50)   | NO   |     | NULL    |               |
| last_name   | varchar(50)   | YES  |     | NULL    |               |
| gender      | enum('Male','Female') | YES  |     | NULL    |               |
| age         | tinyint       | YES  |     | NULL    |               |
| cgpa        | decimal(3,2)  | YES  |     | NULL    |               |
| email       | varchar(100)  | YES  | UNI | NULL    |               |
| phone       | varchar(15)   | YES  |     | NULL    |               |
| active      | tinyint(1)    | YES  |     | 1       |               |
+-----+-----+-----+-----+-----+-----+
```

10 rows in set (0.0048 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select * from s;

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
```

student_id	student_code	first_name	last_name	gender	age	cgpa	email	phone	active
1	s000	y	h	Male	20	4.00	yousuf@gmail.com	0124356	1
2	ST0004	Mahi	Hasan	Male	20	4.00	mahi@gmail.com	01744444444	0
3	ST0005	Nabila	Akter	Female	21	4.00	nabila@gmail.com	01755555555	1

3 rows in set (0.0016 sec)

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > update s
-> set cgpa = 4.00
-> where student_id = 1;
```

Query OK, 1 row affected (0.0013 sec)

Rows matched: 1 Changed: 0 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > update s
-> set cgpa = 8.00
-> where student_id = 2;
```

Query OK, 1 row affected (0.0243 sec)

Rows matched: 1 Changed: 1 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > select * from s;
```

student_id	student_code	first_name	last_name	gender	age	cgpa	email	phone	active
1	s000	y	h	Male	20	4.00	yousuf@gmail.com	0124356	1
2	ST0004	Mahi	Hasan	Male	20	8.00	mahi@gmail.com	01744444444	0
3	ST0005	Nabila	Akter	Female	21	4.00	nabila@gmail.com	01755555555	1

3 rows in set (0.0013 sec)

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > update s
-> set first_name = yousuf
-> where student_id = 1;
```

ERROR: 1054: Unknown column 'yousuf' in 'field list'

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > update s
-> set first_name = 'yousuf'
-> where student_id = 1;
```


Query OK, 1 row affected (0.0058 sec)

Rows matched: 1 Changed: 1 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > update s
      -> set cgpa = cgpa + 0.05
      -> where student_id = 1;
```

Query OK, 1 row affected (0.0265 sec)

Rows matched: 1 Changed: 1 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc s;
```

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES	1		

10 rows in set (0.0041 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select * from s;
```

student_id	student_code	first_name	last_name	gender	age	cgpa	email	phone	active
1	s000	yousuf	h	Male	20	4.05	yousuf@gmail.com	0124356	1
2	ST0004	Mahi	Hasan	Male	20	8.00	mahi@gmail.com	01744444444	0
3	ST0005	Nabila	Akter	Female	21	4.00	nabila@gmail.com	01755555555	1

3 rows in set (0.0012 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > delete from s
      -> where student_id = 1;
```

ERROR: 1451: Cannot delete or update a parent row: a foreign key constraint fails
(`dbms\_f\_parcs`.`enrollments`, CONSTRAINT `enrollments\_ibfk\_1` FOREIGN KEY
(`student\_id`) REFERENCES `s` (`student\_id`))

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > creat table t(
      -> ;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'creat table t(' at line 1

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > CREATE TABLE Stud(
CREATE TABLE Stud(
```

```
-> student_id INT AUTO_INCREMENT PRIMARY KEY,
-> student_code CHAR(6) UNIQUE NOT NULL,
-> first_name VARCHAR(50) NOT NULL,
-> last_name VARCHAR(50),
-> gender ENUM('Male','Female'),
-> age TINYINT,
-> cgpa DECIMAL(3,2),
-> email VARCHAR(100) UNIQUE,
-> phone VARCHAR(15),
-> active BOOLEAN DEFAULT TRUE
-> );
```

Query OK, 0 rows affected (0.0756 sec)

```
MySQL localhost:33060+ ssl dbms... SQL > INSERT INTO
```

```
Stud(student_code,first_name,last_name,gender,age,cgpa,email,phone,active)
```

```
-> VALUES
```

```
->
```

```
('ST0001','Yousuf','Ahmed','Male',22,3.90,'yousuf@gmail.com','01711111111',TRUE),
```

```
->
```

```
('ST0002','Habib','Rahman','Male',21,3.65,'habib@gmail.com','01722222222',TRUE),
```

```
->
```

```
('ST0003','Srijon','Das','Male',22,3.80,'srijon@gmail.com','01733333333',TRUE),
```

```
->
```

```
('ST0004','Mahi','Hasan','Male',20,3.55,'mahi@gmail.com','01744444444',FALSE),
```

```
->
```

```
('ST0005','Nabila','Akter','Female',21,3.95,'nabila@gmail.com','01755555555',TRUE);
```

Query OK, 5 rows affected (0.0107 sec)

Records: 5 Duplicates: 0 Warnings: 0

```
MySQL localhost:33060+ ssl dbms... SQL > desc stud;
```

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES		1	

10 rows in set (0.0040 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select * from stud;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
| student_id | student_code | first_name | last_name | gender | age | cgpa | email          |
| phone      | active |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
|      1 | ST0001      | Yousuf    | Ahmed     | Male   | 22 | 3.90 | yousuf@gmail.com |
| 0171111111 | 1 |
|      2 | ST0002      | Habib     | Rahman    | Male   | 21 | 3.65 | habib@gmail.com   |
| 0172222222 | 1 |
|      3 | ST0003      | Srijon    | Das       | Male   | 22 | 3.80 | srijon@gmail.com  |
| 0173333333 | 1 |
|      4 | ST0004      | Mahi      | Hasan     | Male   | 20 | 3.55 | mahi@gmail.com    |
| 0174444444 | 0 |
|      5 | ST0005      | Nabila    | Akter     | Female | 21 | 3.95 | nabila@gmail.com  |
| 0175555555 | 1 |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
```

5 rows in set (0.0015 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > delete from s
-> where student_id = 1;
```

ERROR: 1451: Cannot delete or update a parent row: a foreign key constraint fails
(`dbms\_f\_parcs`.`enrollments`, CONSTRAINT `enrollments\_ibfk\_1` FOREIGN KEY
(`student\_id`) REFERENCES `s` (`student\_id`))

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > delete from stud
-> where student_id = 1;
```

Query OK, 1 row affected (0.0241 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table stud
-> change cgpa float;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'float' at line 2

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table stud
-> change age int;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'int' at line 2

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table stud
-> change age1 tinyint;
```

Query OK, 0 rows affected (0.0298 sec)

Records: 0 Duplicates: 0 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > alter table stud
-> modify age1 int;
```

Query OK, 4 rows affected (0.1442 sec)

Records: 4 Duplicates: 0 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > delete from stud
-> where student_id = 2 and cgpa < 2.0;
```

Query OK, 0 rows affected (0.0013 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select *from stdu;

ERROR: 1146: Table 'dbms_f_parcs.stdu' doesn't exist

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select * from stdu;

ERROR: 1146: Table 'dbms_f_parcs.stdu' doesn't exist

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select * from stud;

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
---+
| student_id | student_code | first_name | last_name | gender | age1 | cgpa | email          |
| phone      | active |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
---+
|      2 | ST0002      | Habib      | Rahman    | Male    | 21 | 3.65 | habib@gmail.com |
| 01722222222 | 1 |
|      3 | ST0003      | Srijon     | Das       | Male    | 22 | 3.80 | srijon@gmail.com |
| 01733333333 | 1 |
|      4 | ST0004      | Mahi       | Hasan     | Male    | 20 | 3.55 | mahi@gmail.com   |
| 01744444444 | 0 |
|      5 | ST0005      | Nabila     | Akter     | Female  | 21 | 3.95 | nabila@gmail.com |
| 01755555555 | 1 |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
---+
```

4 rows in set (0.0013 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > delete from stdu

-> where student_id = 2 or cgpa <2.00;

ERROR: 1146: Table 'dbms_f_parcs.stdu' doesn't exist

MySQL localhost:33060+ ssl dbms_f_parcs SQL > delete from stud

-> where student_id = 2 or cgpa < 2.00;

Query OK, 1 row affected (0.0061 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select * from stud;

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
---+
| student_id | student_code | first_name | last_name | gender | age1 | cgpa | email          |
| phone      | active |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
---+
|      3 | ST0003      | Srijon     | Das       | Male    | 22 | 3.80 | srijon@gmail.com |
| 01733333333 | 1 |
|      4 | ST0004      | Mahi       | Hasan     | Male    | 20 | 3.55 | mahi@gmail.com   |
| 01744444444 | 0 |
|      5 | ST0005      | Nabila     | Akter     | Female  | 21 | 3.95 | nabila@gmail.com |
| 01755555555 | 1 |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
---+
```

3 rows in set (0.0014 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select * from s;

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
```

student_id	student_code	first_name	last_name	gender	age	cgpa	email	phone	active
1	s000	yousuf	h	Male	20	4.05	yousuf@gmail.com	0124356	1
2	ST0004	Mahi	Hasan	Male	20	8.00	mahi@gmail.com	01744444444	0
3	ST0005	Nabila	Akter	Female	21	4.00	nabila@gmail.com	01755555555	1

3 rows in set (0.0020 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,age from s;

first_name	age
yousuf	20
Mahi	20
Nabila	21

3 rows in set (0.0017 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select cgpa ,age from s;

cgpa	age
4.05	20
8.00	20
4.00	21

3 rows in set (0.0011 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select gender from s;

gender
Male
Male
Female

3 rows in set (0.0011 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name as yn,cgpa as cgpay from s;

yn	cgpay
yousuf	4.05
Mahi	8.00

| Nabila | 4.00 |

+-----+-----+

3 rows in set (0.0012 sec)

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > select age as ageking,
-> cgpa as cgpa_king
-> from s;
```

+-----+-----+

| ageking | cgpa_king |

+-----+-----+

| 20 | 4.05 |

| 20 | 8.00 |

| 21 | 4.00 |

+-----+-----+

3 rows in set (0.0012 sec)

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > select * from s;
```

+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

--+

| student_id | student_code | first_name | last_name | gender | age | cgpa | email | phone | active |

+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

--+

| 1 | s000 | yousuf | h | Male | 20 | 4.05 | yousuf@gmail.com | 0124356

| 1 |

| 2 | ST0004 | Mahi | Hasan | Male | 20 | 8.00 | mahi@gmail.com |

01744444444 | 0 |

| 3 | ST0005 | Nabila | Akter | Female | 21 | 4.00 | nabila@gmail.com |

01755555555 | 1 |

+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

--+

3 rows in set (0.0013 sec)

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > select first_name,cgpa,(cgpa * 0.25) as
percent_cgpa from s;
```

+-----+-----+-----+

| first_name | cgpa | percent_cgpa |

+-----+-----+-----+

| yousuf | 4.05 | 1.0125 |

| Mahi | 8.00 | 2.0000 |

| Nabila | 4.00 | 1.0000 |

+-----+-----+-----+

3 rows in set (0.0041 sec)

```
MySQL localhost:33060+ ssl dbms_f_parc SQL > select first_name,cgpa,(cgpa * 0.50) as
cgpa_king from s;
```

+-----+-----+-----+

| first_name | cgpa | cgpa_king |

+-----+-----+-----+

| yousuf | 4.05 | 2.0250 |

| Mahi | 8.00 | 4.0000 |

| Nabila | 4.00 | 2.0000 |

```
+-----+-----+
```

3 rows in set (0.0012 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select concat (first_name,'-cgpa:', cgpa)
summary
```

```
-> from s;
```

```
+-----+
```

```
| summary      |
```

```
+-----+
```

```
| yousuf-cgpa:4.05 |
```

```
| Mahi-cgpa:8.00  |
```

```
| Nabila-cgpa:4.00 |
```

```
+-----+
```

3 rows in set (0.0016 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select concat(first_name,'-hero', cgpa)
as summary
```

```
-> from s;
```

```
+-----+
```

```
| summary      |
```

```
+-----+
```

```
| yousuf-hero4.05 |
```

```
| Mahi-hero8.00  |
```

```
| Nabila-hero4.00 |
```

```
+-----+
```

3 rows in set (0.0013 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select s.first_name,s.cgpa
```

```
-> from s as s
```

```
-> where cgpa >2.00;
```

```
+-----+-----+
```

```
| first_name | cgpa |
```

```
+-----+-----+
```

```
| yousuf    | 4.05 |
```

```
| Mahi      | 8.00 |
```

```
| Nabila    | 4.00 |
```

```
+-----+-----+
```

3 rows in set (0.0015 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select s.first_name,s.cgpa from s
```

```
-> as s
```

```
-> where cgpa > 2.00;
```

```
+-----+-----+
```

```
| first_name | cgpa |
```

```
+-----+-----+
```

```
| yousuf    | 4.05 |
```

```
| Mahi      | 8.00 |
```

```
| Nabila    | 4.00 |
```

```
+-----+-----+
```

3 rows in set (0.0014 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select distinct cgpa from s;
```

```
+-----+
```

```
| cgpa |
```

```
+-----+
```

```
| 4.05 |
```

```
| 8.00 |
```

```
| 4.00 |
```

```
+-----+
```

```
3 rows in set (0.0024 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select distinct first_name from s;
```

```
+-----+
```

```
| first_name |
```

```
+-----+
```

```
| yousuf    |
```

```
| Mahi      |
```

```
| Nabila    |
```

```
+-----+
```

```
3 rows in set (0.0013 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select distinct age from s;
```

```
+-----+
```

```
| age |
```

```
+-----+
```

```
| 20 |
```

```
| 21 |
```

```
+-----+
```

```
2 rows in set (0.0012 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,age
```

```
-> from s
```

```
-> where age >= 18 and cgpa > 3.5;
```

```
+-----+
```

```
| first_name | age |
```

```
+-----+
```

```
| yousuf    | 20 |
```

```
| Mahi      | 20 |
```

```
| Nabila    | 21 |
```

```
+-----+
```

```
3 rows in set (0.0020 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,age from s
```

```
-> where student_id = 1 or student_id = 3;
```

```
+-----+
```

```
| first_name | age |
```

```
+-----+
```

```
| yousuf    | 20 |
```

```
| Nabila    | 21 |
```

```
+-----+
```

```
2 rows in set (0.0018 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,age,cgpa
```

```
-> from s
```

```
-> where not student_id = 3;
```

```
+-----+
```



```
| first_name | age | cgpa |
```

```
+-----+-----+
```

```
| yousuf    | 20 | 4.05 |
```

```
| Mahi      | 20 | 8.00 |
```

```
+-----+-----+
```

2 rows in set (0.0026 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,age,cgpa
```

```
-> from s
```

```
-> where( student_id = 1 or student_id = 2) and cgpa > 3.5;
```

```
+-----+-----+
```

```
| first_name | age | cgpa |
```

```
+-----+-----+
```

```
| yousuf    | 20 | 4.05 |
```

```
| Mahi      | 20 | 8.00 |
```

```
+-----+-----+
```

2 rows in set (0.0016 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name ,cgpa
```

```
-> from s
```

```
-> where cgpa between 3.0 and 3.5;
```

Empty set (0.0040 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,cgpa
```

```
-> from s
```

```
-> where age between 18 and 25;
```

```
+-----+-----+
```

```
| first_name | cgpa |
```

```
+-----+-----+
```

```
| yousuf    | 4.05 |
```

```
| Mahi      | 8.00 |
```

```
| Nabila    | 4.00 |
```

```
+-----+-----+
```

3 rows in set (0.0014 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name
```

```
-> from s
```

```
-> where age between 17 and 22;
```

```
+-----+
```

```
| first_name |
```

```
+-----+
```

```
| yousuf    |
```

```
| Mahi      |
```

```
| Nabila    |
```

```
+-----+
```

3 rows in set (0.0014 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name
```

```
-> from s
```

```
-> where not age between 10 and 20;
```

```
+-----+
```

```
| first_name |
```

```
+-----+
```

```
| Nabila |
+-----+
1 row in set (0.0015 sec)
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name
-> from s
-> where not age between 10 and 15;
```

```
+-----+
| first_name |
+-----+
| yousuf |
| Mahi |
| Nabila |
+-----+
```

```
3 rows in set (0.0015 sec)
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name
-> from s
-> where student_id(1,2,3,4);
```

ERROR: 1305: FUNCTION dbms_f_parcs.student_id does not exist

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name
-> from s
-> where student_id in(1,2,3,4);
```

```
+-----+
| first_name |
+-----+
| yousuf |
| Mahi |
| Nabila |
+-----+
```

```
3 rows in set (0.0017 sec)
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name
-> from s
-> where not student_id in(1,2);
```

```
+-----+
| first_name |
+-----+
| Nabila |
+-----+
```

```
1 row in set (0.0016 sec)
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name
-> from s
-> where student_id(select student_id from s where first_name
like '%y'));
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'select student_id from s where first_name like '%y'))' at line 3

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT first_name
```

```

-> FROM s
-> WHERE student_id IN (
->   SELECT student_id
->   FROM s
->   WHERE first_name LIKE '%y'
-> );

```

Empty set (0.0040 sec)

```

MySQL localhost:33060+ ssl dbms_f_parac SQL > select first_name from s
-> where first_name like '%o';

```

Empty set (0.0018 sec)

```

MySQL localhost:33060+ ssl dbms_f_parac SQL > select first_name from s
-> where first_name like 'o%';

```

Empty set (0.0012 sec)

```

MySQL localhost:33060+ ssl dbms_f_parac SQL > select first_name from s
-> where first_name like 'N%';

```

ERROR: 1054: Unknown column 'first_name' in 'where clause'

```

MySQL localhost:33060+ ssl dbms_f_parac SQL > select first_name from s
-> whete first_name like 'N%';

```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'first_name like 'N%' at line 2

```

MySQL localhost:33060+ ssl dbms_f_parac SQL > select first_name from s
-> where first_name like 'N%';

```

```

+-----+
| first_name |
+-----+
| Nabila    |
+-----+

```

1 row in set (0.0015 sec)

```

MySQL localhost:33060+ ssl dbms_f_parac SQL > select first_name from s
-> where first_name like 'y%';

```

```

+-----+
| first_name |
+-----+
| yousuf    |
+-----+

```

1 row in set (0.0016 sec)

```

MySQL localhost:33060+ ssl dbms_f_parac SQL > select first_name from s
-> where first_name like 'y_f%';

```

Empty set (0.0014 sec)

```

MySQL localhost:33060+ ssl dbms_f_parac SQL > select first_name from s
-> where first_name like '%y_f';

```

Empty set (0.0021 sec)

```

MySQL localhost:33060+ ssl dbms_f_parac SQL > select first_name from s
-> where first_name not like'y%';

```

```

+-----+
| first_name |

```

```
+-----+
| Mahi   |
| Nabila |
+-----+
```

2 rows in set (0.0016 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_time from s
-> where frist_;
```

ERROR: 1054: Unknown column 'first_time' in 'field list'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name from s
-> where frist_name like '%us%';
```

ERROR: 1054: Unknown column 'frist_name' in 'where clause'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name from s
-> where frist_name like '%us%';
'> ;
'>
'> ^C
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name from s
-> where first_name like '%us%';
'>
'> ^C
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT first_name
-> FROM s
-> WHERE first_name LIKE '%us%';
```

```
+-----+
| first_name |
+-----+
| yousuf     |
+-----+
```

1 row in set (0.0016 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select age from s
-> where first_name is not null;
```

```
+-----+
| age |
+-----+
| 20 |
| 20 |
| 21 |
+-----+
```

3 rows in set (0.0019 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select age from s
-> where first_name is null;
```

Empty set (0.0010 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name ifnull(age,'not age') as
age from s;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '(age,'not age') as age from s' at line 1

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,ifnull(age,'not age') as age from s;

```
+-----+-----+
| first_name | age |
+-----+-----+
| yousuf    | 20  |
| Mahi      | 20  |
| Nabila    | 21  |
+-----+-----+
```

3 rows in set (0.0020 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,age
-> from s
-> order by desc
-> limit 3;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'desc limit 3' at line 3

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,age
-> from s
-> order by desc
-> ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'desc' at line 3

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name ,age
-> from s
-> order by cgpa desc
-> limit 3;

```
+-----+-----+
| first_name | age |
+-----+-----+
| Mahi      | 20  |
| yousuf    | 20  |
| Nabila    | 21  |
+-----+-----+
```

3 rows in set (0.0027 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,age
-> from s
-> order by age desc
-> limit 3 offset 1;

```
+-----+-----+
| first_name | age |
+-----+-----+
| yousuf    | 20  |
| Mahi      | 20  |
+-----+-----+
```

2 rows in set (0.0012 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,age from s
-> order by age desc
-> limit 3,1;
```

Empty set (0.0015 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select count(*) from s;
```

```
+-----+
| count(*) |
+-----+
|      3 |
+-----+
```

1 row in set (0.0021 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select count (studnet_id) from s;
ERROR: 1630: FUNCTION dbms_f_parcs.count does not exist. Check the 'Function Name
Parsing and Resolution' section in the Reference Manual
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > slect count (student_id) from s;
ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'slect count (student_id) from s'
at line 1
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select count (student_id) from s;
ERROR: 1630: FUNCTION dbms_f_parcs.count does not exist. Check the 'Function Name
Parsing and Resolution' section in the Reference Manual
```

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc s;
```

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type                | Null | Key | Default | Extra          |
+-----+-----+-----+-----+-----+-----+
| student_id | int                  | NO   | PRI | NULL    | auto_increment |
| student_code | char(6)              | NO   | UNI | NULL    |                |
| first_name  | varchar(50)          | NO   |    | NULL    |                |
| last_name   | varchar(50)          | YES  |    | NULL    |                |
| gender      | enum('Male','Female') | YES  |    | NULL    |                |
| age         | tinyint              | YES  |    | NULL    |                |
| cgpa        | decimal(3,2)         | YES  |    | NULL    |                |
| email       | varchar(100)         | YES  | UNI | NULL    |                |
| phone       | varchar(15)          | YES  |    | NULL    |                |
| active      | tinyint(1)           | YES  |    | 1       |                |
+-----+-----+-----+-----+-----+-----+
```

10 rows in set (0.0088 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select * from s;
```

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
| student_id | student_code | first_name | last_name | gender | age | cgpa | email          | phone | active |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
|      1 | s000        | yousuf    | h         | Male   | 20 | 4.05 | yousuf@gmail.com | 0124356 | 1 |
```

2	ST0004	Mahi	Hasan	Male	20	8.00	mahi@gmail.com
01744444444	0						
3	ST0005	Nabila	Akter	Female	21	4.00	nabila@gmail.com
01755555555	1						

```

+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
```

3 rows in set (0.0017 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select count (gender) from s;

ERROR: 1630: FUNCTION dbms_f_parcs.count does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select count(gender)
-> from s;

```

+-----+
| count(gender) |
+-----+
|          3 |
+-----+
```

1 row in set (0.0015 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select count(student_id)
-> from s;

```

+-----+
| count(student_id) |
+-----+
|          3 |
+-----+
```

1 row in set (0.0014 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select count(distinct gender)from s;

```

+-----+
| count(distinct gender) |
+-----+
|          2 |
+-----+
```

1 row in set (0.0043 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select sum(cgpa) from s;

```

+-----+
| sum(cgpa) |
+-----+
|    16.05 |
+-----+
```

1 row in set (0.0013 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select sum(age) from s;

```

+-----+
| sum(age) |
+-----+
|    61 |
+-----+
```

1 row in set (0.0012 sec)

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > select sum(age) from s
-> where student_id = 1;
```

```
+-----+
| sum(age) |
```

```
+-----+
|    20    |
```

```
+-----+
1 row in set (0.0012 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > select sum(age) from s
-> where student_id = 1 and student_id = 3;
```

```
+-----+
| sum(age) |
```

```
+-----+
|   NULL   |
```

```
+-----+
1 row in set (0.0011 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > select avg(cgpa) from s;
```

```
+-----+
| avg(cgpa) |
```

```
+-----+
| 5.350000 |
```

```
+-----+
1 row in set (0.0014 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > select round(avg(cgpa),2)as ya from s;
ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near '2)as ya from s' at line 1
```

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > select roun(avg(cgpa),2) as ya from s;
ERROR: 1305: FUNCTION dbms_f_parce.roun does not exist
```

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > select round (avg(cgpa),2) asya from s;
```

```
+-----+
| asya |
```

```
+-----+
| 5.35 |
```

```
+-----+
1 row in set (0.0030 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > select max(cgpa) from s;
```

```
+-----+
| max(cgpa) |
```

```
+-----+
|    8.00    |
```

```
+-----+
1 row in set (0.0042 sec)
```

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > selct max(cgpa) from s
-> where student_id = 1 and student_id = 2;
```

```
ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to
your MySQL server version for the right syntax to use near 'selct max(cgpa) from s
where student_id = 1 and student_id = 2' at line 1
```

```
MySQL localhost:33060+ ssl dbms_f_parce SQL > SELECT MAX(cgpa)
```



```
-> FROM s
-> WHERE student_id IN (1,2);
```

```
+-----+
| MAX(cgpa) |
```

```
+-----+
| 8.00 |
```

```
+-----+
```

1 row in set (0.0014 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT MAX(cgpa)

```
-> FROM s
```

```
-> WHERE student_id = 1 OR student_id = 2;
```

```
+-----+
| MAX(cgpa) |
```

```
+-----+
| 8.00 |
```

```
+-----+
```

1 row in set (0.0014 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,cgpa from s

```
-> where cgpa = (select max(cgpa) from student;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near " at line 2

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,cgpa,from s

```
-> where cgpa = (select max(cgpa) from s);
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'from s

where cgpa = (select max(cgpa) from s)' at line 1

MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT first_name, cgpa

```
-> FROM s
```

```
-> WHERE cgpa = (
```

```
->   SELECT MAX(cgpa)
```

```
->   FROM s
```

```
-> );
```

```
+-----+-----+
| first_name | cgpa |
```

```
+-----+-----+
| Mahi      | 8.00 |
```

```
+-----+-----+
```

1 row in set (0.0043 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select min(cgpa) from s;

```
+-----+
| min(cgpa) |
```

```
+-----+
| 4.00 |
```

```
+-----+
```

1 row in set (0.0014 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select count(*) as all_student,

```

-> round(avg(cgpa),2) as gc,
-> max(cgpa) as mcg,
-> min (cgpa) as mic
-> from s;

```

ERROR: 1630: FUNCTION dbms_f_parc.min does not exist. Check the 'Function Name Parsing and Resolution' section in the Reference Manual

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > SELECT
-> COUNT(*) AS all_student,
-> ROUND(AVG(cgpa), 2) AS gc,
-> MAX(cgpa) AS mcg,
-> MIN(cgpa) AS mic
-> FROM s;

```

```

+-----+-----+-----+-----+
| all_student | gc | mcg | mic |
+-----+-----+-----+-----+
|          3 | 5.35 | 8.00 | 4.00 |
+-----+-----+-----+-----+

```

1 row in set (0.0014 sec)

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > select first_name,cgpa from s
-> order by ace;

```

ERROR: 1054: Unknown column 'ace' in 'order clause'

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > select first_name,cgpa from s

```

```

-> order by cgpa ace;

```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'ace' at line 2

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > select first_name,cgpa from s

```

```

-> order by cgpa asc;

```

```

+-----+-----+
| first_name | cgpa |
+-----+-----+
| Nabila    | 4.00 |
| yousuf    | 4.05 |
| Mahi      | 8.00 |
+-----+-----+

```

3 rows in set (0.0016 sec)

```

MySQL localhost:33060+ ssl dbms_f_parc SQL > select first_name,cgpa from s

```

```

-> order by cgpa desc;

```

```

+-----+-----+
| first_name | cgpa |
+-----+-----+
| Mahi      | 8.00 |
| yousuf    | 4.05 |
| Nabila    | 4.00 |
+-----+-----+

```

3 rows in set (0.0012 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc s;

Field	Type	Null	Key	Default	Extra
student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age	tinyint	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES	1		

10 rows in set (0.0084 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id avg(cgpa) from s
-> group by student_id;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '(cgpa) from s group by student_id' at line 1

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id,avg(cgpa)
-> from s
-> group by student_id;

student_id	avg(cgpa)
1	4.050000
2	8.000000
3	4.000000

3 rows in set (0.0013 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select studen_id,count(*) as allc
-> from s
-> group by student_id;

ERROR: 1054: Unknown column 'studen_id' in 'field list'

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id ,count(*) as
-> from s
-> group by student_id;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'from s group by student_id' at line 2

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id ,count(*) as fuck
-> group by student_id;

ERROR: 1054: Unknown column 'student_id' in 'field list'

MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT student_id, COUNT(*) AS
-> FROM s
-> GROUP BY student_id;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'FROM s GROUP BY student_id' at line 2

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT student_id,
-> COUNT(*) AS total
-> FROM s
-> GROUP BY student_id;
```

```
+-----+-----+
| student_id | total |
+-----+-----+
| 1 | 1 |
| 2 | 1 |
| 3 | 1 |
+-----+-----+
```

3 rows in set (0.0015 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id,count(*) as good
-> from s
-> group by student_id;
```

```
+-----+-----+
| student_id | good |
+-----+-----+
| 1 | 1 |
| 2 | 1 |
| 3 | 1 |
+-----+-----+
```

3 rows in set (0.0008 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc department;
```

ERROR: 1146: Table 'dbms_f_parcs.department' doesn't exist

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc departments;
```

```
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra      |
+-----+-----+-----+-----+-----+-----+
| dept_id    | smallint  | NO   | PRI | NULL    | auto_increment |
| dept_code  | char(5)   | YES  | UNI | NULL    |               |
| dept_name  | varchar(100) | NO   |     | NULL    |               |
| building   | varchar(50) | YES  |     | NULL    |               |
| established | year      | YES  |     | NULL    |               |
| total_students | mediumint | YES  |     | NULL    |               |
| budget     | double    | YES  |     | NULL    |               |
| description | text      | YES  |     | NULL    |               |
+-----+-----+-----+-----+-----+-----+
```

8 rows in set (0.0050 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select dept_name,count(*) as alltotal,
-> round(avg(cgpa),2) as mainavg
-> from s
-> s1 join departments on s.student_id = d.student_id
-> group by student_id;
```

ERROR: 1054: Unknown column 's.student_id' in 'on clause'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT d.dept_name,  
-> COUNT(*) AS alltotal,  
-> ROUND(AVG(s.cgpa),2) AS mainavg  
-> FROM s s  
-> JOIN departments d  
-> ON s.dept_id = d.dept_id  
-> GROUP BY d.dept_name;
```

ERROR: 1054: Unknown column 's.dept_id' in 'on clause'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > UPDATE s SET dept_id = 1 WHERE  
student_id = 1;
```

ERROR: 1054: Unknown column 'dept_id' in 'field list'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > UPDATE s SET dept_id = 1 WHERE  
student_id = 2;
```

ERROR: 1054: Unknown column 'dept_id' in 'field list'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > UPDATE s SET dept_id = 2 WHERE  
student_id = 3;
```

ERROR: 1054: Unknown column 'dept_id' in 'field list'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > UPDATE s SET dept_id = 1 WHERE  
student_id = 1;
```

ERROR: 1054: Unknown column 'dept_id' in 'field list'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > UPDATE s SET dept_id = 1 WHERE  
student_id = 2;
```

ERROR: 1054: Unknown column 'dept_id' in 'field list'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > UPDATE s SET dept_id = 2 WHERE  
student_id = 3;
```

ERROR: 1054: Unknown column 'dept_id' in 'field list'

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > ALTER TABLE s  
-> ADD dept_id SMALLINT;
```

Query OK, 0 rows affected (0.0698 sec)

Records: 0 Duplicates: 0 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > UPDATE s SET dept_id = 1 WHERE  
student_id = 1;
```

Query OK, 1 row affected (0.0035 sec)

Rows matched: 1 Changed: 1 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > UPDATE s SET dept_id = 1 WHERE  
student_id = 2;
```

Query OK, 1 row affected (0.0038 sec)

Rows matched: 1 Changed: 1 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > UPDATE s SET dept_id = 2 WHERE  
student_id = 3;
```

Query OK, 1 row affected (0.0077 sec)

Rows matched: 1 Changed: 1 Warnings: 0

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT d.dept_name,  
-> COUNT(*) AS alltotal,
```

```

-> ROUND(AVG(s.cgpa),2) AS mainavg
-> FROM s
-> s join departments d on s.dept_id = d.dept_id
-> group by d.dept_name;

```

```

+-----+-----+-----+
| dept_name      | alltotal | mainavg |
+-----+-----+-----+
| cse             | 2       | 6.03    |
| Business Administration | 1       | 4.00    |
+-----+-----+-----+

```

2 rows in set (0.0067 sec)

```

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id,age, count(*) as all_s
-> from s
-> group by student_id;

```

```

+-----+-----+-----+
| student_id | age | all_s |
+-----+-----+-----+
| 1         | 20 | 1     |
| 2         | 20 | 1     |
| 3         | 21 | 1     |
+-----+-----+-----+

```

3 rows in set (0.0015 sec)

```

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id ,count(*) as kingcount
-> from s
-> group by student_id
-> having >2;

```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '>2' at line 4

```

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id,count(*) as kingcount
-> from s
-> group by student_id
-> having count(*) >2;

```

Empty set (0.0017 sec)

```

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id ,count(*) as kingcount
-> from s
-> group by student_id
-> having count(*) >1;

```

Empty set (0.0017 sec)

```

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id ,count(*) as kingcount
-> from stdu
-> group by student_id
-> having count(*) >2;

```

ERROR: 1146: Table 'dbms_f_parcs.stdu' doesn't exist

```

MySQL localhost:33060+ ssl dbms_f_parcs SQL > desc stud
-> ;

```

```

+-----+-----+-----+-----+-----+
| Field      | Type          | Null | Key | Default | Extra      |
+-----+-----+-----+-----+-----+

```

student_id	int	NO	PRI	NULL	auto_increment
student_code	char(6)	NO	UNI	NULL	
first_name	varchar(50)	NO		NULL	
last_name	varchar(50)	YES		NULL	
gender	enum('Male','Female')	YES		NULL	
age1	int	YES		NULL	
cgpa	decimal(3,2)	YES		NULL	
email	varchar(100)	YES	UNI	NULL	
phone	varchar(15)	YES		NULL	
active	tinyint(1)	YES	1		

10 rows in set (0.0045 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id ,count(*) as kingcount
-> from stdu
-> group by student_id
-> having count(*) >3;
```

ERROR: 1146: Table 'dbms_f_parcs.stdu' doesn't exist

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT student_id, COUNT(*) AS
kingcount
-> FROM stud
-> GROUP BY student_id
-> HAVING COUNT(*) > 3;
```

Empty set (0.0019 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT student_id, COUNT(*) AS
kingcount
-> FROM stud
-> GROUP BY student_id
-> HAVING COUNT(*) > 1;
```

Empty set (0.0010 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select student_id,avg(cgpa) as king_av
-> from s
-> group by student_id
-> having avg(cgpa) > 2.5;
```

student_id	king_av
1	4.050000
2	8.000000
3	4.000000

3 rows in set (0.0019 sec)

```
MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,(select avg(cgpa)
from s) as good_cgpa
-> from s;
```

first_name	good_cgpa
yousuf	5.350000

```
| Mahi      | 5.350000 |
| Nabila    | 5.350000 |
```

```
+-----+-----+
```

3 rows in set (0.0026 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL >

MySQL localhost:33060+ ssl dbms_f_parcs SQL > select first_name,cgpa

-> from s

-> where cgpa > (selct avg(cgpa)from s);

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'avg(cgpa)from s)' at line 3

MySQL localhost:33060+ ssl dbms_f_parcs SQL > SELECT first_name, cgpa

-> FROM s

-> WHERE cgpa > (SELECT AVG(cgpa) FROM s);

```
+-----+-----+
```

```
| first_name | cgpa |
```

```
+-----+-----+
```

```
| Mahi      | 8.00 |
```

```
+-----+-----+
```

1 row in set (0.0017 sec)

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into (student_id,first_name)

-> select student_id,first_name

-> from s

-> where cgpa > 2.00;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '(student_id,first_name)

select student_id,first_name

from s

where cgpa > 2.00' at line 1

MySQL localhost:33060+ ssl dbms_f_parcs SQL > insert into s(student_id,first_name)

-> select student_id,first_name

-> from s

-> where cgpa > 2.00;

ERROR: 1364: Field 'student_code' doesn't have a default value

MySQL localhost:33060+ ssl dbms_f_parcs SQL > INSERT INTO table_name (student_id, first_name)

-> SELECT student_id, first_name

-> FROM s

-> WHERE cgpa > 2.00;

ERROR: 1146: Table 'dbms_f_parcs.table_name' doesn't exist

MySQL localhost:33060+ ssl dbms_f_parcs SQL > MySQL localhost:33060+ ssl

dbms_f_parcs SQL > insert into s(student_id,first_name)

->

-> select student_id,first_name

->

-> from s

->

-> where cgpa > 2.00;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'MySQL localhost:33060+ ssl dbms_f_parc SQL > insert into s(student_id,first_n' at line 1

MySQL localhost:33060+ ssl dbms_f_parc SQL > ERROR: 1364: Field 'student_code' doesn't have a default value

'> ;

'> ^C

MySQL localhost:33060+ ssl dbms_f_parc SQL > INSERT INTO s

-> (student_code, first_name, last_name, gender, age, cgpa,
email, phone, active)

-> SELECT

-> CONCAT('NEW', student_id),

-> first_name,

-> last_name,

-> gender,

-> age,

-> cgpa,

-> CONCAT('new_', email),

-> phone,

-> active

-> FROM s

-> WHERE cgpa > 2.00;

Query OK, 3 rows affected (0.0085 sec)

Records: 3 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parc SQL > select s.first_name,d.dept_id

-> from s s1 inner join departments d on s.dept_id = d.dept_id;

ERROR: 1054: Unknown column 's.first_name' in 'field list'

MySQL localhost:33060+ ssl dbms_f_parc SQL > select stud.first_name,d,^C

MySQL localhost:33060+ ssl dbms_f_parc SQL > desc departments;

Field	Type	Null	Key	Default	Extra
dept_id	smallint	NO	PRI	NULL	auto_increment
dept_code	char(5)	YES	UNI	NULL	
dept_name	varchar(100)	NO		NULL	
building	varchar(50)	YES		NULL	
established	year	YES		NULL	
total_students	mediumint	YES		NULL	
budget	double	YES		NULL	
description	text	YES		NULL	

8 rows in set (0.0062 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > select s.first_name,d.dept_name

-> from s s1 inner join departments

-> s.dept_id = d.dept_id ;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '.dept_id = d.dept_id' at line 3

```
MySQL localhost:33060+ ssl dbms_f_parac SQL > SELECT s1.first_name, d.dept_name
-> FROM s AS s1
-> INNER JOIN departments AS d
-> ON s1.dept_id = d.dept_id;
```

first_name	dept_name
yousuf	cse
Mahi	cse
Nabila	Business Administration

3 rows in set (0.0027 sec)

```
MySQL localhost:33060+ ssl dbms_f_parac SQL > SELECT s1.first_name, d.dept_name
-> FROM s AS s1
-> INNER JOIN departments AS d
-> ON s1.dept_id = d.dept_id
-> ^C
```

```
MySQL localhost:33060+ ssl dbms_f_parac SQL > SELECT s1.first_name, d.dept_name
-> ^C
```

```
MySQL localhost:33060+ ssl dbms_f_parac SQL > SELECT s1.first_name,
d.dept_name, cgpa
-> ^C
```

```
MySQL localhost:33060+ ssl dbms_f_parac SQL > SELECT s1.first_name,
d.dept_name, s.cgpa
-> FROM s AS s1
-> INNER JOIN departments AS d
-> ON s1.dept_id = d.dept_id
-> where s.cgpa > 3.5
-> order by desc;
```

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'desc' at line 6

```
MySQL localhost:33060+ ssl dbms_f_parac SQL > SELECT s1.first_name,
-> d.dept_name,
-> s1.cgpa
-> FROM s AS s1
-> INNER JOIN departments AS d
-> ON s1.dept_id = d.dept_id
-> WHERE s1.cgpa > 3.5
-> ORDER BY s1.cgpa DESC;
```

first_name	dept_name	cgpa
Mahi	cse	8.00
yousuf	cse	4.05
Nabila	Business Administration	4.00

3 rows in set (0.0020 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > select * from s natural join departments;

```
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
| dept_id | student_id | student_code | first_name | last_name | gender | age | cgpa | email
| phone   | active | dept_code | dept_name          | building | established | total_students
| budget | description |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
|      1 |      1 | s000      | yousuf      | h      | Male | 20 | 4.05 | yousuf@gmail.com |
0124356 |      1 | sss      | cse          | 1k      |      2004 |      500 |      100 | hello
|
|      1 |      2 | ST0004     | Mahi      | Hasan      | Male | 20 | 8.00 | mahi@gmail.com |
01744444444 |      0 | sss      | cse          | 1k      |      2004 |      500 |      100 |
hello |
|      2 |      3 | ST0005     | Nabila     | Akter      | Female | 21 | 4.00 | nabila@gmail.com |
01755555555 |      1 | BBA01     | Business Administration | C      |      2012 |      450 |
2000000 | BBA Department |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+-----+-----+-----+-----+-----+-----+-----+-----+-----+
--+
```

3 rows in set (0.0035 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > create view high

-> as studeent_id,first_name

-> from s

-> where cgpa >= 3.50;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'studeent_id,first_name from s

where cgpa >= 3.50' at line 2

MySQL localhost:33060+ ssl dbms_f_parc SQL > create view high as

-> student_id,first_name

-> from s

-> where cgpa >= 3.50;

ERROR: 1064: You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'student_id,first_name from s

where cgpa >= 3.50' at line 2

MySQL localhost:33060+ ssl dbms_f_parc SQL > create view high as

-> select student_id,first_name

-> from s

-> where cgpa >= 3.50;

Query OK, 0 rows affected (0.0311 sec)

MySQL localhost:33060+ ssl dbms_f_parc SQL > create index ind_name

-> on s(first_name);

Query OK, 0 rows affected (0.1011 sec)

Records: 0 Duplicates: 0 Warnings: 0

MySQL localhost:33060+ ssl dbms_f_parc SQL >