



NATIONAL INSTITUTE OF TECHNOLOGY KARNATAKA  
SURATHKAL, MANGALORE - 575 025

Course Code – CS254

Course Name – Database Systems Lab

Lab - 01

Date – January 27, 2022

Submitted To

Dr. Annappa B

Department of Computer Science and Engineering  
National Institute of Technology Karnataka, Surathkal

Submitted By

Md Rakib Hasan

Roll – 201CS132

Department of Computer Science and Engineering


## 1. Write SQL statements for:

Create a table flights with the following information:

FLIGHT(flno, fromplace, toplace, distance, departs, arrives)

### a. Inserting data into the flight with five entries.

```
USE one_finfo;
CREATE TABLE flight (
  flno INT(5),
  fromplace VARCHAR(50),
  toplace VARCHAR(50),
  distance INT(5),
  departs DATETIME,
  arrives DATETIME);
INSERT INTO flight
VALUES (444, 'Dhaka', 'Kolkata', 1000,
       '2022:01:06 00:05:01', '2022:01:06 00:06:00'),
(424, 'Kolkata', 'Bengalore', 2500,
       '2022:01:06 00:10:01', '2022:01:07 00:00:05'),
(104, 'Bengalore', 'Mangalore', 500,
       '2022:01:07 10:00:01', '2022:01:08 00:00:05'),
(044, 'Kolkata', 'Chennai', 5000,
       '2022:01:22 00:05:01', '2022:01:23 00:06:00'),
(001, 'Delhi', 'Bengalore', 5001,
       '2022:01:01 00:05:01', '2022:01:01 00:06:00');
```




```
MySQL 8.0 Command Line Client
mysql> USE one_finfo;
Database changed
mysql> SELECT *
-> FROM flight;
+-----+-----+-----+-----+-----+-----+
| flno | fromplace | toplace | distance | departs          | arrives          |
+-----+-----+-----+-----+-----+-----+
| 444  | Dhaka    | Kolkata | 1000     | 2022-01-06 00:05:01 | 2022-01-06 00:06:00 |
| 424  | Kolkata  | Bengalore | 2500     | 2022-01-06 00:10:01 | 2022-01-07 00:00:05 |
| 104  | Bengalore | Mangalore | 500      | 2022-01-07 10:00:01 | 2022-01-08 00:00:05 |
| 44   | Kolkata  | Chennai | 5000     | 2022-01-22 00:05:01 | 2022-01-23 00:06:00 |
| 1    | Delhi    | Bengalore | 5001     | 2022-01-01 00:05:01 | 2022-01-01 00:06:00 |
+-----+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql>
```

**b. Altering table by adding new column price.**

```
ALTER TABLE flight
ADD price INT(5);
```



MySQL 8.0 Command Line Client


```
mysql> SELECT *
-> FROM flight;
```

flno	fromplace	toplace	distamce	departs	arrives	price
444	Dhaka	Kolkata	1000	2022-01-06 00:05:01	2022-01-06 00:06:00	NULL
424	Kolkata	Bengalore	2500	2022-01-06 00:10:01	2022-01-07 00:00:05	NULL
104	Bengalore	Mangalore	500	2022-01-07 10:00:01	2022-01-08 00:00:05	NULL
44	Kolkata	Chennai	5000	2022-01-22 00:05:01	2022-01-23 00:06:00	NULL
1	Delhi	Bengalore	5001	2022-01-01 00:05:01	2022-01-01 00:06:00	NULL

5 rows in set (0.06 sec)

**c. Deleting a row from the table.**

```
DELETE FROM flight
WHERE flno = 44
```



MySQL 8.0 Command Line Client

```
mysql> SELECT *
-> FROM flight;
```


flno	fromplace	toplace	distamce	departs	arrives	price
444	Dhaka	Kolkata	1000	2022-01-06 00:05:01	2022-01-06 00:06:00	NULL
424	Kolkata	Bengalore	2500	2022-01-06 00:10:01	2022-01-07 00:00:05	NULL
104	Bengalore	Mangalore	500	2022-01-07 10:00:01	2022-01-08 00:00:05	NULL
1	Delhi	Bengalore	5001	2022-01-01 00:05:01	2022-01-01 00:06:00	NULL

4 rows in set (0.10 sec)

```
mysql>
```

**d. Drop column distance.**

```
ALTER TABLE flight
DROP COLUMN distance;
```



MySQL 8.0 Command Line Client

```
mysql> SELECT *
-> FROM flight;
```


flno	fromplace	toplace	departs	arrives	price
444	Dhaka	Kolkata	2022-01-06 00:05:01	2022-01-06 00:06:00	NULL
424	Kolkata	Bengalore	2022-01-06 00:10:01	2022-01-07 00:00:05	NULL
104	Bengalore	Mangalore	2022-01-07 10:00:01	2022-01-08 00:00:05	NULL
1	Delhi	Bengalore	2022-01-01 00:05:01	2022-01-01 00:06:00	NULL

4 rows in set (0.03 sec)

```
mysql>
```

e. Enter any one row with a price value accepting the NULL value then update it to a particular price.

```
INSERT INTO flight(flno, fromplace, toplace,
    departs, arrives)
VALUES (101, 'A', 'B',
    '2022:01:11 00:01:00', '2022:01:12 00:02:00');
```



MySQL 8.0 Command Line Client


```
mysql> SELECT *
-> FROM flight;
```

flno	fromplace	toplace	departs	arrives	price
444	Dhaka	Kolkata	2022-01-06 00:05:01	2022-01-06 00:06:00	NULL
424	Kolkata	Bengalore	2022-01-06 00:10:01	2022-01-07 00:00:05	NULL
104	Bengalore	Mangalore	2022-01-07 10:00:01	2022-01-08 00:00:05	NULL
1	Delhi	Bengalore	2022-01-01 00:05:01	2022-01-01 00:06:00	NULL
101	A	B	2022-01-11 00:01:00	2022-01-12 00:02:00	NULL

5 rows in set (0.03 sec)

```
mysql>
```

```
UPDATE flight
SET price = 1500
WHERE flno = 101
```



MySQL 8.0 Command Line Client

```
mysql> SELECT *
-> FROM flight
-> ;
```

flno	fromplace	toplace	departs	arrives	price
444	Dhaka	Kolkata	2022-01-06 00:05:01	2022-01-06 00:06:00	NULL
424	Kolkata	Bengalore	2022-01-06 00:10:01	2022-01-07 00:00:05	NULL
104	Bengalore	Mangalore	2022-01-07 10:00:01	2022-01-08 00:00:05	NULL
1	Delhi	Bengalore	2022-01-01 00:05:01	2022-01-01 00:06:00	NULL
101	A	B	2022-01-11 00:01:00	2022-01-12 00:02:00	1500

5 rows in set (0.00 sec)

```
mysql>
```

f. Delete all the data from the table.

```
DELETE FROM flight;
```




MySQL 8.0 Command Line Client

```
mysql> SELECT *
-> FROM flight;
Empty set (0.06 sec)

mysql>
```

g. Rename a column price to journey\_price.

```
ALTER TABLE flight
RENAME COLUMN price TO journey_price;
```



```
MySQL 8.0 Command Line Client
mysql> SHOW COLUMNS
-> FROM one_finfo.flight;
+-----+-----+-----+-----+-----+-----+
| Field      | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| flno       | int       | YES  |     | NULL    |       |
| fromplace  | varchar(50) | YES  |     | NULL    |       |
| toplace    | varchar(50) | YES  |     | NULL    |       |
| departs    | datetime  | YES  |     | NULL    |       |
| arrives    | datetime  | YES  |     | NULL    |       |
| journey_price | int       | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.08 sec)

mysql> _
```

2. Consider the following schema for a Library Database.

BOOK (Book\_id, Title, Publisher\_name, Pub\_year)

BOOK\_AUTHORS (Book\_id, Author\_name)

PUBLISHER (Book\_id, Name, Address, Phone)

```
CREATE DATABASE IF NOT EXISTS one_library;
USE one_library;
CREATE TABLE book (
    book_id INT NOT NULL ,
    title VARCHAR(50),
    publisher_name VARCHAR(50),
    pub_year DATE,
    PRIMARY KEY (book_id));
CREATE TABLE book_authors (
    book_id INT,
    author_name VARCHAR(50),
    FOREIGN KEY (book_id) REFERENCES book(book_id));
CREATE TABLE publisher (
    book_id INT,
    name VARCHAR(50),
    address VARCHAR(100),
```

```
phone INT,  
FOREIGN KEY (book_id) REFERENCES book(book_id));
```

```
mysql> USE one_library;  
Database changed  
mysql> SHOW TABLES;  
+-----+  
| Tables_in_one_library |  
+-----+  
| book                   |  
| book_authors           |  
| publisher               |  
+-----+  
3 rows in set (0.03 sec)  
  
mysql>
```

a. Enter at least five tuples for the given relation.

```
INSERT INTO book  
VALUES (100, 'Book One', 'Publisher one', '2012-01-01'),  
(101, 'Book Two', 'Publisher Two', '2015-01-01'),  
(102, 'Book Three', 'Publisher Three', '2009-01-01'),  
(103, 'Book Four', 'Publisher Four', '2011-01-01'),  
(104, 'Book Five', 'Publisher Five', '2010-01-01');
```

```
INSERT INTO book_authors  
VALUES (101, 'Author A'),  
(102, 'Author B'),  
(103, 'Author C'),  
(104, 'Author D'),  
(100, 'Author E');
```

```
INSERT INTO publisher  
VALUES (100, 'P one', 'Address one', 123456789),  
(101, 'P two', 'Address two', 123456799),  
(102, 'P three', 'Address three', 123056789),  
(103, 'P four', 'Address four', 123451789),  
(104, 'P five', 'Address five', 123454789);
```


book_id	title	publisher_name	pub_year
100	Book One	Publisher one	2012-01-01
101	Book Two	Publisher Two	2015-01-01
102	Book Three	Publisher Three	2009-01-01
103	Book Four	Publisher Four	2011-01-01
104	Book Five	Publisher Five	2010-01-01

book_id	author_name
101	Author A
102	Author B
103	Author C
104	Author D
100	Author E

book_id	name	address	phone
100	P one	Address one	123456789
101	P two	Address two	123456799
102	P three	Address three	123056789
103	P four	Address four	123451789
104	P five	Address five	123454789

b. Retrieve details of all books in the library – id, title, name of the publisher, author, etc.

```
USE one_library;
SELECT *
FROM book
JOIN book_authors
    USING (book_id)
JOIN publisher
    USING (book_id);
```




```
mysql> USE one_library
Database changed
mysql> SELECT *
-> FROM book
-> JOIN book_authors USING (book_id)
-> JOIN publisher USING (book_id);
+-----+-----+-----+-----+-----+-----+-----+-----+
| book_id | title   | publisher_name | pub_year | author_name | name   | address   | phone   |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 100     | Book One | Publisher one  | 2012-01-01 | Author E    | P one  | Address one | 123456789 |
| 101     | Book Two | Publisher Two  | 2015-01-01 | Author A    | P two  | Address two | 123456799 |
| 102     | Book Three | Publisher Three | 2009-01-01 | Author B    | P three | Address three | 123056789 |
| 103     | Book Four | Publisher Four  | 2011-01-01 | Author C    | P four  | Address four | 123451789 |
| 104     | Book Five | Publisher Five  | 2010-01-01 | Author D    | P five  | Address five | 123454789 |
+-----+-----+-----+-----+-----+-----+-----+-----+
5 rows in set (0.03 sec)

mysql>
```

c. Get the books written by a particular author.

```
SELECT *
FROM book_authors
JOIN book
    USING (book_id)
WHERE author_name = 'Author E';
```




```
mysql> SELECT *
-> FROM book_authors
-> JOIN book
-> USING (book_id)
-> WHERE author_name = 'Author E';
+-----+-----+-----+-----+-----+
| book_id | author_name | title   | publisher_name | pub_year |
+-----+-----+-----+-----+-----+
| 100     | Author E    | Book One | Publisher one  | 2012-01-01 |
+-----+-----+-----+-----+-----+
1 row in set (0.01 sec)

mysql>
```

d. Delete a book from the book table.

```
DELETE FROM book
WHERE book_id = 100
```



```
mysql> SELECT *
-> FROM book;
```


book_id	title	publisher_name	pub_year
101	Book Two	Publisher Two	2015-01-01
102	Book Three	Publisher Three	2009-01-01
103	Book Four	Publisher Four	2011-01-01
104	Book Five	Publisher Five	2010-01-01

```
4 rows in set (0.02 sec)

mysql>
```

e. Update the phone number of a publisher.

```
UPDATE publisher
SET phone = 123
WHERE book_id = 101
```




```
mysql> SELECT *
-> FROM publisher;
```

book_id	name	address	phone
101	P two	Address two	123
102	P three	Address three	123056789
103	P four	Address four	123451789
104	P five	Address five	123454789

```
4 rows in set (0.02 sec)
```

f. Through book\_id retrieve the details of author name and publisher details.

```
SELECT *
FROM book_authors
JOIN publisher p
  USING (book_id)
```



```
mysql> SELECT *
-> FROM book_authors
-> JOIN publisher p
-> USING (book_id);
```


book_id	author_name	name	address	phone
101	Author A	P two	Address two	123
102	Author B	P three	Address three	123056789
103	Author C	P four	Address four	123451789
104	Author D	P five	Address five	123454789

```
4 rows in set (0.05 sec)
```



g. Drop author\_name column from Book\_authors.

```
ALTER TABLE book_authors
DROP COLUMN author_name
```




```
mysql> SELECT *
-> FROM book_authors;
+-----+
| book_id |
+-----+
| 101 |
| 102 |
| 103 |
| 104 |
+-----+
4 rows in set (0.00 sec)

mysql>
```

h. Rename Name (from publisher) to Publisher\_name.

```
ALTER TABLE publisher
RENAME COLUMN name TO publisher_name
```



```
mysql> SELECT *
-> FROM publisher;
+-----+-----+-----+-----+
| book_id | publisher_name | address      | phone |
+-----+-----+-----+-----+
| 101 | P two | Address two | 123 |
| 102 | P three | Address three | 123056789 |
| 103 | P four | Address four | 123451789 |
| 104 | P five | Address five | 123454789 |
+-----+-----+-----+-----+
4 rows in set (0.02 sec)

mysql>
```

3. Consider the following schema for OrderDatabase:

SALESMAN (Salesman\_id, Name, City, Salary)

CUSTOMER (Customer\_id, cust\_Name, City, Salesman\_id)

ORDERS (Ord\_No, Purchase\_Amt, Ord\_Date, Customer\_id, Salesman\_id)


Write SQL queries to –

```
CREATE DATABASE one_orderdatabase;
USE one_orderdatabase;
CREATE TABLE salesman (
    salesman_id INT NOT NULL,
    name VARCHAR(50),
    city VARCHAR(100),
    salary INT,
```

```

        PRIMARY KEY (salesman_id));
CREATE TABLE customer (
    customer_id INT NOT NULL,
    cust_name VARCHAR(50),
    city VARCHAR(50),
    salesman_id INT NOT NULL,
    PRIMARY KEY (customer_id),
    FOREIGN KEY (salesman_id) REFERENCES
    salesman(salesman_id)
    ON DELETE CASCADE
    ON UPDATE CASCADE);
CREATE TABLE orders (
    ord_no INT NOT NULL,
    purchase_amt INT,
    ord_date DATE,
    customer_id INT NOT NULL,
    salesman_id INT NOT NULL,
    PRIMARY KEY (ord_no),
    FOREIGN KEY (customer_id) REFERENCES
    customer(customer_id)
    ON DELETE CASCADE
    ON UPDATE CASCADE,
    FOREIGN KEY (salesman_id) REFERENCES
    salesman(salesman_id)
    ON DELETE CASCADE
    ON UPDATE CASCADE);

```



```

MySQL 8.0 Command Li...
mysql> SHOW TABLES;
+-----+
| Tables_in_one_orderdatabase |
+-----+
| customer                     |
| orders                       |
| salesman                     |
+-----+
3 rows in set (0.03 sec)

mysql>


```

a. Insert 5-10 entries.

```
INSERT INTO salesman
VALUES (101, 'Salesman A', 'City 1A', 1000),
(102, 'Salesman B', 'City 1B', 1001),
(103, 'Salesman C', 'City 1C', 1002),
(104, 'Salesman D', 'City 1D', 1003),
(105, 'Salesman E', 'City 1E', 1004);

INSERT INTO customer
VALUES (201, 'Customer A', 'City 2A', 101),
(202, 'Customer B', 'City 2B', 102),
(203, 'Customer C', 'City 2C', 103),
(204, 'Customer D', 'City 2D', 104),
(205, 'Customer E', 'City 2E', 105);


INSERT INTO orders
VALUES (301, 123, '2022-01-02', 201, 101),
(302, 124, '2022-01-03', 202, 102),
(303, 125, '2022-01-04', 203, 103),
(304, 126, '2022-01-05', 204, 104),
(305, 127, '2022-01-06', 205, 105);
```



```
mysql> SELECT *
-> FROM salesman;
```

salesman_id	name	city	salary
101	Salesman A	City 1A	1000
102	Salesman B	City 1B	1001
103	Salesman C	City 1C	1002
104	Salesman D	City 1D	1003
105	Salesman E	City 1E	1004


5 rows in set (0.01 sec)



```
mysql> SELECT *
-> FROM customer;
```

customer_id	cust_name	city	salesman_id
201	Customer A	City 2A	101
202	Customer B	City 2B	102
203	Customer C	City 2C	103
204	Customer D	City 2D	104
205	Customer E	City 2E	105

5 rows in set (0.00 sec)




```
mysql> SELECT *
-> FROM orders;
```

ord_no	purchase_amt	ord_date	customer_id	salesman_id
301	123	2022-01-02	201	101
302	124	2022-01-03	202	102
303	125	2022-01-04	203	103
304	126	2022-01-05	204	104
305	127	2022-01-06	205	105

5 rows in set (0.01 sec)

b. Retrieve the details of all the customers and orders.

```
SELECT *  
FROM customer  
JOIN orders  
    USING (customer_id)
```




The screenshot shows the MySQL 8.0 Command Line Client window. The command entered is `mysql> SELECT * FROM customer JOIN orders USING (customer_id);`. The output is a table with 8 columns: `customer_id`, `cust_name`, `city`, `salesman_id`, `ord_no`, `purchase_amt`, `ord_date`, and `salesman_id`. There are 5 rows of data. Below the table, it says "5 rows in set (0.05 sec)".

customer_id	cust_name	city	salesman_id	ord_no	purchase_amt	ord_date	salesman_id
201	Customer A	City 2A	101	301	123	2022-01-02	101
202	Customer B	City 2B	102	302	124	2022-01-03	102
203	Customer C	City 2C	103	303	125	2022-01-04	103
204	Customer D	City 2D	104	304	126	2022-01-05	104
205	Customer E	City 2E	105	305	127	2022-01-06	105

c. Get the customers handled by a particular salesman.

```
SELECT s.name,  
       c.cust_name AS customer  
FROM salesman s  
JOIN customer c  
    USING (salesman_id)  
WHERE salesman_id = 105
```



The screenshot shows the MySQL Command Line Client window. The command entered is `mysql> SELECT s.name, c.cust_name AS customer FROM salesman s JOIN customer c USING (salesman_id) WHERE salesman_id = 105;`. The output is a table with 2 columns: `name` and `customer`. There is 1 row of data. Below the table, it says "1 row in set (0.01 sec)".

name	customer
Salesman E	Customer E

d. Get the details of orders purchased by customers.

```
SELECT c.cust_name,  
       o.purchase_amt AS price,  
       o.ord_date AS date  
FROM customer c
```

```
JOIN orders o
    USING (customer_id)
WHERE cust_name = 'Customer C'
```

```
mysql> SELECT c.cust_name,o.purchase_amt AS price,
o.ord_date AS date FROM customer c JOIN orders o USING (customer_id) WHERE cust_name = 'Customer C';
+-----+-----+-----+
| cust_name | price | date   |
+-----+-----+-----+
| Customer C | 125   | 2022-01-04 |
+-----+-----+-----+
1 row in set (0.01 sec)

mysql>
```

e. Through salesman\_id retrieve the details of his sold orders.

```
SELECT s.name AS saller,
       c.cust_name AS customer,
       o.ord_no, o.ord_date,
       o.purchase_amt
FROM salesman s
JOIN orders o
    USING (salesman_id)
JOIN customer c
    USING (customer_id)
WHERE s.salesman_id = 103
```


```
mysql> -> JOIN orders o
-> USING (salesman_id)
-> JOIN customer c
-> USING (customer_id)
-> WHERE s.salesman_id = 103;
+-----+-----+-----+-----+-----+
| saller   | customer | ord_no | ord_date | purchase_amt |
+-----+-----+-----+-----+-----+
| Salesman C | Customer C | 303   | 2022-01-04 | 125          |
+-----+-----+-----+-----+-----+
1 row in set (0.01 sec)

mysql>
```

f. One of the salesmen is getting a rise of 2000 and is getting relocated to Delhi. Update his data.

```
UPDATE salesman
SET salary = salary + 2000, city = 'Delhi'
```

```
WHERE salesman_id = 101
```



MySQL 8.0 Command Line Client

```
-> FROM salesman;
```


salesman_id	name	city	salary
101	Salesman A	Delhi	3000
102	Salesman B	City 1B	1001
103	Salesman C	City 1C	1002
104	Salesman D	City 1D	1003
105	Salesman E	City 1E	1004

5 rows in set (0.01 sec)

mysql>

g. Delete an order and its details as the customer placed an order and canceled it.

```
DELETE  
FROM orders  
WHERE ord_no = 301
```



MySQL 8.0 Command Line Client

```
mysql> SELECT *  
-> FROM orders;
```


ord_no	purchase_amt	ord_date	customer_id	salesman_id
302	124	2022-01-03	202	102
303	125	2022-01-04	203	103
304	126	2022-01-05	204	104
305	127	2022-01-06	205	105

4 rows in set (0.00 sec)

mysql>

h. Rename the City column to Place.

```
ALTER TABLE customer  
RENAME COLUMN city TO place;  
ALTER TABLE salesman  
RENAME COLUMN city TO place;
```



MySQL 8.0 Command Line Client

```
se near '' at line 1  
mysql> SHOW COLUMNS FROM salesman;
```


Field	Type	Null	Key	Default	Extra
salesman_id	int	NO	PRI	NULL	
name	varchar(50)	YES		NULL	
place	varchar(100)	YES		NULL	
salary	int	YES		NULL	

4 rows in set (0.04 sec)

mysql>

i. Drop purchase\_amt column from the table orders.

```
ALTER TABLE orders
DROP COLUMN purchase_amt
```



```
mysql> SHOW COLUMNS FROM orders;
+-----+-----+-----+-----+-----+-----+
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| ord_no | int  | NO   | PRI | NULL    |       |
| ord_date | date | YES  |     | NULL    |       |
| customer_id | int | NO   | MUL | NULL    |       |
| salesman_id | int | NO   | MUL | NULL    |       |
+-----+-----+-----+-----+-----+-----+
4 rows in set (0.02 sec)

mysql>
```

j. Drop the table salesman.

```
SET FOREIGN_KEY_CHECKS = 0;
DROP TABLE salesman;
SET FOREIGN_KEY_CHECKS = 1;
```



```
mysql> SHOW TABLES;
+-----+-----+
| Tables_in_one_orderdatabase |
+-----+-----+
| customer                     |
| orders                       |
+-----+-----+
2 rows in set (0.02 sec)

mysql>
```

4. Write SQL statements for the following.

Create a table sub with the following information: column and data types: name varchar(8), age number(5), mark1 number(4), mark2 number(4), mark3 number(4);

```
CREATE DATABASE one_uni;
USE one_uni;
CREATE TABLE sub (
    name VARCHAR(8),
    age INT NOT NULL,
    mark1 INT,
    mark2 INT,
```

```
mark3 INT);
```

```
MySQL... - □ ×
mysql> USE one_uni;
Database changed
mysql> SHOW TABLES;
+-----+
| Tables_in_one_uni |
+-----+
| sub                |
+-----+
1 row in set (0.01 sec)

mysql>
```

a. Enter at least five tuples for the given relation.

```
INSERT INTO sub
VALUES ('Name A', 10, 1, 2, 3),
('Name B', 11, 2, 3, 1),
('Name C', 10, 2, 1, 3),
('Name D', 9, 3, 1, 2),
('Name E', 12, 3, 2, 1);
```

```
MySQL 8.0 Command Line Client - □ ×
mysql> SELECT *
-> FROM sub;
+-----+-----+-----+-----+-----+
| name  | age  | mark1 | mark2 | mark3 |
+-----+-----+-----+-----+-----+
| Name A | 10   | 1     | 2     | 3     |
| Name B | 11   | 2     | 3     | 1     |
| Name C | 10   | 2     | 1     | 3     |
| Name D | 9    | 3     | 1     | 2     |
| Name E | 12   | 3     | 2     | 1     |
+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

b. Add one more column with the field name as total with data type as number(5).


```
ALTER TABLE sub
ADD total INT;
```

```
MySQL 8.0 Command Line Client - □ ×
mysql> SHOW COLUMNS FROM sub;
+-----+-----+-----+-----+-----+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| name  | varchar(8) | YES  |     | NULL    |       |
| age   | int        | NO   |     | NULL    |       |
| mark1 | int        | YES  |     | NULL    |       |
| mark2 | int        | YES  |     | NULL    |       |
| mark3 | int        | YES  |     | NULL    |       |
| total | int        | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
6 rows in set (0.01 sec)
```



c. Update the age of sub for a particular student.

```
UPDATE sub
SET age = 9
WHERE name = 'Name A'
```




```
mysql> SELECT *
-> FROM sub;
```

name	age	mark1	mark2	mark3	total
Name A	9	1	2	3	NULL
Name B	11	2	3	1	NULL
Name C	10	2	1	3	NULL
Name D	9	3	1	2	NULL
Name E	12	3	2	1	NULL

5 rows in set (0.01 sec)

d. Delete a row from the table.

```
DELETE
FROM sub
WHERE name = 'Name A'
```




```
mysql> SELECT *
-> FROM sub;
```

name	age	mark1	mark2	mark3	total
Name B	11	2	3	1	NULL
Name C	10	2	1	3	NULL
Name D	9	3	1	2	NULL
Name E	12	3	2	1	NULL

4 rows in set (0.00 sec)

e. Drop column mark3.

```
ALTER TABLE sub
DROP COLUMN mark3
```




```
mysql> SHOW COLUMNS FROM sub;
```

Field	Type	Null	Key	Default	Extra
name	varchar(8)	YES		NULL	
age	int	NO		NULL	
mark1	int	YES		NULL	
mark2	int	YES		NULL	
total	int	YES		NULL	

5 rows in set (0.01 sec)

f. Modify the table by changing the data type of name to varchar(10).


```
ALTER TABLE sub  
MODIFY COLUMN name VARCHAR(10)
```



```
mysql> SHOW COLUMNS FROM sub;  
+-----+-----+-----+-----+-----+-----+  
| Field | Type      | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| name  | varchar(10) | YES  |     | NULL    |       |  
| age   | int         | NO   |     | NULL    |       |  
| mark1 | int         | YES  |     | NULL    |       |  
| mark2 | int         | YES  |     | NULL    |       |  
| total | int         | YES  |     | NULL    |       |  
+-----+-----+-----+-----+-----+-----+  
5 rows in set (0.01 sec)
```

g. Delete all the data from the sub table.


```
DELETE FROM sub;
```



```
mysql> SELECT *  
-> FROM sub;  
Empty set (0.01 sec)
```

h. Delete the table.

```
DROP table sub
```



```
mysql> SHOW TABLES FROM one_uni;  
Empty set (0.01 sec)  
  
mysql>
```